



AT&T Wireless Group

Fixed Wireless Services
PO Box 97059
Redmond, WA 98073-9759

FCC R3 WCS Type Acceptance Report

11675

Revision 1.0
12/8/00



© 1995-2000 AT&T Fixed Wireless Services
All rights reserved.

For additional copies of this document, please contact:

AT&T Fixed Wireless Services
PO Box 97059
Redmond, WA 98073-9759
Telephone: 425-702-2767
Facsimile: 425-702-3941
Ask for FCC R3 WCS Type Acceptance Report or 11675.

Contents

Contents	iii
List of Figures	ix
List of Tables	xvii
Chapter 1 Attestation Statements	
Chapter 2 Block Diagrams	
2.1 Block Diagrams	2-2
Chapter 3 Cover Letters	
Chapter 4 External Photographs	
4.1 Photographs of the R3 Indoor Unit	4-2
4.2 Photographs of the R3 WCS Outdoor Unit	4-7
Chapter 5 ID Label/Location Information	
5.1 ID Label	5-2
5.2 Location Information	5-3
Chapter 6 Internal Photographs	
6.1 Internal Photographs of the R3 WCS Outdoor Unit	6-2

6.2 Internal Photographs of the R3 Indoor Unit 6-9

Chapter 7 Operational Description

7.1 System Overview 7-2

7.1.1 PWAN General Description 7-2

7.1.2 PWAN Network Element Overview 7-2

7.1.3 Wireless Network Element Deployment 7-4

7.1.4 PWAN Airlink Profile 7-5

7.1.5 PWAN Telephony Functions 7-6

7.1.6 PWAN FAX/Modem VF Traffic Functions 7-9

7.1.7 PWAN High-Speed Data Functions 7-9

7.1.8 HSD Medium Access 7-10

7.2 Airlink Overview 7-11

7.2.1 PWAN Physical Layer Overview 7-11

7.2.1.1 Services Provided by the Physical Layer 7-13

7.2.2 PWAN Airlink Overview 7-13

7.2.2.1 PWAN Implementation of OFDM 7-15

7.2.3 PWAN Airlink Resource Allocation 7-18

7.2.4 PWAN Network Access Channel (NAC) Functional Description 7-19

7.2.4.1 BC Definition 7-19

7.2.4.2 CLC Definition 7-19

7.2.4.3 UCAC Definition 7-20

7.2.4.4 SCAC Definition 7-20

7.2.5 PWAN Voice Traffic Channel (VTch) Functional Description ... 7-21

7.2.5.1 Associated Control Channel Functional Description . 7-21

7.2.6 PWAN High-Speed Data Services 7-21

7.2.6.1 Basic Data Service Allocation Definition 7-21

7.2.6.2 PWAN Data Traffic Channel (DTch) Definition 7-22

7.2.6.3 High-Speed Data Medium Access Control 7-23

7.2.7 Network Synchronization 7-23

Chapter 8 Parts List/Tune Up Information

8.1 Parts List 8-26

8.1.1 R3 WCS Outdoor Unit PCB 8-26

8.1.2 R3 Indoor Unit PCB 8-29

8.1.3 R3 Indoor Unit 2-line Expansion PCB 8-32

8.1.4 R3 Indoor Unit Lucent AC-DC Power Supply 8-33

8.1.5 R3 Indoor Unit Panasonic AC-DC Power Supply 8-34

8.1.6	R3 WCS Outdoor Unit Lucent DC-DC Power Module	8-36
8.2	Output Power Tuning Procedures	8-37
8.2.1	Hardware Output Power Limiting Circuit	8-37
8.2.2	Software Output Power Control	8-39
8.2.3	Manufacturing Calibration	8-40
8.2.4	Hardware Frequency vs Temperature Results	8-40

Chapter 9 RF Exposure

9.1	RF Human Exposure - FDTD Analysis and SAR Testing	9-2
9.1.1	Applicable FCC Rules	9-2
9.1.2	Test Configuration	9-2
9.1.2.1	Modelling	9-2
9.1.2.2	SAR Testing	9-2
9.1.3	Test Results	9-3
9.2	Summary and Conclusions	9-4
9.3	Computer Hardware and Software Used for Performing Calculations	9-4
9.3.1	Computer Hardware	9-4
9.3.2	Computer Software	9-4
9.4	2 FDTD Models	9-5
9.4.1	Antenna Model	9-5
9.4.2	Kuster Homogeneous Head Model	9-9
9.4.2.1	Nose of Model Centered Over Geometric Center of Patch Array	9-9
9.4.2.2	Nose of Model Centered Over Geometric Center of Patches 1 Through 4	9-10
9.4.3	REMCOM Head and Shoulders Model	9-12
9.5	FDTD Calculation and Measurements of SAR in Kuster Head and Shoulders Homogeneous Model	9-14
9.5.1	Orientation with Tip of Nose in Contact with Radome at Center of Four Patch Array	9-16
9.5.2	Orientation with Tip of Nose Centered over Path No. 1 (no radome attached)	9-17
9.5.3	Orientation with Tip of Nose Centered over Path No. 1 (radome attached)	9-18
9.5.4	Orientation with Tip of Nose Centered over Patch No. 2 (no radome attached)	9-19
9.5.5	Orientation with Tip of Nose Centered over Patch No. 4 (no radome attached)	9-22
9.6	FDTD Calculation of SAR in REMCOM Head and Shoulders Inhomogeneous Model (no radome attached)	9-23

Chapter 10 Schematics

10.1	R3 WCS Outdoor Unit PCB	10-2
10.2	R3 Indoor Unit PCB	10-3
10.3	R3 Indoor Unit 2-line Expansion Card PCB	10-4
10.4	R3 Indoor Unit Lucent AC-DC Power Supply	10-5
10.5	R3 Indoor Unit Panasonic AC-DC Power Supply	10-6
10.6	R3 WCS Outdoor Unit Lucent DC-DC Power Module	10-7

Chapter 11 Test Report

11.1	Test Methodology	11-2
11.1.1	Introduction	11-2
11.1.2	Equipment Classification	11-2
11.1.3	Remote Unit RF Frequency Stability vs. Temperature Test Methodology	11-3
11.1.3.1	Applicable FCC Rules Parts	11-3
11.1.3.2	Overview	11-3
11.1.3.3	Test Methodology	11-4
11.1.4	R3 Frequency Stability vs. Input Voltage Test Methodology	11-6
11.1.4.1	Applicable FCC Rule Parts	11-6
11.1.4.2	Overview	11-6
11.1.4.3	Test Methodology	11-7
11.1.5	R3 Occupied Bandwidth Test Methodology	11-9
11.1.5.1	Applicable FCC Rule Parts	11-9
11.1.5.2	Overview	11-9
11.1.5.3	Test Methodology	11-9
11.1.6	Modulation Characterization Test Methodology	11-11
11.1.6.1	Applicable FCC Rules	11-11
11.1.6.2	Overview	11-11
11.1.6.3	Test Methodology	11-12
11.1.7	RF Output Power Test Methodology	11-14
11.1.7.1	Applicable FCC Rules	11-14
11.1.7.2	Overview	11-14
11.1.7.3	Test Methodology	11-15
11.1.8	Spurious Emissions at the Antenna Terminal Test Methodology	11-16
11.1.8.1	Applicable FCC Rules	11-16
11.1.8.2	Overview	11-17
11.1.8.3	Test Methodology	11-18
11.1.9	RF Human Exposure	11-20

11.1.9.1	Applicable FCC Rules	11-20
11.1.9.2	Overview	11-20
11.1.10	Radiated Emissions	11-21
11.1.10.1	Applicable FCC Rules	11-21
11.1.10.2	Overview	11-21
11.1.10.3	Test Methodology	11-22
11.1.10.4	Radiated Emissions Equipment Configuration 30-1000 MHz	11-22
11.1.10.5	Measure Parameters	11-24
11.1.10.6	Antenna Factors	11-25
11.1.10.7	Cable Factors	11-27
11.1.10.8	Radiated Emissions Equipment Configuration 1000-3500 MHz	11-28
11.1.10.9	Cable Factors	11-31
11.2	RF Characterization Test Results	11-32
11.2.1	Test Equipment List	11-33
11.2.2	Equipment Under Test List	11-33
11.2.3	R3 RF Frequency Stability vs. Temperature Test Results	11-34
11.2.3.1	Applicable FCC Rules Parts	11-34
11.2.3.2	Test Configuration	11-34
11.2.4	Results Summary	11-35
11.2.5	R3 Frequency Stability vs. Input Voltage Test Results	11-36
11.2.5.1	Applicable FCC Rule Parts	11-36
11.2.5.2	Test Configuration	11-37
11.2.5.3	Results Summary	11-37
11.2.6	R3 Occupied Bandwidth Test Results	11-38
11.2.6.1	Applicable FCC Rule Parts	11-38
11.2.6.2	Test Configuration	11-38
11.2.6.3	Results Summary	11-39
11.2.7	Modulation Characterization Test Results	11-40
11.2.7.1	Applicable FCC Rules	11-40
11.2.7.2	Test Configuration	11-40
11.2.7.3	Results Summary	11-40
11.2.8	RF Output Power Test Results	11-47
11.2.8.1	Applicable FCC Rules	11-47
11.2.8.2	Test Configuration	11-47
11.2.9	Spurious Emissions at the Antenna Terminal	11-50
11.2.9.1	Applicable FCC Rules	11-50
11.2.9.2	Test Configuration	11-51
11.2.9.3	Results Summary	11-52

- 11.3 Electromagnetic Compatibility Test Results** 11-62
 - 11.3.1 Introduction 11-62
 - 11.3.2 Equipment Lists 11-63
 - 11.3.3 Equipment Under Test List 11-65
 - 11.3.4 Test Results 11-66
 - 11.3.4.1 Radiated Emissions 11-66
 - 11.3.4.2 Conducted Emissions 11-120
- 11.4 R3 WCS Outdoor Unit Specifications** 11-130
 - 11.4.1 Overview 11-130
 - 11.4.2 Antenna Specification 11-131
 - 11.4.3 Operational Temperature Ranges 11-132

Chapter 12 Test Setup Photos

- 12.1 Radiated Emissions Test Setup** 12-2
- 12.2 Conducted Emission Test Setup** 12-8
- 12.3 Testing Facility and Location** 12-9

Chapter 13 User Manuals

List of Figures

Figure 2.1	R3 Indoor Unit Digital Board Comprehensive Block Diagram	2-2
Figure 2.2	R3 WCS Outdoor Unit Transmitter Baseband and IF Functional Block Diagram	2-3
Figure 2.3	R3 WCS Outdoor Unit Transmitter Functional Block Diagram	2-4
Figure 2.4	R3 WCS Outdoor Unit Receiver RF Block Diagram	2-5
Figure 2.5	R3 WCS Outdoor Unit Receiver IF and Baseband Functional Block Diagram	2-6
Figure 2.6	R3 WCS Outdoor Unit RF Phase-Lock Loop Block Diagram	2-7
Figure 2.7	R3 WCS Outdoor Unit Control Logic and 32-MHz Oscillator Block Diagram	2-8
Figure 4.1	Front of the R3 Indoor Unit	4-2
Figure 4.2	Right-side view of the R3 Indoor Unit	4-3
Figure 4.3	Side View of the R3 Indoor Unit	4-4
Figure 4.4	Rear view of the R3 Indoor Unit	4-5
Figure 4.5	R3 WCS Surge Protector	4-6
Figure 4.6	Front View of the R3 WCS Outdoor Unit Antenna	4-7
Figure 4.7	Rear View of the R3 WCS Outdoor Unit	4-8
Figure 4.8	Side View of the Outdoor Unit with Mounting Bracket	4-9
Figure 5.1	FCC ID Label for the R3 Indoor Unit	5-2
Figure 5.2	FCC ID Label for the R3 WCS Outdoor Unit	5-2
Figure 5.3	FCC ID Label Location on Antenna	5-3

Figure 5.4 Close-up of Label on R3 WCS Outdoor Unit 5-4

Figure 5.5 FCC ID Label Location on the R3 Indoor Unit 5-5

Figure 5.6 FCC Label Location on R3 Indoor Unit 5-6

Figure 6.1 R3 WCS Outdoor Unit - Radome Removed Revealing Back View of Antenna
6-2

Figure 6.2 R3 WCS Outdoor Unit Back - Radome Removed Revealing DC-DC Converter
..... 6-3

Figure 6.3 Top View of the R3 WCS Outdoor Unit RF Board 6-4

Figure 6.4 R3 WCS Outdoor Unit Backside of Radome and Frontside of Antenna .. 6-5

Figure 6.5 Bottom View of the R3 WCS Outdoor Unit - Patch Antenna Separated from
the RF PCB 6-6

Figure 6.6 Top View of the DC-DC Converter 6-7

Figure 6.7 Bottom View of the DC-DC Converter 6-8

Figure 6.8 R3 Indoor Unit Cover Removed with Lucent Power Supply 6-9

Figure 6.9 R3 Indoor Unit with Cover Removed and Panasonic Power Supply 6-10

Figure 6.10 R3 Indoor Unit Chassis with Cover Removed 6-11

Figure 6.11 Top View of the Main R3 Indoor Unit Digital PCB 6-12

Figure 6.12 Bottom View of R3 Indoor Unit Main Digital PCB 6-13

Figure 6.13 Top View of The Lucent Power Supply. 6-14

Figure 6.14 Bottom View of the Lucent Power Supply 6-15

Figure 6.15 Top View of the Panasonic Power Supply 6-16

Figure 6.16 Bottom View of the Panasonic Power Supply 6-17

Figure 6.17 Top view of the R3 Indoor Unit Expansion Card 6-18

Figure 6.18 Bottom View of the R3 Indoor Unit Expansion Card 6-19

Figure 6.19 R3 Indoor Unit—View of Batteries and Terminal Cables 6-20

Figure 7.1 PWAN Telephony Architecture 7-3

Figure 7.2 PWAN Figure OSI Model 7-6

Figure 7.3 PWAN Airlink Protocol Profile 7-7

Figure 7.4 PWAN Telephony Processing 7-8

Figure 7.5 PWAN HSD Architecture 7-10

Figure 7.6 HSD Logical Channel Relationships 7-11

Figure 7.7 PWAN OSI Model 7-12

Figure 7.8 Illustration of OFDM Burst Parameters 7-14

Figure 7.9 OFDM Time-Domain Waveform Generation 7-15

Figure 7.10 PWAN Subband Allocation 7-16

Figure 7.11 PWAN FDMA Structure 7-16

Figure 7.12 PWAN TDMA Framing Structure 7-17

Figure 7.13 PWAN Airlink Resource Matrix

.....	7-18
Figure 7.14 NAC Logical Channel Timing Relationships	7-20
Figure 7.15 Basic Data Service Allocation	7-22
Figure 7.16 RSP Definitions	7-24
Figure 8.1 Hardware Output Limiting Circuit	8-39
Figure 9.1	9-6
Figure 9.2	9-6
Figure 9.3	9-7
Figure 9.4	9-7
Figure 9.5	9-8
Figure 9.6	9-9
Figure 9.7	9-10
Figure 9.8	9-11
Figure 9.9	9-11
Figure 9.10	9-12
Figure 9.11	9-12
Figure 9.12	9-13
Figure 9.13	9-14
Figure 9.14	9-16
Figure 9.15	9-16
Figure 9.16	9-17
Figure 9.17	9-17
Figure 9.18	9-18
Figure 9.19	9-18
Figure 9.20	9-19
Figure 9.21	9-19
Figure 9.22	9-20
Figure 9.23	9-20
Figure 9.24	9-21
Figure 9.25	9-22
Figure 9.26	9-22
Figure 9.27	9-23
Figure 9.28	9-24
Figure 9.29	9-24
Figure 9.30	9-25
Figure 11.1 R3 WCS Delay Compensation Pilot Frequency Relationships	11-4
Figure 11.2 R3 WCS Frequency Stability vs. Temperature Test Configuration	11-5

Figure 11.3 R3 WCS Frequency Stability vs. Input Voltage Test Configuration 11-8

Figure 11.4 R3 WCS System Occupied Bandwidth and Modulation Characterization Test Configuration 11-10

Figure 11.5 R3 WCS Output Power Test Configuration 11-16

Figure 11.6 R3 WCS Conducted Power Spectral Mask 11-18

Figure 11.7 Spectral Purity Test Configuration 11-19

Figure 11.8 30 MHz-1 GHz Equipment Set Graph 11-23

Figure 11.9 1000-3500 MHz Equipment Set 11-28

Figure 11.10 R3 Frequency Stability vs. Temperature, DCP Tone #7 11-36

Figure 11.11 R3 WCS Frequency Stability vs. Input Voltage 11-38

Figure 11.12 R3 WCS 99% Occupied Bandwidth During Delay Compensation Pilot Operation 11-39

Figure 11.13 Voice Channel Power vs. Frequency, 99.0% Occupied BW, and Time-Domain Average Burst Power 11-41

Figure 11.14 Voice Channel CCDF 11-42

Figure 11.15 HSD Channel Power vs. Frequency, 99% Occupied BW, and Time-Domain Average Burst Power 11-43

Figure 11.16 HSD Channel CCDF 11-43

Figure 11.17 Network Access Channel Power vs. Frequency, 99% Occupied Bandwidth, and Time-Domain Average Power 11-44

Figure 11.18 Network Access Channel CCDF 11-45

Figure 11.19 Delay Compensation Channel Power vs. Frequency, 99% Occupied BW, and Time-Domain Average Power 11-46

Figure 11.20 Delay Compensation Channel CCDF 11-46

Figure 11.21 Time-Domain Power Envelope, Average Power 11-48

Figure 11.22 Time-Domain Power Envelope, Peak Power at £ 99.0% Occurrence 11-49

Figure 11.23 Time-Domain Power Envelope, Peak/Average Ratio at £ 99.0% Occurrence 11-50

Figure 11.24 R3 WCS Conducted Power Spectral Mask 11-52

Figure 11.25 R3 WCS Block “A” 1-MHz Band-Power Between 2350.5 and 2351.5 MHz 11-52

Figure 11.26 R3 WCS Block “A” 1-MHz Band Power Between 2351.5 and 2352.5 MHz 11-53

Figure 11.27 R3 WCS Block “A” 1 MHz Band Power Between 2353.5 and 2354.5 MHz 11-53

Figure 11.28 R3 WCS Block “A” 1 MHz Band Power Between 2352.5 and 2353.5 MHz 11-54

Figure 11.29 R3 WCS Block “A” 1 MHz Band Power Between 2354.5 and 2355.5 MHz 11-54

Figure 11.30 R3 WCS Block “B” 1 MHz Band Power Between 2355.5 and 2356.5 MHz

11-55

Figure 11.31 R3 WCS Block "B" 1 MHz Band Power Between 2354.5 and 2355.5 MHz . . . 11-55

Figure 11.32 R3 WCS Block "B" 1 MHz Band Power Between 2356.5 and 2357.5 MHz . . . 11-56

Figure 11.33 R3 WCS Block "B" 1 MHz Channel Power Between 2357.5 and 2358.5 MHz 11-56

Figure 11.34 R3 WCS Block "B" 1 MHz Channel Power Between 2358.5 and 2359.5 MHz 11-57

Figure 11.35 R3 WCS Maximum Lower Guard Band Spurious Power, Measured in a 12 kHz Resolution BW 11-57

Figure 11.36 R3 WCS Maximum Upper Guard Band Spurious Power Measured in a 12 kHz Resolution BW 11-58

Figure 11.37 Spectral Purity from 2344.5 MHz to 2351.5 MHz, with Spurious Power Between 2349.5 and 2350.5 MHz Measured in a 1 MHz Bandwidth . . . 11-58

Figure 11.38 Spectral Purity from 2338 to 2345 MHz, with Spurious Power Measured in a 1 MHz Band-Power Marker Centered on 2344.5 MHz 11-59

Figure 11.39 Spectral Purity from 2358.5 MHz to 2365.5 MHz with 1 MHz Band-Power Reference Between 2359.5 and 2360.5 MHz 11-59

Figure 11.40 Spectral Purity from 2365 MHz to 2372 MHz with 1 MHz Band-Power Reference Centered at 2365.5 MHz 11-60

Figure 11.41 R3 WCS Directional Coupler and Cable Sweep 11-62

Figure 11.42 3-meter Chamber Ambient 11-67

Figure 11.43 30 - 1000 MHz: Lucent, Four Voice Calls with HSD 11-69

Figure 11.44 1000 - 3500 MHz: Lucent, Four Voice Calls with HSD 11-72

Figure 11.45 3.5 - 18 GHz: Lucent, Four Voice Calls With HSD, Horizontal Polarization, Full Scan 11-74

Figure 11.46 3.5 - 18 GHz: Lucent, Four Voice Calls With HSD, Horizontal Polarization, Highest Signal, 4.13 GHz Peak 11-75

Figure 11.47 3.5 - 18 GHz: Lucent Four Voice Calls With HSD, Horizontal Polarization, Highest Signal, 4.13 GHz Average 11-76

Figure 11.48 3.5 - 18 GHz: Lucent Four Voice Calls With HSD, Horizontal Polarization, Second Highest Signal, 4.22 GHz Peak 11-77

Figure 11.49 3.5 - 18 GHz: Lucent Four Voice Calls With HSD, Horizontal Polarization, Second Highest Signal, 4.22 GHz Average 11-78

Figure 11.50 3.5 - 18 GHz: Lucent Four Voice Calls With HSD, Horizontal Polarization, Third Highest Signal, 6.19 GHz Peak 11-79

Figure 11.51 3.5 - 18 GHz: Lucent Four Voice Calls With HSD, Horizontal Polarization, Third Highest Signal, 6.19 GHz Average 11-80

Figure 11.52 3.5 - 18 GHz: Lucent Four Voice Calls With HSD, Vertical Polarization, Full Scan 11-81

Figure 11.53 3.5 - 18 GHz: Lucent Four Voice Calls With HSD, Vertical Polarization, High-

est Signal, 4.13 GHz Peak 11-82

Figure 11.54 3.5 - 18 GHz: Four Voice Calls With HSD, Vertical Polarization, Highest Signal, 4.13 GHz Average 11-83

Figure 11.55 3.5 - 18 GHz: Lucent Four Voice Calls With HSD, Vertical Polarization, Second Highest Signal, 4.22 GHz Peak 11-84

Figure 11.56 3.5 - 18 GHz: Lucent Four Voice Calls With HSD, Vertical Polarization, Third Highest Signal, 6.19 GHz Peak 11-85

Figure 11.57 3.5 - 18 GHz: Lucent Four Voice Calls With HSD, Vertical Polarization, Third Highest Signal, 6.19 GHz Average 11-86

Figure 11.58 3.5 - 18 GHz: Lucent Four Voice Calls With HSD, Vertical Polarization, Fourth Highest Signal, 6.33 GHz Peak 11-87

Figure 11.59 18-26.5 GHz: Lucent Four Voice Calls With HSD, Horizontal Polarization, Full Scan 11-88

Figure 11.60 18-26.5 GHz: Lucent Four Voice Calls With HSD, Vertical Polarization, Full Scan 11-89

Figure 11.61 30-1000 MHz: Lucent Two Voice Calls with HSD 11-90

Figure 11.62 1-3.5 GHz: Lucent Two Voice Calls with HSD 11-93

Figure 11.63 30-1000 MHz: Panasonic Four Voice Calls with HSD 11-95

Figure 11.64 1-3.5 GHz: Panasonic Four Voice Calls with HSD 11-99

Figure 11.65 3.5 - 18 GHz: Panasonic Four Voice Calls With HSD, Horizontal Polarization, Full Scan 11-101

Figure 11.66 3.5-18 GHz: Panasonic Four Voice Calls With HSD, Horizontal Polarization, Highest Signal, 4.12 GHz Peak 11-102

Figure 11.67 3.5-18 GHz: Panasonic Four Voice Calls With HSD, Horizontal Polarization, Highest Signal, 4.12 GHz Average 11-103

Figure 11.68 3.5-18 GHz: Panasonic Four Voice Calls With HSD, Horizontal Polarization, Second Highest Signal, 4.22 GHz Peak 11-104

Figure 11.69 3.5-18 GHz: Panasonic Four Voice Calls With HSD, Horizontal Polarization, Second Highest Signal, 4.22 GHz Average 11-105

Figure 11.70 3.5-18 GHz: Panasonic Four Voice Calls With HSD, Horizontal Polarization, Third Highest Signal, 6.19 GHz Peak 11-106

Figure 11.71 3.5-18 GHz: Panasonic Four Voice Calls With HSD, Horizontal Polarization, Third Highest Signal, 6.19 GHz Average 11-107

Figure 11.72 3.5-18 GHz: Panasonic Four Voice Calls With HSD, Vertical Polarization, Full Scan 11-108

Figure 11.73 3.5-18 GHz: Panasonic Four Voice Calls With HSD, Vertical Polarization, Highest Signal, 4.13 GHz Peak 11-109

Figure 11.74 3.5-18 GHz: Panasonic Four Voice Calls With HSD, Vertical Polarization, Highest Signal, 4.13 GHz Average 11-110

Figure 11.75 3.5-18 GHz: Panasonic Four Voice Calls With HSD, Vertical Polarization, Second Highest Signal, 4.22 GHz Peak 11-111

Figure 11.76 3.5-18 GHz: Panasonic Four Voice Calls With HSD, Vertical Polarization,

	Third Highest Signal, 6.19 GHz Peak	11-112
Figure 11.77	3.5-18 GHz: Panasonic Four Voice Calls With HSD, Vertical Polarization, Third Highest Signal, 6.19 GHz Average	11-113
Figure 11.78	3.5-18 GHz: Panasonic Four Voice Calls With HSD, Vertical Polarization, Fourth Highest Signal, 6.33 GHz Peak	11-114
Figure 11.79	18-26.5 GHz: Panasonic Four Voice Calls With HSD, Horizontal Polarization, Full Scan	11-115
Figure 11.80	18-26.5 GHz: Panasonic Four Voice Calls With HSD, Vertical Polarization, Full Scan	11-116
Figure 11.81	30-1000 MHz: Panasonic Two Voice Calls and HSD	11-117
Figure 11.82	1-3.5 GHz Panasonic Two Voice Calls and HSD	11-119
Figure 11.83	Conducted Emission Setup	11-122
Figure 11.84	Two Voice Calls with HSD and Lucent Power Supply: Line 1	11-123
Figure 11.85	Two Voice Calls with HSD and Lucent Power Supply: Line 2	11-124
Figure 11.86	Four Voice Calls with HSD and Lucent Power Supply: Line 1	11-125
Figure 11.87	Four Voice Calls with HSD and Lucent Power Supply: Line 2	11-126
Figure 11.88	Two Voice Calls with HSD and Panasonic Power Supply: Line 1	11-127
Figure 11.89	Two Voice Calls with HSD and Panasonic Power Supply: Line 2	11-128
Figure 11.90	Four Voice Calls with HSD and Panasonic Power Supply: Line 1	11-129
Figure 11.91	Four Voice Calls with HSD and Panasonic Power Supply: Line 2	11-130
Figure 12.1	Radiated Emissions Test Setup	12-3
Figure 12.2	HP 84300A E62 Microwave Intentional Radiator System	12-4
Figure 12.3	HP8546A EMI Receiver with WCS K&L Notch Filter	12-5
Figure 12.4	HP8546A EMI Receiver, No Filter	12-6
Figure 12.5	Overall EUT Setup Picture	12-7
Figure 12.6	Overall Conducted Emissions Test Setup	12-8
Figure 12.7	EMCO 3825/2 Conducted Emissions LISN	12-9



List of Tables

Table 7.1	PWAN Reference Architecture – Interface Definitions	7-4
Table 7.2	Basic PWAN OFDM Parameters	7-17
Table 7.3	NAC Logical Channel Summary	7-19
Table 8.1	R3 WCS Outdoor Unit PCB	8-26
Table 8.2	R3 Indoor Unit PCB	8-29
Table 8.3	R3 2-line Expansion PCB	8-32
Table 8.4	Lucent AC-DC Power Supply	8-33
Table 8.5	Panasonic AC-DC Power Supply	8-34
Table 8.6	R3 WCS Lucent DC-DC Power Module	8-36
Table 8.7	Performance of Transmitter Output Power Level Limit Control Versus Temperature - Board 1	8-41
Table 8.8	Performance of Transmitter Output Power Level Limit Control Versus Temperature - Board 2	8-41
Table 9.1	Summary and Comparison of Calculated and Measured Maximum SARs to FCC MPL for Various Tissue Models Exposed to AT&T R3 WCS Cushcraft Antenna.	9-3
Table 11.1	PWAN Interface Definitions	11-2
Table 11.2	Hewlett-Packard 89441A Occupied Bandwidth Test Parameters	11-10
Table 11.3	Hewlett-Packard 89441A Modulation Characterization Test Parameters	11-12
Table 11.4	Hewlett-Packard 89441A RF Power Test Parameters	11-14
Table 11.5	Hewlett-Packard 89441A Spectral Purity Test Configuration Parameters	11-17
Table 11.6	Antenna (Model CBL 6111A) 3-m Correction Factors	11-25
Table 11.7	Cable (Gore Cable) 53-ft. Correction Factors	11-27
Table 11.8	Antenna (Emco 3115 Serial # 5514-9807) Correction Factors	11-31
Table 11.9	Cable (Gore Cable) 53-ft. Correction Factors	11-32

Table 11.10 Test Equipment 11-33

Table 11.11 WCS System Components Equipment Under Test 11-34

Table 11.12 R3 Transmit Frequency Stability vs. Temperature 11-36

Table 11.13 Transmit Frequency Stability vs. Input Voltage 11-38

Table 11.14 Occupied Bandwidth Test Result Summary 11-39

Table 11.15 R3 WCS Channel Characterization Test Results 11-47

Table 11.16 R3 WCS RF Output Power Characteristics 11-50

Table 11.17 R3 In-Band and Out-Of-Band Power Summary 11-60

Table 11.18 R3 WCS Emissions Test Equipment 11-64

Table 11.19 R3 WCS System Equipment Under Test List 11-65

Table 11.20 FCC Class B Radiated Emissions Limits 11-67

Table 11.21 Data for 30 MHz-1GHz; Lucent Four Voice with HSD 11-70

Table 11.22 Data for 1-3.5 GHz; Lucent Four Voice/HSD 11-73

Table 11.23 Data for 30 MHz-1GHz; Lucent Two Voice /HSD 11-91

Table 11.24 Data for 1 GHz-3.5 GHz; Lucent Two Voice/HSD 11-94

Table 11.25 Data for 30 MHz-1 GHz; Panasonic Four Voice with HSD 11-96

Table 11.26 Data for 1 GHz-3.5 GHz; Panasonic Four Voice with HSD 11-100

Table 11.27 Data for 30 MHz-1 GHz; Panasonic Two Voice /HSD 11-118

Table 11.28 Data for 1 GHz-3.5 GHz; Panasonic Two Voice/HSD 11-120

Table 11.29 Notch Filter Characterization From 1-3.5 GHz 11-120

Table 11.30 FCC Conducted Emission Limits 11-121

Table 11.31 R3 WCS Outdoor Unit Performance Specifications 11-131