

## **GRUNDFOS Holding A/S**

Poul Due Jensens Vej 7  
DK-8850 Bjerringbro  
Denmark

Phone: (+45) 87 50 14 00  
www.grundfos.com

Danske Bank, Copenhagen  
Citibank N.A., New York  
Nordea Bank Danmark A/S,  
Copenhagen  
VAT-No.: 31 85 83 56

Date: 05.02.2021  
Your ref.: FCC ID:OG3-GIM1A  
Our ref.: FCC ID:OG3-GIM1A

nkorshoej@grundfos.com

## **RF Exposure and Transmitter Power Considerations for co-location of FCC ID:OG3-GIM1A and FCC ID:OG3-CIM2X0-3G-4G Module**

For mobile product operation the FCC requires that the calculated MPE be equal to or less than a given limit dependent on frequency at a distance of 20 cm from a device to the body of a user.

The following operating bands are certified:

BT LE: 2402 – 2480MHz

CDMA850/ LTE B5: 824-849MHz

CDMA1900/ LTE B2: 1850-1910MHz

LTE B4: 1710 – 1755MHz

LTE B17: 704 – 716MHz

LTE B12: 698 - 716MHz

LTE B13: 777 – 787MHz

The following FCC Rule Parts and procedures are applicable:

Part 1.1310 – Radiofrequency radiation exposure limits

Part 2.1091 – Radiofrequency radiation exposure evaluation: mobile devices

KDB447498 D01 v06

Mobile and Portable Devices RF Exposure Procedures and Equipment Authorisation Policies

### **MPE CALCULATIONS**

The MPE calculation used to calculate the safe operating distance for the user is:

$$S = \text{EIRP}/4 \pi R^2$$

**Where** S = Power density  
 EIRP = Effective Isotropic Radiated Power (EIRP = P x G)  
 P = Conducted Transmitter Power  
 G = Antenna Gain (relative to an isotropic radiator)  
 R = distance to the centre of radiation of the antenna (safe operating distance)

**Power Density Requirement**

From table 1 (b) - Limits for General Population/ Uncontrolled Exposure of

FCC §1.1310 (e) for f >1500MHz ,  $S_{req1} = 1.0 \text{ mW/cm}^2$

From table 1 (b) - Limits for General Population/ Uncontrolled Exposure of FCC §1.1310 (e) for f <1500MHz,  $S = f/1500 \text{ mW/cm}^2$

(f = operating frequency)

**VALUES**

Conducted power values for the cellular bands have been taken from RF exposure analysis of module grant FCC ID:OG3-CIM2X0-3G-4G (RI7LE910NAV2). Antenna gains are taken from Operational Description document of FCC ID:OG3-GIM1A application.

Frequency Range (MHz)	Operating Band	TX Conducted Power Average (dBm)	Antenna Gain (dBi)	EIRP (mW)	Calculated Distance R @ $S_{req}$ (cm)	Power Density S mw/ cm <sup>2</sup>		
						Limit $S_{req}$	Calculated $S_n$ @ 20cm	$S_n/S_{req}$
2402 - 2480	BT LE	5.5	+2.0	5.6	0.67	1.0	0.001	0.001
824 - 849	CDMA V LTE 5	24.5	+0.3	302.0	6.49	0.57	0.06	0.11
1850 - 1910	CDMA II LTE 2	24.5	-1.2	213.8	4.12	1.0	0.043	0.043
1710 - 1755	LTE4	24.0	+1.5	354.8	5.31	1.0	0.071	0.043
704 - 716	LTE 17	24.0	-7.0	50.1	2.91	0.47	0.01	0.021
699 - 716	LTE 12	24.0	-7.0	50.1	2.91	0.47	0.01	0.021
777 - 787	LTE 13	24.0	-5.0	79.4	3.48	0.52	0.016	0.031

## **KDB447498 D01 v05 Section 7.2 SIMULTANEOUS TRANSMISSION CONSIDERATIONS**

Worst case summation of calculated MPE ratios.

WCDMA/ LTE 5 and BT LE operation:

$$\text{ie: } \sum \text{MPE}_{\text{ratios}} = (S_1 / S_{\text{req1}}) + (S_2 / S_{\text{req2}})$$

$$= 0.01 + 0.11$$

$$= \mathbf{0.12}$$

$\sum$  of MPE ratios < 1.0, so in accordance with KDB447498 Section 7.2, simultaneous transmission test exclusion applies for the worst case WCDMA/ LTE 5 and BT LE operation.

### **Conclusion**

The required 20cm RF exposure limits for General Population/ Uncontrolled Exposure will not be exceeded for co-location of the BT LE transmitter and cellular module using antennas having a maximum gains as detailed in this document