246 Industrial Way West, Eatontown, NJ 07724

LUCENT TECHNOLOGIES CP May 27, 1999

Test Lab:

Lucent Technologies Global Products Compliance Lab

Products to be tested:

Model 9410 - 900 MHz, 90 channel cordless DSS/FH
TO BE TESTED ON CHANNELS 1, 30, and 60
FREQUENCY OF CHANNELS ARE THE SAME FOR BASE AND
HANDSET.

Channel 1 = 902.597 Channel 30 = 916.386 Channel 60 = 927.457

2 CLOCK FREQUENCIES

CSP = 10.24 MHzDSP = 4.096 MHz

Eugenia Reynolds

Email data to: ereynolds@pcc.lucent.com

Model 9410 900 MHz Cordless DSS/FH (OATS)

RADIATED SPURIOUS EMISSIONS 47 CFR 15.209

The Model 9410 Cordless Telephone will be tested for final Radiated Emissions as per 47 CFR 15.209(a)(b)(c)(d)(e). This test is for the determination of spurious or "unwanted" emissions from an intentional radiator. This portion of the radiated emissions testing *does not* include testing the intentional radiating signal produced by the EUT.

The EUT shall be set up with both the handset and the base on the test platform. The EUT cables shall be configured to ANSI C63.4 - 1992.

Furthermore, the EUT shall be in the "off hook" mode of operation. To facilitate this mode the EUT tip/ring line shall be connected to a Viking CO simulator. This mode of operation simulates a "worst case" mode of operation.

Radiated Emissions pre-scan data will be provided to the test operators by Lucent Technologies CP.

The radiated emissions data collected should represent the top six emissions (ANSI C63.4-1992) produced by the EUT or any emissions found to be within 20 dB $\mu\nu$ of the limits specified in 47 CFR 15.209.

RADIATED FIELD STRENGTH MEASUREMENTS OF THE FUNDAMENTAL EMISSION 47 CFR 15.247

The field strength of the fundamental emissions generated by the Model 9410 shall be measured with the EUT configured in the same configuration as above with the following exceptions:

The handset and base will be tested separately.

Three measurements will be taken on the handset and base at low, mid and high channels.

All measurements *over 1GHz* shall be taken with measurement instrumentation employing an *average detector*.

