

According to 447498 D01 General RF Exposure Guidance v05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

--f(GHz) is the RF channel transmit frequency in GHz

--Power and distance are rounded to the nearest mW and mm before calculation

--The result is rounded to one decimal place for comparison

$$\text{eirp} = \text{pt} \times \text{gt} = (\text{EXd})^2/30$$

where:

pt = transmitter output power in watts,

gt = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m, ---  $10^{((\text{dBuV/m})/20)}/10^6$

d = measurement distance in meters (m) ---3m

$$\text{So pt} = (\text{EXd})^2/30 \times \text{gt}$$

### For BT mode

Field strength = 91.08dBuV/m @3m

Ant gain =1dBi, so Ant numeric gain=1.26

$$\text{So pt} = \{ [10^{(91.08/20)}/10^6 \times 3]^2/30 \times 1.26 \} \times 1000 \text{ mW} = 0.306 \text{ mW}$$

$$\text{So } (0.306 \text{ mW} / 5 \text{ mm}) \times \sqrt{2.480} = 0.096 < 3$$

### For BLE mode

Field strength = 90.45dBuV/m @3m

Ant gain =1dBi, so Ant numeric gain= 1.26

$$\text{So pt} = \{ [10^{(90.45/20)}/10^6 \times 3]^2/30 \times 1.26 \} \times 1000 \text{ mW} = 0.264 \text{ mW}$$

$$\text{So } (0.264 \text{ mW} / 5 \text{ mm}) \times \sqrt{2.440} = 0.082 < 3$$

Then SAR evaluation is not required