ERICSSON 📕		Confidential REPORT			1(13
Uppgjord (även faktaansvarig om annan) - Prepared (also subject resp LD/ECS/GT/NFA Ramadan Plicanic	oonsible if other)	Nr - No. GT/NFA 00:0	016		
Dokansv/Godk - Doc respons/Approved LD/ECS/GT/NFAC Thomas Bolin	Kontr - Checked	Datum - <i>Date</i> 2000-03-10	Rev A	File	

SAR Test Report: R290 Satellite

Date of test:	October 28, 1999
Laboratory:	Electromagnetic Near Field and Radio Frequency Dosimetry Laboratory, Ericsson Mobile Communications AB, Nya Vattentornet, SE-221 83 Lund, Sweden
Test Responsible:	Ramadan Plicanic, M.Sc.EE Staff Engineer – Terminal Antennas <u>ramadan.plicanic@ecs.ericsson.se</u> +46 46 19 38 62

Statement of Compliance

Ericsson Mobile Communications AB, declares under its sole responsibility that the product

OHL R290 SAT (Ericsson R290 Satellite)

to which this declaration relates, is in conformity with the requirements of FCC Report and Order ET Docket No. 93-62 for the uncontrolled exposure environment. It also declares that the product was tested in accordance with the guideline FCC OET Bulletin 65, Supplement C(edition 97-01) under its classification as aportable device.

ERICSSON		Confidential REPORT			2(13
Uppgjord (även faktaansvarig om annan) - Prepared (also subject responsible if other) LD/ECS/GT/NFA Ramadan Plicanic		Nr - No. GT/NFA 00:	016	I	
Dokansv/Godk - Doc respons/Approved LD/ECS/GT/NFAC Thomas Bolin	Kontr - Checked	Datum - Date 2000-03-10	Rev A	File	

Table of Contest

1		Introduction	3
2	2.1 2.2	Device Under Test (D.U.T.) Antenna Description Device Description	3 3 3
3	3.1 3.2	<i>Test Equipment</i> Dosimetric System Additional equipment	4 4 4
4		Electrical parameters of the tissue simulating liquid	4
5		System accuracy verification	5
6		Test Results	5
Re	eference	S	6
Aŗ	pendix	1: SAR distribution comparison for system accuracy verification	7
Aŗ	pendix	2: SAR distribution plot	9
Ap	pendix	3: Photographs of the device under test	10
Ap	pendix	4: Position of device on Generic Twin Phantom	12
Ap	pendix	5: Probe calibration parameters for ET3DV4 SN: 1101	13

ERICSSON 📕		Confidential REPORT			3(13
Uppgjord (även faktaansvarig om annan) - Prepared (also subject responsible if other) LD/ECS/GT/NFA Ramadan Plicanic		GT/NFA 00:	016		
Dokansv/Godk - Doc respons/Approved LD/ECS/GT/NFAC Thomas Bolin	Kontr - Checked	Datum - <i>Date</i> 2000-03-10	Rev A	File	

1 Introduction

Under Federal Communications Commission rules set forth in 1996[1], portable radio transmitters, such as the device under test (DUT) in this test report, "are subject to routine environmental evaluation RF exposure prior to equipment authorization or use." According to these rules, the DUT is classified as a "portable device" and must comply with exposure limits for the general population, or "uncontrolled exposure" environment. Compliance is demonstrated by determining that the spatial peak SAR does not exceed 1.6 W/kg as averaged over 1 gram cube of tissue.

In this test report, compliance of the Ericsson R290 Satellite portable telephone with the above-mentioned exposure limits is demonstrated. The device was tested in accordance with FCC guideline [2]. Detailed procedures of the test are described in the *Ericsson SAR Measurement Specifications* [3].

2 Device Under Test

2.1 Antenna description

Туре	Swivel	
Location	Left and back	
	Length	120mm
Dimension	Diameter at base	12mm
Configuration		

2.2 Device description

Device model	R290 Satellite
Serial number	GA2BO454t4
Mode	Satellite
Multiple Access Scheme	CDMA
Maximum Output Power Setting	26dBm
Factory Tolerance in Power Setting	±0.5dB
Maximum Peak Output Power	26.5dBm
Duty Cycle	1
Transmitting Frequency Range	1610.73–1625.49MHz
Prototype or Production Unit	Prototype

ERICSSON 📕		Confidential REPORT			4(13
Uppgjord (även faktaansvarig om annan) - Prepared (also subject resp LD/ECS/GT/NFA Ramadan Plicanic	onsible if other)	Nr - No. GT/NFA 00:01	6	Ι	
Dokansv/Godk - Doc respons/Approved LD/ECS/GT/NFAC Thomas Bolin	Kontr - Checked	Datum - <i>Date</i> 2000-03-10	Rev A	File	

3 Test Equipment

3.1 Dosimetric System

SAR measurements were made using the DASY3 professional system (software version 3.1c) manufactured by Schmid & Partner Engineering AG and installed June, 1996. The total SAR assessment uncertainty (K=1) of the system is $\pm 16\%$ and includes a +15% offset (overestimation). The extended uncertainty (K=2) is $\pm 32\%$ with a +15% offset. This results in a total uncertainty range of -1% to +31% for K=1, or -17% to +47% for K=2. The equipment list is given below.

Description	Serial Number	Due Date
DASY3 DAE V2	215	2000/04
E-Field Probe ETDV4	1101	2000/04
Dipole Validation Kit D900V2	004	2000/04
Dipole Validation Kit, D1800V2	228	2000/04

3.2 Additional Equipment

Description	Serial Number	Due Date
Signal Generator		
Power Amplifier		
Dielectric Probe Kit HP 85070B	Inv. 443029	2000/04
Network Analyzer HP 8753C	Inv. 421670	2000/12
Power Meter R&S NRVD	Inv. 483920	2001/12
Power Sensor R&S NRV-Z5	Inv. 2334	2001/12
Base Station Simulator Wavetek 4106 GPP	Inv. 462991	2000/04

4 Electrical Parameters of the Tissue Simulating Liquid

Prior to conducting SAR measurement, the relative permittivity, ε_r , and the conductivity, σ , of the tissue simulating

liquid were measured with the dielectric probe kit. The mass density, ρ , used by the DASY3 program is also given. These values are shown in the table below. FCC recommended limits for maximum permittivity, minimum conductivity and maximum mass density are also shown [4]. It is seen that the measured parameters satisfy the recommended limits, resulting in an overestimation of SAR.

ERICSSON 📕		Confidential REPORT			5(13
Uppgjord (även faktaansvarig om annan) - Prepared (also subject responsible if other) LD/ECS/GT/NFA Ramadan Plicanic		GT/NFA 00:016	6		
Dokansv/Godk - Doc respons/Approved LD/ECS/GT/NFAC Thomas Bolin	Kontr - Checked	Datum - Date 2000-03-10	Rev A	File	

f(MHz)		Dielectric Parameters			
	Limits/Measured				
		Er	σ(S/m)	ρ (g/cm ³)	
	Measured	38.2	1.68	1.03	
1800	Recommended Limits[4]	43.5	1.15	1.03	
	Difference	- 9.9%	+ 46.1%	0%	

5 System Accuracy Verification

A system accuracy verification of the DASY3 was performed using the dipole validation kit listed in Section 3.1. The system verification test was conducted on the same day as the measurement of the DUT. The obtained results are displayed in the table below. It is seen that the system is operating within its specification, as the results are within \pm 5% of the reference values obtained from the system manufacturer [5]. The SAR distribution also compares well with that provided by the system manufacturer (see Appendix 1).

f(MHz)	Measured	SAR(W/kg)	Diele	ectric Param	eters	Temp.
	Reference	1 gram	٤r	σ(S/m)	ρ(g/cm ³)	(°°)
1800	Measured	38.1	38.2	1.68	1.03	24.1
	Reference[5]	39.1	41.2	1.71	1.00	?

6 Test Results

The conducted output power and the SAR values are shown in table below. The device was tested on both the right hand phantom and left hand phantom, on one frequency for three different antenna positions. The SAR results shown are maximum SAR values averaged over 1g of tissue. A test program was used to control the device during the SAR measurement. The phone was supplied with power box under test. The temperature of the test facility during the tests was 24 ± 1 °C, and the depth of the tissue simulating liquid was 12.9cm.

Mode	f(MHz)	Antenna	Output	SAR (W/kg) in 1g mass
		Position	Power (dBm)	Right Hand Section	Left Hand Section
		90deg Left	27.4	0.0097	0.0187
Satellite	1618.11	45deg Left	27.4	0.0094	0.0048
		45deg Right	27.4	0.0124	0.0066

ERICSSON 📕	Confidential REPORT 6(13				
Uppgjord (även faktaansvarig om annan) - Prepared (also subject responsible if other) LD/ECS/GT/NFA Ramadan Plicanic		GT/NFA 00:016			
Dokansv/Godk - Doc respons/Approved LD/ECS/GT/NFAC Thomas Bolin	Kontr - Checked	Datum - <i>Date</i> 2000-03-10	Rev A	File	

References

[1] Federal Communications Commission, "Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation", Report and Order ET Docket No. 93-62, August, 1996.

[2] Kwok Chan, Robert F. Cleveland, Jr. and David L. Means, "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields," Office of Engineering and Technology Bulletin 65, Edition 97-01, December, 1997.

[3] C. Törnevik, M. Siegbahn, T. Persson, M. Douglas and R. Plicanic, "Ericsson SAR Measurement Specification", Internal Document ERA/T/U-98:442, February 1999.

[4] Federal Communications Commission, "Tissue Dielectric Properties", http://www.fcc.gov/fcc-bin/dielec.sh .

[5] Schmid and Partner Engineering AG, "DASY Dipole Validation Kit", Type: D1800V2, SN:228, Mars, 1998.

ERICSSON 📕	Confidential REPORT 7(13				
Uppgjord (även faktaansvarig om annan) - Prepared (also subject responsible if other) LD/ECS/GT/NFA Ramadan Plicanic		Nr - No. GT/NFA 00:	016		
Dokansv/Godk - Doc respons/Approved LD/ECS/GT/NFAC Thomas Bolin	Kontr - Checked	Datum - <i>Date</i> 2000-03-10	Rev A	File	

Appendix 1: SAR Distribution Comparison for System Accuracy Verification



SAR distribution of validation dipole antenna from system accuracy verification test.





SAR distribution of validation dipole antenna provided by system manufacturer.

Validation Dipole D1800V2 SN:228, d = 10mm

Frequency: 1800 [MHz], Antanna Input Power: 250 [mW]

Powerdrift: 0.00 dB

ERICSSON 📕	Confidential REPORT 9(13				
Uppgjord (även faktaansvarig om annan) - Prepared (also subject responsible if other) LD/ECS/GT/NFA Ramadan Plicanic		Nr - No. GT/NFA 00:016			
Dokansv/Godk - Doc respons/Approved LD/ECS/GT/NFAC Thomas Bolin	Kontr - Checked	Datum - <i>Date</i> 2000-03-10	Rev A	File	

Appendix 2: SAR Distribution Plot

R290 Satellite

EX.2.50 (SALCHINE Generic Twin Phantom, Left Hand Section, (72°,65°); Frequency: 1618 MHz Probe: ET3DV4- SN1101; ConvP(5:20,5:20); Crest factor: 1:0; Evain 1800 b0Hz; σ = 1:68 mho/m n_c = 38.2 p = 1.03 g/cm³ Cube 5a52; SAR((g):00187 mWg; SAR(10g): 0.0113 mW/g; (Worst-case extrapolation) Coarse: Dz = 20.0, Dy = 20.0, Dz = 10.0 Powerdmit: -0.00 dB



Distribution of worst case SAR

ERICSSON 📕	Confidential REPORT 10(13				
Uppgjord (även faktaansvarig om annan) - Prepared (also subject responsible if other) LD/ECS/GT/NFA Ramadan Plicanic		Nr - No. GT/NFA 00:	016		
Dokansv/Godk - Doc respons/Approved LD/ECS/GT/NFAC Thomas Bolin	Kontr - Checked	Datum - Date 2000-03-10	Rev A	File	

Appendix 3: Photographs of the Device Under Test



Front view of device

ERICSSON 📕	Confidential REPORT 11(13				
Uppgjord (även faktaansvarig om annan) - Prepared (also subject responsible if other) LD/ECS/GT/NFA Ramadan Plicanic		GT/NFA 00:016			
Dokansv/Godk - Doc respons/Approved LD/ECS/GT/NFAC Thomas Bolin	Kontr - Checked	Datum - <i>Date</i> 2000-03-10	Rev A	File	



Side view of device

ERICSSON 📕	Confidential REPORT 12(13				
Uppgjord (även faktaansvarig om annan) - Prepared (also subject responsible if other) LD/ECS/GT/NFA Ramadan Plicanic		Nr - <i>No.</i> GT/NFA 00:01	6		
Dokansv/Godk - Doc respons/Approved LD/ECS/GT/NFAC Thomas Bolin	Kontr - Checked	Datum - <i>Date</i> 2000-03-10	Rev A	File	

Appendix 4: Position of Device on Generic Twin Phantom



ERICSSON 📕	Confidential REPORT 13(13					
Uppgjord (även faktaansvarig om annan) - Prepared (also subject responsible if other) LD/ECS/GT/NFA Ramadan Plicanic		Nr - No. GT/NFA 00:	016	l		
Dokansv/Godk - Doc respons/Approved LD/ECS/GT/NFAC Thomas Bolin	Kontr - Checked	Datum - Date 2000-03-10	Rev A	File		

Appendix 5: Probe Calibration Parameters for ET3DV4 SN:1101

ET3DV4 SN:1101

DASY2 - Parameters of Probe: ET3DV4 SN:1101

Sensitiv	vity in Free	Space	Dioc	de Compress	sion
	NormX	1.23 μV/(V/	m) ²	DCP X	80 mV
	NormY	1.36 µV/(V/	m) ²	DCP Y	80 mV
	NormZ	1.17 μV/(V/	m) ²	DCP Z	80 mV
Sensitiv	vity in Tiss	ue Simulating	I Liquid		
450 MHz	ConvF X	6.2	extrapolated	s ₇ =	48 ± 5%
	ConvF Y	6.2	extrapolated	σ=	0.50 ± 10% mho/m
	ConvF Z	6.2	extrapolated	(brain tissu	e simulating liquid)
	Alpha	0.65			
	Depth	2.00			
900 MHz	ConvF X	5.9	± 10%	ε _r =	42.5 ± 5%
	ConvF Y	5.9	± 10%	σ =	0.86 ± 10% mho/m
	ConvF Z	5.9	± 10%	(brain tissu	e simulating liquid)
	Alpha	0.65			
	Depth	2.00			
1500 MHz	ConvF X	5.4	interpolated	s,=	41 ± 5%
	ConvF Y	5.4	interpolated	σ=	1.32 ± 10% mho/m
	ConvF Z	5.4	interpolated	(brain tissu	e simulating liquid)
	Alpha	0.65			
	Depth	2.00			
1800 MHz	ConvF X	5.2	± 10%	s,=	41 ± 5%
	ConvF Y	5.2	± 10%	σ =	1.69 ± 10% mho/m
	ConvF Z	5.2	± 10%	(brain tissu	e simulating liquid)
	Alpha	0.65			
	Depth	2.00			
Sensor	Offset				
	Prohe Tin to	Sensor Center	27		mm

Page 2 of 7

Surface to Probe Tip

 1.9 ± 0.2

mm