



American Telecommunications Certification Body Inc.
6731 Whittier Ave, McLean, VA 22101

June 25, 2002

RE: Kai-Link Corporation

FCC ID: OIBKWL-210

I have a few comments on this Application.

- 1.) Please provide Information to User as described in 15.21 within the manual.
- 2.) The RF Exposure report quotes a safe MPE distance of 2.5cm. However, there continues to be no prohibition from co-location of other transmitters or antennas as required by the Rules. Please add this to the Manual
- 3.) FYI: Radiated data showing compliance with the restricted bands provision of 15.205 especially the band below 2390MHz, and above 2483.5MHz must be done in both peak and average modes. Unless compliance can be demonstrated exclusively with Peak settings [1MHz RBW/1MHzVBW], average readings [1MHzRBW, 10HzVBW] will be required. It is recommended practice that average readings always be taken with peak during radiated band edge tests above 1GHz.

I look forward to your response.

Sincerely,

William H. Graff
President and Examining Engineer

[mailto: whgraff@AmericanTCB.com](mailto:whgraff@AmericanTCB.com)

The items indicated above must be submitted before processing can continue on the above referenced application. Failure to provide the requested information may result in application termination. Correspondence should be considered part of the permanent submission and may be viewed from the Internet after a Grant of Equipment Authorization is issued.

Please do not respond to this correspondence using the email reply button. In order for your response to be processed expeditiously, you must submit your documents through the AmericanTCB.com website. Also, please note that partial responses increase processing time and should not be submitted.

Any questions about the content of this correspondence should be directed to the sender.