

# FCC Part 15B

## Measurement and Test Report




For

LB Technology Co., Ltd.

No.5 of Xiaoyang Rd, First Industrial Park, Tanzhou Town, Zhongshan City,

Guangdong, P.R. China

**FCC ID: OIE96601W**

<b>Test Rule(s):</b>	<u>FCC Part 15 Subpart B</u>
<b>Product Description:</b>	<u>IP VIDEO DOOR PHONE</u>
<b>Tested Model:</b>	<u>96601W</u>
<b>Report No.:</b>	<u>STR14078256I-2</u>
<b>Tested Date:</b>	<u>2014-07-23 to 2014-08-30</u>
<b>Issued Date:</b>	<u>2014-09-01</u>
<b>Tested By:</b>	<u>Vigoss Liang / Engineer</u> 
<b>Reviewed By:</b>	<u>Lahm Peng / EMC Manager</u> 
<b>Approved &amp; Authorized By:</b>	<u>Jandy so / PSQ Manager</u> 
<b>Prepared By:</b>	

**Shenzhen SEM.Test Technology Co., Ltd.**  
1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,  
Bao'an District, Shenzhen, P.R.C. (518101)  
Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM.Test Technology Co., Ltd.

**TABLE OF CONTENTS**

**1. GENERAL INFORMATION.....3**  
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....3  
1.2 TEST STANDARDS.....4  
1.3 TEST METHODOLOGY .....4  
1.4 TEST FACILITY .....4  
1.5 EUT SETUP AND OPERATION MODE .....5

**2. SUMMARY OF TEST RESULTS .....6**

**3. CONDUCTED EMISSIONS .....7**  
3.1 MEASUREMENT UNCERTAINTY .....7  
3.2 TEST EQUIPMENT LIST AND DETAILS .....7  
3.3 TEST PROCEDURE.....7  
3.4 BASIC TEST SETUP BLOCK DIAGRAM.....7  
3.5 ENVIRONMENTAL CONDITIONS .....8  
3.6 SUMMARY OF TEST RESULTS/PLOTS .....8  
3.7 CONDUCTED EMISSIONS TEST DATA.....8

**4. RADIATED EMISSIONS.....11**  
4.1 MEASUREMENT UNCERTAINTY .....11  
4.2 TEST EQUIPMENT LIST AND DETAILS .....11  
4.3 TEST PROCEDURE.....11  
4.4 TEST RECEIVER SETUP .....12  
4.5 CORRECTED AMPLITUDE & MARGIN CALCULATION .....12  
4.6 ENVIRONMENTAL CONDITIONS .....12  
4.7 SUMMARY OF TEST RESULTS/PLOTS .....12

## 1. GENERAL INFORMATION

### 1.1 Product Description for Equipment Under Test (EUT)

#### Client Information

Applicant: LB Technology Co., Ltd.  
 Address of applicant: No.5 of Xiaoyang Rd, First Industrial Park, Tanzhou Town, Zhongshan City, Guangdong, P.R. China  
 Manufacturer: LB Technology Co., Ltd.  
 Address of manufacturer: No.5 of Xiaoyang Rd, First Industrial Park, Tanzhou Town, Zhongshan City, Guangdong, P.R. China

General Description of EUT	
Product Name:	IP VIDEO DOOR PHONE
Trade Name:	LBtech
Model No.:	96601W
Adding Model(s):	96601W-P
<p><i>Note: The test data is gathered from a production sample, provided by the manufacturer. The appearance of others models listed in the report is different from main-test model 96601W, but the circuit and the electronic construction do not change, declared by the manufacturer.</i></p>	

Technical Characteristics of EUT	
Rated Voltage:	AC120V 60Hz Adapter:DV12V
Rated Current:	1000mA
Rated Power:	12W
Power Adapter Model:	FJ-SW1201000U
Lowest Internal Frequency:	32.768kHz
Highest Internal Frequency:	24MHz
Classification of ITE:	Class B

## 1.2 Test Standards

The following report is prepared on behalf of the LB Technology Co., Ltd in accordance with Part 2, Subpart J, and Part 15, Subparts A and B of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart B, and section 15.205, 15.107, and 15.109 rules.

**Maintenance of compliance** is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

## 1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

## 1.4 Test Facility

### **FCC – Registration No.: 934118**

Shenzhen SEM.Test Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 934118.

### **Industry Canada (IC) Registration No.: 11464A**

The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

### **CNAS Registration No.: L4062**

Shenzhen SEM.Test Technology Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 1/F, Building A, Hongwei Industrial Park, Liuxian 2<sup>nd</sup> Road, Bao'an District, Shenzhen, P.R.C (518101).

## 1.5 EUT Setup and Operation Mode

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted according to the operation manual for use, more detailed description as follows:

### Test Mode List:

Test Mode	Description	Remark
TM1	Network video	for EMI testing
TM2	/	/

### EUT Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
Adapter Cable	1.5	Unshielded	Without Core

### Auxiliary Equipment List and Details

Description	Manufacturer	Model	Serial Number
Notebook	Lenovo	E23	EB12648265
Wireless router	/	/	/

### Special Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
Network Cable X 2	1.5m	Unshielded	Without Core

## 2. SUMMARY OF TEST RESULTS

---

<b>FCC Rules</b>	<b>Description of Test Item</b>	<b>Result</b>
§ 15.107 (a)	Conducted Emissions	Compliant
§ 15.109 (a)	Radiated Emissions	Compliant

N/A: not applicable

### 3. Conducted Emissions

#### 3.1 Measurement Uncertainty

Base on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement is  $\pm 2.88$  dB.


#### 3.2 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2014-05-28	2015-05-27
L.I.S.N	Schwarz beck	NSLK8126	8126-224	2014-05-28	2015-05-27
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2014-05-28	2015-05-27

#### 3.3 Test Procedure

Test is conducting under the description of ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

#### 3.4 Basic Test Setup Block Diagram



### 3.5 Environmental Conditions

Temperature:	23 °C
Relative Humidity:	52%
ATM Pressure:	1011 mbar

### 3.6 Summary of Test Results/Plots

According to the data in section 3.7, the EUT complied with the FCC Part 15.107(a) Conducted margin for a Class B device, with the *worst* margin reading of:


**-0.35dB at 0.1660 MHz in the Neutral, Peak detector, 0.15-30MHz**

### 3.7 Conducted Emissions Test Data




**Plot of Conducted Emissions Test Data**

EUT: IP VIDEO DOOR PHONE  
 Tested Model: 96601W  
 Operating Condition: Network video  
 Comment: AC120V/60Hz Adapter:DV12V-1000mA  
 Test Specification: Neutral



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1660	55.31	9.50	64.81	65.16	-0.35	peak
2	0.3780	24.89	9.50	34.39	48.32	-13.93	AVG
3	20.2580	29.81	12.00	41.81	60.00	-18.19	peak
4	20.2580	24.91	12.00	36.91	50.00	-13.09	AVG
5	29.2340	31.02	13.00	44.02	60.00	-15.98	peak
6	29.2340	22.99	13.00	35.99	50.00	-14.01	AVG

Test Specification: Line



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1500	46.77	9.50	56.27	66.00	-9.73	peak
2	0.4220	25.46	9.50	34.96	47.41	-12.45	AVG
3	18.2460	31.65	11.65	43.30	60.00	-16.70	peak
4	18.2460	25.63	11.65	37.28	50.00	-12.72	AVG

## 4. Radiated Emissions

### 4.1 Measurement Uncertainty

Base on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any radiation emissions measurement is  $\pm 5.10$  dB.


### 4.2 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	R&S	FSP	836079/035	2014-05-28	2015-05-27
EMI Test Receiver	R&S	ESVB	825471/005	2014-05-28	2015-05-27
Pre-amplifier	Agilent	8447F	3113A06717	2014-05-28	2015-05-27
Pre-amplifier	Compliance Direction	PAP-0118	24002	2014-05-28	2015-05-27
Trilog Broadband Antenna	SCHWARZBECK	VULB9163	9163-333	2014-05-24	2015-05-23
Horn Antenna	ETS	3117	00086197	2014-05-24	2015-05-23
Loop Antenna	SCHWARZECK	HFRA 5165	9365	2014-05-24	2015-05-23

### 4.3 Test Procedure

The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC Part 15.109 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.



### 4.4 Test Receiver Setup

Frequency :9kHz-30MHz	Frequency :30MHz-1GHz	Frequency :Above 1GHz
RBW=10KHz,	RBW=120KHz,	RBW=1MHz,
VBW =30KHz	VBW=300KHz	VBW=3MHz(Peak), 10Hz(AV)
Sweep time= Auto	Sweep time= Auto	Sweep time= Auto
Trace = max hold	Trace = max hold	Trace = max hold
Detector function = peak	Detector function = peak, QP	Detector function = peak, AV

### 4.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} - \text{Corr. Factor}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dBμV means the emission is 6dBμV below the maximum limit for a Class B device. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15.109(a) Limit}$$

### 4.6 Environmental Conditions

Temperature:	23 °C
Relative Humidity:	55 %
ATM Pressure:	1011 mbar

### 4.7 Summary of Test Results/Plots


According to the data, the EUT complied with the FCC Part 15.109(a) rule, and had the worst margin of:

**-1.93 dB at 726.8052 MHz in the Horizontal polarization, 9 kHz to 1 GHz, 3Meters**

**Plot of Radiated Emissions Test Data**


EUT: IP VIDEO DOOR PHONE  
 Tested Model: 96601W  
 Operating Condition: Network video  
 Comment: AC120V/60Hz Adapter: DV12V-1000mA

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	104.1701	26.80	5.69	32.49	43.50	-11.01	0	100	QP
2	135.0319	29.22	2.81	32.03	43.50	-11.47	0	100	QP
3	325.5958	34.20	9.14	43.34	46.00	-2.66	120	100	QP
4	400.4319	31.30	10.12	41.42	46.00	-4.58	120	100	QP
5	601.4265	29.37	13.22	42.59	46.00	-3.41	180	100	QP
6	726.8052	31.30	12.77	44.07	46.00	-1.93	180	100	QP

Test Specification: Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	35.6240	26.84	8.49	35.33	40.00	-4.67	120	100	QP
2	56.3948	29.17	5.69	34.86	40.00	-5.14	360	100	QP
3	104.1701	30.23	5.69	35.92	43.50	-7.58	120	100	QP
4	325.5958	29.61	9.14	38.75	46.00	-7.25	30	100	QP
5	400.4319	27.16	10.12	37.28	46.00	-8.72	120	100	QP
6	601.4265	29.80	13.22	43.02	46.00	-2.98	120	100	QP

Note: The measurements greater than 20dB below the limit from 9kHz to 30MHz and test data are not provided.

\*\*\*\*\* END OF REPORT \*\*\*\*\*