



FCC RADIO TEST REPORT

FCC ID: OIHG-807

Product : Wireless Bluetooth speakers

Trade Name : Indena

Model Name : G-807

Prepared for

Shenzhen Leader-Union Technology Co., Ltd.

3F, No. 88, Alley 5, Hekan Village, Ban Tian, LongGang District, Shenzhen City,
China

Prepared by

DongGuan Precise Testing Service Co.,Ltd.

Room 203-204, 2F, Xinye Building, No.67 Shijing, Guanzhang
Road, Dongguan, China

TEST RESULT CERTIFICATION

Applicant's name Shenzhen Leader-Union Technology Co., Ltd.

Address 3F, No. 88, Alley 5, Hekan Village, Ban Tian, LongGang District,
Shenzhen City, China

Manufacture's Name... Shenzhen Indena Electronic Technology Co.,Ltd

Address 3F, No. 88, Alley 5, Hekan Village, Ban Tian, LongGang
District, Shenzhen City, China

Product description

Product name Wireless Bluetooth speakers

Model and/or type
reference G-807

Serial Model N/A

In all, the original product and the alternative product are the same.

Standards FCC Part15.247

Test procedure ANSI C63.10-2003

This device described above has been tested by PTS, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of PTS, this document may be altered or revised by PTS, personal only, and shall be noted in the revision of the document.


Date of Test

Date (s) of performance of tests 20.Oct, 2014 ~ 28.Oct, 2014

Date of Issue 24. Nov, 2014


Test Result..... **Pass**

Testing Engineer :



Assistant

Technical Manager :



Supervisor

Authorized
Signatory :



Jacky Ou /
Manager

Test Summary

Test Items	Test Requirement	Result
Spurious Radiated Emissions	15.205(a) 15.209 15.247(d)	PASS
Band edge Emissions	15.247(d)	PASS
Conducted Emissions	15.207	PASS
20dB Bandwidth	15.215c 15.247(a)(1)	PASS
Maximum Peak Output Power	15.247(b)(1)	PASS
Frequency Separation	15.247(a)(1)	PASS
Number of Hopping Frequency	15.247(a)(1)(iii)	PASS
Dwell time	15.247(a)(1)(iii)	PASS
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	1.1307(b)(1)	PASS

TABLE OF CONTENTS

TEST SUMMARY	3
GENERAL INFORMATION	5
GENERAL DESCRIPTION OF E.U.T.	5
DETAILS OF E.U.T.	5
CHANNEL LIST	5
DESCRIPTION OF SUPPORT UNITS	5
TEST FACILITY	6
TEST LOCATION	6
EQUIPMENT USED DURING TEST	7
EQUIPMENTS LIST	7
MEASUREMENT UNCERTAINTY	7
TEST EQUIPMENT CALIBRATION	7
CONDUCTED EMISSION	8
E.U.T. OPERATION	8
EUT SETUP	8
CONDUCTED EMISSION TEST RESULT	8
SPURIOUS RADIATED EMISSIONS	11
EUT OPERATION :	11
TEST SETUP	12
SPECTRUM ANALYZER SETUP	13
TEST PROCEDURE	14
CORRECTED AMPLITUDE & MARGIN CALCULATION	14
SUMMARY OF TEST RESULTS	15
BAND EDGE MEASUREMENT	18
TEST PROCEDURE	18
TEST RESULT:	19
20 DB BANDWIDTH MEASUREMENT	20
TEST PROCEDURE:	20
TEST RESULT:	20
MAXIMUM PEAK OUTPUT POWER	22
TEST PROCEDURE:	22
TEST RESULT:	22
HOPPING CHANNEL SEPARATION	25
TEST PROCEDURE:	25
TEST RESULT:	25
NUMBER OF HOPPING FREQUENCY	28
TEST PROCEDURE:	28
TEST RESULT:	28
DWELL TIME	29
TEST PROCEDURE:	29
TEST RESULT:	29
ANTENNA REQUIREMENT	35

General Information

General Description of E.U.T.

Product Name	: Wireless Bluetooth speakers
Model No.	: G-807
Brand Name	: Indena
Model Description	: Series Product
Operation Frequency	: 2400MHz ~ 2483.5MHz,79 channels in total, separated by 1MHz
Type of Modulation	: GFSK
Oscillator	: 26MHz
Antenna installation	: PCB Printed Antenna
Antenna Gain	: 0dBi

Details of E.U.T.

Technical Data	: (1)DC 9V from adapter (2)AC 100-240V, 0.5A
-----------------------	---

Channel List

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	2402	2	2403	3	2404	4	2405
5	2406	6	2407	7	2408	8	2409
9	2410	10	2411	11	2412	12	2413
13	2414	14	2415	15	2416	16	2417
17	2418	18	2419	19	2420	20	2421
21	2422	22	2423	23	2424	24	2425
25	2426	26	2427	27	2428	28	2429
29	2430	30	2431	31	2432	32	2433
33	2434	34	2435	35	2436	36	2437
37	2438	38	2439	39	2440	40	2441
41	2442	42	2443	43	2444	44	2445
45	2446	46	2447	47	2448	48	2449
49	2450	50	2451	51	2452	52	2453
53	2454	54	2455	55	2456	56	2457
57	2458	58	2459	59	2460	60	2461
61	2462	62	2463	63	2464	64	2465
65	2466	66	2467	67	2468	68	2469
69	2470	70	2471	71	2472	72	2473
73	2474	74	2475	75	2476	76	2477
77	2478	78	2479	79	2480	-	-

Description of Support Units

No.	Equipment	Manufacturer	Model No.	Serial No.
1.	Notebook	SONY	PCG-51111T	27532998

Test Facility

The test facility has a test site registered with the following organizations:

NTEK Testing Technology Co., Ltd

Add.:1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen P.R. China.

FCC Registration No.:238937; IC Registration No.:9270A-1

CNAS Registration No.:L5516

Test Location

All the tests were performed at:

1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen P.R. China.

Equipment Used during Test

Equipments List

Mains Terminal Disturbance Voltage (Conducted Emission)						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	EMI Test Receiver	R&S	ESCI	101155	Sep.17,2014	1 Year
2.	LISN	SCHWARZBECK	NSLK 8128	8128-289	Sep.17,2014	1 Year
3.	Cable	LARGE	RF300	-	Sep.17,2014	1 Year
3m Semi-anechoic Chamber for Radiation						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	EMC Analyzer	Agilent	E7405A	MY45114943	Sep.17,2014	1 Year
2	Active Loop Antenna	Beijing Dazhi	ZN30900A	-	Sep.17,2014	1 Year
3	Trilog Broadband Antenna	SCHWARZBECK	VULB9163	336	Apr.19,2014	1 Year
4	Coaxial Cable (below 1GHz)	Top	TYPE16(13M)	-	Sep.17,2014	1 Year
5	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9120 D	667	Apr.19,2014	1 Year
6	Broadband Preamplifier	COMPLIANCE DIRECTION	PAP-1G18	2004	Apr.06,2014	1 Year
7	Coaxial Cable (above 1GHz)	Top	25MHz-18GHz	EW02014-7	Apr.19,2014	1 Year
8	Horn Antenna	EM	EM-AH-10180	2011071402	Apr.19,2014	1 Year

Measurement Uncertainty

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-6}$
Bandwidth	$\pm 1.5 \times 10^{-6}$
RF Power	± 1.0 dB
RF Power Density	± 2.2 dB
Temperature	± 1 °C
DC Source	$\pm 0.05\%$
Radiated Emissions test	± 5.03 dB (Bilog antenna 30M~1000MHz)
	± 4.74 dB (Horn antenna 1000M~25000MHz)
Conducted Emissions test	3.64dB (150kHz~30MHz)

Test Equipment Calibration

All the test equipments used are valid and calibrated by CEPREI Certification Body that address is No.110 Dongguan Zhuang RD. Guangzhou, P.R.China.

Conducted Emission

Test Requirement:	FCC CFR 47 Part 15 Section 15.207
Test Method:	ANSI C63.4:2003
Test Result:	PASS
Frequency Range:	150kHz to 30MHz
Class:	Class B
Limit:	66-56 dB μ V between 0.15MHz & 0.5MHz 56 dB μ V between 0.5MHz & 5MHz 60 dB μ V between 5MHz & 30MHz
Detector:	Peak for pre-scan (9kHz Resolution Bandwidth) Quasi-Peak & Average if maximised peak within 6dB of Average Limit

E.U.T. Operation

Operating Environment:


Temperature: 26°C
 Humidity: 51 % RH
 Atmospheric Pressure: 1012 mbar

EUT Operation:

The pre-test was performed in Bluetooth linking, and the data were shown as follow.
 The EUT was tested according to ANSI C63.4:2003. The frequency spectrum from 150kHz to 30MHz was investigated.
 The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.

EUT Setup


The EUT was placed on the test table in shielding room.



Conducted Emission Test Result


An initial pre-scan was performed on the live and neutral lines.
 Test Mode: Running

Live line:



Freq MHz	Reading dBuV	Factor dB	Result dBuV/m	Limit dBuV/m	Over Limit dB	Remark	Phase
0.47	46.52	1.30	47.82	56.58	-8.76	QP	LINE
0.85	44.11	1.31	45.42	56.00	-10.58	QP	LINE
1.08	43.79	1.32	45.11	56.00	-10.89	QP	LINE
1.40	43.28	1.32	44.60	56.00	-11.40	QP	LINE
1.65	43.88	1.33	45.21	56.00	-10.79	QP	LINE
2.31	46.00	1.34	47.34	56.00	-8.66	QP	LINE

Neutral line:



Freq MHz	Reading dBuV	Factor dB	Result dBuV/m	Limit dBuV/m	Over Limit dB	Remark	Phase
0.40	45.81	1.29	47.10	57.77	-10.67	QP	NEUTRAL
0.50	45.99	1.30	47.29	56.00	-8.71	QP	NEUTRAL
0.58	45.47	1.30	46.77	56.00	-9.23	QP	NEUTRAL
0.64	44.42	1.31	45.73	56.00	-10.27	QP	NEUTRAL
0.99	44.18	1.32	45.50	56.00	-10.50	QP	NEUTRAL
1.73	44.55	1.33	45.88	56.00	-10.12	QP	NEUTRAL

Spurious Radiated Emissions

Test Requirement: FCC CFR47 Part 15 Section 15.209 & 15.247

Test Method: DA 00-705

Test Result: PASS

Measurement Distance: 3m

Limit:

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	2400/F(kHz)	300	10000 * 2400/F(kHz)	$20\log^{(2400/F(kHz))} + 80$
0.490 ~ 1.705	24000/F(kHz)	30	100 * 24000/F(kHz)	$20\log^{(24000/F(kHz))} + 40$
1.705 ~ 30	30	30	100 * 30	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

EUT Operation :

Operating Environment:

Temperature: 25.5 °C

Humidity: 51 % RH


Atmospheric Pressure: 1010 mbar

Operation Mode:


The EUT was tested in transmitting mode, and the data were shown as follow.

Test Setup


The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.4: 2003.
The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.



Spectrum Analyzer Setup

According to FCC Part15 Rules, the system was tested 9kHz to 25000MHz.

Below 30MHz

Sweep Speed Auto
 IF Bandwidth..... 10kHz
 Video Bandwidth..... 10kHz
 Resolution Bandwidth..... 10kHz

30MHz ~ 1GHz

Sweep Speed Auto
 Detector PK
 Resolution Bandwidth..... 100kHz
 Video Bandwidth..... 300kHz

Above 1GHz

Sweep Speed Auto
 Detector PK
 Resolution Bandwidth..... 1MHz
 Video Bandwidth..... 3MHz
 Detector Ave.
 Resolution Bandwidth..... 1MHz
 Video Bandwidth..... 10Hz

Test Procedure

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are tested under 3-axes(X,Y,Z) position(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand), After pre-test, It was found that the worse radiation emission was get at the X position. So the data shown was the X position only.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Limit}$$

Summary of Test Results

Test Frequency :Below 30MHz

The measurements were more than 20 dB below the limit and not reported.

Test Frequency : 30MHz ~ 18GHz

Test mode: transmitting

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBµV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBµV/m)	(dBµV/m)	(dB)
GFSK Lower Channel 2402MHz									
153.24	25.02	QP	34	1.3	H	11.13	36.15	40.00	-3.85
153.24	24.35	QP	7	1.6	V	11.13	35.48	40.00	-4.52
4804.00	50.03	PK	325	1.4	V	-1.06	48.97	74.00	-25.03
4804.00	39.36	Ave	325	1.4	V	-1.06	38.30	54.00	-15.70
7206.00	40.02	PK	189	1.4	H	1.33	41.35	74.00	-32.65
7206.00	30.24	Ave	189	1.4	H	1.33	31.57	54.00	-22.43
2326.01	39.25	PK	292	1.9	V	-13.19	26.06	74.00	-47.94
2326.01	28.35	Ave	292	1.9	V	-13.19	15.16	54.00	-38.84
2380.15	37.25	PK	132	1.7	H	-13.14	24.11	74.00	-49.89
2380.15	28.25	Ave	132	1.7	H	-13.14	15.11	54.00	-38.89
2489.34	38.02	PK	210	2.0	V	-13.08	24.94	74.00	-49.06
2489.34	30.02	Ave	210	2.0	V	-13.08	16.94	54.00	-37.06

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBµV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBµV/m)	(dBµV/m)	(dB)
GFSK Center Channel 2441MHz									
153.24	25.54	QP	74	1.8	H	11.13	36.67	40.00	-3.33
153.24	25.02	QP	336	1.3	V	11.13	36.15	40.00	-3.85
4882.00	51.06	PK	63	1.2	V	-0.62	50.44	74.00	-23.56
4882.00	40.69	Ave	63	1.2	V	-0.62	40.07	54.00	-13.93
7323.00	42.03	PK	122	1.1	H	2.21	44.24	74.00	-29.76
7323.00	31.26	Ave	122	1.1	H	2.21	33.47	54.00	-20.53
2340.01	40.65	PK	250	1.6	V	-13.19	27.46	74.00	-46.54
2340.01	31.47	Ave	250	1.6	V	-13.19	18.28	54.00	-35.72
2386.57	38.59	PK	6	1.8	H	-13.14	25.45	74.00	-48.55
2386.57	29.58	Ave	6	1.8	H	-13.14	16.44	54.00	-37.56
2487.05	42.73	PK	94	1.8	V	-13.08	29.65	74.00	-44.35
2487.05	36.26	Ave	94	1.8	V	-13.08	23.18	54.00	-30.82

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBµV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBµV/m)	(dBµV/m)	(dB)
GFSK Upper Channel 2480MHz									
153.24	24.84	QP	318	1.9	H	11.13	35.97	40.00	-4.03
153.24	24.36	QP	170	1.6	V	11.13	35.49	40.00	-4.51
4960.00	50.95	PK	216	1.6	V	-0.24	50.71	74.00	-23.29
4960.00	40.25	Ave	216	1.6	V	-0.24	40.01	54.00	-13.99
7440.00	40.24	PK	237	1.5	H	2.84	43.08	74.00	-30.92
7440.00	31.25	Ave	237	1.5	H	2.84	34.09	54.00	-19.91
2326.92	38.57	PK	266	1.7	V	-13.19	25.38	74.00	-48.62
2326.92	30.25	Ave	266	1.7	V	-13.19	17.06	54.00	-36.94
2383.26	37.36	PK	306	1.5	H	-13.14	24.22	74.00	-49.78
2383.26	28.95	Ave	306	1.5	H	-13.14	15.81	54.00	-38.19
2493.10	40.14	PK	33	1.5	V	-13.08	27.06	74.00	-46.94
2493.10	30.36	Ave	33	1.5	V	-13.08	17.28	54.00	-36.72

Test Frequency :Above 18GHz

The measurements were more than 20 dB below the limit and not reported.

Band Edge Measurement



1. Test Requirement: FCC Part 15.247(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.
2. Test Method: DA 00-705
3. Test Status: Transmitting mode
4. Both hopping-on mode and hopping-off mode had been pre-tested and only the worst case (hopping –off mode) is recorded in the test report.

Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set to span from the lowest frequency generated in the device up to and including the tenth harmonic of the highest fundamental frequency.
3. Set RBW = 100kHz and VBW = 300kHz. Sweep = auto.
4. mark the worst point and record.

Test Result:

Test result plots shown as follows:



20 dB Bandwidth Measurement

Test Requirement: FCC CFR47 Part 15 Section 15.247
 Test Method: DA 00-705
 Test Mode: Test in fixing operating frequency at low, Middle, high channel.


Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 100kHz


Test Result:

Modulation	Test Channel	Bandwidth(MHz)
GFSK	Lower	0.873
	Middle	0.903
	Upper	0.910


Test result plot as follows:



GFSK Middle Channel



GFSK High Channel



Maximum Peak Output Power

Test Requirement:	FCC CFR47 Part 15 Section 15.247
Test Method:	DA 00-705
Test Limit:	Regulation 15.247 (b)(1), For frequency hopping systems operating in the 2400-2483 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483 MHz band: 0.125 watts. Refer to the result "Number of Hopping Frequency" of this document. The 1watts (30 dBm) limit applies.
Test mode:	Test in fixing frequency transmitting mode.

Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 3 MHz. VBW =3 MHz. Sweep = auto; Detector Function = Peak.
3. Keep the EUT in transmitting at lowest, medium and highest channel individually. Record the max value.


Test Result:

Modulation	Test Channel	Output Power (dBm)	Limit (dBm)
GFSK	Lower	-3.14	30
	Middle	-4.62	30
	Upper	-6.44	30


Test result plot as follows:


Test plots

GFSK Low Channel



GFSK Middle Channel





Hopping Channel Separation

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: DA 00-705

Test Limit: Regulation 15.247(a)(1) Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 1W.

Test Mode: Test in hopping transmitting operating mode.



Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 100KHz. VBW = 100KHz , Span = 6MHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section Submit this plot.


Test Result:

Modulation	Test Channel	Separation (MHz)
GFSK	Lower	1.004
	Middle	1.004
	Upper	1.004

Test result plot as follows:



GFSK High Channel



Number of Hopping Frequency


Test Requirement: FCC CFR47 Part 15 Section 15.247
 Test Method: DA 00-705
 Test Limit: Regulation 15.247 (a)(1)(iii) Frequency hopping systems in the 2400-2483 MHz band shall use at least 15 channels.
 Test Mode: Test in hopping transmitting operating mode.

Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 1MHz. VBW = 1MHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. It may prove necessary to break the span up to sections. in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section.
4. Set the spectrum analyzer: Centre Frequency = 2.441GHz, Span = 86MHz. Sweep=auto;

Test Result:

Total Channels are 79 Channels.



Dwell Time

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: DA 00-705

Test Limit: Regulation 15.247(a)(1)(iii) Frequency hopping systems in the 2400-2483 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Mode: Test in hopping transmitting operating mode.

Test Procedure:

- 1.Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
- 2.Set spectrum analyzer span = 0. centred on a hopping channel;
- 3.Set RBW = 1MHz and VBW = 1MHz. Sweep = as necessary to capture the entire dwell time per hopping channel.
- 4.Use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g.. data rate. modulation format. etc.). repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).

Test Result:

Dwell time = Pulse wide x (Hopping rate / Number of channels) x Period

The test period: $T = 0.4(s) * 79 = 31.6 (s)$

DH5 Packet permit maximum 1600 / 79 / 6 hops per second in each channel (5 time slots RX, 1 time slot TX).

DH3 Packet permit maximum 1600 / 79 / 4 hops per second in each channel (3 time slots RX, 1 time slot TX).


DH1 Packet permit maximum 1600 / 79 / 2 hops per second in each channel (1 time slot RX, 1 time slot TX).

So, the Dwell Time can be calculated as follows:


Data Packet	Dwell Time(s)
DH5	$1600/79/6*31.6*(MkrDelta)/1000$
DH3	$1600/79/4*31.6*(MkrDelta)/1000$
DH1	$1600/79/2*31.6*(MkrDelta)/1000$
Remark	Mkr Delta is single pulse time.

Modulation	Frequency	Data Packet	Mkr Delta(ms)	Dwell Time(s)	Limits(s)
GFSK	Lower channel	DH1	0.428	0.137	0.4
	Middle channel		0.432	0.138	0.4
	Upper channel		0.436	0.140	0.4
	Lower channel	DH3	1.704	0.273	0.4
	Middle channel		1.686	0.270	0.4
	Upper channel		1.692	0.271	0.4
	Lower channel	DH5	2.950	0.315	0.4
	Middle channel		2.958	0.316	0.4
	Upper channel		2.982	0.318	0.4


Modulation: GFSK
Data Packet:DH1,Lower channel




Data Packet:DH1,Middle channel




Data Packet:DH1,Upper channel




Data Packet:DH3,Lower channel




Data Packet: DH3,Middle channel




Data Packet: DH3, Upper channel




Data Packet:DH5, Lower channel



Data Packet:DH5, Middle channel



Data Packet:DH5, Upper channel



Antenna Requirement

According to the FCC Part 15 Paragraph 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. This product has a PCB printed antenna, fulfill the requirement of this section.

===== End of Test Report =====