



FCC TCB & IC CB

#### Ultratech's Accreditations:



0685



31040/SIT



C-1376



46390-2049



200093-0



SL2-IN-E-1119R

#### Korea MIC-RRL

2005-82 & 83

3000 Bristol Circle,  
Oakville, Ontario,  
Canada L6H 6G4

Tel.: (905) 829-1570  
Fax.: (905) 829-8050

Website: [www.ultratech-labs.com](http://www.ultratech-labs.com)  
Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com)

May 02, 2008

#### Federal Communication Commission

7435 Oakland Mills Road  
Columbia, MD 21046  
USA

**Subject:** Certification Application under FCC CFR 47, Parts 2 and 90  
(Subpart Z) - Wireless Broadband Services in the 3653.75-3675 MHz.

**Applicant:** Axxcelera Broadband Wireless Inc.

**Product:** Access Point  
**Model:** ETDAP-C4AC  
**FCC ID:** OJB-APC4-365

Dear Sir/Madam,

As appointed agent for Axxcelera Broadband Wireless Inc., we would like to submit the application for certification of the above product. Please review all required documents uploaded to your E-Filing web site.

If you have any queries, please do not hesitate to contact us.

Yours truly,



Tri Minh Luu, P. Eng.,  
V.P., Engineering



**Ultratech's  
Accreditations:**



0685



31040/SIT



C-1376



46390-2049



200093-0



SL2-IN-E-1119R

**Korea MIC-RRL**  
2005-82 & 83

3000 Bristol Circle,  
Oakville, Ontario,  
Canada L6H 6G4

Tel.: (905) 829-1570  
Fax.: (905) 829-8050

Website: [www.ultratech-labs.com](http://www.ultratech-labs.com)  
Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com)

May 02, 2008

**Axxcelera Broadband Wireless Inc.**

1600 E. Parham Rd.  
Richmond, Virginia  
USA 23228

**Attn.:** **Mr. Christopher Moritz**

**Subject:** **Certification Testing in accordance with FCC CFR 47, Parts 2 and 90 (Subpart Z) - Wireless Broadband Services in the 3653.75-3675 MHz.**

**Product:** **Access Point**

**Model:** **ETDAP-C4AC**

**FCC ID:** **OJB-APC4-365**

Dear Mr. Moritz,

The product sample has been tested in accordance with **FCC CFR 47, Parts 2 and 90 (Subpart Z) - Wireless Broadband Services in the 3653.75-3675 MHz**, and the results and observation were recorded in the engineering report, Our File No.: ABW-007FCC90Z.


Enclosed you will find copy of the engineering report. If you have any queries, please do not hesitate to contact us.

Yours truly,



**Tri Minh Luu, P.Eng**  
**Vice President - Engineering**

# ENGINEERING TEST REPORT



**Access Point**  
**Model No.: ETDAP-C4AC**  
**FCC ID: OJB-APC4-365**

Applicant: **Axxcelera Broadband Wireless Inc.**  
1600 E. Parham Rd.  
Richmond, Virginia  
USA 23228

*Tested in Accordance With*

**Federal Communications Commission (FCC)**  
**CFR 47, PARTS 2 and 90 (Subpart Z)**  
**Wireless Broadband Services in the 3653.75-3675 MHz**

**UltraTech's File No.: ABW-007FCC90Z**

This Test report is Issued under the Authority of  
Tri M. Luu, Professional Engineer,  
Vice President of Engineering  
UltraTech Group of Labs

Date: May 02, 2008



Report Prepared by: Dharmajit Solanki, RF Engineer

Tested by: Hung Trinh, RFI Technician

Issued Date: May 02, 2008

Test Dates: April 01-03, 2008

- The results in this Test Report apply only to the sample(s) tested, and the sample tested is randomly selected.*
- This report must not be used by the client to claim product endorsement by NVLAP or any agency of the US Government.*

## UltraTech

3000 Bristol Circle, Oakville, Ontario, Canada, L6H 6G4  
Tel.: (905) 829-1570 Fax.: (905) 829-8050

Website: [www.ultratech-labs.com](http://www.ultratech-labs.com) Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Email: [tri.luu@sympatico.ca](mailto:tri.luu@sympatico.ca)



0685



31040/SIT



C-1376



46390-2049



200093-0



SL2-IN-E-1119R

**Korea  
MIC-RRL**

2005-82 & 83

## TABLE OF CONTENTS

<b>EXHIBIT 1. INTRODUCTION .....</b>	<b>3</b>
1.1. SCOPE.....	3
1.2. RELATED SUBMITAL(S)/GRANT(S).....	4
1.3. NORMATIVE REFERENCES .....	4
<b>EXHIBIT 2. PERFORMANCE ASSESSMENT .....</b>	<b>5</b>
2.1. CLIENT INFORMATION .....	5
2.2. EQUIPMENT UNDER TEST (EUT) INFORMATION .....	5
2.3. EUT'S TECHNICAL SPECIFICATIONS .....	6
2.4. LIST OF EUT'S PORTS .....	6
2.5. ANCILLARY EQUIPMENT .....	6
<b>EXHIBIT 3. EUT OPERATING CONDITIONS AND CONFIGURATIONS DURING TESTS .....</b>	<b>7</b>
3.1. CLIMATE TEST CONDITIONS .....	7
3.2. OPERATIONAL TEST CONDITIONS & ARRANGEMENT FOR TEST SIGNALS.....	7
3.3. TEST SETUP BLOCK DIAGRAM.....	8
<b>EXHIBIT 4. SUMMARY OF TEST RESULTS .....</b>	<b>9</b>
4.1. LOCATION OF TESTS .....	9
4.2. APPLICABILITY & SUMMARY OF EMC EMISSION TEST RESULTS.....	9
4.3. MODIFICATIONS INCORPORATED IN THE EUT FOR COMPLIANCE PURPOSES .....	9
4.4. DEVIATION OF STANDARD TEST PROCEDURES.....	9
<b>EXHIBIT 5. MEASUREMENTS, EXAMINATIONS &amp; TEST DATA FOR EMC EMISSIONS.....</b>	<b>10</b>
5.1. TEST PROCEDURES .....	10
5.2. MEASUREMENT UNCERTAINTIES .....	10
5.3. MEASUREMENT EQUIPMENT USED:.....	10
5.4. ESSENTIAL/PRIMARY FUNCTIONS AS DECLARED BY THE MANUFACTURER:.....	10
5.5. POWER AND ANTENNA LIMITS @ FCC 90.1321 .....	11
5.5.1. <i>Limits</i> .....	11
5.5.2. <i>Method of Measurements</i> .....	11
5.5.3. <i>Test Equipment List</i> .....	12
5.5.4. <i>Test Arrangement</i> .....	12
5.5.5. <i>Test Data</i> .....	13
5.6. RF EXPOSURE REQUIREMENTS @ SEC. 90.1217, 1.1310 & 2.1091 .....	41
5.6.1. <i>Limits</i> .....	41
5.6.2. <i>Method of Measurements</i> .....	41
5.6.3. <i>Test Data</i> .....	43
5.7. 99% OCCUPIED BANDWIDTH @ FCC 2.1049 .....	44
5.7.1. <i>Limits</i> .....	44
5.7.2. <i>Method of Measurements</i> .....	44
5.7.3. <i>Test Equipment List</i> .....	44
5.7.4. <i>Test Arrangement</i> .....	44
5.7.5. <i>Test Data</i> .....	45
5.8. FREQUENCY STABILITY @ FCC 2.1055.....	52
5.8.1. <i>Limits</i> .....	52
5.8.2. <i>Method of Measurements</i> .....	52
5.8.3. <i>Test Equipment List</i> .....	52

---

5.8.4. <i>Test Arrangement</i> .....	52
5.8.5. <i>Test Data</i> .....	53
5.9. CONDUCTED BAND-EDGE & SPURIOUS EMISSIONS @ FCC 90.1323 .....	54
5.9.1. <i>Limits @ 90.1323</i> .....	54
5.9.2. <i>Method of Measurements</i> .....	54
5.9.3. <i>Test Equipment List</i> .....	54
5.9.4. <i>Test Arrangement</i> .....	54
5.9.5. <i>Plots</i> .....	55
5.10. TRANSMITTER SPURIOUS/HARMONIC RADIATED EMISSIONS @ FCC 90.1323 .....	72
5.10.1. <i>Limits @ 90.1323</i> .....	72
5.10.2. <i>Method of Measurements</i> .....	72
5.10.3. <i>Test Equipment List</i> .....	72
5.10.4. <i>Test Data</i> .....	73
<b>EXHIBIT 6. MEASUREMENT UNCERTAINTY</b> .....	<b>76</b>
6.1. RADIATED EMISSION MEASUREMENT UNCERTAINTY.....	76
<b>EXHIBIT 7. MEASUREMENT METHODS</b> .....	<b>77</b>
7.1. MEASURING THE EIRP OF SPURIOUS/HARMONIC EMISSIONS USING SUBSTITUTION METHOD: .....	77
7.2. FREQUENCY STABILITY .....	79

## EXHIBIT 1. INTRODUCTION

### 1.1. SCOPE

<b>Reference:</b>	FCC Parts 2 and 90 Subpart Z
<b>Title:</b>	Telecommunication - Code of Federal Regulations, CFR 47, Parts 2 & 90 Subpart Z
<b>Purpose of Test:</b>	To gain FCC Certification Authorization for Radio operating in the frequency bands 3653.75-3675 MHz
<b>Test Procedures:</b>	Both conducted and radiated emissions measurements were conducted in accordance with American National Standards Institute ANSI C63.4 - American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 KHz to 40 GHz.

**§ 90.1305 Permissible operations:-** Use of the 3653.75–3700 MHz band must be consistent with the allocations for this band as set forth in Part 2 of the Commission’s Rules. All stations operating in this band must employ a contention- based protocol (as defined in § 90.7).

**§ 90.1307 Licensing:-** The 3653.75–3700 MHz band is licensed on the basis of non-exclusive nationwide licenses. Non- exclusive nationwide licenses will serve as a prerequisite for registering individual fixed and base stations. A licensee cannot operate a fixed or base station before registering it under its license and licensees must delete registrations for unused fixed and base stations.

**§ 90.1309 Regulatory status:-** Licensees are permitted to provide services on a non-common carrier and/or on a common carrier basis. A licensee may render any kind of communications service consistent with the regulatory status in its license and with the Commission’s rules applicable to that service.

**§ 90.1311 License term:-** The license term is ten years, beginning on the date of the initial authorization (non-exclusive nationwide license) grant. Registering fixed and base stations will not change the overall renewal period of the license.

**§ 90.1312 Assignment and transfer:-** Licensees may assign or transfer their non-exclusive nationwide licenses, and any fixed or base stations registered under those licenses will remain associated with those licenses.

### § 90.1319 Policies governing the use of the 3653.75–3700 MHz band:-

- (a) Channels in this band are available on a shared basis only and will not be assigned for the exclusive use of any licensee
- (b) Any base, fixed, or mobile station operating in the band must employ a contention-based protocol.
- (c) All applicants and licensees shall cooperate in the selection and use of frequencies in the 3650–3700 MHz band in order to minimize the potential for interference and make the most effective use of the authorized facilities. A database identifying the locations of registered stations will be available at <http://wireless.fcc.gov/uls>. Licensees should examine this database before seeking station authorization, and make every effort to ensure that their fixed and base stations operate at a location, and with technical parameters, that will minimize the potential to cause and receive interference. Licensees of stations suffering or causing harmful interference are expected to cooperate and resolve this problem by mutually satisfactory arrangements.

## 1.2. RELATED SUBMITAL(S)/GRANT(S)

None

## 1.3. NORMATIVE REFERENCES

Publication	Year	Title
FCC CFR Parts 2 and 90	2007	Code of Federal Regulations – Telecommunication
ANSI C63.4	2003	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 KHz to 40 GHz
CISPR 16-1-1	2004	Specification for Radio Disturbance and Immunity measuring apparatus and methods
TIA/EIA 603, Edition C	2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards

## EXHIBIT 2. PERFORMANCE ASSESSMENT

### 2.1. CLIENT INFORMATION

APPLICANT	
<b>Name:</b>	Axxcelera Broadband Wireless Inc.
<b>Address:</b>	1600 E. Parham Rd. Richmond, Virginia USA 23228
<b>Contact Person:</b>	Mr. Christopher Moritz Phone #: 804-357-0828 Fax #: 804-864-4100 Email Address: cmoritz@axxcelera.com

MANUFACTURER	
<b>Name:</b>	Axxcelera Broadband Wireless Inc.
<b>Address:</b>	1600 E. Parham Rd. Richmond, Virginia USA 23228
<b>Contact Person:</b>	Mr. Christopher Moritz Phone #: 585-242-8374 Fax #: 585-241-5523 Email Address: cmoritz@axxcelera.com

### 2.2. EQUIPMENT UNDER TEST (EUT) INFORMATION

The following information (with the exception of the Date of Receipt) has been supplied by the applicant.

<b>Brand Name:</b>	Axxcelera Broadband Wireless Inc.
<b>Product Name:</b>	Access Point
<b>Model Name or Number:</b>	ETDAP-C4AC
<b>Serial Number:</b>	N/A
<b>EUT Application:</b>	Access Point for wireless broadband data transmission.
<b>Type of Equipment:</b>	Non-broadcast Radio Communication Equipment
<b>Power Supply:</b>	120 Vac, 60 Hz using external power supply (Manufacturer: Cinnon Electronics Co. Ltd., Model TR60A-POE-L, Input: 120/240Vac, Output: 48 Vdc)
<b>Transmitting/Receiving Antenna Type:</b>	Non-integral

## 2.3. EUT'S TECHNICAL SPECIFICATIONS

TRANSMITTER	
<b>Equipment Type:</b>	Fixed base station
<b>Intended Operating Environment:</b>	Residential, Commercial, Light Industry & Heavy Industry
<b>Power Supply Requirement:</b>	120 Vac, 60 Hz using external power supply (Manufacturer: Cinnon Electronics Co. Ltd., Model TR60A-POE-L, Input: 120/240Vac, Output: 48 Vdc)
<b>RF Output Power Rating:</b>	-21.9 to 35.1 dBm - total Peak EIRP power in 3.5 MHz BW -20.6 to 36.6 dBm - total Peak EIRP power in 7 MHz BW
<b>Operating Frequency Range:</b>	3653.75-3675 MHz (3.5 MHz BW) 3654.25-3675 MHz (7.0 MHz BW)
<b>RF Output Impedance:</b>	50 Ohms
<b>Channel Spacing:</b>	3.5 and 7 MHz
<b>Occupied Bandwidth (99%):</b>	3.18 MHz (3.5 MHz Ch) 6.34 MHz (7.0 MHz Ch)
<b>Modulation:</b>	Auto-select BPSK, QPSK, 16QAM, 64QAM
<b>Emission Designation*:</b>	3M18DXW (for 3.5 MHz BW) 6M34DXW (for 7.0 MHz BW)
<b>Antenna Connector Type:</b>	“N” type connector
<b>Antenna Description:</b>	Manufacturer: Various Type: Sector Model: 60deg, 90deg, or OMNI Frequency Range: 3.3-3.8 GHz Gain: 16.5, 14, 10 dBi
<b>Operating Temperature:</b>	-33 °C to +55 °C

## 2.4. LIST OF EUT'S PORTS

Port Number	EUT's Port Description	Number of Identical Ports	Connector Type	Cable Type (Shielded/Non-shielded)
1	RF Antenna Port	1	N	Shielded
2	Ethernet & DC Port	1	RJ45	Shielded

## 2.5. ANCILLARY EQUIPMENT

Dell Inspiron 1501 Laptop Computer, Model PP23LA, P/N: 153A01

## EXHIBIT 3. EUT OPERATING CONDITIONS AND CONFIGURATIONS DURING TESTS

### 3.1. CLIMATE TEST CONDITIONS

The climate conditions of the test environment are as follows:


Temperature:	21°C
Humidity:	25%
Pressure:	102 kPa
Power input source:	120 Vac, 60 Hz using external power supply (Manufacturer: Cinnon Electronics Co. Ltd., Model TR60A-POE-L, Input: 120/240Vac, Output: 48 Vdc)

### 3.2. OPERATIONAL TEST CONDITIONS & ARRANGEMENT FOR TEST SIGNALS

<b>Operating Modes:</b>	The transmitter was operated in a burst mode with the carrier modulated as specified in the Test Data.
<b>Special Test Software:</b>	Axxcelera Set-up Software used to setup frequency, power level and channel spacing.
<b>Transmitter Test Antenna:</b>	The EUT is tested with the transmitter antenna port terminated to a 50 Ohms RF Load.

<b>Transmitter Test Signals</b>	
<b>Frequency Band(s):</b>	Lowest, Middle & Highest frequencies in each frequency bands that the transmitter covers: <ul style="list-style-type: none"><li>▪ 3653.75 - 3675 MHz (3.5 MHz BW)</li><li>▪ 3654.25 - 3675 MHz (7.0 MHz BW)</li><li>▪ 3653.75, 3662.50 and 3675 MHz</li><li>▪ 3654.25 - 3675 MHz (3.5 MHz BW)</li></ul>
<b>Transmitter Wanted Output Test Signals:</b>	<ul style="list-style-type: none"><li>▪ RF Power Output (measured maximum output power):</li><li>▪ Normal Test Modulation</li><li>▪ Modulating signal source:</li><li>▪ -21.9 to 35.1 dBm (total Peak EIRP power in 3.5 MHz BW) and -20.6 to 36.6 dBm (total Peak EIRP power in 7 MHz BW)</li><li>▪ Auto-select BPSK, QPSK, 16QAM, 64 QAM</li><li>▪ Internal</li></ul>

### 3.3. TEST SETUP BLOCK DIAGRAM



## EXHIBIT 4. SUMMARY OF TEST RESULTS

### 4.1. LOCATION OF TESTS

All of the measurements described in this report were performed at Ultratech Group of Labs located in the city of Oakville, Province of Ontario, Canada.

- Radiated Emissions were performed at the Ultratech's 3-10 TDK Semi-Anechoic Chamber situated in the Town of Oakville, province of Ontario. This test site been calibrated in accordance with ANSI C63.4, and found to be in compliance with the requirements of Sec. 2.948 of the FCC Rules. The descriptions and site measurement data of the Oakville 3-10 TDK Semi-Anechoic Chamber has been filed with FCC office (FCC File No.: 31040/SIT 1300B3) and Industry Canada office (Industry Canada File No.: IC2049-1). Last Date of Site Calibration: May 17, 2007.

### 4.2. APPLICABILITY & SUMMARY OF EMC EMISSION TEST RESULTS

FCC PARAGRAPH	TEST REQUIREMENTS	APPLICABILITY (YES/NO)
<b>90.1321</b>	Power and Antenna Limits	Yes
<b>1.1307, 1.1310, 2.1091 &amp; 2.1093</b>	RF Exposure Limit	Yes
<b>2.1049</b>	99% Occupied Bandwidth	Yes
<b>2.1055</b>	Frequency Stability	Yes
<b>90.1323</b>	Conducted Emission Limits and Band-edge emissions	Yes
<b>90.1323</b>	Emission Limits - Field Strength of Spurious Emissions	Yes
Access Point, Model No.: ETDAP-C4AC, by Axxcelera Broadband Wireless Inc. has also been tested and found to comply with FCC Part 15, Subpart B - Radio Receivers and Class B Digital Device. The engineering test report has been documented and kept in file and it is available anytime upon FCC request.		

### 4.3. MODIFICATIONS INCORPORATED IN THE EUT FOR COMPLIANCE PURPOSES

None

### 4.4. DEVIATION OF STANDARD TEST PROCEDURES

None

## EXHIBIT 5. MEASUREMENTS, EXAMINATIONS & TEST DATA FOR EMC EMISSIONS

### 5.1. TEST PROCEDURES

This section contains test results only. Details of test methods and procedures can be found in Exhibit 8 of this report

### 5.2. MEASUREMENT UNCERTAINTIES

The measurement uncertainties stated were calculated in accordance with requirements of UKAS Document NIS 81 with a confidence level of 95%. Please refer to Exhibit 7 for Measurement Uncertainties.

### 5.3. MEASUREMENT EQUIPMENT USED:

The measurement equipment used complied with the requirements of the Standards referenced in the Methods & Procedures ANSI C63.4 and CISPR 16-1-1

### 5.4. ESSENTIAL/PRIMARY FUNCTIONS AS DECLARED BY THE MANUFACTURER:

The essential function of the EUT is to correctly communicate data to and from radios over RF link.

## 5.5. POWER AND ANTENNA LIMITS @ FCC 90.1321

### 5.5.1. Limits

#### § 90.1321 Power and antenna limits:

- (a) Base and fixed stations are limited to 25 watts/25 MHz equivalent isotropically radiated power (EIRP). In any event, the peak EIRP power density shall not exceed 1 Watt in any one megahertz slice of spectrum.
- (b) In addition to the provisions in paragraph (a) of this section, transmitters operating in the 3650–3700 MHz band that emit multiple directional beams, simultaneously or sequentially, for the purpose of directing signals to individual receivers or to groups of receivers provided the emissions comply with the following:
  - (1) Different information must be transmitted to each receiver.
  - (2) If the transmitter employs an antenna system that emits multiple directional beams but does not emit multiple directional beams simultaneously, the total output power conducted to the array or arrays that comprise the device, *i.e.*, the sum of the power supplied to all antennas, antenna elements, staves, etc. and summed across all carriers or frequency channels, shall not exceed the limit specified in paragraph (a) of this section, as applicable. The directional antenna gain shall be computed as follows:
    - (i) The directional gain, in dBi, shall be calculated as the sum of  $10 \log$  (number of array elements or staves) plus the directional gain, in dBi, of the individual element or stave having the highest gain.
    - (ii) A lower value for the directional gain than that calculated in paragraph (b)(2)(i) of this section will be accepted if sufficient evidence is presented, *e.g.*, due to shading of the array or coherence loss in the beam-forming.
  - (3) If a transmitter employs an antenna that operates simultaneously on multiple directional beams using the same or different frequency channels and if transmitted beams overlap, the power shall be reduced to ensure that the aggregate power from the overlapping beams does not exceed the limit specified in paragraph (b)(2) of this section. In addition, the aggregate power transmitted simultaneously on all beams shall not exceed the limit specified in paragraph (b)(2) of this section by more than 8 dB.
- (4) Transmitters that emit a single directional beam shall operate under the provisions of paragraph (b)(2) of this section.
- (c) Mobile and portable stations are limited to 1 watt/25 MHz EIRP. In any event, the peak EIRP density shall not exceed 40 milliwatts in any one-megahertz slice of spectrum.

### 5.5.2. Method of Measurements


- The total conducted power was measured using the Peak Power meter
- The peak conducted power density in 1 MHz was measured using an EMI receiver (spectrum analyzer) with  $RBW = 1$  MHz,  $VBW \geq RBW$ .

### 5.5.3. Test Equipment List


Test Instruments	Manufacturer	Model No.	Serial No.	Frequency Range
Peak Power Meter	Hewlett Packard	890D	2131801044	10 kHz – 50 GHz, sensor dependent
Power Sensor	Hewlett Packard	8481A	2702A68983	10 MHz – 18 GHz
Spectrum Analyzer/ EMI Receiver	Rohde & Schawrz	FSEK30	100077	20 Hz – 40 GHz with external mixer
10 dB Attenuator	Narda	4768-10	N/A	..

### 5.5.4. Test Arrangement

#### 5.5.4.1. Test Setup for Total Peak Conducted Power Measurements



#### 5.5.4.2. Test Setup for Peak Conducted Power Density Measurements



## 5.5.5. Test Data

**Note:** The following tables show the power levels with respect to antenna system assembly to achieve the maximum EIRP or EIRP density. For actual settings of power levels with respect to actual antennas used, please refer to the User's Manual.

### 5.5.5.1. Maximum Total Peak EIRP Power for 3.5 MHz Channel Bandwidth Operation

Fundamental Frequency (MHz)	Minimum Measured Peak Conducted Power (dBm) (Minimum Power Setting: -30 dBm)	Maximum Measured Peak Conducted Power (dBm) (Maximum Power Setting: 23 dBm)	Antenna System Assembly Gain Range (Ant Gain-Cable Loss) (dBi)	Calculated Maximum Total Peak EIRP (dBm)	Maximum Allowable Total Peak EIRP for fixed station uses (dBm)
<b>Modulation: BPSK</b>					
3653.75	-22.86	33.74	10 – 16.5	35.44	35.44
3662.50	-23.16	34.20	10 – 16.5	35.44	35.44
3675.00	-22.86	34.89	10 – 16.5	35.44	35.44
<b>Modulation: QPSK</b>					
3653.75	-24.21	34.77	10 – 16.5	35.44	35.44
3662.50	-21.85	34.00	10 – 16.5	35.44	35.44
3675.00	-21.61	34.80	10 – 16.5	35.44	35.44
<b>Modulation: 16QAM</b>					
3653.75	-24.20	33.68	10 – 16.5	35.44	35.44
3662.50	-22.04	34.16	10 – 16.5	35.44	35.44
3675.00	-22.96	34.92	10 – 16.5	35.44	35.44
<b>Modulation: 64QAM</b>					
3653.75	-23.90	33.91	10 – 16.5	35.44	35.44
3662.50	-22.67	34.31	10 – 16.5	35.44	35.44
3675.00	-22.66	35.09	10 – 16.5	35.44	35.44

**Notes:**

- (1) Total Peak EIRP Power allowed is 3.5W/3.5MHz for 3.5 MHz Channel Spacing
- (2) The rf output power will be varied depending on the antenna system assembly gain employed to ensure that the total Peak EIRP less than 35.44 dBm.

**5.5.5.2. Maximum Total Peak EIRP Power for 7 MHz Channel Bandwidth Operation**

Fundamental Frequency (MHz)	Minimum Measured Peak Conducted Power (dBm) (Minimum Power Setting: -30 dBm)	Maximum Measured Peak Conducted Power (dBm) (Maximum Power Setting: 23 dBm)	Antenna System Assembly Gain Range (Ant Gain-Cable Loss) (dBi)	Calculated Maximum Total Peak EIRP (dBm)	Maximum Allowable Total Peak EIRP for fixed station uses (dBm)
<b>Modulation: BPSK</b>					
3654.25	-22.73	35.89	10 – 16.5	38.45	38.45
3662.50	-22.97	36.35	10 – 16.5	38.45	38.45
3675.00	-20.91	36.23	10 – 16.5	38.45	38.45
<b>Modulation: QPSK</b>					
3654.25	-22.76	35.02	10 – 16.5	38.45	38.45
3662.50	-21.82	35.34	10 – 16.5	38.45	38.45
3675.00	-21.76	35.20	10 – 16.5	38.45	38.45
<b>Modulation: 16QAM</b>					
3654.25	-22.69	35.40	10 – 16.5	38.45	38.45
3662.50	-21.37	36.07	10 – 16.5	38.45	38.45
3675.00	-21.35	35.75	10 – 16.5	38.45	38.45
<b>Modulation: 64QAM</b>					
3654.25	-21.68	35.83	10 – 16.5	38.45	38.45
3662.50	-21.86	36.62	10 – 16.5	38.45	38.45
3675.00	-20.63	36.18	10 – 16.5	38.45	38.45

**Notes:**

- (1) Total Peak EIRP Power allowed is 7 W/ 7 MHz for 7 MHz Channel Spacing
- (2) The rf output power will be varied depending on the antenna system assembly gain employed to ensure that the total Peak EIRP less than 38.45 dBm.

**5.5.5.3. Maximum Peak EIRP Power Density in 1 MHz BW for 3.5 MHz Channel Bandwidth Operation**

Fundamental Frequency (MHz)	Minimum Measured Peak EIRP Density in 1 MHz BW (dBm/MHz)  (Minimum Power Setting: -30 dBm)	Maximum Measured Peak EIRP Density in 1 MHz BW (dBm/MHz)  (Maximum Power Setting: 23 dBm)	Antenna System Assembly Gain Range (Ant Gain-Cable Loss) (dBi)	Calculated Maximum Peak EIRP Density in 1 MHz BW (dBm/MHz)	FCC Peak EIRP Density in 1 MHz BW Limits (dBm/MHz)
<b>Modulation: BPSK</b>					
3653.75	-28.3	28.30	10 – 16.5	30.0	30.0
3662.50	-28.6	28.76	10 – 16.5	30.0	30.0
3675.00	-28.3	29.45	10 – 16.5	30.0	30.0
<b>Modulation: QPSK</b>					
3653.75	-29.65	29.33	10 – 16.5	30.0	30.0
3662.50	-27.29	28.56	10 – 16.5	30.0	30.0
3675.00	-27.05	29.36	10 – 16.5	30.0	30.0
<b>Modulation: 16QAM</b>					
3653.75	-29.64	28.24	10 – 16.5	30.0	30.0
3662.50	-27.48	28.72	10 – 16.5	30.0	30.0
3675.00	-28.40	29.48	10 – 16.5	30.0	30.0
<b>Modulation: 64QAM</b>					
3653.75	-29.34	28.47	10 – 16.5	30.0	30.0
3662.50	-28.11	28.87	10 – 16.5	30.0	30.0
3675.00	-28.10	29.65	10 – 16.5	30.0	30.0

**Notes:**

- (1) The rf output power will be varied depending on the antenna system assembly gain employed to ensure that the total peak EIRP less than 30 dBm.
- (2) Refer to Plots # 1(a), (b), (c) and (d) to 3(a), (b), (c) and (d) for details of measurements , with the maximum power settings.


**5.5.5.4. Maximum Peak EIRP Power Density in 1 MHz BW for 7 MHz Channel Bandwidth Operation**

Fundamental Frequency (MHz)	Minimum Measured Peak EIRP Density in 1 MHz BW (dBm/MHz) (Minimum Power Setting: -30 dBm)	Maximum Measured Peak EIRP Density in 1 MHz BW (dBm/MHz) (Maximum Power Setting: 23 dBm)	Antenna System Assembly Gain Range (Ant Gain-Cable Loss) (dBi)	Calculated Maximum Peak EIRP Density in 1 MHz BW (dBm/MHz)	FCC Peak EIRP Density in 1 MHz BW Limits (dBm/MHz)
<b>Modulation: BPSK</b>					
3654.25	-31.18	27.44	10 – 16.5	30.0	30.0
3662.50	-31.42	27.90	10 – 16.5	30.0	30.0
3675.00	-29.36	27.78	10 – 16.5	30.0	30.0
<b>Modulation: QPSK</b>					
3654.25	-31.21	26.57	10 – 16.5	30.0	30.0
3662.50	-30.27	26.89	10 – 16.5	30.0	30.0
3675.00	-30.21	26.75	10 – 16.5	30.0	30.0
<b>Modulation: 16QAM</b>					
3654.25	-31.14	26.95	10 – 16.5	30.0	30.0
3662.50	-29.82	27.62	10 – 16.5	30.0	30.0
3675.00	-29.80	27.30	10 – 16.5	30.0	30.0
<b>Modulation: 64QAM</b>					
3654.25	-30.13	27.38	10 – 16.5	30.0	30.0
3662.50	-30.31	28.17	10 – 16.5	30.0	30.0
3675.00	-29.08	27.73	10 – 16.5	30.0	30.0

**Notes:**

- (1) The rf output power will be varied depending on the antenna system assembly gain employed to ensure that the total peak EIRP less than 30 dBm.
- (2) Refer to Plots # 4(a), (b), (c) and (d) to 6(a), (b), (c) and (d) for details of measurements , with the maximum power settings.

Plot # 1(a): Peak Conducted Power Density Measurement (Maximum Power Setting: 23 dBm)  
Center Freq.: 3653.75 MHz, Ch Spacing: 3.5 MHz, Modulation: BPSK




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>


File #: ABW-007FCC90Z  
May 02, 2008

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)


Plot # 1(b): Peak Conducted Power Density Measurement (Maximum Power Setting: 23 dBm)  
Center Freq.: 3653.75 MHz, Ch Spacing: 3.5 MHz, Modulation: QPSK



Plot # 1(c): Peak Conducted Power Density Measurement (Maximum Power Setting: 23 dBm)  
Center Freq.: 3653.75 MHz, Ch Spacing: 3.5 MHz, Modulation: 16QAM



Plot # 1(d): Peak Conducted Power Density Measurement (Maximum Power Setting: 23 dBm)  
Center Freq.: 3653.75 MHz, Ch Spacing: 3.5 MHz, Modulation: 64QAM




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>


File #: ABW-007FCC90Z  
May 02, 2008

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)


Plot # 2(a): Peak Conducted Power Density Measurement (Maximum Power Setting: 23 dBm)  
Center Freq.: 3662.50 MHz, Ch Spacing: 3.5 MHz, Modulation: BPSK




Plot # 2(b): Peak Conducted Power Density Measurement (Maximum Power Setting: 23 dBm)  
Center Freq.: 3662.50 MHz, Ch Spacing: 3.5 MHz, Modulation: QPSK



Plot # 2(c): Peak Conducted Power Density Measurement (Maximum Power Setting: 23 dBm)  
Center Freq.: 3662.50 MHz, Ch Spacing: 3.5 MHz, Modulation: 16QAM



Plot # 2(d): Peak Conducted Power Density Measurement (Maximum Power Setting: 23 dBm)  
Center Freq.: 3662.50 MHz, Ch Spacing: 3.5 MHz, Modulation: 64QAM




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>


File #: ABW-007FCC90Z  
May 02, 2008

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)


Plot # 3(a): Peak Conducted Power Density Measurement (Maximum Power Setting: 23 dBm)  
Center Freq.: 3675 MHz, Ch Spacing: 3.5 MHz, Modulation: BPSK




Plot # 3(b): Peak Conducted Power Density Measurement (Maximum Power Setting: 23 dBm)  
Center Freq.: 3750 MHz, Ch Spacing: 3.5 MHz, Modulation: QPSK




Plot # 3(c): Peak Conducted Power Density Measurement (Maximum Power Setting: 23 dBm)  
Center Freq.: 3750 MHz, Ch Spacing: 3.5 MHz, Modulation: 16QAM




Plot # 3(d): Peak Conducted Power Density Measurement (Maximum Power Setting: 23 dBm)  
Center Freq.: 3750 MHz, Ch Spacing: 3.5 MHz, Modulation: 64QAM



Plot # 4(a): Peak Conducted Power Density Measurement (Maximum Power Setting: 23 dBm)  
Center Freq.: 3654.25 MHz, Ch Spacing: 7 MHz, Modulation: BPSK



Plot # 4(b): Peak Conducted Power Density Measurement (Maximum Power Setting: 23 dBm)  
Center Freq.: 3654.25 MHz, Ch Spacing: 7 MHz, Modulation: QPSK




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: ABW-007FCC90Z  
May 02, 2008

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

Plot # 4(c): Peak Conducted Power Density Measurement (Maximum Power Setting: 23 dBm)  
Center Freq.: 3654.25 MHz, Ch Spacing: 7 MHz, Modulation: 16QAM




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: ABW-007FCC90Z  
May 02, 2008

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

Plot # 4(d): Peak Conducted Power Density Measurement (Maximum Power Setting: 23 dBm)  
Center Freq.: 3654.25 MHz, Ch Spacing: 7 MHz, Modulation: 64QAM




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>


File #: ABW-007FCC90Z  
May 02, 2008

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)


Plot # 5(a): Peak Conducted Power Density Measurement (Maximum Power Setting: 23 dBm)  
Center Freq.: 3662.50 MHz, Ch Spacing: 7 MHz, Modulation: BPSK




Plot # 5(b): Peak Conducted Power Density Measurement (Maximum Power Setting: 23 dBm)  
Center Freq.: 3662.50 MHz, Ch Spacing: 7 MHz, Modulation: QPSK




Plot # 5(c): Peak Conducted Power Density Measurement (Maximum Power Setting: 23 dBm)  
Center Freq.: 3662.50 MHz, Ch Spacing: 7 MHz, Modulation: 16QAM




Plot # 5(d): Peak Conducted Power Density Measurement (Maximum Power Setting: 23 dBm)  
Center Freq.: 3662.50 MHz, Ch Spacing: 7 MHz, Modulation: 64QAM




Plot # 6(a): Peak Conducted Power Density Measurement (Maximum Power Setting: 23 dBm)  
Center Freq.: 3750 MHz, Ch Spacing: 7 MHz, Modulation: BPSK




Plot # 6(b): Peak Conducted Power Density Measurement (Maximum Power Setting: 23 dBm)  
Center Freq.: 3750 MHz, Ch Spacing: 7 MHz, Modulation: QPSK



Plot # 6(c): Peak Conducted Power Density Measurement (Maximum Power Setting: 23 dBm)  
Center Freq.: 3750 MHz, Ch Spacing: 7 MHz, Modulation: 16QAM



Plot # 6(d): Peak Conducted Power Density Measurement (Maximum Power Setting: 23 dBm)  
Center Freq.: 3750 MHz, Ch Spacing: 3.5 MHz, Modulation: 64QAM



## 5.6. RF EXPOSURE REQUIREMENTS @ SEC. 90.1217, 1.1310 & 2.1091

### 5.6.1. Limits

- **FCC 1.1310:-** The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b).

**LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)**

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (minutes)
<b>(A) Limits for Occupational/Control Exposures</b>				
1500-100,000	...	...	5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
1500-100,000	...	...	1.0	30

F = Frequency in MHz

### 5.6.2. Method of Measurements

Refer to FCC @ 1.1310, 2.1091 and Public Notice DA 00-705 (March 30, 2000)

- Spread spectrum transmitters operating under section 15.247 are categorically from routine environmental evaluation to demonstrating RF exposure compliance with respect to MPE and/or SAR limits. These devices are not exempted from compliance (As indicated in Section 15.247(b)(4), these transmitters are required to operate in a manner that ensures that exposure to public users and nearby persons) does not exceed the Commission's RF exposure guidelines (see Section 1.1307 and 2.1093). Unless a device operates at substantially low power levels, with a low gain antenna(s), supporting information is generally needed to establish the various potential operating configurations and exposure conditions of a transmitter and its antenna(s) in order to determine compliance with the RF exposure guidelines.
- In order to demonstrate compliance with MPE requirements (see Section 2.1091), the following information is typically needed:
  - (1) Calculation that estimates the minimum separation distance (20 cm or more) between an antenna and persons required to satisfy power density limits defined for free space.
  - (2) Antenna installation and device operating instructions for installers (professional/unskilled users), and the parties responsible for ensuring compliance with the RF exposure requirement
  - (3) Any caution statements and/or warning labels that are necessary in order to comply with the exposure limits
  - (4) Any other RF exposure related issues that may affect MPE compliance

**Calculation Method of RF Safety Distance:**

$$S = PG/4\pi r^2 = EIRP/4\pi r^2$$

Where:

P: power input to the antenna in mW

EIRP: Equivalent (effective) isotropic radiated power.

S: power density mW/cm<sup>2</sup>

G: numeric gain of antenna relative to isotropic radiator

r: distance to centre of radiation in cm

FCC radio frequency exposure limits may be exceeded at distances closer than r cm from the antenna of this device

$$r = \sqrt{\frac{PG}{4\pi S}}$$

FCC radio frequency exposure limits may not be exceeded at distances closer than r cm from the antenna of this device

- For portable transmitters (see Section 2.1093), or devices designed to operate next to a person's body, compliance is determined with respect to the SAR limit (define in the body tissues) for near-field exposure conditions. If the maximum average output power, operating condition configurations and exposure conditions are comparable to those of existing cellular and PCS phones., an SAR evaluation may be required in order to determine if such a device complies with SAR limit. When SAR evaluation data is not available, and the additional supporting information cannot assure compliance, the Commission may request that a SAR evaluation be performed, as provided for in Section 1.1307(d)

### 5.6.3. Test Data

Antennas Gain Range specified by Manufactuer: 10.0 dBi

Frequency (MHz)	Channel Spacing (MHz)	Maximum Total Peak EIRP Power (dBm)	Laboratory's Recommended Minimum RF Safety Distance $r$ (cm)
3653.75	7.0	38.4	24
3653.75	3.5	35.4	20

Note 1: RF EXPOSURE DISTANCE LIMITS:  $r = (PG/4\pi S)^{1/2} = (EIRP/4\pi S)^{1/2}$   
 $S = 1.0 \text{ mW/cm}^2$

For 7 MHz channel spacing:

$$r = (PG/4\pi S)^{1/2} = (EIRP/4\pi S)^{1/2} \\ = (7000/4 \times 3.14 \times 1)^{1/2} \\ = 23.6 \text{ cm}$$

For 3.5 MHz channel spacing:

$$r = (PG/4\pi S)^{1/2} = (EIRP/4\pi S)^{1/2} \\ = (3500/4 \times 3.14 \times 1)^{1/2} \\ = 16.7 \text{ cm}$$

Evaluation of RF Exposure Compliance Requirements	
RF Exposure Requirements	Compliance with FCC Rules
Minimum calculated separation distance between antenna and persons required: 23.6 cm (7 MHz channel spacing) & 16.7 cm (3.5 MHz channel spacing)	Manufacturer's instruction for separation distance between antenna and persons required: 25 cm. Please refer to page # 7 of the User Manual.
Antenna installation and device operating instructions for installers (professional/unskilled users), and the parties responsible for ensuring compliance with the RF exposure requirement	Professional Installation only, Refer to Page # 7 of the User Manual for details.
Caution statements and/or warning labels that are necessary in order to comply with the exposure limits	Please refer to page # 7 of the User Manual.

## 5.7. 99% OCCUPIED BANDWIDTH @ FCC 2.1049

### 5.7.1. Limits

Not Specified.


### 5.7.2. Method of Measurements

The 99% occupied bandwidth is measured using EMI receiver (spectrum analyzer) with RBW = 1% of 99% OBW, VBW >= RBW.

### 5.7.3. Test Equipment List

Test Instruments	Manufacturer	Model No.	Serial No.	Frequency Range
Spectrum Analyzer/ EMI Receiver	Rohde & Schawrz	FSEK30	100077	20 Hz – 40 GHz with external mixer
10 dB Attenuator	Narda	4768-10	N/A	..

### 5.7.4. Test Arrangement




### 5.7.5. Test Data

**Remark:** Since the 99% OBW were pre-scanned and found to be the same with all different modulations, the final 99% OBW measurements with 64QAM


Transmitter Channel	Fundamental Frequency (MHz)	Channel Spacing (MHz)	99% Occupied Bandwidth (MHz)
Lowest	3653.75	3.5	3.18
Middle	3662.50	3.5	3.18
Highest	3675.00	3.5	3.18
Lowest	3654.25	7.0	6.34
Middle	3662.50	7.0	6.34
Highest	3675.00	7.0	6.34

Please refer to Plots # 7 to 12 for details of measurements.


**Plot # 7: 99% Occupied Bandwidth**  
**Center Freq.: 3653.75 MHz, Ch Spacing: 3.5 MHz, Modulation: 64QAM**




**Plot # 8: 99% Occupied Bandwidth**  
**Center Freq.: 3662.50 MHz, Ch Spacing: 3.5 MHz, Modulation: 64QAM**




**Plot # 9: 99% Occupied Bandwidth**  
**Center Freq.: 3675 MHz, Ch Spacing: 3.5 MHz, Modulation: 64QAM**




**Plot # 10: 99% Occupied Bandwidth**  
**Center Freq.: 3654.25 MHz, Ch Spacing: 7 MHz, Modulation: 64QAM**



**Plot # 11: 99% Occupied Bandwidth**  
**Center Freq.: 3662.50 MHz, Ch Spacing: 7 MHz, Modulation: 64QAM**



**Plot # 12: 99% Occupied Bandwidth**  
**Center Freq.: 3675 MHz, Ch Spacing: 7 MHz, Modulation: 64QAM**



## 5.8. FREQUENCY STABILITY @ FCC 2.1055

### 5.8.1. Limits

The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

### 5.8.2. Method of Measurements


Refer to Exhibit 7, Section 7.2 for details of measurement methods.

The frequency stability will be specified in the station authorization. For the purpose of compliance, the carrier frequency stability will be checked for out-of-band emissions at room temperature (20°C) and extreme temperatures (-30°C and +50°C).

### 5.8.3. Test Equipment List

Test Instruments	Manufacturer	Model No.	Serial No.	Frequency Range
Spectrum Analyzer/ EMI Receiver	Rohde & Schawrz	FSEK30	100077	20 Hz – 40 GHz with external mixer
10 dB Attenuator	Narda	4768-10	N/A	DC – 22 GHz
Temperature & Humidity Chamber	Tenney	T5	9723B	-40° to +60° C range

### 5.8.4. Test Arrangement



### 5.8.5. Test Data

<b>Center Frequency:</b>	3653.75 MHz
<b>Total Peak Power Level:</b>	23.28 dBm (conducted)
<b>Frequency Tolerance Limit:</b>	Not Specified
<b>Max. Frequency Tolerance Measured:</b>	- 6682 Hz or 0.0018 ppm
<b>Input Voltage Rating:</b>	120 V AC

Frequency Tolerance CENTER FREQUENCY (Hz)			
Ambient Temperature	Supply Voltage (120 V, 60 Hz Nominal) Volts	Supply Voltage (102 V, 650Hz - 85% Nominal) 100 Volts	Supply Voltage (138V, 60Hz - 115% Nominal) 240 Volts
(°C)	Hz	Hz	Hz
-33	6682	N/A	N/A
+20	0	55	99
+55	-5770	N/A	N/A

## 5.9. CONDUCTED BAND-EDGE & SPURIOUS EMISSIONS @ FCC 90.1323

### 5.9.1. Limits @ 90.1323

(a) The power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least  $43 + 10 \log (P)$  dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or less, but at least one percent of the emission bandwidth of the fundamental emission of the transmitter, provided the measured energy is integrated over a 1 MHz bandwidth.

(b) When an emission outside of the authorized bandwidth causes harmful interference, the Commission may, at its discretion, require greater attenuation than specified in this section.


### 5.9.2. Method of Measurements

With transmitter modulation characteristics described in Out-of-Band Emissions measurements @ 2.1049 and the transmitter was operated in full rated power, the transmitter spurious and harmonic emissions were scanned. The spurious and harmonic emissions were measured with the EMI Receiver controls set as RBW = 1 MHz, VBW  $\geq$  RBW and SWEEP TIME = AUTO).

### 5.9.3. Test Equipment List

Test Instruments	Manufacturer	Model No.	Serial No.	Frequency Range
Spectrum Analyzer/ EMI Receiver	Rohde & Schawrz	FSEK30	100077	20 Hz – 40 GHz with external mixer
10 dB Attenuator	Narda	4768-10	N/A	DC – 22 GHz
Audio Oscillator	Hewlett Packard	HP 204C	0989A08798	DC to 1.2 MHz

### 5.9.4. Test Arrangement




### 5.9.5. Plots


**Remark:** The transmitter setting with maximum output and 64QAM will be selected to test for final since it was found their characteristics are the same with different modulations.

- **Conducted Band-edge Emissions: conforms, please refer to Plots # 13(a)&(b) through # 14(a)&(b) for details of measurements.**
- **Conducted Spurious Emissions: conforms, please refer to Plots # 15(a)&(b) through # 20(a)&(b) for details of measurements from 30 MHz to 40 GHz.**


**Plot # 13(a): Conducted Band-edge Emissions (Lower Edge)**  
**Center Freq.: 3653.75 MHz, Power Setting: High, Ch. Spacing: 3.5 MHz**




**Plot # 13(b): Conducted Band-edge Emissions (Higher Edge)  
Center Freq.: 3675 MHz, Power Setting: High, Ch. Spacing: 3.5 MHz**



**Plot # 14(a): Conducted Band-edge Emissions (Lower Edge)  
Center Freq.: 3654.25 MHz, Power Setting: High, Ch. Spacing: 7 MHz**




**Plot # 14(b): Conducted Band-edge Emissions (Higher Edge)  
Center Freq.: 3675 MHz, Power Setting: High, Ch. Spacing: 7 MHz**




**Plot # 15(a): Transmitter Conducted Spurious Emissions**

Center Freq.: 3653.75 MHz, Power Setting: High (23 dBm), Ch. Spacing: 3.5 MHz,  
Modulation: 64QAM




**Plot # 15(b): Transmitter Conducted Spurious Emissions**

Center Freq.: 3653.75 MHz, Power Setting: High (23 dBm), Ch. Spacing: 3.5 MHz,  
Modulation: 64QAM




**Plot # 16(a): Transmitter Conducted Spurious Emissions**

Center Freq.: 3662.50 MHz, Power Setting: High (23 dBm), Ch. Spacing: 3.5 MHz,  
Modulation: 64QAM




**Plot # 16(b): Transmitter Conducted Spurious Emissions**

Center Freq.: 3662.50 MHz, Power Setting: High (23 dBm), Ch. Spacing: 3.5 MHz,  
Modulation: 64QAM




**Plot # 17(a): Transmitter Conducted Spurious Emissions**

Center Freq.: 3675.00 MHz, Power Setting: High (23 dBm), Ch. Spacing: 3.5 MHz,  
Modulation: 64QAM




**Plot # 17(b): Transmitter Conducted Spurious Emissions**

Center Freq.: 3675.00 MHz, Power Setting: High (23 dBm), Ch. Spacing: 3.5 MHz,  
Modulation: 64QAM




**Plot # 18(a): Transmitter Conducted Spurious Emissions**  
Center Freq.: 3653.75 MHz, Power Setting: High (23 dBm), Ch. Spacing: 7 MHz,  
Modulation: 64QAM




## Plot # 18(b): Transmitter Conducted Spurious Emissions

**Center Freq.: 3653.75 MHz, Power Setting: High (23 dBm), Ch. Spacing: 7 MHz,  
Modulation: 64QAM**




**Plot # 19(a): Transmitter Conducted Spurious Emissions**  
Center Freq.: 3662.50 MHz, Power Setting: High (23 dBm), Ch. Spacing: 7 MHz,  
Modulation: 64QAM




**Plot # 19(b): Transmitter Conducted Spurious Emissions**

Center Freq.: 3662.50 MHz, Power Setting: High (23 dBm), Ch. Spacing: 7 MHz,  
Modulation: 64QAM




**Plot # 20(a): Transmitter Conducted Spurious Emissions**

Center Freq.: 3675.00 MHz, Power Setting: High (23 dBm), Ch. Spacing: 7 MHz,  
Modulation: 64QAM



**Plot # 20(b): Transmitter Conducted Spurious Emissions**

Center Freq.: 3675.00 MHz, Power Setting: High (23 dBm), Ch. Spacing: 7 MHz,  
Modulation: 64QAM



## 5.10. TRANSMITTER SPURIOUS/HARMONIC RADIATED EMISSIONS @ FCC 90.1323

### 5.10.1. Limits @ 90.1323

- (a) The power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least  $43 + 10 \log (P)$  dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or less, but at least one percent of the emission bandwidth of the fundamental emission of the transmitter, provided the measured energy is integrated over a 1 MHz bandwidth.
- (b) When an emission outside of the authorized bandwidth causes harmful interference, the Commission may, at its discretion, require greater attenuation than specified in this section.

### 5.10.2. Method of Measurements

The spurious/harmonic ERP measurements are using substitution method specified in Exhibit 7, § 7.1 of this report and its value in dBc is calculated as follows:

1. If the transmitter's antenna is an integral part of the EUT, the ERP is measured using substitution method.
2. If the transmitter's antenna is non-integral and diverse, the lowest ERP of the carrier with 0 dBi antenna gain is used for calculation of the spurious/harmonic emissions in dBc:
3. Lowest ERP of the carrier =  $EIRP - 2.15 \text{ dB} = P_c + G - 2.15 \text{ dB} = \text{xxx dBm (conducted)} + 0 \text{ dBi} - 2.15 \text{ dB}$
4. Spurious /harmonic emissions levels expressed in dBc (dB below carrier) are as follows:

$$\text{ERP of spurious/harmonic (dBc)} = \text{ERP of carrier (dBm)} - \text{ERP of spurious/harmonic emission (dBm)}$$

### 5.10.3. Test Equipment List

Test Instruments	Manufacturer	Model No.	Serial No.	Frequency Range
Spectrum Analyzer/ EMI Receiver	Rohde & Schwarz	FSEK20/B4/B21	834157/005	9 kHz – 40 GHz with external mixer
RF Amplifier	Com-Power	PA-102		1 MHz to 1 GHz, 30 dB gain nominal
Microwave Amplifier	Hewlett Packard	HP 8449B	300BA00769	1 GHz to 26.5 GHz, 30 dB nominal
Biconilog Antenna	EMCO	3142	10005	30 MHz to 2 GHz
Dipole Antenna	EMCO	3121C	8907-434	30 GHz – 1 GHz
Horn Antenna	EMCO	3155	9911-5955	1 GHz – 18 GHz
Horn Antenna	EMCO	3160-09	1007	18 GHz – 26.5 GHz
Horn Antenna		RA28-K-T-4B-C	920311-001	26.5 GHz – 40 GHz
RF Signal Generator	Hewlett Packard	HP 83752B	3610A00457	0.01 – 20 GHz

#### 5.10.4. Test Data

##### 5.10.4.1. Lowest Frequency (3653.75 MHz), Channel Bandwidth: 3.5 MHz

Fundamental Frequency:	3653.75 MHz					
Channel Bandwidth:	3.5 MHz					
Modulation:	64QAM					
RF Output Power:	22.82 dBm (total conducted Peak Power) wrt. To power setting: 23 dBm					
Test Frequency Range:	30 MHz – 40 GHz					
Frequency (MHz)	E-Field (dB $\mu$ V/m)	EMI Detector (Peak/QP)	Antenna Polarization (H/V)	ERP measured by Substitution Method (dBm)	Limit (dBm)	Margin (dB)
7307.500	60.76	Peak	V	-36.18	-13.0	-23.2
7307.500	63.50	Peak	H	-33.44	-13.0	-20.4

\*\*\* All other emissions are more than 30 dB below the limit.

##### 5.10.4.2. Middle Frequency (3662.50 MHz), Channel Bandwidth: 3.5 MHz

Fundamental Frequency:	3662.50 MHz					
Channel Bandwidth:	3.5 MHz					
Modulation:	64QAM					
RF Output Power:	23.32 dBm (total conducted Peak Power) wrt. To power setting: 23 dBm					
Test Frequency Range:	30 MHz – 40 GHz					
Frequency (MHz)	E-Field (dB $\mu$ V/m)	EMI Detector (Peak/QP)	Antenna Polarization (H/V)	ERP measured by Substitution Method (dBm)	Limit (dBm)	Margin (dB)
7325.000	65.08	Peak	V	-31.81	-13	-18.8
7325.000	66.04	Peak	H	-30.85	-13	-17.9

\*\*\* All other emissions are more than 30 dB below the limit.

**5.10.4.3. Highest Frequency (3675 MHz), Channel Bandwidth: 3.5 MHz**

Fundamental Frequency:	3675.00 MHz					
Channel Bandwidth:	3.5 MHz					
Modulation:	64QAM					
RF Output Power:	23.05 dBm (total conducted Peak Power) wrt. To power setting: 23 dBm					
Test Frequency Range:	30 MHz – 40 GHz					
Frequency (MHz)	E-Field (dB $\mu$ V/m)	EMI Detector (Peak/QP)	Antenna Polarization (H/V)	ERP measured by Substitution Method (dBm)	Limit (dBm)	Margin (dB)
7350.000	62.71	Peak	V	-34.07	-13	-21.1
7350.000	65.59	Peak	H	-31.19	-13	-18.2

\*\*\* All other emissions are more than 30 dB below the limit.

**5.10.4.4. Lowest Frequency (3654.25 MHz), Channel Bandwidth: 7 MHz**

Fundamental Frequency:	3654.25 MHz					
Channel Bandwidth:	7 MHz					
Modulation:	64QAM					
RF Output Power:	22.82 dBm (total conducted Peak Power) wrt. To power setting: 23 dBm					
Test Frequency Range:	30 MHz – 40 GHz					
Frequency (MHz)	E-Field (dB $\mu$ V/m)	EMI Detector (Peak/QP)	Antenna Polarization (H/V)	ERP measured by Substitution Method (dBm)	Limit (dBm)	Margin (dB)
7308.500	53.06	Peak	V	-43.88	-13	-30.9
7308.500	54.14	Peak	H	-42.80	-13	-29.8

\*\*\* All other emissions are more than 30 dB below the limit.

**5.10.4.5. Middle Frequency (3662.50 MHz), Channel Bandwidth: 7 MHz**

Fundamental Frequency:	3662.50 MHz					
Channel Bandwidth:	7 MHz					
Modulation:	64QAM					
RF Output Power:	22.81 dBm (total conducted Peak Power) wrt. To power setting: 23 dBm					
Test Frequency Range:	30 MHz – 40 GHz					
Frequency (MHz)	E-Field (dB $\mu$ V/m)	EMI Detector (Peak/QP)	Antenna Polarization (H/V)	ERP measured by Substitution Method (dBm)	Limit (dBm)	Margin (dB)
7325.000	59.31	Peak	V	-37.58	-13	-24.6
7325.000	58.33	Peak	H	-38.56	-13	-25.6

\*\*\* All other emissions are more than 30 dB below the limit.

**5.10.4.6. Highest Frequency (3675 MHz), Channel Bandwidth: 7 MHz**

Fundamental Frequency:	3675.00 MHz					
Channel Bandwidth:	7 MHz					
Modulation:	64QAM					
RF Output Power:	22.92 dBm (total conducted Peak Power) wrt. To power setting: 23 dBm					
Test Frequency Range:	30 MHz – 40 GHz					
Frequency (MHz)	E-Field (dB $\mu$ V/m)	EMI Detector (Peak/QP)	Antenna Polarization (H/V)	ERP measured by Substitution Method (dBm)	Limit (dBm)	Margin (dB)
7350.000	55.78	Peak	V	-41.00	-13	-28.0
7350.000	56.53	Peak	H	-40.25	-13	-27.3

\*\*\* All other emissions are more than 30 dB below the limit.

## EXHIBIT 6. MEASUREMENT UNCERTAINTY

The measurement uncertainties stated were calculated in accordance with the requirements of NIST Technical Note 1297 and NIS 81 (1994)

### 6.1. RADIATED EMISSION MEASUREMENT UNCERTAINTY

CONTRIBUTION (Radiated Emissions)	PROBABILITY DISTRIBUTION	UNCERTAINTY ( $\pm$ dB)	
		3 m	10 m
Antenna Factor Calibration	Normal (k=2)	$\pm 1.0$	$\pm 1.0$
Cable Loss Calibration	Normal (k=2)	$\pm 0.3$	$\pm 0.5$
EMI Receiver specification	Rectangular	$\pm 1.5$	$\pm 1.5$
Antenna Directivity	Rectangular	$+0.5$	$+0.5$
Antenna factor variation with height	Rectangular	$\pm 2.0$	$\pm 0.5$
Antenna phase center variation	Rectangular	0.0	$\pm 0.2$
Antenna factor frequency interpolation	Rectangular	$+0.25$	$+0.25$
Measurement distance variation	Rectangular	$\pm 0.6$	$\pm 0.4$
Site imperfections	Rectangular	$\pm 2.0$	$\pm 2.0$
Mismatch: Receiver VRC $\Gamma_1 = 0.2$ Antenna VRC $\Gamma_R = 0.67(Bi)$ 0.3 (Lp) Uncertainty limits $20\log(1+\Gamma_1\Gamma_R)$	U-Shaped	+1.1 -1.25	$\pm 0.5$
System repeatability	Std. Deviation	$\pm 0.5$	$\pm 0.5$
Repeatability of EUT		-	-
Combined standard uncertainty	Normal	+2.19 / -2.21	+1.74 / -1.72
Expanded uncertainty U	Normal (k=2)	+4.38 / -4.42	+3.48 / -3.44

Calculation for maximum uncertainty when 3m biconical antenna including a factor of k=2 is used:

$$U = 2u_c(y) = 2x(+2.19) = +4.38 \text{ dB} \quad \text{And} \quad U = 2u_c(y) = 2x(-2.21) = -4.42 \text{ dB}$$

## EXHIBIT 7. MEASUREMENT METHODS

### 7.1. MEASURING THE EIRP OF SPURIOUS/HARMONIC EMISSIONS USING SUBSTITUTION METHOD:

(a) Set the EMI Receiver (for measuring E-Field) and Receiver #2 (for measuring EIRP) as follows:

Center Frequency: equal to the signal source  
Resolution BW: 10 kHz  
Video BW: same  
Detector Mode: positive  
Average: off  
Span: 3 x the signal bandwidth

(b) Load an appropriate correction factors file in EMI Receiver for correcting the field strength reading level

Total Correction Factor recorded in the EMI Receiver = Cable Loss + Antenna Factor  
 $E \text{ (dBuV/m)} = \text{Reading (dBuV)} + \text{Total Correction Factor (dB/m)}$

(c) Select the frequency and E-field levels obtained in the Section 7.2.1 for ERP/EIRP measurements.  
(d) Substitute the EUT by a signal generator and one of the following transmitting antenna (substitution antenna):  
◆ DIPOLE antenna for frequency from 30-1000 MHz or  
◆ HORN antenna for frequency above 1 GHz }.  
(e) Mount the transmitting antenna at 1.5 meter high from the ground plane.  
(f) Use one of the following antenna as a receiving antenna:  
◆ DIPOLE antenna for frequency from 30-1000 MHz or  
◆ HORN antenna for frequency above 1 GHz }.  
(g) If the DIPOLE antenna is used, tune it's elements to the frequency as specified in the calibration manual.  
(h) Adjust both transmitting and receiving antenna in a VERTICAL polarization.  
(i) Tune the EMI Receivers to the test frequency.  
(j) Lower or raise the test antenna from 1 to 4 meters until the maximum signal level was detected.  
(k) The transmitter was rotated through 360° about a vertical axis until a higher maximum signal was received.  
(l) Lower or raise the test antenna from 1 to 4 meters until the maximum signal level was detected.  
(m) Adjust input signal to the substitution antenna until an equal or a known related level to that detected from the transmitter was obtained in the test receiver.  
(n) Record the power level read from the Average Power Meter and calculate the ERP/EIRP as follows:

$$P = P1 - L1 = (P2 + L2) - L1 = P3 + A + L2 - L1$$

$$EIRP = P + G1 = P3 + L2 - L1 + A + G1$$


$$ERP = EIRP - 2.15 \text{ dB}$$

Total Correction factor in EMI Receiver # 2 = L2 - L1 + G1


Where: P: Actual RF Power fed into the substitution antenna port after corrected.  
P1: Power output from the signal generator  
P2: Power measured at attenuator A input  
P3: Power reading on the Average Power Meter  
EIRP: EIRP after correction  
ERP: ERP after correction

(o) Adjust both transmitting and receiving antenna in a HORIZONTAL polarization, then repeat step (k) to (o)  
(p) Repeat step (d) to (o) for different test frequency  
(q) Repeat steps (c) to (j) with the substitution antenna oriented in horizontal polarization.  
(r) Actual gain of the EUT's antenna is the difference of the measured EIRP and measured RF power at the RF port. Correct the antenna gain if necessary.:

**Figure 1**



**Figure 2**



## 7.2. FREQUENCY STABILITY

Refer to FCC @ 2.1055.

- (a) The frequency stability shall be measured with variation of ambient temperature as follows: From -30 to +50 centigrade except that specified in subparagraph (2) & (3) of this paragraph.
- (b) Frequency measurements shall be made at extremes of the specified temperature range and at intervals of not more than 10 centigrade through the range. A period of time sufficient to stabilize all of the components of the oscillator circuit at each temperature level shall be allowed prior to frequency measurement. The short-term transient effects on the frequency of the transmitter due to keying (except for broadcast transmitters) and any heating element cycling normally occurring at each ambient temperature level also shall be shown. Only the portion or portions of the transmitter containing the frequency determining and stability circuitry need be subjected to the temperature variation test.
- (d) The frequency stability supply shall be measured with variation of primary supply voltage as follows:
  - (1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.
  - (2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery operating end point which shall be specified by the manufacturer.
  - (3) The supply voltage shall be measured at the input to the cable normally provide with the equipment, or at the power supply terminals if cables are not normally provided. Effects on frequency of transmitter keying (except for broadcast transmitters) and any heating element cycling at the nominal supply voltage and at each extreme also shall be shown.
- (e) When deemed necessary, the Commission may require tests of frequency stability under conditions in addition to those specifically set out in paragraphs (a), (b), (c) and (d) of this section. (For example, measurements showing the effect of proximity to large metal objects, or of various types of antennas, may be required for portable equipment).