

December 9, 2008

### AXXC06 –Tri-Band CPE

#### **1.1.1. Maximum Permissible Exposure**

**FCC, Part 15 Subpart C §15.247(i)**  
**Industry Canada RSS-Gen §5.5**

#### **Calculations for Maximum Permissible Exposure Levels**

Power Density =  $P_d$  (mW/cm<sup>2</sup>) = EIRP/(4πd<sup>2</sup>)

EIRP = P \* G P = Peak output power (mW)

G = Antenna numeric gain (numeric)

d = Separation distance (cm)

Numeric Gain = 10 ^ (G (dBi)/10)

Because the EUT belongs to the General Population/Uncontrolled Exposure the limit of power density is 1.0 mW/cm<sup>2</sup>

Maximum power permissible using 17.5 dBi antenna = +18.5 dBm

Freq. Band (GHz)	Antenna Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Safe Distance @ 1mW/cm <sup>2</sup> Limit(cm)	Minimum Separation Distance (cm)
5.8	17.5	56.23	+18.5	70.8	17.80	20.00

\*Note: for mobile or fixed location transmitters the minimum separation distance is 20cm, even if calculations indicate the MPE distance to be less.

#### **Specification**

#### **Maximum Permissible Exposure Limits**

**§15.247(i)** Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency levels in excess of the Commission's guidelines.

**FCC §1.1310** Limit = 1mW / cm<sup>2</sup> from 1.310 Table 1

**RSS-Gen §5.5** Before equipment certification is granted, the applicable requirements of RSS-102 shall be met.