

Test of Axxcelera Tri-Band CPE

To: FCC 47 CFR Part15.247 & IC RSS-210

Test Report Serial No.: AXXC06-A2 Rev A



TEST REPORT
FROM
MiCOMLabs

Test of Axxcelera Tri-Band CPE
to
To FCC 47 CFR Part15.247 & IC RSS-210

Test Report Serial No.: AXXC06-A2 Rev A

Note: this report only contains data with regards to the 5.8 GHz operational modes of the Axxcelera Tri-Band Customer Premise Equipment. (CPE). 5,470-5,725 MHz test data is reported in MiCOM Labs test report AXXC06-A6

This report supersedes: None

Applicant: Axxcelera
1600 E.Parham Road
Richmond
Virginia 23228 USA

Product Function: 802.16 Customer Premise Equipment (CPE)

Copy No: pdf **Issue Date:** 10th December 2008

This Test Report is Issued Under the Authority of:

MiCOM Labs, Inc.
440 Boulder Court, Suite 200
Pleasanton, CA 94566 USA
Phone: +1 (925) 462-0304
Fax: +1 (925) 462-0306
www.micomlabs.com



CERTIFICATE #2381.01

MiCOM Labs is an ISO 17025 Accredited Testing Laboratory



Title: Axxcelera Tri-Band CPE
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: AXXC06-A2 Rev A
Issue Date: 10th December 2008
Page: 3 of 86

This page has been left intentionally blank

TABLE OF CONTENTS

ACCREDITATION & LISTINGS.....	5
1. TEST RESULT CERTIFICATE	8
2. REFERENCES AND MEASUREMENT UNCERTAINTY	9
2.1. Normative References	9
2.2. Test and Uncertainty Procedures	9
3. PRODUCT DETAILS AND TEST CONFIGURATIONS	10
3.1. Technical Details	10
3.2. Scope of Test Program.....	11
3.3. Equipment Model(s) and Serial Number(s)	14
3.4. Antenna Details	14
3.5. Cabling and I/O Ports	14
3.6. Test Configurations.....	14
3.7. Equipment Modifications.....	15
3.8. Deviations from the Test Standard	15
4. TEST SUMMARY	16
5. TEST RESULTS	18
5.1. Device Characteristics	18
5.1.1. <i>6 dB and 99 % Bandwidth</i>	18
5.1.2. <i>Peak Output Power</i>	29
5.1.3. <i>Peak Power Spectral Density</i>	40
5.1.4. <i>Maximum Permissible Exposure</i>	51
5.1.5. <i>Conducted Spurious Emissions</i>	52
5.1.6. <i>Radiated Emissions</i>	59
5.1.7. <i>AC Wireline Conducted Emissions (150 kHz – 30 MHz)</i>	77
6. PHOTOGRAPHS.....	80
6.1. Radiated Spurious Emissions >1 GHz.....	80
6.2. Radiated Spurious Emissions <1 GHz.....	81
6.3. AC Wireline Emissions (150 kHz - 30 MHz)	82
6.4. General Measurement Test Set-Up #1	83
6.5. General Measurement Test Set-Up Environmental Chamber	84
7. TEST EQUIPMENT DETAILS.....	85

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Axxcelera Tri-Band CPE
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: AXXC06-A2 Rev A
Issue Date: 10th December 2008
Page: 5 of 86

ACCREDITATION & LISTINGS

MiCOM Labs, Inc. an accredited laboratory complies with the international standard BS EN ISO/IEC 17025. The company is accredited by the American Association for Laboratory Accreditation (A2LA) www.a2la.org test laboratory number 2381.01. MiCOM Labs test schedule is available at the following URL; <http://www.a2la.org/scopepdf/2381-01.pdf>



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Axxcelera Tri-Band CPE
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: AXXC06-A2 Rev A
Issue Date: 10th December 2008
Page: 6 of 86

LISTINGS

MiCOM Labs test facilities are listed by the following organizations;

North America

United States of America

Federal Communications Commission (FCC) Listing #: 102167

Canada

Industry Canada: 4143A

RECOGNITION

APEC MRA (Asia-Pacific Economic Community Mutual Recognition Agreement)

Conformity Assessment Body (CAB) – MiCOM Labs

Test data generated by MiCOM Labs is accepted in the following countries under the APEC MRA.

Country	Recognition Body	Phase	CAB Identification No.
Australia	Australian Communications and Media Authority (ACMA)	I	US0159
Hong Kong	Office of the Telecommunication Authority (OFTA)	I	
Korea	Ministry of Information and Communication Radio Research Laboratory (RRL)	I	
Singapore	Infocomm Development Authority (IDA)	I	
Taiwan	Directorate General of Telecommunications (DGT) Bureau of Standards, Metrology and Inspection (BSMI)	I	

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Axxcelera Tri-Band CPE
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: AXXC06-A2 Rev A
Issue Date: 10th December 2008
Page: 7 of 86

DOCUMENT HISTORY

Document History		
Revision	Date	Comments
Draft		
A	10 th December 2008	Initial Release

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Axxcelera Tri-Band CPE
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: AXXC06-A2 Rev A
Issue Date: 10th December 2008
Page: 8 of 86

1. TEST RESULT CERTIFICATE

Applicant:	Axxcelera 1600 E.Parham Road Richmond Virginia 23228 USA	Tested By: MiCOM Labs, Inc. 440 Boulder Court, Suite 200 Pleasanton California, 94566, USA
EUT:	Client Device for Wireless PMP cellular coverage	Telephone: +1 925 462 0304
Model:	Tri-Band CPE	Fax: +1 925 462 0306
S/N:	N/A	
Test Date(s):	31st Oct to 5th Dec 2008	Website: www.micomlabs.com


STANDARD(S)	TEST RESULTS
FCC 47 CFR Part15.247 & IC RSS-210	EQUIPMENT COMPLIES


MiCOM Labs, Inc. tested the equipment mentioned in accordance with the requirements set forth in the above standards. Test results indicate that the equipment tested is capable of demonstrating compliance with the requirements as documented within this report.

Notes:

1. This document reports conditions under which testing was conducted and the results of testing performed.
2. Details of test methods used have been recorded and kept on file by the laboratory.
3. Test results apply only to the item(s) tested.

Approved & Released for MiCOM Labs, Inc. by:


Graeme Grieve
Quality Manager MiCOM Labs,


ACCREDITED
CERTIFICATE #2381.01

Gordon Hurst
President & CEO MiCOM Labs, Inc.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Axxcelera Tri-Band CPE
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: AXXC06-A2 Rev A
Issue Date: 10th December 2008
Page: 9 of 86

2. REFERENCES AND MEASUREMENT UNCERTAINTY

2.1. Normative References

Ref.	Publication	Year	Title
(i)	FCC 47 CFR Part 15.247	2007	Code of Federal Regulations
(ii)	Industry Canada RSS-210	Issue 7 June 2007	Low Power License-Exempt Radiocommunication Devices (All Frequency Bands)
(iii)	Industry Canada RSS-Gen	Issue 2 June 2007	General Requirements and Information for the Certification of Radiocommunication Equipment.
(iv)	ANSI C63.4	2003	American National Standards for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
(v)	CISPR 22/ EN 55022	1997 1998	Limits and Methods of Measurements of Radio Disturbance Characteristics of Information Technology Equipment
(vi)	M 3003	Edition 1 Dec. 1997	Expression of Uncertainty and Confidence in Measurements
(vii)	LAB34	Edition 1 Aug 2002	The expression of uncertainty in EMC Testing
(viii)	ETSI TR 100 028	2001	Parts 1 and 2 Electromagnetic compatibility and Radio Spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics
(ix)	A2LA	14 th September 2005	Reference to A2LA Accreditation Status – A2LA Advertising Policy

2.2. Test and Uncertainty Procedures

Conducted and radiated emission measurements were conducted in accordance with American National Standards Institute ANSI C63.4, listed in the Normative References section of this report.

Measurement uncertainty figures are calculated in accordance with ETSI TR 100 028 Parts 1 and 2.

Measurement uncertainties stated are based on a standard uncertainty multiplied by a coverage factor $k = 2$, providing a level of confidence of approximately 95 % in accordance with UKAS document M 3003 listed in the Normative References section of this report.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Axxcelera Tri-Band CPE
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: AXXC06-A2 Rev A
Issue Date: 10th December 2008
Page: 10 of 86

3. PRODUCT DETAILS AND TEST CONFIGURATIONS

3.1. Technical Details

Details	Description
Purpose:	Test of the Axxcelera Tri-Band CPE to FCC Part 15.247 and Industry Canada RSS-210 regulations.
Manufacturer:	As Applicant
Applicant:	Axxcelera 1600 E.Parham Road Richmond Virginia 23228 USA
Laboratory performing the tests:	MiCOM Labs, Inc. 440 Boulder Court, Suite 200 Pleasanton, California 94566 USA
Test report reference number:	AXXC06-A2 Rev A
Date EUT received:	31 st October 2008
Standard(s) applied:	FCC 47 CFR Part15.247 & IC RSS-210
Dates of test (from - to):	31st Oct to 5th Dec 2008
No of Units Tested:	2 - Conducted and radiated testing were separate units
Type of Equipment:	802.16 Wireless Customer Premise Equipment
Manufacturers Trade Name:	Customer Premise Equipment
Model:	Tri-Band CPE
Location for use:	Outdoor
Declared Frequency Range(s):	5725 - 5850 MHz
Type of Modulation:	BPSK, QPSK, 16QAM, 64QAM
Declared Nominal Output Power:	+18 dBm
EUT Modes of Operation:	Modulation Types: BPSK, QPSK, 16QAM, 64QAM Bandwidths: 5, 10 & 15 MHz
Transmit/Receive Operation:	Time Division Duplex
Rated Input Voltage and Current:	48 Vdc, 250 mA
Operating Temperature Range:	-40°C to +55°C
ITU Emission Designator:	5 MHz BW – 4M7W7D 10 MHz BW – 9M1W7D 15 MHz BW – 13M5W7D
Clock/Oscillator(s):	25 kHz, 40 MHz, 5725 MHz
Frequency Stability:	±20 ppm max
Equipment Dimensions:	8" X 8" X 2.5"
Weight:	3 lbs
Primary function of equipment:	Client device for wireless Point to MultiPoint cellular coverage

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: Axxcelera Tri-Band CPE
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: AXXC06-A2 Rev A
Issue Date: 10th December 2008
Page: 11 of 86

3.2. Scope of Test Program

The scope of the test program was to test the Axxcelera Tri-Band CPE wireless Customer Premise Equipment in the frequency range 5725 – 5850 MHz for compliance against FCC 47 CFR Part 15.247 and Industry Canada RSS-210 specifications.

Axxcelera Tri-Band CPE Wireless Customer Premise Equipment




This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Axxcelera Tri-Band CPE
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: AXXC06-A2 Rev A
Issue Date: 10th December 2008
Page: 12 of 86

Axxcelera Tri-Band CPE
Wireless Customer Premise Equipment



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Axxcelera Tri-Band CPE
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: AXXC06-A2 Rev A
Issue Date: 10th December 2008
Page: 13 of 86

Axxcelera Tri-Band CPE POE Adapter



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Axxcelera Tri-Band CPE
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: AXXC06-A2 Rev A
Issue Date: 10th December 2008
Page: 14 of 86

3.3. Equipment Model(s) and Serial Number(s)

Type (EUT/ Support)	Equipment Description (Including Brand Name)	Mfr	Model No.	Serial No.
EUT	Wireless AP	Axxcelera	Tri-Band CPE	N/A
EUT	Single Port POE Power Supply Gigabit Compatible 100-240Vac 50-60Hz 56Vdc, 0.55A	PhiHong	POE30U-560(G)	N/A
Support	Laptop PC	Dell	Inspiron	None

3.4. Antenna Details

1. Maximum Gain: +17.5 dBi (integral antenna)

3.5. Cabling and I/O Ports

Number and type of I/O ports

1. POE 10/100 Ethernet

3.6. Test Configurations

Testing was performed to determine the worst case test scenario. It was found through exercising each modulation with each bandwidth that there was no difference. Test data is available and held on file by the laboratory identifying cross checks performed.

Matrix of channel test configurations.

Operational Mode	Frequencies (MHz)
802.16	5,735 5,785 5,840


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

3.7. Equipment Modifications

The following modifications were required to bring the equipment into compliance:

1. AC Wireline Emissions

There was problem with an AC Wireline Emission at 23.129 MHz. The client added two chokes L2 and L7 to bring the EUT into compliance.



2. Restricted Band-Edge

It was found that the noise floor within the 5,350 – 5460 MHz Restricted Band was non-compliant when transmitting within the 5.8 GHz band. Modifications were made to existing filter (FL4) to tweak the frequency for band-edge compliance. The result of the modification (L&C adjustments) allows for enhanced electrical performance at power when operating in the 5.8 GHz band.

3.8. Deviations from the Test Standard

The following deviations from the test standard were required in order to complete the test program:

1. None

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Axxcelera Tri-Band CPE
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: AXXC06-A2 Rev A
Issue Date: 10th December 2008
Page: 16 of 86

4. TEST SUMMARY

List of Measurements

The following table represents the list of measurements required under the **FCC CFR47 Part 15.247** and **Industry Canada RSS-210** and **Industry Canada RSS-Gen**.

Section(s)	Test Items	Description	Condition	Result	Test Report Section
15.247(a)(2) A8.2(1) 4.4	6 dB and 99 % Bandwidths	≥500 kHz	Conducted	Complies	5.1.1
15.247(b)(3) 15.31(e) A8.4(4)	Peak Output Power Voltage Variation	Shall not exceed 1W Variation of supply voltage 85 % -115 %	Conducted	Complies	5.1.2
15.247(e) A8.2	Peak Power Spectral Density	Shall not be greater than +8 dBm in any 3 kHz band	Conducted	Complies	5.1.3
15.247(i) 5.5	Maximum Permissible Exposure	Exposure to radio frequency energy levels	Conducted	Complies	5.1.4
15.247(d) 15.205 / 15.209 A8.5 2.2 4.7	Spurious Emissions (30MHz - 26 GHz b/g and 30 MHz - 40 GHz a)	The radiated emission in any 100 kHz of out-band shall be at least 20 dB below the highest in-band spectral density	Conducted	Complies	5.1.5

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Axxcelera Tri-Band CPE
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: AXXC06-A2 Rev A
Issue Date: 10th December 2008
Page: 17 of 86

List of Measurements (continued)

The following table represents the list of measurements required under the **FCC CFR47 Part 15.247**, **Industry Canada RSS-210**, and **Industry Canada RSS-Gen**.

Section(s)	Test Items	Description	Condition	Result	Test Report Section
15.247(d) 15.205 / 15.209 A8.5 2.2 2.6 4.7 Industry Canada only RSS-Gen §4.8, §6	Radiated Emissions Transmitter Radiated Spurious Emissions Receiver Radiated Spurious Emissions	Restricted Bands Emissions above 1 GHz Emissions above 1 GHz	Radiated	Complies Complies Complies	5.1.6 5.1.6.1 5.1.6.2
15.205 / 15.209 2.2	Radiated Spurious Emissions	Emissions <1 GHz (30M-1 GHz)	Radiated	Complies	5.1.6.3
15.207 7.2.2	AC Wireline Conducted Emissions 150 kHz - 30 MHz	Conducted Emissions	Conducted	Complies	5.1.7

Note 1: Test results reported in this document relate only to the items tested

Note 2: The required tests demonstrated compliance as per client declaration of test configuration, monitoring methodology and associated pass/fail criteria

Note 3: Appendix A - Equipment Modifications highlights the equipment modifications that were required to bring the product into compliance with the above test matrix

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

5. TEST RESULTS

5.1. Device Characteristics

5.1.1. 6 dB and 99 % Bandwidth

FCC, Part 15 Subpart C §15.247(a)(2)


Industry Canada RSS-210 §A8.2

Industry Canada RSS-Gen §4.4

Test Procedure

The bandwidth at 6 dB and 99 % is measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate center frequency.

Test Measurement Set up



Measurement set up for 6 dB and 99 % bandwidth test

Measurement Results for 6 dB and 99 % Operational Bandwidth(s)


Ambient conditions.

Temperature: 17 to 23 °C Relative humidity: 31 to 57 % Pressure: 999 to 1012 mbar

TABLE OF RESULTS – 64 QAM 5 MHz BW


Center Frequency (MHz)	6 dB Bandwidth (MHz)	99 % BW (MHz)
5,735	4.609	4.689
5,785	4.569	4.689
5,840	4.569	4.689

5,735 MHz 64 QAM 5 MHz BW 6 dB and 99% Bandwidth



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.


5,785 MHz 64 QAM 5 MHz BW 6 dB and 99% Bandwidth



Date: 31.OCT.2008 16:43:41

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

5,840 MHz 64 QAM 5 MHz BW 6 dB and 99% Bandwidth




Date: 31.OCT.2008 16:47:44

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

TABLE OF RESULTS - 64 QAM 10 MHz BW

Center Frequency (MHz)	6 dB Bandwidth (MHz)	99 % BW (MHz)
5,735	9.138	9.138
5,785	9.138	9.138
5,840	9.138	9.138


5,735 MHz 64 QAM 10 MHz BW 6 dB and 99% Bandwidth



Date: 31.OCT.2008 16:56:27

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.


5,785 MHz 64 QAM 10 MHz BW 6 dB and 99% Bandwidth



Date: 31.OCT.2008 16:53:56

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

5,840 MHz 64 QAM 10 MHz BW 6 dB and 99% Bandwidth



Date: 31.OCT.2008 16:50:52

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: Axxcelera Tri-Band CPE
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: AXXC06-A2 Rev A
Issue Date: 10th December 2008
Page: 25 of 86

TABLE OF RESULTS – 64 QAM 15 MHz BW


Center Frequency (MHz)	6 dB Bandwidth (MHz)	99 % BW (MHz)
5,735	13.627	13.527
5,785	13.627	13.527
5,840	13.627	13.527

5,735 MHz 64 QAM 15 MHz BW 6 dB and 99% Bandwidth




This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

5,785 MHz 64 QAM 15 MHz BW 6 dB and 99% Bandwidth



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

5,840 MHz 64 QAM 15 MHz BW 6 dB and 99% Bandwidth



Date: 31.OCT.2008 17:06:45

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Axxcelera Tri-Band CPE
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: AXXC06-A2 Rev A
Issue Date: 10th December 2008
Page: 28 of 86

Specification

Limits

§15.247 (a)(2) & RSS-210 §A8.2(1)

The minimum 6 dB bandwidth shall be at least 500 kHz.

§ IC RSS-Gen 4.4.1 Occupied Bandwidth When an occupied bandwidth value is not specified in the applicable RSS, the transmitted signal bandwidth to be reported is to be its 99% emission bandwidth, as calculated or measured.

§ IC RSS-Gen 4.4.2 6 dB Bandwidth Where indicated, the 6 dB bandwidth is measured at the points when the spectral density of the signal is 6 dB down from the in –band spectral density of the modulated signal, with the transmitter modulated by a representative signal.

Laboratory Measurement Uncertainty for Spectrum Measurement

Measurement uncertainty	±2.81 dB
-------------------------	----------

Traceability

Method	Test Equipment Used
Measurements were made per work instruction WI-03 'Measurement of RF Spectrum Mask'	0158, 0193, 0252, 0313, 0314, 0070, 0116, 0117

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.


5.1.2. Peak Output Power

FCC, Part 15 Subpart C §15.247(b)(3), §15.31(e)
Industry Canada RSS-210 §A8.4(4)

Test Procedure

The transmitter terminal of EUT was connected to the input of the spectrum analyzer set to measure peak power. The resolution filter bandwidth was set to 6 dB, peak detector selected and the analyzer built-in power function was used to measure peak power over the 99 % bandwidth.

Test Measurement Set up



Measurement set up for Transmitter Peak Output Power

Ambient conditions.

Temperature: 17 to 23 °C Relative humidity: 31 to 57 % Pressure: 999 to 1012 mbar

Maximum Antenna Gain = + 17.5 dBi


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

TABLE OF RESULTS – 64 QAM 5 MHz BW

Antenna Gain = 0 dBi

Center Frequency (MHz)	99% Measurement Bandwidth (MHz)	Peak Power (dBm)	EIRP (0 dBi Antenna) (dBm)
5,735	4.609	+24.67	+24.67
5,785	4.569	+25.05	+25.05
5,840	4.569	+26.35	+26.35


5,735 MHz 64 QAM 5 MHz Peak Power (dBm)



Date: 3.NOV.2008 12:18:36

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.


5,785 MHz 64 QAM 5 MHz Peak Power (dBm)



Date: 3.NOV.2008 12:22:46

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

5,840 MHz 64 QAM 5 MHz Peak Power (dBm)




This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

TABLE OF RESULTS – 64 QAM 10 MHz BW

Maximum Antenna Gain = 0 dBi

Center Frequency (MHz)	99% Measurement Bandwidth (MHz)	Peak Power (dBm)	EIRP (0 dBi Antenna) (dBm)
5,735	9.138	+24.71	+24.71
5,785	9.138	+25.33	+25.33
5,840	9.138	+26.22	+26.22


5,735 MHz 64 QAM 10 MHz Peak Power (dBm)



Date: 3.NOV.2008 12:27:28

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.


5,785 MHz 64 QAM 10 MHz Peak Power (dBm)



Date: 3.NOV.2008 12:29:04

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

5,840 MHz 64 QAM 10 MHz Peak Power (dBm)



Date: 3.NOV.2008 12:32:18


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

TABLE OF RESULTS – 64 QAM 15 MHz BW

Maximum Antenna Gain = 0 dBi

Center Frequency (MHz)	99% Measurement Bandwidth (MHz)	Peak Power (dBm)	EIRP (0 dBi Antenna) (dBm)
5,735	13.627	+24.77	+24.77
5,785	13.627	+25.18	+25.18
5,840	13.627	+26.09	+26.09


5,735 MHz 64 QAM 15 MHz Peak Power (dBm)



Date: 3.NOV.2008 12:41:43


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

5,785 MHz 64 QAM 15 MHz BW 6 dB Bandwidth Peak Power (dBm)



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

5,840 MHz 64 QAM 15 MHz BW 6 dB Bandwidth Peak Power (dBm)



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Axxcelera Tri-Band CPE
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: AXXC06-A2 Rev A
Issue Date: 10th December 2008
Page: 39 of 86

Specification

Limits

§15.247 (b) The maximum peak output power of the intentional radiator shall not exceed the following:

§15.247 (b) (3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz bands: 1.0 watt.

§15.31 (e) For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. For battery operated equipment, the equipment tests shall be performed using a new battery.

§ RSS-210 A8.4(4) For systems employing digital modulation techniques operating in the 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz bands the maximum peak conducted power shall not exceed 1 watt.

Laboratory Measurement Uncertainty for Power Measurements

Measurement uncertainty	±1.33 dB
-------------------------	----------

Traceability

Method	Test Equipment Used
Measurements were made per work instruction WI-01 'Measuring RF Output Power'	0158, 0193, 0252, 0313, 0314, 0070, 0116, 0117

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

5.1.3. Peak Power Spectral Density


FCC, Part 15 Subpart C §15.247(e)

Industry Canada RSS-210 §A8.2

Test Procedure

The transmitter output was connected to a spectrum analyzer and the maximum level in a 3 kHz bandwidth was measured. A peak value was found over the full emission bandwidth and the frequency span reduced to obtain enhanced resolution. Sweep time \geq span / 3 kHz with video averaging turned off. The Peak Power Spectral Density is the highest level found across the emission in a 3 kHz resolution bandwidth.

Test Measurement Set up



Measurement set up for Peak Power Spectral Density


Measurement Results for Peak Power Spectral Density

Ambient conditions.

Temperature: 17 to 23 °C Relative humidity: 31 to 57 % Pressure: 999 to 1012 mbar

TABLE OF RESULTS – 64 QAM 5 MHz BW

Center Frequency (MHz)	Peak Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Margin (dBm)
5,735	5,736.45	-4.44	+8	-12.44
5,785	5,784.09	-3.66	+8	-13.66
5,840	5,841.45	-2.90	+8	-10.90




Date: 3.NOV.2008 10:50:35

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Axxcelera Tri-Band CPE
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: AXXC06-A2 Rev A
Issue Date: 10th December 2008
Page: 42 of 86

5,785 MHz 64 QAM 5 MHz Peak Power Spectral Density




Date: 3.NOV.2008 11:01:27

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Axxcelera Tri-Band CPE
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: AXXC06-A2 Rev A
Issue Date: 10th December 2008
Page: 43 of 86

5,840 MHz 64 QAM 5 MHz Peak Power Spectral Density




Date: 3.NOV.2008 11:12:54

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

TABLE OF RESULTS – 64 QAM 10 MHz BW


Center Frequency (MHz)	Peak Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Margin (dBm)
5,735	5,738.03	-6.69	+8	-14.69
5,785	5,784.16	-5.78	+8	-13.78
5,840	5,839.15	-4.67	+8	-12.67

5,735 MHz 64 QAM 10 MHz Peak Power Spectral Density



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

5,785 MHz 64 QAM 10 MHz Peak Power Spectral Density




Date: 3.NOV.2008 10:19:55

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Axxcelera Tri-Band CPE
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: AXXC06-A2 Rev A
Issue Date: 10th December 2008
Page: 46 of 86

5,840 MHz 64 QAM 10 MHz Peak Power Spectral Density




Date: 3.NOV.2008 10:36:28

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.


TABLE OF RESULTS – 64 QAM 15 MHz BW

Center Frequency (MHz)	Peak Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Margin (dBm)
5,735	5,733.75	-7.48	+8	-15.48
5,785	5,783.75	-6.88	+8	-14.88
5,840	5,380.75	-5.60	+8	-13.60



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.


5,785 MHz 64 QAM 15 MHz Peak Power Spectral Density



Date: 3.NOV.2008 09:43:32

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

5,840 MHz 64 QAM 15 MHz Peak Power Spectral Density



Date: 3.NOV.2008 09:26:31

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Axxcelera Tri-Band CPE
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: AXXC06-A2 Rev A
Issue Date: 10th December 2008
Page: 50 of 86

Specification

Peak Power Spectral Density Limits

§15.247(e) For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than +8 dBm in any 3 kHz band during any time interval of continuous transmission

RSS-210 §A8.2(2) The transmitter power spectral density (into the antenna) shall not be greater than +8 dBm in any 3 kHz band during any time interval of continuous transmission or over 1.0 second if the transmission exceeds 1.0 second duration.

Laboratory Measurement Uncertainty for Spectral Density

Measurement uncertainty	±1.33 dB
-------------------------	----------

Traceability

Method	Test Equipment Used
Measurements were made per work instruction WI-01 'Measuring RF Output Power'	0158, 0193, 0252, 0313, 0314, 0070, 0116, 0117

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Axxcelera Tri-Band CPE
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: AXXC06-A2 Rev A
Issue Date: 10th December 2008
Page: 51 of 86

5.1.4. Maximum Permissible Exposure

FCC, Part 15 Subpart C §15.247(i)

Industry Canada RSS-Gen §5.5

Calculations for Maximum Permissible Exposure Levels

Power Density = P_d (mW/cm²) = EIRP/(4πd²)

EIRP = P * G P = Peak output power (mW)

G = Antenna numeric gain (numeric)

d = Separation distance (cm)

Numeric Gain = 10 ^ (G (dBi)/10)

Because the EUT belongs to the General Population/Uncontrolled Exposure the limit of power density is 1.0 mW/cm²

Maximum power permissible using 17.5 dBi antenna = +18.5 dBm

Freq. Band (GHz)	Antenna Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Safe Distance @ 1mW/cm ² Limit(cm)	Minimum Separation Distance (cm)
5.8	17.5	56.23	+18.5	70.8	17.80	20.00

***Note:** for mobile or fixed location transmitters the minimum separation distance is 20cm, even if calculations indicate the MPE distance to be less.

Specification

Maximum Permissible Exposure Limits

§15.247(i) Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency levels in excess of the Commission's guidelines.

FCC §1.1310 Limit = 1mW / cm² from 1.310 Table 1

RSS-Gen §5.5 Before equipment certification is granted, the applicable requirements of RSS-102 shall be met.

Laboratory Measurement Uncertainty for Power Measurements

Measurement uncertainty	±1.33 dB
-------------------------	----------

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

5.1.5. Conducted Spurious Emissions

FCC, Part 15 Subpart C §15.247(d); 15.205; 15.209

Industry Canada RSS-210 §A8.5, §2.2

Industry Canada RSS-Gen 4.7

Test Procedure

Conducted emissions were measured at a limit of 20 dB below the highest in-band spectral density measured with a spectrum analyzer connected to the antenna terminal. Emissions at the band edge were measured and recorded. Measurements were made while EUT was operating in transmit mode of operation at the appropriate center frequency.

Test Measurement Set up



Band-edge measurement test configuration

Measurement Results of Conducted Spurious Emissions

Ambient conditions.

Temperature: 17 to 23 °C Relative humidity: 31 to 57 % Pressure: 999 to 1012 mbar

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.


Conducted Band-Edge Results

Measurements were performed with the transmitter tuned to the channel closest to the band-edge being measured. All emissions were maximized during measurement. Limits which were derived from the band-edge measurements provided below are drawn on each plot.

TABLE OF RESULTS – 64 QAM 15 MHz BW

Center Frequency (MHz)	Band edge Frequency (MHz)	Limit (20 dB below peak of fundamental)	Amplitude @ Band edge (dBm)	Margin (dB)
5,735	5,725	-14.22	-28.89	-14.67
5,840	5,850	-12.70	-26.26	-13.56


64 QAM 15 MHz BW - Conducted Spurious Emissions at the 5,735 MHz Band Edge



Date: 3.NOV.2008 11:32:29

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

64 QAM 15 MHz BW - Conducted Spurious Emissions at the 5,840 MHz Band Edge



Date: 3.NOV.2008 11:45:06

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.


Spurious Emissions (30 - 40,000 MHz)

TABLE OF RESULTS – 64 QAM 15 MHz BW

Channel Centre Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Maximum Emission Observed (dBm)	Limit (dBm)	Margin (dB)
5,735	30	40,000	-35.17	-15.99	-19.18

5 MHz BW

5,735 MHz Conducted Spurious Emissions 30 MHz to 40,000 MHz




This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

TABLE OF RESULTS

Channel Centre Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Maximum Emission Observed (dBm)	Limit (dBm)	Margin (dB)
5,785	30	40,000	-35.28	-15.15	-20.13

5 MHz BW

5,785 MHz Conducted Spurious Emissions 30 MHz to 40,000 MHz




This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

TABLE OF RESULTS

Channel Centre Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Maximum Emission Observed (dBm)	Limit (dBm)	Margin (dB)
5,840	30	40,000	-35.70	-14.88	-20.82

5 MHz BW

5,840 MHz Conducted Spurious Emissions 30 MHz to 40,000 MHz



Date: 11.SEP.2008 09:51:26

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

Specification

§15.247(d) and RSS-210 §A8.5 In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

§15.247(d)

If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section §15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(a)).

RSS-210 §A8.5 If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under section A8.4(4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Tables 2 and 3 is not required. In addition, radiated emissions which fall in the restricted bands of Table 1 must also comply with the radiated emission limits specified in Tables 2 and 3.

RSS-Gen §4.7

The search for unwanted emissions shall be from the lowest frequency internally generated or used in the device (local oscillator, intermediate of carrier frequency), or from 30 MHz, whichever is the lowest frequency, to the 5th harmonic of the highest frequency generated without exceeding 40 GHz.

Laboratory Measurement Uncertainty for Conducted Spurious Emissions

Measurement uncertainty	±2.37 dB
-------------------------	----------

Traceability

Method	Test Equipment Used
Measurements were made per work instruction WI-05 'Measurement of Spurious Emissions'	0088, 0158, 0193, 0252, 0313, 0314, 0070, 0116, 0117.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

5.1.6. Radiated Emissions

5.1.6.1. Transmitter Radiated Spurious Emissions (above 1 GHz)

FCC, Part 15 Subpart C §15.247(d) 15.205; 15.209

Industry Canada RSS-210 §A8.5, §2.2, §2.6


Industry Canada RSS-Gen §4.7

Test Procedure

Radiated emissions above 1 GHz are measured in the anechoic chamber at a 3-meter distance on every azimuth in both horizontal and vertical polarities. The emissions are recorded and maximized as a function of azimuth by rotation through 360° with a spectrum analyzer in peak hold mode. Depending on the frequency band spanned a notch filter and waveguide filter was used to remove the fundamental frequency. The highest emissions relative to the limit are listed for each frequency spanned.

All measurements on any frequency or frequencies over 1 MHz are based on the use of measurement instrumentation employing an average detector function. All measurements above 1 GHz were performed using a minimum resolution bandwidth of 1 MHz.

Test Measurement Set up



Measurement set up for Radiated Emission Test

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Loss, and subtracting Amplifier Gain from the measured reading. All factors are included in the reported data.

$$FS = R + AF + CORR - FO$$

where: FS = Field Strength

R = Measured Spectrum analyzer Input Amplitude

AF = Antenna Factor

CORR = Correction Factor = CL – AG + NFL

CL = Cable Loss

AG = Amplifier Gain

FO = Distance Falloff Factor

NFL = Notch Filter Loss or Waveguide Loss

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Axxcelera Tri-Band CPE
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: AXXC06-A2 Rev A
Issue Date: 10th December 2008
Page: 60 of 86

For example:

Given receiver input reading of 51.5 dB μ V; Antenna Factor of 8.5 dB; Cable Loss of 1.3 dB; Falloff Factor of 0 dB, an Amplifier Gain of 26 dB and Notch Filter Loss of 1 dB. The Field Strength of the measured emission is:

$$FS = 51.5 + 8.5 + 1.3 - 26.0 + 1 = 36.3 \text{ dB}\mu\text{V/m}$$

Conversion between dB μ V/m (or dB μ V) and μ V/m (or μ V) are done as:

$$\text{Level (dB}\mu\text{V/m)} = 20 * \text{Log} (\text{level (}\mu\text{V/m)})$$

$$40 \text{ dB}\mu\text{V/m} = 100 \mu\text{V/m}$$

$$48 \text{ dB}\mu\text{V/m} = 250 \mu\text{V/m}$$

Maximum Emissions

It was found that the CPE lying flat on the polystyrene table was the worst case orientation for radiated emissions.

Some evaluation testing was performed first of all to determine which of the four different modulation schemes and bandwidth variants had the worst radiated emissions. As a result it was determined that the 64QAM modulation 5 MHz channel spacing represented worst case emissions.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.


Radiated Spurious Emissions above 1 GHz

TABLE OF RESULTS - 5,735 MHz BPSK 5 MHz BW

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
5734.319	56.34	34.75	35.09	126.18	Peak [Scan]	V	Maximized	N/A	N/A	N/A	Pass	Peak Emission
5350-5460		Power Setting = 16		65.88	Peak Max	V	Maximized	74	-8.12	Pass	Band-edge	
				53.19	Average Max	V		54	-0.81	Pass	Band-edge	


There are three emissions breaking the Average limit line and reported in the above table: fundamental and both band-edges. The following plot represents peak emissions only. No additional spurious emissions were found within 6 dB of the limit line.

Radiated Emissions - 5,735 MHz BPSK 5 MHz BW




This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

Peak Emission - 5,735 MHz 64 QAM 5 MHz BW



Band-edge @ 5,350 – 5,460 MHz: 5,735 MHz 64 QAM 5 MHz BW




This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

TABLE OF RESULTS - 5,785 MHz 5 MHz BW

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
5784.82	55.48	34.78	35.13	125.39	Peak [Scan]	V	Maximized	N/A	N/A	N/A	Pass	Peak Emission
5350-5460	Power Setting = 17			65.58	Peak Max	V	Maximized	74	-8.42	Pass	Pass	Band-edge
5350-5460				52.98	Average Max	V		54	-1.02	Pass	Pass	Band-edge


There are three emissions breaking the Average limit line and reported in the above table: fundamental and both band-edges. The following plot represents peak emissions only. No additional spurious emissions were found within 6 dB of the limit line.

Radiated Emissions - 5,785 MHz 5 MHz BW




This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

Peak Emission - 5,785 MHz 64 QAM 5 MHz BW



Band-edge @ 5,350 – 5,460 MHz: 5,785 MHz 64 QAM 5 MHz BW




This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

TABLE OF RESULTS - 5,840 MHz 5 MHz BW

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
5838.627	55.46	34.81	35.17	125.44	Peak [Scan]	V	Maximized	N/A	N/A	N/A	Pass	Peak Emission
5350-5460	Power Setting = 17			66.02	Peak Max	V	Maximized	74	-7.98	Pass	Band-edge	
5350-5460				52.92	Average Max	V		54	-1.08	Pass	Band-edge	


There are three emissions breaking the Average limit line and reported in the above table: fundamental and both band-edges. The following plot represents peak emissions only. No additional spurious emissions were found within 6 dB of the limit line.

Radiated Emissions - 5,840 MHz 5 MHz BW




This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

Peak Emission - 5,840 MHz 64 QAM 5 MHz BW



Band-edge @ 5,350 – 5,460 MHz: 5,840 MHz 64 QAM 5 MHz BW



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Axxcelera Tri-Band CPE
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: AXXC06-A2 Rev A
Issue Date: 10th December 2008
Page: 67 of 86

Specification Limits

FCC §15.247(d) and RSS-210 §A8.5 In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

FCC §15.247(d)

If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section §15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(a)).

IC RSS-210 §A8.5 If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under section A8.4(4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Tables 2 and 3 is not required. In addition, radiated emissions which fall in the restricted bands of Table 1 must also comply with the radiated emission limits specified in Tables 2 and 3.

IC RSS-Gen §4.7

The search for unwanted emissions shall be from the lowest frequency internally generated or used in the device (local oscillator, intermediate of carrier frequency), or from 30 MHz, whichever is the lowest frequency, to the 5th harmonic of the highest frequency generated without exceeding 40 GHz.

FCC §15.205 (a) Except as shown in paragraph (d) of 15.205 (a), only spurious emissions are permitted in any of the frequency bands listed.

FCC §15.205 (a) Except as shown in paragraphs (d) and (e) of this section, the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section §15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

FCC §15.209 (a) Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Axxcelera Tri-Band CPE
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: AXXC06-A2 Rev A
Issue Date: 10th December 2008
Page: 68 of 86

Frequency (MHz)	Field Strength (μ V/m)	Field Strength (dB μ V/m)	Measurement Distance (meters)
30-88	100	40.0	3
88-216	150	43.5	3
216-960	200	46.0	3
Above 960	500	54.0	3

Laboratory Measurement Uncertainty for Radiated Emissions

Measurement uncertainty	+5.6/ -4.5 dB
-------------------------	---------------

Traceability

Method	Test Equipment Used
Measurements were made per work instruction WI-03 'Measurement of Radiated Emissions'	0088, 0158, 0134, 0304, 0311, 0315, 0310, 0312

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

5.1.6.2. Receiver Radiated Spurious Emissions (above 1 GHz)


Industry Canada RSS-Gen §4.8, §6

Test Procedure

Radiated emissions above 1 GHz are measured in the anechoic chamber at a 3-meter distance on every azimuth in both horizontal and vertical polarities. The emissions are recorded and maximized as a function of azimuth by rotation through 360° with a spectrum analyzer in peak hold mode. Depending on the frequency band spanned a notch filter and waveguide filter was used to remove the fundamental frequency. The highest emissions relative to the limit are listed for each frequency spanned.

All measurements on any frequency or frequencies over 1 MHz are based on the use of measurement instrumentation employing an average detector function. All measurements above 1 GHz were performed using a minimum resolution bandwidth of 1 MHz.

Test Measurement Set up



Measurement set up for Radiated Emission Test

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Loss, and subtracting Amplifier Gain from the measured reading. All factors are included in the reported data.

$$FS = R + AF + CORR - FO$$

where: FS = Field Strength

R = Measured Spectrum analyzer Input Amplitude

AF = Antenna Factor

CORR = Correction Factor = CL - AG + NFL

CL = Cable Loss

AG = Amplifier Gain

FO = Distance Falloff Factor

NFL = Notch Filter Loss or Waveguide Loss



Title: Axxcelera Tri-Band CPE
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: AXXC06-A2 Rev A
Issue Date: 10th December 2008
Page: 70 of 86

For example:

Given receiver input reading of 51.5 dB μ V; Antenna Factor of 8.5 dB; Cable Loss of 1.3 dB; Falloff Factor of 0 dB, an Amplifier Gain of 26 dB and Notch Filter Loss of 1 dB. The Field Strength of the measured emission is:

$$FS = 51.5 + 8.5 + 1.3 - 26.0 + 1 = 36.3 \text{ dB}\mu\text{V/m}$$

Conversion between dB μ V/m (or dB μ V) and μ V/m (or μ V) are done as:

$$\text{Level (dB}\mu\text{V/m)} = 20 * \text{Log} (\text{level (\mu V/m)})$$

$$40 \text{ dB}\mu\text{V/m} = 100 \mu\text{V/m}$$

$$48 \text{ dB}\mu\text{V/m} = 250 \mu\text{V/m}$$

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.


Receiver Radiated Spurious Emissions above 1 GHz

TABLE OF RESULTS – 5,785 MHz

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments

No emissions within 6dB of the limit line were found

5,785 MHz – Receiver Radiated Emissions



The above plot depicts peak receiver spurious emissions

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Axxcelera Tri-Band CPE
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: AXXC06-A2 Rev A
Issue Date: 10th December 2008
Page: 72 of 86

Specification

Receiver Radiated Spurious Emissions

Industry Canada RSS-Gen §4.8,

The search for spurious emissions shall be from the lowest frequency internally generated or used in the receiver (e.g. local oscillator, intermediate or carrier frequency), or 30 MHz, whichever is the higher, to at least 3 times the highest tunable or local oscillator frequency, whichever is the higher, without exceeding 40 GHz.

RSS-Gen §6

The following receiver spurious emission limits shall be complied with;

(a) If a radiated measurement is made, all spurious emissions shall comply with the limits of Table 1.

Frequency (MHz)	Field Strength (μ V/m)	Field Strength (dB μ V/m)	Measurement Distance (meters)
30-88	100	40.0	3
88-216	150	43.5	3
216-960	200	46.0	3
Above 960	500	54.0	3

Laboratory Measurement Uncertainty for Radiated Emissions

Measurement uncertainty	+5.6/ -4.5 dB
-------------------------	---------------

Traceability

Method	Test Equipment Used
Measurements were made per work instruction WI-03 'Measurement of Radiated Emissions'	0088, 0158, 0134, 0304, 0311, 0315, 0310, 0312

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.


5.1.6.3. Radiated Spurious Emissions (30M-1 GHz)

FCC, Part 15 Subpart C §15.205/ §15.209
Industry Canada RSS-210 §2.2

Test Procedure

Testing 30M-1 GHz was performed in a 3-meter anechoic chamber using a CISPR compliant receiver. Preliminary radiated emissions were measured on every azimuth and with the receiving antenna in both horizontal and vertical polarizations. To further maximize emissions the receive antenna was varied between 1 and 4 meters. The emissions are recorded with receiver in peak hold mode. Emissions closest to the limits are measured in the quasi-peak mode with the tuned receiver using a bandwidth of 120 kHz. Only the highest emissions relative to the limit are listed. The anechoic chamber test set-up is identified in Section 6 Test Set-Up Photographs.

Test Measurement Set up



Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Loss, and subtracting Amplifier Gain from the measured reading. In this test facility, the Antenna Factor, Cable Loss, and Amplifier Gains are loaded into the Rohde & Schwarz Receiver and the corrected field strength can be read directly on the receiver.

$$FS = R + AF + CORR$$

where:

FS = Field Strength

R = Measured Receiver Input Amplitude

AF = Antenna Factor

CORR = Correction Factor = CL - AG + NFL

CL = Cable Loss

AG = Amplifier Gain



Title: Axxcelera Tri-Band CPE
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: AXXC06-A2 Rev A
Issue Date: 10th December 2008
Page: 74 of 86

For example:

Given a Receiver input reading of 51.5dB μ V; Antenna Factor of 8.5dB; Cable Loss of 1.3dB; Falloff Factor of 0dB, an Amplifier Gain of 26dB and Notch Filter Loss of 1dB. The Field Strength of the measured emission is:

$$FS = 51.5 + 8.5 + 1.3 - 26.0 + 1 = 36.3\text{dB}\mu\text{V/m}$$

Conversion between dB μ V/m (or dB μ V) and μ V/m (or μ V) are done as:

$$\text{Level (dB}\mu\text{V/m)} = 20 * \text{Log} (\text{level (}\mu\text{V/m)})$$

$$40 \text{ dB}\mu\text{V/m} = 100\mu\text{V/m}$$

$$48 \text{ dB}\mu\text{V/m} = 250\mu\text{V/m}$$

Measurement Results for Spurious Emissions (30 MHz – 1 GHz)

Ambient conditions.

Temperature: 17 to 23 °C Relative humidity: 31 to 57 % Pressure: 999 to 1012 mbar


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

Test Setup

TABLE OF RESULTS

Freq. (MHz)	Peak (dBuV/m)	QP (dBuV/m)	QP Lmt (dBuV/m)	QP Margin (dB)	Height (cm)	Angle (deg)	Polarity
30.00	43.69	33.49	40	-6.51	160	122	V
90.261	41.53	37.31	43.5	-6.19	383	206	H
30.654	37.04	35.48	40	-4.52	166	235	V
800.006	40.94	41.97	46	-4.03	104	83	H
840.003	38.51	37.75	46	-8.25	101	42	H
600.00	34.20	39.29	46	-6.71	107	33	V

Radiated Spurious Emissions 30 MHz to 1 GHz



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Axxcelera Tri-Band CPE
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: AXXC06-A2 Rev A
Issue Date: 10th December 2008
Page: 76 of 86

Specification

Limits

§15.205 (a) Except as shown in paragraph (d) of 15.205 (a), only spurious emissions are permitted in any of the frequency bands listed.

§15.205 (a) Except as shown in paragraphs (d) and (e) of this section, the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section §15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

§15.209 (a) Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table.

§15.209 (a) and RSS-Gen §2.2 Limit Matrix

Frequency(MHz)	Field Strength (μ V/m)	Field Strength (dB μ V/m)	Measurement Distance (meters)
30-88	100	40.0	3
88-216	150	43.5	3
216-960	200	46.0	3
Above 960	500	54.0	3

Laboratory Measurement Uncertainty for Radiated Emissions

Measurement uncertainty	+5.6/ -4.5 dB
-------------------------	---------------

Traceability

Method	Test Equipment Used
Measurements were made per work instruction WI-03 'Measurement of Radiated Emissions'	0088, 0158, 0134, 0304, 0311, 0315, 0310, 0312

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.


5.1.7. AC Wireline Conducted Emissions (150 kHz – 30 MHz)

FCC, Part 15 Subpart C §15.207
Industry Canada RSS-Gen §7.2.2

Test Procedure

The EUT is configured in accordance with ANSI C63.4. The conducted emissions are measured in a shielded room with a spectrum analyzer in peak hold in the first instance. Emissions closest to the limit are measured in the quasi-peak mode (QP) with the tuned receiver using a bandwidth of 9 kHz. The emissions are maximized further by cable manipulation. The highest emissions relative to the limit are listed.

Test Measurement Set up



Measurement set up for AC Wireline Conducted Emissions Test

Measurement Results for AC Wireline Conducted Emissions (150 kHz – 30 MHz)

Ambient conditions.


Temperature: 17 to 23 °C Relative humidity: 31 to 57 % Pressure: 999 to 1012 mbar

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

TABLE OF RESULTS

Freq (MHz)	Line	Peak (dB μ V)	QP (dB μ V)	QP Limit (dB μ V)	QP Margin (dB)	Ave. (dB μ V)	Ave. Limit (dB μ V)	Ave. Margin (dB)
4.977	Neutral	50.76	50.03	56	-5.97	45.65	46	-0.35
1.009	Live	47.84	47.12	56	-8.90	45.44	46	-0.56
5.237	Neutral	51.66	49.43	60	-10.57	41.97	50	-8.03
0.150	Live	56.70	53.31	66	-12.70	40.26	56	-15.70
1.267	Live	43.82	44.25	56	-11.75	40.40	46	-5.60
26.609	Live	46.08	45.84	50	-14.16	37.93	50	-12.07

AC Wireline Conducted Emissions – Live and Neutral Lines (150 kHz – 30 MHz)



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Axxcelera Tri-Band CPE
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: AXXC06-A2 Rev A
Issue Date: 10th December 2008
Page: 79 of 86

Specification

Limit

§15.207 (a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 $\mu\Omega$ line impedance stabilization network (LISN), see §15.207 (a) matrix below. Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal.

RSS-Gen §7.2.2

The radio frequency voltage that is conducted back into the AC power lines in the frequency range of 0.15 MHz to 30 MHz shall not exceed the limits shown in the table below. The tighter limit applies at the frequency range boundaries.

§15.207 (a) and RSS-Gen §7.2.2 Limit Matrix

The lower limit applies at the boundary between frequency ranges

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency

Laboratory Measurement Uncertainty for Conducted Emissions

Measurement uncertainty	± 2.64 dB
-------------------------	---------------

Traceability

Method	Test Equipment Used
Measurements were made per work instruction WI-EMC-01 'Measurement of Conducted Emissions'	0158, 0184, 0193, 0190, 0293, 0307

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

6. PHOTOGRAPHS

6.1. Radiated Spurious Emissions >1 GHz




This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

6.2. Radiated Spurious Emissions <1 GHz




This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

6.3. AC Wireline Emissions (150 kHz - 30 MHz)



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

6.4. General Measurement Test Set-Up #1



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

6.5. General Measurement Test Set-Up Environmental Chamber



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Axxcelera Tri-Band CPE
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: AXXC06-A2 Rev A
Issue Date: 10th December 2008
Page: 85 of 86

7. TEST EQUIPMENT DETAILS

Asset #	Instrument	Manufacturer	Part #	Serial #
0088	Spectrum Analyzer	Hewlett Packard	8564E	3410A00141
0134	Amplifier	Com Power	PA 122	181910
0158	Barometer /Thermometer	Control Co.	4196	E2846
0193	EMI Receiver	Rhode & Schwartz	ESI 7	838496/007
0252	SMA Cable	Megaphase	Sucoflex 104	None
0310	2m SMA Cable	Micro-Coax	UFA210A-0-0787-3G03G0	209089-001
0312	3m SMA Cable	Micro-Coax	UFA210A-1-1181-3G0300	209092-001
0313	Coupler	Hewlett Packard	86205A	3140A01285
0314	30dB N-Type Attenuator	ARRA	N9444-30	1623
0070	Power Meter	Hewlett Packard	437B	3125U11552
0116	Power Sensor	Hewlett Packard	8485A	3318A19694
0117	Power Sensor	Hewlett Packard	8487D	3318A00371
0184	Pulse Limiter	Rhode & Schwartz	ESH3Z2	357.8810.52
0190	LISN	Rhode & Schwartz	ESH3Z5	836679/006
0293	BNC Cable	Megaphase	1689 1GVT4	15F50B001
0301	5.6 GHz Notch Filter	Micro-Tronics	RBC50704	001
0302	5.25 GHz Notch Filter	Micro-Tronics	BRC50703	002
0303	5.8 GHz Notch Filter	Micro-Tronics	BRC50705	003
0304	2.4GHzHz Notch Filter	Micro-Tronics	--	001
0307	BNC Cable	Megaphase	1689 1GVT4	15F50B002
0335	1-18GHz Horn Antenna	ETS- Lindgren	3117	00066580
0337	Amplifier	MiCOM Labs	--	--
0338	Antenna	Sunol Sciences	JB-3	A052907

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



440 Boulder Court, Suite 200
Pleasanton, CA 94566, USA
Tel: 1.925.462.0304
Fax: 1.925.462.0306
www.micomlabs.com