

# R.F Exposure/Safety Calculation for MRU - PCS

The E.U.T. is rack or wall mounted. The typical distance between the E.U.T. and the general population is >100cm.

Calculation of Maximum Permissible Exposure (MPE)  
Based on Section 1.1310 Requirements

(a) FCC limit at 1993.8MHz is:  $1 \frac{mW}{cm^2}$

Using table 1 of Section 1.1310 limit for general population/uncontrolled exposures, the above level is an average over 30 minutes.

(b)The power density produced by the E.U.T. is

$$S = \frac{P_t G_t}{4\pi R^2}$$

P<sub>t</sub>- Transmitted Peak Power (worst case)

G<sub>T</sub>- Antenna Gain, 12.5dBi= 17.8 numeric

R- Distance from Transmitter 100 cm

(c) Peak power density at worst case continuous transmission:

Band	Modulation	Pt (dBm)	Pt (mW)	Antenna type	G <sub>T</sub> (dBi)	G <sub>T</sub> numeric	R (cm)	S <sub>AV</sub> (mW/cm <sup>2</sup> )	Spec (mW/cm <sup>2</sup> )
PCS	LTE 64QAM	33.9	2455	External	12.5	17.8	100	0.347746	1
	GSM	34.3	2692	External	12.5	17.8	100	0.381316	1
	W-CDMA	34.3	2692	External	12.5	17.8	100	0.381316	1

(d) This is below the FCC limit.