





Appendix G-Frequency Stability

Test Data:

Frequency Stability vs temperature:

1.Test for FDD LTE Band 66 Downlink (Middle Channel: 2145MHz)

'		
Temperature(°C)	Frequency Error (Hz)	Tolerance(ppm)
50	53.22	0.0248
40	49.69	0.0232
30	64.15	0.0299
20	16.87	0.0079
10	95.77	0.0446
0	36.31	0.0169
-10	6.74	0.0031
-20	34.24	0.0160
-30	27.54	0.0128

Frequency Stability vs voltage:

1. Test for FDD LTE Band 66 Downlink (Middle Channel: 2145MHz)

Voltage (V dc)	Frequency Error (Hz)	Tolerance(ppm)
43.2	60.76	0.0283
48	77.76	0.0362
52.8	57.36	0.0267



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printe overleaf, available on request or accessible at http://www.aga.com/an/Terms-and-Conditions.agv.and, for electronic formst document subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.asp. Attention is drawn to the limitation of liability, indemnification and jurisdiction is seed effined therein. Any holder of this document advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduce except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.