

DATE: 18 February 2009

I.T.L. (PRODUCT TESTING) LTD.
FCC Radio Test Report
for
MobileAccess Networks

Equipment under test:

**WLAN Module With WCE (WiFi Coverage Extender) for
DAS With Four Cisco 1242 Access Points**

860M-AU With WCE-AU

5 GHz Transmitter

Written by:




D. Shidowsky, Documentation

Approved by:



A. Sharabi, Test Engineer

Approved by:



I. Raz, EMC Laboratory Manager

This report must not be reproduced, except in full, without the written permission of I.T.L. (Product Testing) Ltd.

This report relates only to items tested.

Measurement/Technical Report for MobileAccess Networks

WLAN Module With WCE (WiFi Coverage Extender) for DAS With Four Cisco 1242 Access Points

860M-AU With WCE-AU

FCC ID: OJFMA860WCE-AU

This report concerns: Original Grant: X

Class I Change:

Class II Change:

Equipment type: NII

Limits used:

47CFR15 Section 15.407

Measurement procedure used is ANSI C63.4-2003.

Application for Certification
prepared by:

Ishaishou Raz

ITL (Product Testing) Ltd.

Kfar Bin Nun

D.N. Shimshon 99780

Israel

e-mail Sraz@itl.co.il

Applicant for this device:
(different from "prepared by")

Steve Blum

Mobile Access Networks

8391 Old Courthouse Rd., Suite #300

Vienna, VA. 22182

U.S.A.

Tel: +1-541-758-2880

Fax: +1-703-848-0260

e-mail: sblum@mobileaccess.com

TABLE OF CONTENTS

1. GENERAL INFORMATION -----	5
1.1 Administrative Information.....	5
1.2 List of Accreditations	6
1.3 Product Description	7
1.4 Test Methodology.....	7
1.5 Test Facility	7
1.6 Measurement Uncertainty	7
2. SYSTEM TEST CONFIGURATION-----	8
2.1 Justification.....	8
2.2 EUT Exercise Software	9
2.3 Special Accessories	9
2.4 Equipment Modifications	9
2.5 Configuration of Tested System.....	10
3. THEORY OF OPERATION -----	11
3.1 Theory of Operation	11
4. CONDUCTED EMISSION DATA-----	13
4.1 Test Specification	13
4.2 Test Procedure.....	13
4.3 Measured Data.....	13
4.4 Test Instrumentation Used, Conducted Measurement	18
5. SPURIOUS RADIATED EMISSION IN THE RESTRICTED BAND, BELOW 1 GHZ	19
 802.11B/G+802.11A + WMTS + AWS SIGNALS-----	19
5.1 Test Specification	19
5.2 Test Procedure.....	19
5.3 Test Data.....	20
5.4 Test Instrumentation Used, Radiated Measurements	21
5.5 Field Strength Calculation	22
6. SPURIOUS RADIATED EMISSION IN THE RESTRICTED BAND, ABOVE 1 GHZ	23
 802.11B/G+802.11A + WMTS + AWS SIGNALS-----	23
6.1 Radiated Emission Above 1 GHz.....	23
6.2 Test Data.....	24
6.3 Test Instrumentation Used, Radiated Measurements Above 1 GHz	31
7. 26 DB BANDWIDTH 802.11B/G+802.11A +WMTS + AWS SIGNALS -----	32
7.1 Test procedure	32
7.2 Test Equipment Used.....	39
8. MAXIMUM CONDUCTED OUTPUT POWER 802.11B/G+802.11A + WMTS + AWS SIGNALS -----	40
8.1 Test procedure	40
8.2 Results table.....	47
8.3 Test Equipment Used.....	48
9. PEAK POWER SPECTRAL DENSITY 802.11B/G+802.11A + WMTS + AWS SIGNALS -----	49
9.1 Test procedure	49
9.2 Results table.....	55
9.3 Test Equipment Used.....	56
10. RATIO OF PEAK EXCURSION OF MODULATION ENVELOPE TO MAXIMUM CONDUCTED OUTPUT POWER 802.11B/G+802.11A + WMTS + AWS SIGNALS-----	57
10.1 Test procedure	57
10.2 Results table.....	63
10.3 Test Equipment Used.....	64

11. PEAK POWER OUTPUT OUT OF 5150-5250; 5725-5825 MHZ BANDS	
802.11B/G+802.11A + WMTS + AWS SIGNALS -----	65
11.1 Test procedure	65
11.2 Results table.....	115
11.3 Test Equipment Used.....	116
12. BAND EDGE SPECTRUM 802.11B/G+802.11A + WMTS + AWS SIGNALS-----	117
12.1 Test procedure	117
12.2 Results table.....	122
12.3 Results table.....	123
12.4 Test Equipment Used.....	124
13. ANTENNA GAIN 802.11B/G+802.11A + WMTS + AWS SIGNALS -----	125
14. R.F EXPOSURE/SAFETY 802.11B/G+802.11A + WMTS + AWS SIGNALS -----	126
15. INTERMODULATION TESTS-----	127
15.1 Test procedure	127
15.2 Test Equipment Used.....	134
16. APPENDIX A - CORRECTION FACTORS-----	135
16.1 Correction factors for CABLE.....	135
16.2 Correction factors for CABLE.....	136
16.3 Correction factors for CABLE.....	137
16.4 Correction factors for CABLE.....	138
16.6 Correction factors for LOG PERIODIC ANTENNA.....	139
16.5 Correction factors for LOG PERIODIC ANTENNA.....	140
16.6 Correction factors for BICONICAL ANTENNA.....	141
16.7 Correction factors for BICONICAL ANTENNA.....	142
16.8 Correction factors for Double-Ridged Waveguide Horn	143
16.9 Correction factors for Horn Antenna	144
16.10 Correction factors for Horn Antenna	145
16.11 Correction factors for ACTIVE LOOP ANTENNA	146

1. General Information

1.1 Administrative Information

Manufacturer: MobileAccess Networks

Manufacturer's Address: 8391 Old Courthouse Rd.
Suite #300
Vienna, VA 22182
U.S.A.
Tel: +1-541-758-2880
Fax: +1-703-848-0260

Manufacturer's Representative: Steve Blum

Equipment Under Test (E.U.T): WLAN Module With WCE (WiFi Coverage Extender) for DAS With Four Cisco 1242 Access Points

Equipment Model No.: 860M-AU With WCE-AU

Equipment Serial No.: 860M-AU: 0837453; WCE-AU: 0847A54

Date of Receipt of E.U.T: 01.02.09

Start of Test: 01.02.09

End of Test: 05.02.09

Test Laboratory Location: I.T.L (Product Testing) Ltd.
Kfar Bin Nun,
ISRAEL 99780

Test Specifications: See Section 2

1.2 List of Accreditations

The EMC laboratory of I.T.L. is accredited by the following bodies:

1. The American Association for Laboratory Accreditation (A2LA) (U.S.A.), Certificate No. 1152.01.
2. The Federal Communications Commission (FCC) (U.S.A.), Registration No. 90715.
3. The Israel Ministry of the Environment (Israel), Registration No. 1104/01.
4. The Voluntary Control Council for Interference by Information Technology Equipment (VCCI) (Japan), Registration Numbers: C-1350, R-1285.
5. Industry Canada (Canada), IC File No.: 46405-4025; Site No. IC 4025B-1.
6. TUV Product Services, England, ASLLAS No. 97201.
7. Nemko (Norway), Authorization No. ELA 207.

I.T.L. Product Testing Ltd. is accredited by the American Association for Laboratory Accreditation (A2LA) and the results shown in this test report have been determined in accordance with I.T.L.'s terms of accreditation unless stated otherwise in the report.

1.3 **Product Description**

The MobileAccess 860 WLAN Solution delivers pervasive WLAN coverage throughout enterprise environments using a unique multi-service wireless architecture. With the MA-860 approach, enterprises can seamlessly translate their WLAN investments and design expertise into a comprehensive, multi-service wireless solution.

The MA-860 combines WLAN services with signals from other wireless sources, including voice and data services from multiple wireless operators, public safety, and building automation applications. It then distributes the combined RF signals over a common set of broadband cables and antennas. One-Click calibration between the MA-860 module and the MobileAccess Wi-Fi Coverage Expander (WCE) ensures optimal coverage by mirroring the coverage footprint and system behavior of “AP-on-Ceiling” deployments for 802.11a and 802.11b/g WLAN services.

This Wire-it-Once™ approach spreads WLAN deployment costs across multiple wireless service needs, providing facility-wide coverage for WLAN and all other wireless services while creating a flexible infrastructure that adapts to evolving technology requirements.

In addition, the MA-860 WLAN solution locates Access Points (APs) in secure telecom closets alongside other LAN internetworking equipment, yielding significant operational benefits:

- Provides physical security of the APs
- Makes APs more accessible to IT staff
- Reduces ongoing operational expenses

1.4 **Test Methodology**

Both conducted and radiated testing were performed according to the procedures in ANSI C63.4: 2003. Radiated testing was performed at an antenna to EUT distance of 3 meters.

1.5 **Test Facility**

The radiated emissions tests were performed at I.T.L.’s testing facility at Kfar Bin-Nun, Israel. This site is a FCC listed test laboratory (FCC Registration No. 90715, date of listing August 22, 2006).

I.T.L.’s EMC Laboratory is also accredited by A2LA, certificate No. 1152.01.

1.6 **Measurement Uncertainty**

Radiated Emission

The Open Site complies with the ± 4 dB Normalized Site Attenuation requirements of ANSI C63.4-2003. In accordance with Paragraph 5.4.6.1 of this standard, this tolerance includes instrumentation calibration errors, measurement technique errors, and errors due to site anomalies.

2. System Test Configuration

2.1 Justification

The E.U.T. was originally authorized for FCC under FCC ID OJFMA860WCE. Due to changes in both the 860M and the WCE a new certification is required. Testing was performed according to correspondence with Mr. Joe Dichoso of the FCC dated 29 May 2008 :

“From: Steve Blum [mailto:sblum@mobileaccess.com]

Sent: Thursday, May 29, 2008 3:06 PM

To: Joe Dichoso

Subject: RE: FCC Guidance

Yes, we have two issues: summary of test data attached. Let me know if you need more details.

1. MobileAccess is requesting updated guidance on the part 15 testing for the model 860. The 860 is essentially a part 15 subpart C amplifier for 802.11 b/g/a WLAN services.

a. Main difference is the 860 couples licensed services (via certificated transmitters) onto the coax with the 802.11b/g and a services.

1. Licensed services are passively coupled and all services are filtered to prevent interference.

b. Previous guidance from FCC from March 2006, requires 3 sets of tests, b/g only, b/g and a, b/g with a and cell/pcs.

c. Test data from all submissions to date (summary attached) shows that “b/g and a” is worse case while passing all b/g and a tests.

d. Request that guidance be modified to require only “b/g and a” test for future submissions

1. MobileAccess agrees that the 860 is professionally installed and must be tested and sold with labels on transmitter for the specific transmitter approved.

Reply: As before, the amplifier must be certified with a specific transmitter FCC ID XXXXXX it was tested with. Please note marketing requirements per 15.204(d). The amplifier must be marketed with the transmitter or designed in such a fashion that it can be used only with that transmitter. You can submit full tests with all “b/g and a” and cell/pcs active. Prescan tests can be made in all other modes.

Steve Blum

Product Manager

MobileAccess

Office 541 758-2880

Mobile 541 990-3470

Making Wireless an Indoor State of Mind

This electronic mail message and any attached files or documents contain information intended for the exclusive use of the party or parties to whom it is addressed and may contain information that is confidential, proprietary and/or privileged. If you are not an intended recipient, or the person responsible for delivering the e-mail to the intended recipient, you are hereby notified that you have received this message in error and that any viewing, copying, disclosure, distribution, dissemination, forwarding, printing or other use of this information is strictly prohibited and may be subject to legal restriction or sanction. Please notify the sender, by electronic mail or telephone, of any unintended recipients and destroy all copies of this message and the attachments (if any) without making any copies thereof."

The EUT consists of the 860M, WCE and 4 identical access points. The system combines 802.11 signals with the cellular signals. The cellular signal are represented in the setup by the WMTS and AWS portion of the setup, which were connected to the EUT through MobileAccess standard infrastructure (i.e. RIU, BU, RHU and a controller) to represent a normal installation of the EUT. An “Exercise” SW on the laptops was used to trigger the access points to transmit continuously, while the EUT output was connected to the spectrum analyzer.

2.2 *EUT Exercise Software*

The Acces Point (AP) (as part of the EUT) was triggered to transmit using an “Exercise SW”.

The program “Air Magnet” was used to trigger the AP to continuously transmit packets.

2.3 *Special Accessories*

No special accessories were needed to achieve compliance.

2.4 *Equipment Modifications*

No modifications were necessary in order o achieve compliance.

2.5 Configuration of Tested System




Figure 1. Configuration of Tested System

Note: The system was tested using four identical Cisco Access Points M/N 1242, S/N FTX1108B616, S/N FTX11013B13Q, S/N FTX1108B60Z, S/N FTX1108B605, FCC ID: LDK102056.

3. Theory of Operation

3.1 Theory of Operation



Making Wireless an Indoor State of Mind


MA-860 WLAN Solution

MA-860 Solution Overview

The MobileAccess 860 WLAN Solution delivers pervasive WLAN coverage throughout enterprise environments using a unique multi-service wireless architecture. With the MA-860 approach, enterprises can seamlessly translate their WLAN investments and design expertise into a comprehensive, multi-service wireless solution.

The MA-860 combines WLAN services with signals from other wireless sources, including voice and data services from multiple wireless operators, public safety, and building automation applications. It then distributes the combined RF signals over a common set of broadband cables and antennas. One-Click calibration between the MA-860 module and the MobileAccess Wi-Fi Coverage Expander (WCE) ensures optimal coverage by mirroring the coverage footprint and system behavior of "AP-on-Ceiling" deployments for 802.11a and 802.11b/g WLAN services.

This Wire-it-Once™ approach spreads WLAN deployment costs across multiple wireless service needs, providing facility-wide coverage for WLAN and all other wireless services while creating a flexible infrastructure that adapts to evolving technology requirements.



In addition, the MA-860 WLAN solution locates Access Points (APs) in secure telecom closets alongside other LAN internetworking equipment, yielding significant operational benefits:

- ▶ Provides physical security of the APs
- ▶ Makes APs more accessible to IT staff
- ▶ Reduces ongoing operational expenses

MobileAccess 860 WLAN Module



Benefits

Cost-Effective Multi-Service Solution

- ▶ Delivers WLAN and other wireless RF signals over a single multi-service infrastructure
- ▶ Spreads WLAN deployment costs across multiple wireless services

Dependable WLAN Coverage

- ▶ MobileAccess WLAN architecture mirrors the behaviors and coverage footprint of "AP-on-Ceiling" deployment
- ▶ One-Click compensation ensures optimal 802.11b/g and 802.11a coverage
- ▶ Dedicated AP to antenna relationships ensure transparent support for WLAN applications such as VOIP and location services (RTLS)
- ▶ Redundant power option

Centralized & Secure AP Management

- ▶ Lowers operating expenses
- ▶ Provides physical security and simplifies management

Proactive End-to-End Monitoring

- ▶ Remote SNMP monitoring for status, alerting, and fault detection
- ▶ Monitoring extends to attached multi-service antennas


Simplified IT Deployment Model

- ▶ Uses standard WLAN design techniques



8391 Old Courthouse Road, Suite 300, Vienna, VA 22182
 Tel: (800)436-9266, (703) 848-0200 TAC:(800) 787-1266 Fax:(703) 848-0280
www.mobileaccess.com

MA-860 Product Specifications

802.11 RF Parameters			Power																									
860(M/R) with Wi-Fi Coverage Expander (WCE):			Power																									
<table border="1"> <thead> <tr> <th></th><th>802.11a</th><th>802.11b/g</th></tr> </thead> <tbody> <tr> <td>Gain TX (dB)</td><td>0</td><td>0</td></tr> <tr> <td>Output Power (dBm)</td><td>17</td><td>b: 20 g: 17</td></tr> <tr> <td>Gain RX (dB)</td><td>4</td><td>4</td></tr> <tr> <td>NF RX (dB)</td><td>5</td><td>5</td></tr> <tr> <td>Flatness (dB)</td><td>+/- 2.0</td><td>+/- 1.5</td></tr> </tbody> </table>				802.11a	802.11b/g	Gain TX (dB)	0	0	Output Power (dBm)	17	b: 20 g: 17	Gain RX (dB)	4	4	NF RX (dB)	5	5	Flatness (dB)	+/- 2.0	+/- 1.5	2 DC Power Inputs DC-1 = 28V Mandatory DC Power, 66 Watts DC-2= 9.8V Optional Redundant Power, 40 Watts							
	802.11a	802.11b/g																										
Gain TX (dB)	0	0																										
Output Power (dBm)	17	b: 20 g: 17																										
Gain RX (dB)	4	4																										
NF RX (dB)	5	5																										
Flatness (dB)	+/- 2.0	+/- 1.5																										
860(M/R) Module Standalone:			Physical Specifications																									
<table border="1"> <thead> <tr> <th></th><th>802.11a</th><th>802.11b/g</th></tr> </thead> <tbody> <tr> <td>Insertion Loss (dB)</td><td>3</td><td>2</td></tr> <tr> <td>Flatness (dB)</td><td>+/- 1.0</td><td>+/- 1.0</td></tr> </tbody> </table>				802.11a	802.11b/g	Insertion Loss (dB)	3	2	Flatness (dB)	+/- 1.0	+/- 1.0	Dimensions: 860(M/R): 242 mm x 279 mm x 38 mm (9.54 in x 10.98 in x 1.5 in) WCE: 130 mm x 120 mm x 20 mm (5.12 in x 4.73in x 0.8 in)																
	802.11a	802.11b/g																										
Insertion Loss (dB)	3	2																										
Flatness (dB)	+/- 1.0	+/- 1.0																										
Mobile Services Parameters			Weight: 860(M/R): 2.82 kg (6.2 lb) WCE: 0.80 kg (1.8 lb)																									
<table border="1"> <thead> <tr> <th></th><th>Cell</th><th></th><th>PCS</th></tr> </thead> <tbody> <tr> <td>Band (MHz)</td><td>896-960</td><td></td><td>1710-1990</td></tr> <tr> <td>Insertion Loss (dB)</td><td></td><td></td><td></td></tr> <tr> <td>MA-860</td><td>1.0</td><td></td><td>2.5</td></tr> <tr> <td>WCE</td><td>1.2</td><td></td><td>3.5</td></tr> <tr> <td>System</td><td>2.2</td><td></td><td>6.0</td></tr> </tbody> </table>				Cell		PCS	Band (MHz)	896-960		1710-1990	Insertion Loss (dB)				MA-860	1.0		2.5	WCE	1.2		3.5	System	2.2		6.0	Environmental Specifications	
	Cell		PCS																									
Band (MHz)	896-960		1710-1990																									
Insertion Loss (dB)																												
MA-860	1.0		2.5																									
WCE	1.2		3.5																									
System	2.2		6.0																									
RF Connections			Temperature: Operating 0°C to +50°C (32°F to 122°F) Storage -20°C to +85°C (-4°C to 185°C)																									
<u>860(M/R)</u> 802.11 b/g (4) SMA Female, 50 ohm 802.11 a (4) SMA Female, 50 ohm Mobile Services Antenna Ports (4) SMA Female, 50 ohm WCE (4) N-type Female, 50 ohm			Humidity: Operating 95% (non-condensing) Storage 95% (non-condensing)																									
WCE			Ordering Information																									
Coax (860 facing) (1) N-type Male Coax (Ant facing) (1) N-type Female			860M 860 WLAN Module 860R 860 WLAN Module - Redundant Power Supply Option WCE Wi-Fi Coverage Expander																									
Standards and Approvals			Accessory Kits for mounting 860(M/R):																									
FCC-47, CFR 15.109, Part 15 Sections B, C, and E UL / IEC 60950 -1 UL1960 Fire Safety requirements UL2043 Fire/Plenum (WCE) CE EN 60950 CAN/CSA C22.2 No 60950			AK-860-1000 860 with MA-1000 AK-860-1200 860 with MA-1200 AK-860-MDLT 860 with ModuLite AK-860-2000 860 with MA-2000 AK-860-SA 860 stand alone AK-860-2000L 860 with MA-2000 Lite AK-860-PWR Redundant Power Supply																									
Management			Wiring Diagram																									
The 860(M/R) can be configured and monitored through either a local RS-485 connection or a Web browser application via an RJ-45 Ethernet connection																												

8391 Old Courthouse Road, Suite 300, Vienna, VA 22182
 Tel: (800)436-9266, (703) 845-0200 TAC (600) 737-1266 Fax: (703) 845-0280
www.mobileaccess.com

4. Conducted Emission Data

4.1 Test Specification

F.C.C., Part 15, Subpart C

4.2 Test Procedure

The E.U.T operation mode and test set-up are as described in Section 3.1. In order to minimize background noise interference, the conducted emission testing was performed inside a shielded room, with the E.U.T placed on an 0.8 meter high wooden table, 0.4 meter from the room's vertical wall.

The E.U.T was powered from 115 V AC / 60 Hz via a 50 Ohm / 50 μ Hn Line Impedance Stabilization Network (LISN) on the phase and neutral lines. The LISN's were grounded to the shielded room ground plane (floor), and were kept at least 0.8 meters from the nearest boundary of the E.U.T

The center of the E.U.T AC cable was folded back and forth, in order to form a bundle less than 0.40 meters and a total cable length of 1 meter.

The emission voltages at the LISN's outputs were measured using a computerized receiver, complying with CISPR 16 requirements. The specification limits are loaded to the receiver via a 3.5" floppy disk and are displayed on the receiver's spectrum display.

A frequency scan between 0.15 and 30 MHz was performed at 9 kHz I.F. band width, and using peak detection.

The spectral components having the highest level on each line were measured using a quasi-peak and average detector.

4.3 Measured Data

JUDGEMENT: Passed by 1.6 dB

The margin between the emission levels and the specification limit was, in the worst case, 1.6 dB for the phase line at 1.23 MHz and 9.7 dB for the neutral line at 9.88 MHz.

The EUT met the F.C.C. Part 15, Subpart C specification requirements.

The details of the highest emissions are given in *Figure 2* to *Figure 5*.

TEST PERSONNEL:

Tester Signature:  Date: 22.02.09

Typed/Printed Name: A. Sharabi

Conducted Emission

E.U.T Description WLAN Module With WCE (WiFi Coverage Extender) for DAS With Four Cisco 1242 Access Points
 Type 860M-AU With WCE-AU
 Serial Number: 860M-AU: 0837453; WCE-AU: 0847A54

Specification: FCC Part 15, Subpart C
 Lead: Phase
 Detectors: Peak, Quasi-peak, Average

Signal Number	Frequency (MHz)	Peak (dBuV)	QP (dBuV)	QP Delta L 1 (dB)	Avg (dBuV)	Av Delta L 2 (dB)	Corr (dB)
1	0.168282	43.7	36.0	-29.1	31.3	-23.8	0.0
2	0.341864	41.6	40.5	-18.7	39.4	-9.8	0.0
3	1.230928	48.0	45.7	-10.3	44.3	-1.6	0.0
4	2.496622	45.5	42.4	-13.6	39.5	-6.4	0.0
5	5.202922	49.4	45.2	-14.8	29.4	-20.6	0.0
6	9.886600	43.5	42.5	-17.5	36.7	-13.4	0.0

Figure 2. Detectors: Peak, Quasi-peak, AVERAGE .

Note: QP Delta/Av Delta refer to the test results obtained minus specified requirement; thus a positive number indicates failure, and a negative result indicates that the product passes the test.

Conducted Emission

E.U.T Description WLAN Module With WCE (WiFi Coverage Extender) for DAS With Four Cisco 1242 Access Points
 Type 860M-AU With WCE-AU
 Serial Number: 860M-AU: 0837453; WCE-AU: 0847A54

Specification: FCC Part 15, Subpart C
 Lead: Phase
 Detectors: Peak, Quasi-peak, Average

 10:32:47 FEB 05, 2009




Figure 3. Detectors: Peak, Quasi-peak, Average

Note: Fail indication on the spectral plot results from peak detector level reading above the limit. This indication is for information only and it should not be interpreted as a test failure.

Conducted Emission

E.U.T Description WLAN Module With WCE (WiFi Coverage Extender) for DAS With Four Cisco 1242 Access Points
 Type 860M-AU With WCE-AU
 Serial Number: 860M-AU: 0837453; WCE-AU: 0847A54

Specification: FCC Part 15, Subpart C
 Lead: Neutral
 Detectors: Peak, Quasi-peak, Average

Signal Number	Frequency (MHz)	Peak (dBuV)	QP (dBuV)	QP Delta L 1 (dB)	Avg (dBuV)	Av Delta L 2 (dB)	Corr (dB)
1	0.167876	41.8	33.3	-31.8	11.9	-43.2	0.0
2	1.037234	12.9	5.1	-50.9	-3.1	-49.1	0.0
3	1.230733	31.8	30.1	-25.9	29.3	-16.7	0.0
4	5.272493	40.8	35.7	-24.3	20.7	-29.3	0.0
5	6.862503	34.8	30.3	-29.7	16.7	-33.3	0.0
6	9.884819	45.5	42.7	-17.4	40.3	-9.7	0.0

Figure 4. Detectors: Peak, Quasi-peak, AVERAGE

Note: QP Delta/Av Delta refer to the test results obtained minus specified requirement; thus a positive number indicates failure, and a negative result indicates that the product passes the test.

Conducted Emission

E.U.T Description WLAN Module With WCE (WiFi Coverage Extender) for DAS With Four Cisco 1242 Access Points
 Type 860M-AU With WCE-AU
 Serial Number: 860M-AU: 0837453; WCE-AU: 0847A54

Specification: FCC Part 15, Subpart C
 Lead: Neutral
 Detectors: Peak, Quasi-peak, Average

 10:37:36 FEB 05, 2009

ACTV DET: PEAK
 MEAS DET: PEAK QP AVG
 MKR 9.87 MHz
 43.50 dB μ V




Figure 5 Conducted Emission: NEUTRAL
Detectors: Peak, Quasi-peak, Average

4.4 Test Instrumentation Used, Conducted Measurement

Instrument	Manufacturer	Model	Serial No.	Last Calibration Date	Period
LISN	Fischer	FCC-LISN-2A	127	March 8, 2008	1 Year
LISN	Fischer	FCC-LISN-2A	128	March 8, 2008	1 Year
EMI Receiver	HP	85422E	3906A00276	November 17, 2008	1 Year
RF Filter Section	HP	85420E	3705A00248	November 16, 2008	1 Year
Printer	HP	LaserJet 2200	JPKGC19982	N/A	N/A

5. Spurious Radiated Emission in the Restricted Band, Below 1 GHz **802.11b/g+802.11a + WMTS + AWS Signals**

5.1 ***Test Specification***

9kHz-1000 MHz, F.C.C., Part 15, Subpart C

5.2 ***Test Procedure***

The E.U.T. operation mode and test set-up are as described in Section 3.

See Section 3.1 Justification of the System Test Configuration concerning the E.U.T. orientation for this test.

A preliminary measurement to characterize the E.U.T was performed inside the shielded room at a distance of 3 meters, using peak detection mode and broadband antennas. The preliminary measurements produced a list of the highest emissions. The E.U.T was then transferred to the open site, and placed on a remote-controlled turntable. The E.U.T was placed on a non-metallic table, 0.8 meters above the ground. The configuration tested is shown in Figure 3.1.

The frequency range 9 kHz-1000 MHz was scanned, and the list of the highest emissions was verified and updated accordingly.

The levels of the emissions within the frequency ranges of the restricted bands (Section 15.205 of FCC Part 15) were compared to the limits of the table in Section 15.209 (a), General Requirements.

The emissions were measured using a computerized EMI receiver complying to CISPR 16 requirements. The specification limits and applicable correction factors are loaded to the receiver via a 3.5" floppy disk.

In the frequency range 9 kHz-30 MHz, the loop antenna was rotated on its vertical axis, The antenna height (center of loop) was 1 meter.

In the frequency range 30-1000 MHz, the readings were maximized by adjusting the antenna height between 1-4 meters, the turntable azimuth between 0-360°, and the antenna polarization.

Verification of the E.U.T emissions was based on the following methods:

Turning the E.U.T on and off.

Using a frequency span less than 10 MHz.

Observation of the signal level during turntable rotation. Background noise is not affected by the rotation of the E.U.T.

The E.U.T. was tested at the operating frequencies of, 5180, 5200, 5240, 5745, 5765, and 5805 MHz using the following modulations: 64QAM, and BPSK.

5.3 **Test Data**

JUDGEMENT: Passed

The signals in the band 9 kHz – 1.0 GHz were below the spectrum analyzer noise level, at least 20 dB below the specification limit.

The results for all operating frequencies and modulations were the same.

The EUT met the requirements of the F.C.C. Part 15, Subpart C, specification.

The results for all operating frequencies and modulations were the same.

TEST PERSONNEL:

Tester Signature:  Date: 22.02.09

Typed/Printed Name: A. Sharabi

5.4 Test Instrumentation Used, Radiated Measurements

Instrument	Manufacturer	Model	Serial Number	Calibration	Period
EMI Receiver	HP	85422E	3906A00276	November 17, 2008	1 year
RF Section	HP	85420E	3705A00248	November 16, 2008	1 year
Antenna Bioconical	ARA	BCD 235/B	1041	March 23, 2008	1 year
Antenna Log Periodic	ARA	LPD-2010/A	1038	November 06, 2008	1 year
Active Loop Antenna	EMCO	6502	9506-2950	October 15, 2008	1 year
Antenna Mast	ARA	AAM-4A	1001	N/A	N/A
Turntable	ARA	ART-1001/4	1001	N/A	N/A
Mast & Table Controller	ARA	ACU-2/5	1001	N/A	N/A
Printer	HP	LaserJet 2200	JPKGC19982	N/A	N/A

5.5 **Field Strength Calculation**

The field strength is calculated directly by the EMI Receiver software, and a "Correction Factors" data disk, using the following equation:

$$[\text{dB}\mu\text{v}/\text{m}] \text{ FS} = \text{RA} + \text{AF} + \text{CF}$$

FS: Field Strength [dB μ v/m]

RA: Receiver Amplitude [dB μ v]

AF: Receiving Antenna Correction Factor [dB/m]

CF: Cable Attenuation Factor [dB]

No external pre-amplifiers are used.

6. Spurious Radiated Emission in the Restricted Band, Above 1 GHz

802.11b/g+802.11a + WMTS + AWS Signals

6.1 Radiated Emission Above 1 GHz

The E.U.T operation mode and test set-up are as described in Section 3.

See Section 3.1 Justification of the System Test Configuration concerning the E.U.T. orientation for this test.

A preliminary measurement to characterize the E.U.T was performed inside the shielded room, using peak detection mode and broadband antennas. The preliminary measurements produced a list of the highest emissions. The E.U.T was then transferred to the open site, and placed on a remote-controlled turntable. The E.U.T was placed on a non-metallic table, 0.8 meters above the ground. The configuration tested is shown in Figure 3.1.

The levels of the emissions within the frequency ranges of the restricted bands (Section 15.205 of FCC Part 15) were compared to the limits of the table in Section 15.209 (a), General Requirements.

In the frequency range 1-2.9 GHz, a computerized EMI receiver complying to CISPR 16 requirements was used.

In the frequency range 2.9-40.0 GHz, a spectrum analyzer including a low noise amplifier was used. During average measurements, the IF bandwidth was 1 MHz and the video bandwidth was 100Hz. During peak measurements, the IF bandwidth was 1 MHz and the video bandwidth was 3 MHz.

The test distance was 3 meters.

The readings were maximized by adjusting the antenna height between 1-4 meters, the turntable azimuth between 0-360°, and the antenna polarization.

Verification of the E.U.T emissions was based on the following methods: turning the E.U.T on and off; using a frequency span less than 10 MHz; observation of the signal level during turntable rotation. (Background noise is not affected by the rotation of the E.U.T.)

The E.U.T. was tested at the operating frequencies of, 5180, 5200, 5240, 5745, 5765, and 5805 MHz using the following modulations: 64QAM, and BPSK.

6.2 **Test Data**

JUDGEMENT: Passed by 6.1 dB

For the operating frequencies of 5180, 5200, and 5240, the signals in the frequency range of 1.0 – 40.0 GHz were more than 20 dB below the specification limit.

For the operation frequency of 5745 MHz, the margin between the emission level and the specification limit is 7.6 dB in the worst case at the frequency of 11490.00 MHz, vertical polarization.


For the operation frequency of 5765 MHz, the margin between the emission level and the specification limit is 8.6 dB in the worst case at the frequency of 11530.00 MHz, vertical polarization.

For the operation frequency of 5805 MHz, the margin between the emission level and the specification limit is 6.1 dB in the worst case at the frequency of 11610.00 MHz, vertical polarization.

The results for all modulations were the same.

The EUT met the requirements of the F.C.C. Part 15, Subpart C, specification.

TEST PERSONNEL:

Tester Signature:  Date: 22.02.09

Typed/Printed Name: A. Sharabi

Radiated Emission Above 1 GHz

E.U.T Description WLAN Module With WCE (WiFi Coverage Extender) for DAS With Four Cisco 1242 Access Points
 Type 860M-AU With WCE-AU
 Serial Number: 860M-AU: 0837453; WCE-AU: 0847A54

Specification: FCC, Part 15, Subpart C

Antenna Polarization: Horizontal/Vertical Frequency range: 1.0 GHz to 40.0 GHz
 Test Distance: 3 meters Detector: Peak
 Operation Frequency: 5745 MHz

Freq. (MHz)	Polarity (H/V)	Peak Reading (dB μ V/m)	Peak. Specification (dB μ V/m)	Peak. Margin (dB)
11490.00	H	54.6	74.0	-19.4
11490.00	V	56.8	74.0	-17.2

**Figure 6. Radiated Emission. Antenna Polarization: HORIZONTAL / VERTICAL.
Detector: Peak**

Margin refers to the test results obtained minus specified requirement; thus a positive number indicates failure, and a negative result indicates that the product passes the test.

“Peak Reading” includes correction factor.

“Correction Factor” = Antenna Factor + Cable Loss- Low Noise Amplifier Gain

Radiated Emission Above 1 GHz

E.U.T Description WLAN Module With WCE (WiFi Coverage Extender) for DAS With Four Cisco 1242 Access Points

Type 860M-AU With WCE-AU

Serial Number: 860M-AU: 0837453; WCE-AU: 0847A54

Specification: FCC, Part 15, Subpart C

Antenna Polarization: Horizontal/Vertical Frequency range: 1.0 GHz to 40.0 GHz

Test Distance: 3 meters Detector: Average

Operation Frequency: 5745 MHz

Freq. (MHz)	Polarity (H/V)	Average Reading (dB μ V/m)	Average Specification (dB μ V/m)	Peak. Margin (dB)
11490.00	H	45.3	54.0	-8.7
11490.00	V	46.4	54.0	-7.6

**Figure 7. Radiated Emission. Antenna Polarization: HORIZONTAL / VERTICAL.
Detector: Average**

Notes:

Margin refers to the test results obtained minus specified requirement; thus a positive number indicates failure, and a negative result indicates that the product passes the test.

“Average Reading” includes correction factor.

“Correction Factor” = Antenna Factor + Cable Loss- Low Noise Amplifier Gain

Radiated Emission Above 1 GHz

E.U.T Description WLAN Module With WCE (WiFi Coverage Extender) for DAS With Four Cisco 1242 Access Points
 Type 860M-AU With WCE-AU
 Serial Number: 860M-AU: 0837453; WCE-AU: 0847A54

Specification: FCC, Part 15, Subpart C

Antenna Polarization: Horizontal/Vertical Frequency range: 1.0 GHz to 40.0 GHz
 Test Distance: 3 meters Detector: Peak
 Operation Frequency: 5765 MHz

Freq. (MHz)	Polarity (H/V)	Peak Reading (dB μ V/m)	Peak. Specification (dB μ V/m)	Peak. Margin (dB)
11530.00	H	54.6	74.0	-19.4
11530.00	V	57.6	74.0	-16.4

**Figure 8. Radiated Emission. Antenna Polarization: HORIZONTAL / VERTICAL.
Detector: Peak**

Margin refers to the test results obtained minus specified requirement; thus a positive number indicates failure, and a negative result indicates that the product passes the test.

“Peak Reading” includes correction factor.

“Correction Factor” = Antenna Factor + Cable Loss- Low Noise Amplifier Gain

Radiated Emission Above 1 GHz

E.U.T Description WLAN Module With WCE (WiFi Coverage Extender) for DAS With Four Cisco 1242 Access Points

Type 860M-AU With WCE-AU

Serial Number: 860M-AU: 0837453; WCE-AU: 0847A54

Specification: FCC, Part 15, Subpart C

Antenna Polarization: Horizontal/Vertical Frequency range: 1.0 GHz to 40.0 GHz

Test Distance: 3 meters

Detector: Average

Operation Frequency: 5765 MHz

Freq.	Polarity	Average Reading	Average Specification	Peak Margin
(MHz)	(H/V)	(dB μ V/m)	(dB μ V/m)	(dB)
11530.00	H	43.9	54.0	-10.1
11530.00	V	45.4	54.0	-8.6

**Figure 9. Radiated Emission. Antenna Polarization: HORIZONTAL / VERTICAL.
Detector: Average**

Notes:

Margin refers to the test results obtained minus specified requirement; thus a positive number indicates failure, and a negative result indicates that the product passes the test.

“Average Reading” includes correction factor.

“Correction Factor” = Antenna Factor + Cable Loss- Low Noise Amplifier Gain

Radiated Emission Above 1 GHz

E.U.T Description WLAN Module With WCE (WiFi Coverage Extender)
 for DAS With Four Cisco 1242 Access Points

Type 860M-AU With WCE-AU

Serial Number: 860M-AU: 0837453; WCE-AU: 0847A54

Specification: FCC, Part 15, Subpart C

Antenna Polarization: Horizontal/Vertical Frequency range: 1.0 GHz to 40.0 GHz
 Detector: Peak
 Test Distance: 3 meters
 Operation Frequency: 5805 MHz

Freq.	Polarity	Peak Reading	Peak. Specification	Peak. Margin
(MHz)	(H/V)	(dB μ V/m)	(dB μ V/m)	(dB)
11610.00	H	57.5	74.0	-16.5
11610.00	V	58.5	74.0	-15.5

**Figure 10. Radiated Emission. Antenna Polarization: HORIZONTAL / VERTICAL.
 Detector: Peak**

Margin refers to the test results obtained minus specified requirement; thus a positive number indicates failure, and a negative result indicates that the product passes the test.

“Peak Reading” includes correction factor.

“Correction Factor” = Antenna Factor + Cable Loss- Low Noise Amplifier Gain

Radiated Emission Above 1 GHz

E.U.T Description WLAN Module With WCE (WiFi Coverage Extender) for DAS With Four Cisco 1242 Access Points
 Type 860M-AU With WCE-AU
 Serial Number: 860M-AU: 0837453; WCE-AU: 0847A54

Specification: FCC, Part 15, Subpart C

Antenna Polarization: Horizontal/Vertical Frequency range: 1.0 GHz to 40.0 GHz

Test Distance: 3 meters

Detector: Average

Operation Frequency: 5805 MHz

Freq. (MHz)	Polarity (H/V)	Average Reading (dB μ V/m)	Average Specification (dB μ V/m)	Peak. Margin (dB)
11610.00	H	45.3	54.0	-8.7
11610.00	V	47.9	54.0	-6.1

**Figure 11. Radiated Emission. Antenna Polarization: HORIZONTAL / VERTICAL.
Detector: Average**

Notes:

Margin refers to the test results obtained minus specified requirement; thus a positive number indicates failure, and a negative result indicates that the product passes the test.

“Average Reading” includes correction factor.

“Correction Factor” = Antenna Factor + Cable Loss- Low Noise Amplifier Gain

6.3 Test Instrumentation Used, Radiated Measurements Above 1 GHz

Instrument	Manufacturer	Model	Serial Number	Calibration	Period
Receiver	HP	85422E	3411A00102	November 17, 2008	1 year
RF Section	HP	85420E	3427A00103	November 16, 2008	1 year
Antenna Mast	ARA	AAM-4A	1001	N/A	N/A
Turntable	ARA	ART-1001/4	1001	N/A	N/A
Mast & Table Controller	ARA	ACU-2/5	1001	N/A	N/A
Printer	HP	LaserJet 2200	JPKGC19982	N/A	N/A
Antenna-Log Periodic	A.H.System	SAS-200/511	253	January 29, 2009	2 years
Double Ridged Waveguide Horn Antenna	EMCO	3115	29845	March 15, 2006	2 years
Horn Antenna	ARA	SWH-28	1008	December 23, 2008	2 year
Low Noise Amplifier	DBS MICROWAVE	LNA-DBS-0411N313	013	November 3, 2008	1 year
Low Noise Amplifier	Sophia Wireless	LNA 28-B	232	January 8, 2009	1 year
Low Noise Amplifier	MK Milliwave	MKT6-3000 400-30-13P	399	January 8, 2009	1 year
Spectrum Analyzer	HP	8592L	3826A01204	March 5, 2008	1 year
Spectrum Analyzer	HP	8546E	3442A00275	December 15, 2008	1 year
Printer	HP	LaserJet 2200	JPKGC19982	N/A	N/A

7. 26 dB Bandwidth 802.11b/g+802.11a +WMTS + AWS Signals

7.1 Test procedure

The E.U.T. was set to the applicable test frequency. The E.U.T. antenna terminal was connected to the spectrum analyzer through an external attenuator (20 dB) and appropriate coaxial cable. The spectrum analyzer was set to 300 kHz resolution BW. The spectrum bandwidth of the E.U.T. was measured and recorded.

The E.U.T. was tested at 5180, 5200, 5240, 5745, 5765, and 5805 MHz with the following modulations: 64QAM (54Mbit/sec) and BPSK (6Mbit/sec).




Figure 12 —5180 MHz 64QAM




Figure 13 —5200 MHZ 64QAM




Figure 14 —5240 MHZ 64QAM




Figure 15 — 5745 MHz 64QAM




Figure 16 — 5765 MHz 64QAM




Figure 17 —5805 MHZ 64QAM




Figure 18 —5180 MHz BPSK




Figure 19 —5200 MHZ BPSK




Figure 20 —5240 MHZ BPSK




Figure 21 —5745 MHz BPSK




Figure 22 —5765 MHz BPSK




Figure 23 —5805 MHZ BPSK

Operation Frequency (MHz)	Modulation	26 dB Bandwidth (dBm)
5180	64QAM	18.8
	BPSK	19.8
5200	64QAM	18.7
	BPSK	19.5
5240	64QAM	18.6
	BPSK	19.8
5745	64QAM	18.8
	BPSK	19.5
5765	64QAM	18.7
	BPSK	19.5
5805	64QAM	18.6
	BPSK	19.1

TEST PERSONNEL:

Tester Signature: 

Date: 22.02.09

Typed/Printed Name: A. Sharabi

7.2 Test Equipment Used.

26 dB Minimum Bandwidth

Instrument	Manufacturer	Model	Serial/Part Number	Calibration	
				Last Calibr.	Period
Spectrum Analyzer	HP	8592L	3826A01204	March 5, 2008	1 year
Attenuator	Jyebao	-	FAT-AM5AF5G6G2W20	February 1, 2009	1 year
Cable	Rhophase	KPS-5000-KPS	A1674	February 1, 2009	1 year
Cable	Rhophase	KPS-1501-1000	A1675	February 1, 2009	1 year

Figure 24 Test Equipment Used

8. Maximum Conducted Output Power 802.11b/g+802.11a + WMTS + AWS Signals

8.1 *Test procedure*

The E.U.T. antenna terminal was connected to the Spectrum Analyzer through an external attenuator (20 dB) and an appropriate coaxial cable (Cable Loss = 1.3dB). The Spectrum Analyzer was set to 1.0 MHz resolution BW. Sample detector and maximum hold were used.

The E.U.T. was tested at 5180, 5200, 5240, 5745, 5765, and 5805 MHz with the following modulations: 64QAM (54Mbit/sec) and BPSK (6Mbit/sec).




Figure 25 5180 MHz 64QAM




Figure 26 5200 MHz 64QAM




Figure 27 5240 MHz 64QAM




Figure 28 5745 MHz 64QAM




Figure 29 5765 MHz 64QAM




Figure 30 5805 MHz 64QAM




Figure 31 5180 MHz BPSK




Figure 32 5200 MHz BPSK




Figure 33 5240 MHz BPSK




Figure 34 5745 MHz BPSK




Figure 35 5765 MHz BPSK




Figure 36 5805 MHz BPSK

8.2 Results table

E.U.T. Description: WLAN Module With WCE (WiFi Coverage Extender) for DAS With Four Cisco 1242 Access Points

Model No.: 860M-AU With WCE-AU

Serial Number: 860M-AU: 0837453; WCE-AU: 0847A54

Specification: F.C.C. Part 15, Subpart E

Operation Frequency (MHz)	Modulation	Power (dBm)	Specification (dBm)	Margin (dB)
5180	64QAM	11.87158	15.74158	-3.87
	BPSK	11.90665	15.96665	-4.06
5200	64QAM	11.79842	15.71842	-3.92
	BPSK	12.07035	15.90035	-3.83
5240	64QAM	13.09513	15.69513	-2.6
	BPSK	12.05665	15.96665	-3.91
5745	64QAM	10.60158	28.74158	-18.14
	BPSK	11.10035	28.90035	-17.8
5765	64QAM	9.098416	28.71842	-19.62
	BPSK	9.820346	28.90035	-19.08
5805	64QAM	10.43513	28.69513	-18.26
	BPSK	10.39033	28.81033	-18.42

Figure 37 Maximum Peak Power Output

Note: Antenna Gain is 7 dBi

Peak Output Power = Reading + 10log EBW

For 5.18; 5.20, 5.24 GHz Peak Output Power Limit = 4 + 10log EBW - (Antenna Gain -6)

For 5.745; 5.765, 5.805 GHz Peak Output Power Limit = 17 + 10log EBW - (Antenna Gain -6)

JUDGEMENT: Passed by 2.6 dB

TEST PERSONNEL:

Tester Signature:  Date: 22.02.09
 Typed/Printed Name: A. Sharabi

8.3 Test Equipment Used.

Peak Power Output

Instrument	Manufacturer	Model	Serial/Part Number	Calibration	
				Last Calibr.	Period
Spectrum Analyzer	HP	8592L	3826A01204	March 5, 2008	1 year
Attenuator	Jyebao	-	FAT-AM5AF5G6G2W20	February 1, 2009	1 year
Cable	Rhophase	KPS-5000-KPS	A1674	February 1, 2009	1 year

Figure 38 Test Equipment Used

9. Peak Power Spectral Density 802.11b/g+802.11a + WMTS + AWS Signals

[In accordance with section 15.407(a)]

9.1 Test procedure

The E.U.T. antenna terminal was connected to the spectrum analyzer through an external attenuator (20dB) and an appropriate coaxial cable (Cable Loss = 1 dB). The spectrum analyzer was set to 1 MHz resolution BW. and 1 MHz video BW. The spectrum peaks were located at 5180, 5200, 5240, 5745, 5765, and 5805 MHz with the following modulations: 64QAM (54Mbit/sec) and BPSK (6Mbit/sec).




Figure 39 —5180 MHz 64QAM




Figure 40 — 5200 MHz 64QAM




Figure 41 — 5240 MHz 64QAM




Figure 42 —5745 MHz 64QAM




Figure 43 —5765 MHz 64QAM




Figure 44 — 5805 MHz 64QAM




Figure 45 — 5180 MHz BPSK




Figure 46 —5200 MHz BPSK




Figure 47 —5240 MHz BPSK




Figure 48 —5745 MHz BPSK




Figure 49 —5765 MHz BPSK




Figure 50 —5805 MHz BPSK

9.2 Results table

E.U.T. Description: WLAN Module With WCE (WiFi Coverage Extender) for DAS With Four Cisco 1242 Access Points

Model No.: 860M-AU With WCE-AU

Serial Number: 860M-AU: 0837453; WCE-AU: 0847A54

Specification: F.C.C. Part 15, Subpart E (15.407(a))

Operation Frequency (MHz)	Modulation	Reading Spectrum Analyzer (dBm)	Specification (dBm)	Margin (dB)
5180	64QAM	-0.87	3	-3.87
	BPSK	-1.06	3	-4.06
5200	64QAM	-0.92	3	-3.92
	BPSK	-0.83	3	-3.83
5240	64QAM	0.4	3	-2.6
	BPSK	-0.91	3	-3.91
5745	64QAM	-2.14	16	-18.214
	BPSK	-1.8	16	-17.8
5765	64QAM	-3.62	16	-19.62
	BPSK	-3.08	16	-19.08
5805	64QAM	-2.26	16	-18.26
	BPSK	-2.42	16	-18.42

Figure 51 Test Results

JUDGEMENT: Passed by 2.6 dB

TEST PERSONNEL:

Tester Signature:  Date: 22.02.09
 Typed/Printed Name: A. Sharabi

9.3 Test Equipment Used.

Peak Power Spectral Density

Instrument	Manufacturer	Model	Serial/Part Number	Calibration	
				Last Calibr.	Period
Spectrum Analyzer	HP	8592L	3826A01204	March 5, 2008	1 year
Attenuator	Jyebao	-	FAT-AM5AF5G6G2W20	February 1, 2009	1 year
Cable	Rhophase	KPS-5000-KPS	A1674	February 9, 2009	1 year

Figure 52 Test Equipment Used

10. Ratio of Peak Excursion of Modulation Envelope to Maximum Conducted Output Power 802.11b/g+802.11a + WMTS + AWS Signals

[In accordance with section 15.407(a)(6)]

10.1 Test procedure

The E.U.T. antenna terminal was connected to the spectrum analyzer through an external attenuator (20dB) and an appropriate coaxial cable (Cable Loss = 1.3 dB). The spectrum analyzer was set to 1 MHz resolution BW. and 1 MHz video BW.

Trace A: Sample Detector

Trace B: Peak Detector

The E.U.T. was tested at 5180, 5200, 5240, 5745, 5765, and 5805 MHz with the following modulations: 64QAM (54Mbit/sec) and BPSK (6Mbit/sec).




Figure 53 — 5180 MHz 64QAM




Figure 54 —5200 MHz 64QAM




Figure 55 —5240 MHz 64QAM




Figure 56 —5745 MHz 64QAM




Figure 57 —5765 MHz 64QAM




Figure 58 —5805 MHz 64QAM




Figure 59 —5180 MHz BPSK




Figure 60 —5200 MHz BPSK




Figure 61 —5240 MHz BPSK




Figure 62 —5745 MHz BPSK




Figure 63 —5765 MHz BPSK




Figure 64 —5805 MHz BPSK

10.2 Results table

E.U.T Description: WLAN Module With WCE (WiFi Coverage Extender) for DAS With Four Cisco 1242 Access Points

Model No.: 860M-AU With WCE-AU

Serial Number: 860M-AU: 0837453; WCE-AU: 0847A54


Specification: F.C.C. Part 15, Subpart E (15.407(a)(6))

Operation Frequency (MHz)	Modulation	Delta (dB)	Specification (dB)	Margin (dB)
5180	64QAM	3.77	13	-9.23
	BPSK	3.69	13	-9.31
5200	64QAM	3.21	13	-9.79
	BPSK	3.68	13	-9.32
5240	64QAM	3.71	13	-9.29
	BPSK	2.98	13	-10.02
5745	64QAM	3.52	13	-9.48
	BPSK	3.18	13	-9.82
5765	64QAM	2.63	13	-10.37
	BPSK	2.70	13	-10.3
5805	64QAM	2.99	13	-10.01
	BPSK	2.91	13	-10.09

Figure 65 Test Results

JUDGEMENT: Passed by 9.23 dB

TEST PERSONNEL:

Tester Signature:  Date: 22.02.09
 Typed/Printed Name: A. Sharabi

10.3 Test Equipment Used.

Peak Power Spectral Density

Instrument	Manufacturer	Model	Serial/Part Number	Calibration	
				Last Calibr.	Period
Spectrum Analyzer	HP	8592L	3826A01204	March 5, 2008	1 year
Attenuator	Jyebao	-	FAT-AM5AF5G6G2W20	February 1, 2009	1 year
Cable	Rhophase	KPS-5000-KPS	A1674	February 9, 2009	1 year

Figure 66 Test Equipment Used

11. Peak Power Output Out of 5150-5250; 5725-5825 MHz Bands 802.11b/g+802.11a + WMTS + AWS Signals

11.1 *Test procedure*

The E.U.T. antenna terminal was connected to the spectrum analyzer through an appropriate coaxial cable. The spectrum analyzer was set to 1 MHz resolution BW except for the frequency range 9 kHz-150 kHz where the RBW was set to 1kHz and the frequency range 150 kHz-10.0 MHz where the RBW was set to 10kHz. The frequency range from 9 kHz to 40 GHz was scanned. Level of spectrum components out of the 5150-5250; 5725-5825 MHz bands was measured at the selected operation frequencies.

The E.U.T. was tested at 5180, 5200, 5240, 5745, 5765, and 5805 MHz with the following modulations: 64QAM (54Mbit/sec) and BPSK (6Mbit/sec).




Figure 67 —5180 MHz 64QAM




Figure 68 —5180 MHz 64QAM




Figure 69 —5180 MHz 64QAM




Figure 70 —5180 MHz 64QAM




Figure 71 —5180 MHz 64QAM




Figure 72 —5180 MHz 64QAM




Figure 73 —5180 MHz 64QAM




Figure 74 —5180 MHz 64QAM




Figure 75 —5200 MHz 64QAM




Figure 76 —5200 MHz 64QAM




Figure 77 —5200 MHz 64QAM




Figure 78 —5200 MHz 64QAM




Figure 79 —5200 MHz 64QAM




Figure 80 —5200 MHz 64QAM




Figure 81 —5200 MHz 64QAM




Figure 82 —5200 MHz 64QAM




Figure 83 —5240 MHz 64QAM




Figure 84 —5240 MHz 64QAM




Figure 85 —5240 MHz 64QAM




Figure 86 —5240 MHz 64QAM




Figure 87 —5240 MHz 64QAM




Figure 88 —5240 MHz 64QAM




Figure 89 —5240 MHz 64QAM




Figure 90 —5240 MHz 64QAM




Figure 91 —5745 MHz 64QAM




Figure 92 —5745 MHz 64QAM




Figure 93 —5745 MHz 64QAM




Figure 94 —5745 MHz 64QAM




Figure 95 —5745 MHz 64QAM




Figure 96 —5745 MHz 64QAM




Figure 97 —5745 MHz 64QAM




Figure 98 —5745 MHz 64QAM




Figure 99 —5765 MHz 64QAM




Figure 100 — 5765 MHz 64QAM




Figure 101 — 5765 MHz 64QAM




Figure 102 —5765 MHz 64QAM




Figure 103 —5765 MHz 64QAM




Figure 104 — 5765 MHz 64QAM




Figure 105 — 5765 MHz 64QAM




Figure 106 — 5765 MHz 64QAM




Figure 107 —5805 MHz 64QAM




Figure 108 —5805 MHz 64QAM




Figure 109 —5805 MHz 64QAM




Figure 110 —5805 MHz 64QAM




Figure 111 — 5805 MHz 64QAM




Figure 112 — 5805 MHz 64QAM




Figure 113 — 5805 MHz 64QAM




Figure 114 — 5805 MHz 64QAM




Figure 115 — 5180 MHz BPSK




Figure 116 — 5180 MHz BPSK




Figure 117 — 5180 MHz BPSK




Figure 118 —5180 MHz BPSK




Figure 119 —5180 MHz BPSK




Figure 120 — 5180 MHz BPSK




Figure 121 — 5180 MHz BPSK




Figure 122 —5180 MHz BPSK




Figure 123 —5200 MHz BPSK




Figure 124 —5200 MHz BPSK




Figure 125 —5200 MHz BPSK




Figure 126 — 5200 MHz BPSK




Figure 127 — 5200 MHz BPSK




Figure 128 —5200 MHz BPSK




Figure 129 —5200 MHz BPSK




Figure 130 —5200 MHz BPSK




Figure 131 —5240 MHz BPSK




Figure 132 —5240 MHz BPSK




Figure 133 —5240 MHz BPSK




Figure 134 —5240 MHz BPSK




Figure 135 —5240 MHz BPSK




Figure 136 — 5240 MHz BPSK




Figure 137 — 5240 MHz BPSK




Figure 138 — 5240 MHz BPSK




Figure 139 —5745 MHz BPSK




Figure 140 —5745 MHz BPSK




Figure 141 —5745 MHz BPSK




Figure 142 —5745 MHz BPSK




Figure 143 —5745 MHz BPSK




Figure 144 —5745 MHz BPSK




Figure 145 —5745 MHz BPSK




Figure 146 —5745 MHz BPSK




Figure 147 — 5765 MHz BPSK




Figure 148 — 5765 MHz BPSK




Figure 149 —5765 MHz BPSK




Figure 150 —5765 MHz BPSK




Figure 151 —5765 MHz BPSK




Figure 152 —5765 MHz BPSK




Figure 153 — 5765 MHz BPSK




Figure 154 — 5765 MHz BPSK




Figure 155 —5805 MHz BPSK




Figure 156 —5805 MHz BPSK




Figure 157 —5805 MHz BPSK




Figure 158 —5805 MHz BPSK




Figure 159 —5805 MHz BPSK




Figure 160 —5805 MHz BPSK




Figure 161 —5805 MHz BPSK




Figure 162 —5805 MHz BPSK

11.2 Results table

E.U.T Description: WLAN Module With WCE (WiFi Coverage Extender) for DAS With Four Cisco 1242 Access Points

Model No.: 860M-AU With WCE-AU

Serial Number: 860M-AU: 0837453; WCE-AU: 0847A54


Specification: F.C.C. Part 15, Subpart E

Operation Frequency (MHz)	Modulation	Reading (dBm)	Specification (dBm)	Margin (dB)
5180	64QAM	-29.23	-27.0	-2.23
	BPSK	-27.70	-27.0	-0.70
5200	64QAM	-28.95	-27.0	-1.95
	BPSK	-28.16	-27.0	-1.16
5240	64QAM	-28.93	-27.0	-1.93
	BPSK	-28.78	-27.0	-1.78
5745	64QAM	-28.11	-27.0	-1.11
	BPSK	-28.29	-27.0	-1.29
5765	64QAM	-28.66	-27.0	-1.66
	BPSK	-29.84	-27.0	-2.84
5805	64QAM	-28.56	-27.0	-1.56
	BPSK	-28.47	-27.0	-1.47

Figure 163 Peak Power Output of 5150-5250; 5725-5825 MHz Bands

JUDGEMENT: Passed by 0.7 dB

TEST PERSONNEL:

Tester Signature: 

Date: 22.02.09

Typed/Printed Name: A. Sharabi

11.3 Test Equipment Used.

Peak Power Output of 5150-5825 MHz Band

Instrument	Manufacturer	Model	Serial/Part Number	Calibration	
				Last Calibr.	Period
Spectrum Analyzer	HP	8592L	3826A01204	March 5, 2008	1 year
Spectrum Analyzer	HP	8564E	3442A00275	December 15, 2008	1 year
Attenuator	Jyebao	-	FAT-AM5AF5G6G2W20	February 1, 2009	1 year
Cable	Rhophase	KPS-5000-KPS	A1674	February 9, 2009	1 year

Figure 164 Test Equipment Used

12. Band Edge Spectrum 802.11b/g+802.11a + WMTS + AWS Signals

[In Accordance with section 15.407)

12.1 Test procedure

The E.U.T. antenna terminal was connected to the spectrum analyzer through an external attenuator (20 dB) and an appropriate coaxial cable (cable loss = 1.3B). The spectrum analyzer was set to 1 MHz resolution BW. Maximum power level below 5150 MHz and above 5350 MHz was measured at 5180 MHz and 5240MHz correspondingly. Maximum power level below 5725 MHz and above 5825 MHz was measured at 5745 MHz and 5805 MHz correspondingly.

The E.U.T. was tested at 5180, 5240, 5745, and 5805 MHz with the following modulations: 64QAM (54Mbit/sec) and BPSK (6Mbit/sec).




Figure 165 —5180 MHz 64QAM




Figure 166 —5240 MHz 64QAM




Figure 167 —5745 MHz 64QAM




Figure 168 —5805 MHz 64QAM




Figure 169 —5180 MHz BPSK




Figure 170 —5240 MHz BPSK




Figure 171 —5745 MHz BPSK




Figure 172 —5805 MHz BPSK




Figure 173 —Band Edge at 5.25 GHz Operation at 5.24 GHz 64QAM (Section 15.215(c))




Figure 174 —Band Edge at 5.25 GHz Operation at 5.24 GHz BPSK (Section 15.215(c))

12.2 Results table

E.U.T. Description: WLAN Module With WCE (WiFi Coverage Extender) for DAS With Four Cisco 1242 Access Points
 Model No.: 860M-AU With WCE-AU
 Serial Number: 860M-AU: 0837453; WCE-AU: 0847A54
 Specification: F.C.C. Part 15, Subpart C (15.215(c))

Operation Frequency (MHz)	Modulation	Band Edge Frequency (MHz)	Result (dBc)	Specification (dBc)	Margin (dB)
5240	64QAM	5250.00	32.5	20.0	-12.5
	BPSK	5250.00	32.33	20.0	-12.33

Figure 175 Band Edge at 5.25 GHz operation at 5.24 GHz

JUDGEMENT: Passed by 12.33 dB

TEST PERSONNEL:

Tester Signature: A. Sharabi Date: 22.02.09

Typed/Printed Name: A. Sharabi

12.3 Results table

E.U.T. Description: WLAN Module With WCE (WiFi Coverage Extender) for DAS
With Four Cisco 1242 Access Points

Model No.: 860M-AU With WCE-AU

Serial Number: 1. 860M: 73903D 2. WCE: 739038

Specification: F.C.C. Part 15, Subpart C (15.407)

Operation Frequency (MHz)	Modulation	Band Edge Frequency (MHz)	Result (dBm)	Specification (dBm)	Margin (dB)
5180	64QAM	5150.00	-43.33	-27.0	-16.33
	BPSK	5148.20	-41.74	-27.0	-14.74
5240	64QAM	5350.00	-43.88	-27.0	-16.88
	BPSK	5350.00	-43.60	-27.0	-16.60
5745	64QAM	5725.00	-38.10	-17.0	-21.1
	BPSK	5725.00	-37.04	-17.0	-20.04
5805	64QAM	5825.60	-41.25	-17.0	-24.25
	BPSK	5825.00	-42.39	-17.0	-25.39

Figure 176 Band Edge Spectrum

JUDGEMENT: Passed by 14.74 dB

TEST PERSONNEL:

Tester Signature: A. Sharabi Date: 22.02.09

Typed/Printed Name: A. Sharabi

12.4 Test Equipment Used.

Band edge Spectrum

Instrument	Manufacturer	Model	Serial/Part Number	Calibration	
				Last Calibr.	Period
Spectrum Analyzer	HP	8592L	3826A01204	March 5, 2008	1 year
Spectrum Analyzer	HP	8564E	3442A00275	December 15, 2008	1 year
Attenuator	Jyebao	-	FAT-AM5AF5G6G2W20	February 1, 2009	1 year
Cable	Rhophase	KPS-5000-KPS	A1674	February 9, 2009	1 year

Figure 177 Test Equipment Used

13. Antenna Gain 802.11b/g+802.11a + WMTS + AWS Signals

The antenna gain is 7 dBi.

14. R.F Exposure/Safety 802.11b/g+802.11a + WMTS + AWS Signals

Typical use of the E.U.T. is repeating WiFi signals for DAS. The typical placement of the E.U.T. is on a wall near the ceiling. The typical distance between the E.U.T. and the user in the worst case application, is >1 m.

Calculation of Maximum Permissible Exposure (MPE)

Based on Section 1.1307(b)(1) Requirements

(a) FCC limits at 5745 MHz is: $1 \frac{mW}{cm^2}$

Using table 1 of Section 1.1310 limit for general population/uncontrolled exposures, the above level is an average over 30 minutes.

(b) The power density produced by the E.U.T. is

$$S = \frac{P_t G_t}{4\pi R^2}$$

P_t- Transmitted Power (Peak) 20.41 mW= 13.1 dBm

G_T- Antenna Gain, 7 dBi = 5

R- Distance from Transmitter using 1 m worst case

(c) The peak power density is :

$$S_p = \frac{20.41 \times 5}{4\pi(100)^2} = 8.1 \times 10^{-4} \frac{mW}{cm^2}$$

(d) This is 4 orders of magnitude below the FCC limit.

15. Intermodulation Tests

15.1 Test procedure

An access point having maximum RF output power was used for this test.

The E.U.T. antenna terminal was connected to the spectrum analyzer through an external attenuator (20 dB) and an appropriate coaxial cable (cable loss = 1 dB). The spectrum analyzer was set to 1 kHz resolution BW for the frequency range 9.0-150.0 kHz, 10kHz for the frequency range 10kHz–10.0MHz, 100kHz for the frequency range 10.0MHz-2.4385GHz, and 1MHz for the frequency range 2.4385-25.0GHz.

4 input signals were sent simultaneously to the E.U.T. as follows:

802.11b/g: in the frequency range 2400-2483 MHz, 2412MHz 64QAM

802.11a: in the frequency range 5150-5250 MHz, 5180MHz BPSK

WMTS: in the frequency range 608-614 MHz, 608 MHz CW

AWS: in the frequency range 2110-2155 MHz, 2155MHz CW

The frequency range of 9 kHz – 40.0GHz was scanned for unwanted signals.




Figure 178 —2412MHz 64QAM




Figure 179 —5180MHz BPSK




Figure 180 — 608MHz CW




Figure 181 — 2155MHz CW




Figure 182




Figure 183




Figure 184 (Second harmonic of the 608MHz Signal generator)




Figure 185




Figure 186




Figure 187




Figure 188

JUDGEMENT: Passed

TEST PERSONNEL:

Tester Signature:  Date: 22.02.09

Typed/Printed Name: A. Sharabi

15.2 Test Equipment Used.

Intermodulation

Instrument	Manufacturer	Model	Serial/Part Number	Calibration	
				Last Calibr.	Period
Spectrum Analyzer	HP	8592L	3826A01204	March 5, 2008	1 year
Spectrum Analyzer	HP	8564E	3442A00275	December 15, 2008	1 year
Attenuator	Jyebao	-	FAT-AM5AF5G6G2W20	February 1, 2009	1 year
Cable	Rhophase	KPS-1501-1000	A1675	February 1, 2009	1 year

Figure 189 Test Equipment Used

16. APPENDIX A - CORRECTION FACTORS

16.1 Correction factors for

CABLE

**from EMI receiver
to test antenna
at 3 meter range.**

FREQUENCY (MHz)	CORRECTION FACTOR (dB)	FREQUENCY (MHz)	CORRECTION FACTOR (dB)
10.0	0.3	1200.0	7.3
20.0	0.6	1400.0	7.8
30.0	0.8	1600.0	8.4
40.0	0.9	1800.0	9.1
50.0	1.1	2000.0	9.9
60.0	1.2	2300.0	11.2
70.0	1.3	2600.0	12.2
80.0	1.4	2900.0	13.0
90.0	1.6		
100.0	1.7		
150.0	2.0		
200.0	2.3		
250.0	2.7		
300.0	3.1		
350.0	3.4		
400.0	3.7		
450.0	4.0		
500.0	4.3		
600.0	4.7		
700.0	5.3		
800.0	5.9		
900.0	6.3		
1000.0	6.7		

NOTES:

1. The cable type is RG-214.
2. The overall length of the cable is 27 meters.
3. The above data is located in file 27MO3MO.CBL on the disk marked "Radiated Emission Tests EMI Receiver".

16.2 **Correction factors for****CABLE**

**from EMI receiver
to test antenna
at 3 meter range.**

FREQUENCY (GHz)	CORRECTION FACTOR (dB)
1.0	1.2
2.0	1.6
3.0	2.0
4.0	2.4
5.0	3.0
6.0	3.4
7.0	3.8
8.0	4.2
9.0	4.6
10.0	5.0
12.0	5.8

NOTES:

1. The cable type is RG-8.
2. The overall length of the cable is 10 meters.

16.3 Correction factors for

CABLE from spectrum analyzer to test antenna above 2.9 GHz

FREQUENCY (GHz)	CORRECTION FACTOR (dB)	FREQUENCY (GHz)	CORRECTION FACTOR (dB)
1.0	1.9	14.0	9.1
2.0	2.7	15.0	9.5
3.0	3.5	16.0	9.9
4.0	4.2	17.0	10.2
5.0	4.9	18.0	10.4
6.0	5.5	19.0	10.7
7.0	6.0	20.0	10.9
8.0	6.5	21.0	11.2
9.0	7.0	22.0	11.6
10.0	7.5	23.0	11.9
11.0	7.9	24.0	12.3
12.0	8.3	25.0	12.6
13.0	8.7	26.0	13.0

NOTES:

1. The cable type is SUCOFLEX 104 E manufactured by SUHNER.
2. The cable is used for measurements above 2.9 GHz.
3. The overall length of the cable is 10 meters.

16.4 Correction factors for

**CABLE
from EMI receiver
to test antenna
at 10 meter range.**

FREQUENCY (MHz)	CORRECTION FACTOR (dB)	FREQUENCY (MHz)	CORRECTION FACTOR (dB)
10.0	0.3	1200.0	9.8
20.0	0.8	1400.0	10.0
30.0	0.9	1600.0	11.3
40.0	1.2	1800.0	12.2
50.0	1.4	2000.0	13.1
60.0	1.6	2300.0	14.5
70.0	1.8	2600.0	15.9
80.0	1.9	2900.0	16.4
90.0	2.0		
100.0	2.1		
150.0	2.6		
200.0	3.2		
250.0	3.8		
300.0	4.2		
350.0	4.6		
400.0	5.1		
450.0	5.3		
500.0	5.6		
600.0	6.3		
700.0	7.0		
800.0	7.6		
900.0	8.0		
1000.0	8.7		

NOTES:

1. The cable type is RG-214.
2. The overall length of the cable is 34 meters.
3. The above data is located in file 34M10MO.CBL on the disk marked "Radiated Emissions Tests EMI Receiver".

12.6 Correction factors for LOG PERIODIC ANTENNA
Type LPD 2010/A
at 3 and 10 meter ranges.

Distance of 3 meters		Distance of 10 meters	
FREQUENCY (MHz)	AFE (dB/m)	FREQUENCY (MHz)	AFE (dB/m)
200.0	9.1	200.0	9.0
250.0	10.2	250.0	10.1
300.0	12.5	300.0	11.8
400.0	15.4	400.0	15.3
500.0	16.1	500.0	15.6
600.0	19.2	600.0	18.7
700.0	19.4	700.0	19.1
800.0	19.9	800.0	20.2
900.0	21.2	900.0	21.1
1000.0	23.5	1000.0	23.2

NOTES:

1. Antenna serial number is 1038.
2. The above lists are located in file number 38M30.ANT for a 3 meter range, and file number 38M100.ANT for a 10 meter range.
3. The files mentioned above are located on the disk marked "Radiated Emission Test EMI Receiver".

16.5 Correction factors for

LOG PERIODIC ANTENNA

Type SAS-200/511
at 3 meter range.

FREQUENCY (GHz)	ANTENNA FACTOR (dB)
1.0	24.9
1.5	27.8
2.0	29.9
2.5	31.2
3.0	32.8
3.5	33.6
4.0	34.3
4.5	35.2
5.0	36.2
5.5	36.7
6.0	37.2
6.5	38.1

FREQUENCY (GHz)	ANTENNA FACTOR (dB)
7.0	38.6
7.5	39.2
8.0	39.9
8.5	40.4
9.0	40.8
9.5	41.1
10.0	41.7
10.5	42.4
11.0	42.5
11.5	43.1
12.0	43.4
12.5	44.4
13.0	44.6

NOTES:

1. Antenna serial number is 253.
2. The above lists are located in file number SAS3M0.ANT for a 3 meter range.
3. The files mentioned above are located on the disk marked "Antenna Factors".

16.6 Correction factors for

BICONICAL ANTENNA Type BCD-235/B, at 3 meter range

FREQUENCY (MHz)	AFE (dB/m)
20.0	19.4
30.0	14.8
40.0	11.9
50.0	10.2
60.0	9.1
70.0	8.5
80.0	8.9
90.0	9.6
100.0	10.3
110.0	11.0
120.0	11.5
130.0	11.7
140.0	12.1
150.0	12.6
160.0	12.8
170.0	13.0
180.0	13.5
190.0	14.0
200.0	14.8
210.0	15.3
220.0	15.8
230.0	16.2
240.0	16.6
250.0	17.6
260.0	18.2
270.0	18.4
280.0	18.7
290.0	19.2
300.0	19.9
310	20.7
320	21.9
330	23.4
340	25.1
350	27.0

NOTES:

1. Antenna serial number is 1041.
2. The above list is located in file 19BC10M1.ANT on the disk marked "Radiated Emissions Tests EMI Receiver".

16.7 Correction factors for

BICONICAL ANTENNA

**Type BCD-235/B,
10 meter range**

FREQUENCY (MHz)	AFE (dB/m)
30.0	12.1
40.0	10.6
50.0	10.6
60.0	8.9
70.0	8.5
80.0	9.6
90.0	9.4
100.0	9.6
110.0	10.3
120.0	10.7
130.0	12.6
140.0	12.7
150.0	12.7
160.0	13.8
170.0	13.7
180.0	14.9
190.0	13.4
200.0	13.1
210.0	14.0
220.0	14.5
230.0	15.8
240.0	16.0
250.0	16.6
260.0	16.7
270.0	18.3
280.0	18.5
290.0	19.3
300.0	20.9

NOTES:

1. Antenna serial number is 1041.
2. The above list is located in file 41BC10M1.ANT on the disk marked "Radiated Emissions Tests EMI Receiver".

16.8 Correction factors for Double-Ridged Waveguide Horn

**Model: 3115, S/N 29845
at 3 meter range.**

FREQUENCY (GHz)	ANTENNA FACTOR (dB 1/m)	ANTENN A Gain (dBi)	FREQUENCY (GHz)	ANTENNA FACTOR (dB 1/m)	ANTENNA Gain (dBi)
1.0	24.8	5.4	10.0	38.8	11.4
1.5	26.1	7.6	10.5	38.9	11.8
2.0	28.6	7.7	11.0	39.0	12.1
2.5	29.8	8.4	11.5	39.6	11.8
3.0	31.4	8.4	12.0	39.8	12.0
3.5	32.4	8.7	12.5	39.6	12.5
4.0	33.7	8.6	13.0	40.0	12.5
4.5	33.4	9.9	13.5	39.8	13.0
5.0	34.5	9.7	14.0	40.2	13.0
5.5	35.1	9.9	14.5	40.6	12.9
6.0	35.4	10.4	15.0	41.3	12.4
6.5	35.6	10.8	15.5	39.5	14.6
7.0	36.2	10.9	16.0	38.8	15.5
7.5	37.3	10.4	16.5	40.0	14.6
8.0	37.7	10.6	17.0	41.4	13.4
8.5	38.3	10.5	17.5	44.8	10.3
9.0	38.5	10.8	18.0	47.2	8.1
9.5	38.7	11.1			

16.9 Correction factors for

Horn Antenna

**Model: SWH-28
at 1 meter range.**

FREQUENCY (GHz)	AFE (dB /m)	Gain (dB1)
18.0	40.3	16.1
19.0	40.3	16.3
20.0	40.3	16.1
21.0	40.3	16.3
22.0	40.4	16.8
23.0	40.5	16.4
24.0	40.5	16.6
25.0	40.5	16.7
26.0	40.6	16.4

16.10 Correction factors for

Horn Antenna Model: V637

FREQUENCY (GHz)	AFE (dB /m)	Gain (dB1)
26.0	43.6	14.9
27.0	43.7	15.1
28.0	43.8	15.3
29.0	43.9	15.5
30.0	43.9	15.8
31.0	44.0	16.0
32.0	44.1	16.2
33.0	44.1	16.4
34.0	44.1	16.7
35.0	44.2	16.9
36.0	44.2	17.1
37.0	44.2	17.4
38.0	44.2	17.6
39.0	44.2	17.8
40.0	44.2	18.0

16.11 Correction factors for ACTIVE LOOP ANTENNA

Model 6502

S/N 9506-2950

FREQUENCY (MHz)	Magnetic Antenna Factor (dB)	Electric Antenna Factor (dB)
.009	-35.1	16.4
.010	-35.7	15.8
.020	-38.5	13.0
.050	-39.6	11.9
.075	-39.8	11.8
.100	-40.0	11.6
.150	-40.0	11.5
.250	-40.0	11.6
.500	-40.0	11.5
.750	-40.1	11.5
1.000	-39.9	11.7
2.000	-39.5	12.0
3.000	-39.4	12.1
4.000	-39.7	11.9
5.000	-39.7	11.8
10.000	40.2	11.3
15.000	-40.7	10.8
20.000	-40.5	11.0
25.000	-41.3	10.2
30.000	42.3	9.2