



RF EXPOSURE EVALUATION REPORT

FCC ID : OJFRN610
Equipment : Corning 5G Sub-6 N77 Radio Node, Corning 5G Sub-6 N77 External Antenna Radio Node
Brand Name : Everon RAN
Model Name : SCRN-610-77
Applicant : Corning Optical Communications LLC
6 Concord Road, Shrewsbury, MA 01545
Manufacturer : Corning Optical Communications LLC
6 Concord Road, Shrewsbury, MA 01545
Standard : 47 CFR Part 2.1091

We, SPORTON INTERNATIONAL INC has been evaluated this product in accordance with 47 CFR Part2.1091 and it complies with applicable limit.

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190) and the FCC designation No. TW1190 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC evaluation.

The results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Laboratory, the test report shall not be reproduced except in full

Approved by: Cona Huang / Deputy Manager



SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

1. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	4
2. MAXIMUM RF AVERAGE OUTPUT POWER AMONG PRODUCTION UNITS	4
3. DETERMINATION OF EXEMPTION	5
4. RF EXPOSURE EVALUATION	6
4.1. Standalone assessment	6



1. **Description of Equipment Under Test (EUT)**

Product Feature & Specification	
EUT Type	Corning 5G Sub-6 N77 Radio Node, Corning 5G Sub-6 N77 External Antenna Radio Node
Brand Name	Everon RAN
Model Name	SCRN-610-77
FCC ID	OJFRN610
Wireless Technology and Frequency Range	5G NR n77 : 3700 MHz ~ 3980 MHz
Mode	5G NR: DFT-s-OFDM/CP-OFDM, Pi/2 BPSK/QPSK/16QAM/64QAM/256QAM
EUT Stage	Identical Prototype

Antenna Information	
External Antenna (E-Sku)	6.22dBi
Internal Antenna (I-Sku)	ANT 1 = 4.32dBi ANT 2 = 4.55dBi ANT 3 = 4.38dBi ANT 4 = 4.01dBi

Reviewed by: **Jason Wang**

Report Producer: **Daisy Peng**

2. **Maximum RF average output power among production units**

Radio Tech	Band Number	Maximum Transmit Power Level (dBm)	
		Per antenna	Total
FR1	n77	24.50	30.50

3. Determination of exemption

Per 1.1307(b)(3), (i) For single RF sources (i.e., any single fixed RF source, mobile device, or portable device, as defined in paragraph (b)(2) of this section): A single RF source is exempt if:

- (A) The available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(ii)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(ii)(A);
- (B) Or the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold Pth (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). Pth is given by:

$$P_{th} \text{ (mW)} = ERP_{20cm} (d / 20)^x \text{ for distance } d \leq 20\text{cm}$$

$$P_{th} \text{ (mW)} = ERP_{20cm} \text{ for distance } 20\text{cm} < d \leq 40\text{cm}$$

$$x = -\log_{10} \left(\frac{60}{ERP_{20cm} \sqrt{f}} \right)$$

$ERP_{20cm} \text{ (mW)}$	$0.3 \text{ GHz} \leq f < 1.5 \text{ GHz}:$	$2040 f$
	$1.5 \text{ GHz} \leq f \leq 6 \text{ GHz}:$	3060

- (C) Or using Table 1 and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2.$
1.34-30	$3,450 R^2/f^2.$
30-300	$3.83 R^2.$
300-1,500	$0.0128 R^2 f.$
1,500-100,000	$19.2 R^2.$



4. RF Exposure Evaluation

4.1. Standalone assessment

General Note:

1. In this report was used Part1.1307(b)(3)(i)(B) perform RF Exposure evaluation
2. P_i is mean the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm
3. P_{th} is mean the exemption threshold power (P_{th}) according to the § 1.1307(b)(3)(i)(B) formula for fixed, mobile, or portable RF source i .
4. The distance of 20cm is for this device

<External Antenna E-Sku>

Band	Antenna Gain (dBi)	Maximum Conducted Power (dBm)	Maximum EIRP (dBm)	Maximum ERP (dBm)	Maximum EIRP (mW)	Maximum ERP (mW)	P_i (dBm)	P_i (mW)	Part1.1307 option(b) Threshold (mW)
5G NR n77	6.22	30.50	36.7	34.57	4698.94	2864.18	34.57	2864.18	3060.000

<Internal Antenna I-Sku >

Band	Antenna Gain (dBi)	Maximum Conducted Power (dBm)	Maximum EIRP (dBm)	Maximum ERP (dBm)	Maximum EIRP (mW)	Maximum ERP (mW)	P_i (dBm)	P_i (mW)	Part1.1307 option(b) Threshold (mW)
5G NR n77	4.55	30.50	35.1	32.90	3198.90	1949.84	32.90	1949.84	3060.000

Conclusion:

According to 47 CFR §1.1307, the RF exposure analysis concludes that the RF Exposure is FCC compliant.