

R.F Exposure/Safety Calculation for VE LTE 700 MB

The E.U.T. is an in-building antenna distribution system, supporting a single frequency band. The “worst case” distance between the E.U.T. and the general population is 10 cm.

Calculation of Maximum Permissible Exposure (MPE)

Based on Section 1.1307(b)(1) Requirements

(a) FCC Occupational user limit at 733 MHz is: $\frac{f}{300} = \frac{733}{300} = 2.44 \frac{mW}{cm^2}$

FCC Occupational user limit at 741 MHz is: $\frac{f}{300} = \frac{741}{300} = 2.47 \frac{mW}{cm^2}$

FCC Occupational user limit at 751 MHz is: $\frac{f}{300} = \frac{751}{300} = 2.50 \frac{mW}{cm^2}$

Using table 1 of Section 1.1310 limit for general population/uncontrolled exposures, the above level is an average over 30 minutes.

(b) The power density produced by the E.U.T. is

$$S = \frac{P_t G_t}{4\pi R^2}$$

P_t - Transmitted Peak Power (worst case)

G_t - Antenna Gain

R- Distance from Transmitter

(c) Peak power density:

Operation Frequency	Modulation	P _t (mW)	Antenna type	G _T (dBi)	R (cm)	S _{AV} (mW/cm ²)	Spec (mW/cm ²)
733 MHz.	QPSK	27.4	External	10	10	0.218	2.44
	16QAM	26.6	External	10	10	0.212	2.44
	64QAM	25.7	External	10	10	0.205	2.44
741 MHz	QPSK	25.9	External	10	10	0.206	2.47
	16QAM	27.2	External	10	10	0.216	2.47
	64QAM	26.9	External	10	10	0.214	2.47
751 MHz	QPSK	27.0	External	10	10	0.215	2.50
	16QAM	27.2	External	10	10	0.216	2.50
	64QAM	26.5	External	10	10	0.211	2.50