

**F C C -**

**TEST REPORT**

REPORT NO.: 25744A/1/400F

# FCC – Test Report

Date: 2001-05-10

No. 25744A/1/400F

Page 2 of 11

## FCC listed testlab acc. to Section 2.948 of the FCC - Rules

in compliance with the requirements of  
ANSI C63.4 - 1992

**Product** : R/C Rock Climber  
**Model** : 0215A (49MHz)  
**Applicant** : WOWWEE LIMITED  
**Manufacturer** : WOWWEE LIMITED

# **FCC – Test Report**

Date: 2001-05-10

No. 25744A/1/400F

Page 3 of 11

## **TABLE OF CONTENTS**

1. **Cover sheet**
2. **Introduction**
3. **Table of Contents**
4. **Laboratory Report**
5. **Summary of Testresults**
6. **Test Equipment List**
7. **Radiated Emission Testprocedure**
8. **Interference Radiation (Datasheet)**
9. **Notes for Radiation Measurement (acc. to ANSI C63.4 - 1992)**
10. **Measurement of Emissions within Band Edges (Datasheet)**
11. **Notes for Measurement of Emissions within Band Edges**

# FCC – Test Report

Date: 2001-05-10

No. 25744A/1/400F

Page 4 of 11

## LABORATORY - REPORT

**APPLICANT:** WOWWEE LIMITED  
**ADDRESS:** Unit 301C, Energy Plaza  
92 Granville Road  
Tsimshatsui East, Kowloon  
HONG KONG

**DATE OF SAMPLE RECEIVED:** 2001-03-16

**DATE OF TESTING:** 2001-05-02

### DESCRIPTION OF SAMPLE:

Product: R/C Rock Climber  
Manufacturer: WOWWEE LIMITED  
Model number: 0215A (49MHz)  
Rating: DC 9V ('6F22' Size Battery x 1)  
Country of Origin: P.R. CHINA

**INVESTIGATIONS REQUESTED:** Measurements to the relevant clauses of F.C.C. Rules and Regulations Part 15 Subpart C - Intentional Radiators

**RESULTS:** See the attached test sheets

**CONCLUSIONS** From the measurement data obtained, the tested sample was considered to have COMPLIED with the requirements for the relevant clauses of Federal Communications Commission Rules as specified above.

---

Authorized Signature

**Remark:** Purpose of those tests in this report is to provide the applicant with the necessary test data of their device for the submission to FCC with application for Equipment Authorization under the FCC Equipment Authorization Program. The tests themselves are not Approval Tests

# FCC – Test Report

Date: 2001-05-10

No. 25744A/1/400F

Page 5 of 11

## Summary of Test Results

### Interference Radiation:

**Test result:** O.K.  
**Test data:** See attached data sheet


### Interference Voltage:

**Test result:** N.A.  
**Test data:** N.A.

### Measurement of Emissions within Band Edges

**Test result:** O.K.  
**Test data:** See attached data sheet

### PHOTOGRAPH OF THE SAMPLE



# FCC – Test Report

Date: 2001-05-10

No. 25744A/1/400F

Page 6 of 11

## TEST EQUIPMENT LIST

Equipment	Manufacturer	Model	Serial No.	Remark
Test Receiver	Rohde & Schwarz	ESH 3	863497/015	10KHz – 30MHz
Test Receiver	Rohde & Schwarz	ESVP	860688/022	25MHz – 1,300 MHz
Artificial Mains Network (LISN)	Schwarzbeck	NSLK 8127	--	2 x 10A, 50Ω, 50μH 10KHz-30MHz
Antenna System	Schwarzbeck	BBA 9106 / UHALP 9107	--	30MHz – 1000MHz
Antenna Mast System	Schwarzbeck	AM9104	--	Max. 4 meters height
Spectrum Analyzer with Q. Peak	Tektronix	2712	B023006	9KHz – 1.8GHz
Interface for Spectrum 2712	Tektronix	TD3F14A	--	
Test Receiver	Rohde & Schwarz	ESH 3	892580/006	10KHz – 30MHz
Test Receiver	Rohde & Schwarz	ESVP	863512/012	25MHz – 1,300 MHz
Impulse Limiter	Rohde & Schwarz	ESH-3-Z2	--	
Artificial Mains Network (LISN)	Schwarzbeck	NSLK 8127	--	2 x 10A, 50Ω, 50μH 10KHz-30MHz
Antenna System	Schwarzbeck	BBA 9106 / UHALP 9107	--	30MHz – 1000MHz
Signal Generator	Rohde & Schwarz	SWS 2	879113/42	100KHz – 1040 MHz
Digital Multimeter	Tektronix	DM2510G	DM- 2510GTW10555	10KHz – 30MHz
Turntable with Controller	Drehtisch	DT312	--	φ120 cm


# FCC – Test Report

Date: 2001-05-10

No. 25744A/1/400F

Page 7 of 11

## Radiated Emission Test Procedure




# Interference Radiation

Measurement of Radiated Emissions (30MHz-1000MHz)  
Acc: FCC Part 15 Subpart C

**IECC Ref:** 25744A/1/400F  
**Model:** 0215A (49MHz)  
**Applicant:** WOWWEE LIMITED  
**Ser.Nr.:** 1  
**Set under test:** R/C Rock Climber  
**Connected sets:** -  
**Operating mode:** Power "On"

Test Equipment  
 Receiver: ESVP Rohde & Schwarz  
 Antenna: Schwarzbeck BBA 9106  
 and UHALP 9107

	Frequency (MHz)	Horz. Reading dB(µV)	Vert. Reading dB(µV)	Antenna Factor (dB)	Horiz. Test Result (µV/m)	Vert. Test Result (µV/m)	Limit (µV/m)
Peak	49.86	52	59	11.7	1538	3443	100,000
Av.	49.86	50.5	57	11.7	1294	2735	10000
Harm. 2	99.72	22	< 16	10.3	41	< 21	150
Harm. 3	149.58	21	< 16	15.0	63	< 36	150
Harm. 4	199.44	20	< 16	16.5	67	< 42	150
Harm. 5	249.3	18	< 16	17.7	61	< 49	200
Harm. 6	299.16	< 16	< 16	20.0	< 63	< 63	200
Harm. 7	349.02	< 16	< 16	17.4	< 47	< 47	200
Harm. 8	398.88	< 16	< 16	18.3	< 52	< 52	200
Harm. 9	448.74	< 16	< 16	19.0	< 56	< 56	200
Harm. 10	498.6	< 16	< 16	19.7	< 61	< 61	200
Harm. 11	548.46	< 16	< 16	20.2	< 64	< 64	200
Harm. 12	598.32	< 16	< 16	20.9	< 70	< 70	200
Harm. 13	648.18	< 16	< 16	21.6	< 76	< 76	200
Harm. 14	698.04	< 16	< 16	22.4	< 83	< 83	200
Harm. 15	747.9	< 16	< 16	23.0	< 90	< 90	200
Harm. 16	797.76	< 16	< 16	23.7	< 96	< 96	200
Harm. 17	847.62	< 16	< 16	24.3	< 104	< 104	200
Harm. 18	897.48	< 16	< 16	25.0	< 112	< 112	200
Harm. 19	947.34	< 16	< 16	25.7	< 122	< 122	200



Test result:  O.K. Date: \_\_\_\_\_  
Operator: \_\_\_\_\_



## Notes for Radiation Measurement

**1. Measurement facility:**

Measurement facility located at Fanling (Hong Kong), placed on file with the FCC Pursuant to Section 2.948 of the FCC Rules.

**2. Distance between the EUT and measuring antenna:**

3 meters.

**3. Measuring instrumentations:**

Rohde & Schwarz ESVP Test Receiver ( 20 - 1300 MHz ) with a CISPR weighting QP detector, 6 dB bandwidth set at 120 KHz.

In the frequency range above 1000 MHz Spectrum Analyzer FMSM26 and Analyzer Display Unit FSA-D are used, bandwidth set at 100 kHz.

**4. Measuring antenna:**

Broad-band antenna for the frequency range 30 - 300 MHz and frequency range 300 - 1000 MHz, connected with 10 meters coaxial cable. Cable loss of the coaxial cable included in the Antenna Factor for measurement data. The antennas are capable of measuring both horizontal and vertical polarizations.

In the frequency range above 1 GHz horn-antenna RGA 50/60 is used.

**5. Frequency range scanned:**

The frequency range 30 - 5000 MHz has been scanned. Readings of the highest emissions relating to the limit were reported as above.

**6. Arrangement of EUT:**

During the test, the sample was operated at rated supply voltage and arranged for maximum emissions. To find the maximum emission, the antenna was raised from 1 to 4 meters and was stopped at the maximum emission point.

**7. Measuring Procedure:**

In accordance with the relevant sections of the American National Standards Institute (ANSI) C63.4-1992 'Methods of Measurement of Radio Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9KHz to 40GHz'.

# FCC – Test Report

Date: 2001-05-10

No. 25744A/1/400F

Page 10 of 11

## Measurement Data of Emissions within Band Edges

MKR: 49.8584 MHz

59.045 dB $\mu$ V

5dB/

Apr/27


A\_view

REF: 62.3 dB $\mu$ V

ATT: 0 dB

12: 42

B\_blank



ST: 49.8100 MHz

SP: 49.9100 MHz

RBW: 9 kHz

VBW: 100 kHz

SWP: 200 ms

## Notes for Measurement of Emissions within Band Edges

1. **Measurement facility:**  
Measurement facility located at Fanling (Hong Kong) placed on file with the FCC Pursuant to Section 2.948 of the FCC Rules.
  
2. **Measuring instrumentations:**  
Spectrum Analyzer: Tektronix 2712
  
3. **Frequency range scanned:**  
The frequency range acc. to FCC rules and regulations part 15 subpart C - Intentional Radiators.
  
4. **Arrangement of EUT:**  
During the test, the sample was operated.
  
5. **Measuring Procedure:**  
In accordance with the relevant sections of American National Standards Institute (ANSI) C63.4 - 1992 'Methods of Measurement of Radio Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz'.