

THRU lab & Engineering.

RM1105,11FL, ACE TECHNO TOWER

197-22, GURO-DONG GURO-GU SEOUL KOREA

T81221095059F81221095056 email thrukang@kornet.net



Test Report

Product Name: 49.82-49.90 MHz Wireless R/C Toy - TX

FCC ID: OKP0232A

Applicant:

**WOW Wee Ltd.
Energy Plaza, Suite 301A-C,
92 Granville Road
T.S.T East, Hong Kong.**

Date Receipt:03/10/2004

Date Tested:03/12/2004

APPLICANT: WOW Wee Ltd.
FCC ID: OKP0232A
REPORT #: THRU-403007

COVER SHEET

THRU lab & Engineering

**RM1105,11FL, ACE TECHNO TOWER
197-22, GURO-DONG GURO-GU SEOUL KOREA
T81221095059F81221095056 email thrukang@kornet.net**

TABLE OF CONTENTS LIST

APPLICANT: WOW Wee Ltd.

FCC ID: OKP0232A

TEST REPORT CONTAINING:

PAGE 1.....TEST EQUIPMENT LIST
PAGE 2.....TEST PROCEDURE
PAGE 3-5.....RADIATION INTERFERENCE TEST DATA
PAGE 6.....OCCUPIED BANDWIDTH
PAGE 7.....OCCUPIED BANDWIDTH PLOT

EXHIBITS CONTAINING:

EXHIBIT 2.....BLOCK DIAGRAM
EXHIBIT 3.....SCHEMATIC
EXHIBIT 4A-4B.....PARTS LIST
EXHIBIT 5.....INSTRUCTION MANUAL
EXHIBIT 6.....SAMPLE OF FCC ID LABEL
EXHIBIT 7.....LOCATION OF FCC ID LABEL
EXHIBIT 8.....EXTERNAL PHOTO - FRONT SIDE
EXHIBIT 9.....EXTERNAL PHOTO - BACK SIDE
EXHIBIT 10.....INTERNAL PHOTO - COMPONENT SIDE
EXHIBIT 11.....INTERNAL PHOTO - COPPER SIDE
EXHIBIT 14.....CIRCUIT DESCRIPTION

APPLICANT: WOW Wee Ltd.

FCC ID: OKP0232A

REPORT #: THRU-403007

TABLE OF CONTENTS

THRULab & Engineering

RM1105,11FL, ACE TECHNO TOWER

197-22, GURO-DONG GURO-GU SEOUL KOREA

T81221095059F81221095056 email thrukang@kornet.net

Test Equipment List

DEVICE	MODEL	MFGR	SERNO	DUE . CAL
EMI Test Receiver	ESVS 10	Rohde & Schwarz	830489/001	2004.04.25.
Spectrum Analyzer	8566B	Hewlett Packard	2311A02394	2004.03.17
Spectrum Display	85662A	Hewlett Packard	2542A12429	2004.03.17
Quasi-Peak Adapter	85650A	Hewlett Packard	2521A00887	2004.03.17
RF Preselector	85685A	Hewlett Packard	2648A00504	2004.03.17
Pre-Amplifier	8449B	Hewlett Packard	3008A00375	2004.03.17
Pre-Amplifier	8447F	Hewlett Packard	3113A05367	2004.03.17
Spectrum Monitor	EZM	Rohde & Schwarz	862304/007	2004.03.17
Bico-Antenna	94455-1	Eaton	977	2004.03.17
Log-Periodic Antenna	3146	EMCO	2051	2004.03.17
Dipole Antenna	TDA25/1/2	Electro Metrics	176/200/200	2004.03.17
Horn Antenna	SAS-571	A.H Systems	414	2004.03.17
Spectrum Analyzer	R3261C	Advantest	71720189	2004.04.26
LISN	KNW-242	Kyoritsu	8-923-2	2004.07.12
LISN	8012-50-R-24	Solar	8379121	2004.07.12
Loop Ant	6507	EMCO	1435	2004.10.06

APPLICANT: WOW Wee Ltd.

FCC ID: OKP0232A

REPORT #: THRU-403007

THRULab & Engineering

RM1105,11FL, ACE TECHNO TOWER

197-22, GURO-DONG GURO-GU SEOUL KOREA

T81221095059F81221095056 email thrukang@kornet.net

TEST PROCEDURE

GENERAL: This report shall NOT be reproduced except in full without the written approval of THRULab & ENGINEERING.

RADIATION INTERFERENCE: The test procedure used was ANSI STANDARD C63.4-1992 using a HEWLETT PACKARD spectrum analyzer with a preselector. The bandwidth of the spectrum analyzer was 100 kHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100 kHz and the video bandwidth was 300 kHz. The ambient temperature of the UUT was 15°C with a humidity of 28%.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Preselector was accounted for in the Spectrum Analyzer Meter Reading.

Example:

Freq (MHz) METER READING + ACF = FS
33 20 dBuV + 10.36 dB = 30.36 dBuV/m @ 3m

ANSI STANDARD C63.4-1992 10.1.7 MEASUREMENT PROCEDURES: The unit under test was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The table used for radiated measurements is capable of continuous rotation.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

The situation was similar for the conducted measurement except that the table did not rotate. The EUT was setup as described in ANSIC63.4-1992 with the EUT 40 cm from the vertical ground wall.

Not Applicable, battery operated.

APPLICANT: WOW Wee Ltd.

FCC ID: OKP0232A

REPORT #: THRU-403007

THRULab & Engineering

RM1105,11FL, ACE TECHNO TOWER
197-22, GURO-DONG GURO-GU SEOUL KOREA
T81221095059F81221095056 email thrukang@kornet.net

APPLICANT: WOW Wee Ltd.
FCC ID: OKP0232A
NAME OF TEST: RADIATION INTERFERENCE
RULES PART NO.: 15.235
REQUIREMENTS: CARRIER FREQUENCY SHALL NOT EXCEEDS 10,000 microvolts/meter AT 3M.

Frequency (MHz)	Reading Receiver dBuv/m PK	Reading Receiver dBuv/m PK	Polar	Ant Height m	Antenna Factor dB	Cable Loss dB	Result dBuv PK	Result dBuv AV	Limit dBuv/m PK	Limit dBuv/m AV	Margin dBuv/m PK	Margin dBuv/m AV
49.858	45.1	39.9	H	2.8	10.9	1.0	57.0	51.8	100	80	-43	-28.2
49.858	59.2	54.0	V	2.60	10.9	1.0	71.1	65.9	100	80	-28.9	-14.1

SAMPLE CALCULATION: FSdBuV/m = MR (dBuV) + ACFdB.

TEST PROCEDURE: The procedure used was ANSI STANDARD C63.4-1992. The spectrum was scanned from 30 MHz to 1000 MHz. When an emission was found, the table was rotated to produce the maximum signal strength. The antenna was placed in both the horizontal and vertical planes and the worse case emissions were reported. The UUT was tested in 3 orthogonal planes.

TEST RESULTS: THE UNIT DOES MEET THE FCC REQUIREMENTS.

PERFORMED BY: K.M CHOI

DATE: 03/12/2004

APPLICANT: WOW Wee Ltd.

FCC ID: OKP0232A

REPORT #: THRU-403007

THRULab & Engineering

RM1105,11FL, ACE TECHNO TOWER
197-22, GURO-DONG GURO-GU SEOUL KOREA
T81221095059F81221095056 email thrukang@kornet.net

APPLICANT: WOW Wee Ltd.

FCC ID: OKP0232A

NAME OF TEST: RADIATION INTERFERENCE

RULES PART NO.: 15.235

REQUIREMENTS: CARRIER FREQUENCY WILL NOT EXCEEDS 80 dBuV/m AT 3M.
OUT-OF-BAND EMISSIONS SHALL NOT EXCEED:

30 - 88 MHz	40.0 dBuV/M MEASURED AT 3 METERS
88 - 216 MHz	43.5 dBuV/M
216 - 960 MHz	46.0 dBuV/M
ABOVE 960 MHz	54.0 dBuV/M

TEST DATA:

No	Frequency (MHz)	Result (dBuV/m)	Polar	Ant Height m	Antenna Factor dB	Cable Loss dB	Limit (dBuV/m)	Reading S/A (dBuV/m)	Margin (dBuV/m)
1	99.69	21.4	H	1.0	11.2	1.6	43.5	8.6	-22.1
2	149.58	26.0	H	2.3	16.7	2.1	43.5	7.2	-17.5
3	199.44	25.4	H	2.6	16.0	2.5	43.5	6.9	-18.1
4	249.29	17.9	H	2.8	11.8	3.1	46.0	3.0	-28.1
5	299.13	23.2	H	3.0	16.3	3.4	46.0	3.5	-22.8
6	348.99	20.5	H	2.0	14.9	3.8	46.0	1.8	-25.5
7	398.84	21.2	H	2.1	15.4	4.2	46.0	1.6	-24.8
8	448.69	22.1	H	1.8	16.4	4.5	46.0	1.2	-23.9
9	498.53	24.9	H	1.5	18.2	4.9	46.0	1.8	-21.1

SAMPLE CALCULATION: $FSdBuV/m = MR (dBuV) + ACFdB$.

TEST PROCEDURE: The procedure used was ANSI STANDARD C63.4-1992. The spectrum was scanned from 30 MHz to 1000 MHz. When an emission was found, the table was rotated to produce the maximum signal strength. The antenna was placed in both the horizontal and vertical planes and the worse case emissions were reported. The UUT was tested in 3 orthogonal planes.

TEST RESULTS: THE UNIT DOES MEET THE FCC REQUIREMENTS.

PERFORMED BY: Kyoung.M Choi

DATE: 03/12/2004

APPLICANT: WOW Wee Ltd.

FCC ID: OKP0232A

REPORT #: THRU-403007

THRULab & Engineering

RM1105,11FL, ACE TECHNO TOWER
197-22, GURO-DONG GURO-GU SEOUL KOREA
T81221095059F81221095056 email thrukang@kornet.net

APPLICANT: WOW Wee Ltd.

FCC ID: OKP0232A

NAME OF TEST: RADIATION INTERFERENCE

RULES PART NO.: 15.235

REQUIREMENTS: CARRIER FREQUENCY WILL NOT EXCEEDS 80 dBuV/m AT 3M.
OUT-OF-BAND EMISSIONS SHALL NOT EXCEED:

30 - 88 MHz	40.0 dBuV/M MEASURED AT 3 METERS
88 - 216 MHz	43.5 dBuV/M
216 - 960 MHz	46.0 dBuV/M
ABOVE 960 MHz	54.0 dBuV/M

TEST DATA:

No	Frequency (MHz)	Result (dBuV/m)	Polar	Ant Height m	Antenna Factor dB	Cable Loss dB	Limit (dBuV/m)	Reading S/A (dBuV/m)	Margin (dBuV/m)
1	99.69	27.8	V	1.2	11.2	1.6	43.5	15.0	-15.7
2	149.58	25.2	V	1.9	16.7	2.1	43.5	6.4	-18.3
3	199.44	24.1	V	1.3	16.0	2.5	43.5	5.6	-19.4
4	249.29	18.6	V	2.0	11.8	3.1	46.0	3.7	-27.4
5	299.13	27.1	V	1.8	16.3	3.4	46.0	7.4	-18.9
6	348.99	21.6	V	2.9	14.9	3.8	46.0	2.9	-24.4
7	398.84	21.2	V	2.5	15.4	4.2	46.0	1.6	-24.8
8	448.69	22.6	V	1.6	16.4	4.5	46.0	1.7	-23.4
9	498.53	24.9	V	1.0	18.2	4.9	46.0	1.8	-21.1

SAMPLE CALCULATION: $FSdBuV/m = MR (dBuV) + ACFdB$.

TEST PROCEDURE: The procedure used was ANSI STANDARD C63.4-1992. The spectrum was scanned from 30 MHz to 1000 MHz. When an emission was found, the table was rotated to produce the maximum signal strength. The antenna was placed in both the horizontal and vertical planes and the worse case emissions were reported. The UUT was tested in 3 orthogonal planes.

TEST RESULTS: THE UNIT DOES MEET THE FCC REQUIREMENTS.

PERFORMED BY: Kyoung.M Choi

DATE: 03/12/2004

APPLICANT: WOW Wee Ltd.

FCC ID: OKP0232A

REPORT #: THRU-403007

THRULab & Engineering

RM1105,11FL, ACE TECHNO TOWER
197-22, GURO-DONG GURO-GU SEOUL KOREA
T81221095059F81221095056 email thrukang@kornet.net

APPLICANT: WOW Wee Ltd.
FCC ID: OKP0232A
NAME OF TEST: Occupied Bandwidth
RULES PART NO.: 15.235

REQUIREMENTS: The field strength of any emissions appearing between the band edges and up to 10 kHz above and below the band edges shall be attenuated at least 26 dB below the level of the unmodulated carrier or to the general limits of 15.209, whichever permits the higher emission levels.

30 - 88 MHz	40.0 dBuV/M	MEASURED AT 3 METERS
88 - 216 MHz	43.5 dBuV/M	
216 - 960 MHz	46.0 dBuV/m	
ABOVE 960 MHz	54.0 dBuV/m	

THE GRAPH ON THE NEXT PAGE REPRESENTS THE EMISSIONS TAKEN FOR THE DEVICE.

METHOD OF MEASUREMENT: A small sample of the transmitter output was fed into the spectrum analyzer and the attached plot was taken. The vertical scale is set to 10 dB per division.

TEST RESULTS: The unit DOES meet the FCC requirements.

PERFORMED BY: Kyoung.M Choi


DATE: 03/12/2004

APPLICANT: WOW Wee Ltd.
FCC ID: OKP0232A
REPORT #: THRU-403007

THRUlab & Engineering

RM1105,11FL, ACE TECHNO TOWER
197-22, GURO-DONG GURO-GU SEOUL KOREA
T81221095059F81221095056 email thrukang@kornet.net

OCCUPIED BANDWIDTH PLOT



APPLICANT: WOW Wee Ltd.
FCC ID: OKP0232A
REPORT #: THRU-403007