

## Analysis Report

The Equipment Under Test (EUT), is a portable 2.4GHz Transceiver (Controller Unit) for a RC Mouse. The sample supplied operated on 24 channels, normally at 2430 - 2453MHz. The channels are separated with 1MHz spacing.

The EUT is powered by 3 x 1.5V LR44 button batteries. After switching on the EUT, the mouse will be moved forward or backward and turned left and right based on the switches pressed in the controller.

Antenna Type: Internal, Integral antenna  
Antenna Gain: 0dBi  
Nominal rated field strength is 94.7 dB $\mu$ V/m at 3m  
Maximum allowed production tolerance: +/- 3dB

According to the KDB 447498:

Based on the maximum average field strength of production tolerance was 97.7dB $\mu$ V/m at 3m in frequency 2.442GHz.

Thus, it below calculated field strength according to minimum SAR exclusion threshold level as follows:

The worst case of SAR Exclusion Threshold Level:  
=  $3.0 * (\text{min. test separation distance, mm}) / \text{sqrt}(\text{freq. in GHz})$   
=  $3.0 * 5 / \text{sqrt}(2.483.5) \text{ mW}$   
= 9.52 mW

According to the KDB 412172 D01:  
EIRP =  $[(\text{FS} * \text{D})^2 * 1000 / 30]$

Calculated Field Strength for 9.52mW is 105dBuV/m @3m

Since maximum average field strength plus production tolerance  $\leq$  105dBuV/m @3m and antenna gain is  $\geq$  0.0dBi, it is concluded that maximum Conducted Power and Field Strength are well below the SAR Exclusion threshold level, so the EUT is considered to comply with SAR requirement without testing.