

FCC CLASS B COMPLIANCE REPORT

for

Electromagnetic Emissions

of

LCD Monitor

Trade Name : GrandView
Model Number : 104TVA
FCC ID : OKTLM104
Serial Number : N/A
Report Number : 990309-F
Date : July 15, 1999

Prepared for :

GrandView Technology Inc.
8F, No. 780-1, Chung-Cheng Road, Chung-Huo City,
Taipei Hsien , Taiwan , R.O.C.

Prepared by :

C&C LABORATORY, CO., LTD.

1st Fl., No. 344, Fu Ching Street,

Taipei, Taiwan, R.O.C.

TEL: (02)2746-8584

FAX: (02)2763-2154

**This report shall not be reproduced, except in full, without the written approval of
C&C Laboratory, Co., Ltd.**

TABLE OF CONTENTS


| DESCRIPTION | PAGE |
|---|------|
| VERIFICATION OF COMPLIANCE | 3 |
| SYSTEM DESCRIPTION | 4 |
| PRODUCT INFORMATION | 5 |
| SUPPORT EQUIPMENT | 6 |
| MEASUREMENT PROCEDURE & LIMIT (LINE CONDUCTED EMISSION TEST) | 7 |
| MEASUREMENT PROCEDURE & LIMIT (RADIATED EMISSION TEST) | 9 |
| SUMMARY DATA | 12 |
| APPENDIX 1 LETTER OF AGENT AUTHORIZATION | 15 |
| APPENDIX 2 LETTER OF MODIFICATION | 16 |
| APPENDIX 3 FCC ID LABEL & LOCATION | 17 |
| APPENDIX 4 BLOCK DIAGRAM/SCHEMATICS OF EUT | 19 |
| APPENDIX 5 USER'S MANUAL OF EUT | 20 |
| APPENDIX 6 TEST FACILITY | 21 |
| APPENDIX 7 TEST EQUIPMENT | 23 |
| APPENDIX 8 BLOCK DIAGRAM OF TEST SETUP | 27 |
| APPENDIX 9 PHOTOGRAPHS (TEST SETUP OF LINE CONDUCTED EMISSION TEST) | 29 |
| APPENDIX 10 PHOTOGRAPHS (TEST SETUP OF RADIATED EMISSION TEST) | 31 |
| APPENDIX 11 PHOTOGRAPHS OF EUT | 33 |

VERIFICATION OF COMPLIANCE

Equipment Under Test: LCD Monitor
Trade Name: GrandView
FCC ID: OKTLM104
Model Number: 104TVA
Serial Number: N/A
Applicant: **GrandView Technology Inc.**
8F, No. 780-1, Chung-Cheng Road, Chung-Huo City,
Taipei Hsien , Taiwan , R.O.C.
Manufacturer: **GrandView Technology Inc.**
8F, No. 780-1, Chung-Cheng Road, Chung-Huo City,
Taipei Hsien , Taiwan , R.O.C.
Type of Test: FCC Class B
Measurement Procedure: ANSI C63.4: 1992
File Number: 990309-F
Date of test: July 10/12 , 1999
Tested by: Michael Chen
Deviation: None
Condition of Test Sample: Normal

The above equipment was tested by C&C Laboratory, Co., Ltd. for compliance with the requirements set forth in the FCC Rules and Regulations Part 15, Subpart B and the measurement procedure according to ANSI C63.4, 1992. This said equipment in the configuration described in this report shows the maximum emission levels emanating from equipment are within the compliance requirements.

The test results of this report relate only to the tested sample identified in this report.



Charles Wang / Director

SYSTEM DESCRIPTION

EUT Test Program:

1. EMI test program was loaded and executed in Windows mode.
2. Data was sent to EUT filling the screen with upper case of "H" patterns.
3. Test program sequentially exercised printer and modem, and sent "H" patterns to them individually.
4. Repeat 1 to 3. Test program is self-repeating throughout the test.

PRODUCT INFORMATION

Housing Type: Plastic
EUT Power Rating: +12V, from power Adapter
AC power during Test: 120VAC/60Hz to power Adapter
Adapter Power Rating: I/P : 100-240VAC, 47-63Hz, 1.6A
O/P :+12V, 3.75A
Power Adapter Manufacturer: SYN
Power Adapter Model: SYS1097-4512
AC Power Cord Type: Unshielded, 1.8m (Detachable)
DC Power Cable Type: Unshielded, 0.8m (Non-detachable) with a Ferrite
LCD Panel Manufacturer: TOSHIBA **Model:** LTM10C209A
Video Cable Type: Shielded, 1.3m (Detachable) with two Ferrite core.

| I/O PORT TYPES | Q'TY | TESTED WITH |
|-------------------|------|-------------|
| 1). Video Port | 1 | 1 |
| 2). DC Power Port | 1 | 1 |

SUPPORT EQUIPMENT

| Equipment | Model # | Serial # | FCC ID | Trade Name | Data Cable | Power Cord |
|---------------|---------|---------------|------------|---------------------|------------------------------|--|
| PC | D6923A | TW85000069 | FCC DoC | HP | Shielded, 1.3m with two core | Unshielded, 0.9m |
| Modem | 2400 | 94-364-176270 | DK467GSM24 | Computer Peripheral | Shielded, 1.8m | Unshielded, 1.8m |
| Printer | C2642A | MY8251CSFK | B94C2642X | HP | Shielded, 1.8m | AC I/P Unshielded, 0.9m DC O/P Unshielded, 1.9m |
| PS/2 Keyboard | KB-9000 | 9809048153 | LFCACEKEY1 | ACEKEY | Unshielded, 1.5m | N/A |
| PS/2 Mouse | M-S34 | LZC84359502 | DZL211029 | LOGITECH | Unshielded, 1.8m | N/A |

Note: All the above equipment/cables were placed in worse case positions to maximize emission signals.

Grounding: Grounding was in accordance with the manufacturer's requirements and conditions for the intended use.

MEASUREMENT PROCEDURE (PRELIMINARY LINE CONDUCTED EMISSION TEST)

- 1) The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4: 1992 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2) Support equipment, if needed, was placed as per ANSI C63.4: 1992.
- 3) All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4: 1992.
- 4) The EUT received AC power through a Line Impedance Stabilization Network (LISN) which supplied power source of 115VAC/60Hz and was grounded to the ground plane.
- 5) All support equipment received power from a second LISN supplying power of 110VAC/60Hz.
- 6) The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum analyzer connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to analyzer and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the analyzer.
- 7) Analyzer scanned from 150kHz to 30MHz for emissions in each of the test modes. Analyzer settings were stated on the Measuring Instrument Settings page.
- 8) During the above scans, the emissions were maximized by cable manipulation.
- 9) The following test mode(s) were scanned during the preliminary test:

Mode(s):

1. 800 x 600
2. 640 x 480

- 10) After the preliminary scan, we found the following test mode(s) producing the highest emission level.

Mode: 1

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

MEASUREMENT PROCEDURE (FINAL LINE CONDUCTED EMISSION TEST)

- 1) EUT and support equipment was set up on the test bench as per step 10 of the preliminary test.
- 2) A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less -2dB to the A.V. limit in peak mode, then the emission signal was re-checked using a Quasi-Peak/A.V. detector.
- 3) The test data of the worst case condition(s) was reported on the Summary Data page.

Data Sample:

| Freq. MHz | Q.P. Raw dBuV | Average Raw dBuV | Q.P. Limit dBuV | Average Limit dBuV | Q.P. Margin dB | Average Margin dB | Note |
|--------------|---------------------|------------------------|-----------------------|--------------------------|----------------------|-------------------------|------|
| x.xx | 43.95 | --- | 56 | 46 | -12.05 | --- | L 1 |

- Freq. = Emission frequency in MHz
- Raw dBuV = Uncorrected Analyzer/Receiver reading
- Limit dBuV = Limit stated in standard
- Margin dB = Reading in reference to limit
- Note = Current carrying line of reading
- “---“ = The emission level complied with the Average limits, with at least 2 dB margin, so no further recheck.

LINE CONDUCTED EMISSION LIMIT

| Frequency | Maximum RF Line Voltage | |
|---------------|-------------------------|-----------|
| | Q.P. | AVERAGE |
| 150kHz-500kHz | 66-56dBuV | 56-46dBuV |
| 500kHz-5MHz | 56dBuV | 46dBuV |
| 5MHz-30MHz | 60dBuV | 50dBuV |

Note: The lower limit shall apply at the transition frequency.

MEASUREMENT PROCEDURE (PRELIMINARY RADIATED EMISSION TEST)

- 1) The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden turntable with a height of 0.8 meters is used which is placed on the ground plane as per ANSI C63.4: 1992 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2) Support equipment, if needed, was placed as per ANSI C63.4: 1992.
- 3) All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4: 1992.
- 4) The EUT received 115VAC/60Hz power source from the outlet socket under the turntable. All support equipment received 110VAC/60Hz power from another socket under the turntable.
- 5) The antenna was placed at some given distance away from the EUT as stated in ANSI C63.4: 1992. The antenna connected to the analyzer via a cable and at times a pre-amplifier would be used.
- 6) The analyzer quickly scanned from 30MHz to 1000MHz. Analyzer settings were stated on the Measuring Instrument Settings page. The EUT test program was started. Emissions were scanned and measured rotating the EUT to 360 degrees and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.
- 7) The following test mode(s) were scanned during the preliminary test:
Mode(s):
 1. 800 x 600
 2. 640 x 480
- 8) After the preliminary scan, we found the following test mode(s) producing the highest emission level.

Mode: 1

Then, the EUT and cable configuration, antenna position, polarization and turntable position of the above highest emission level were recorded for reference of final testing.

MEASUREMENT PROCEDURE (FINAL RAIDATED EMISSION TEST)

- 1) EUT and support equipment were set up on the turntable as per step 8 of the preliminary test.
- 2) The analyzer scanned from 30MHz to 1000MHz. Emissions were scanned and measured rotating the EUT to 360 degrees, varying cable placement and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.
- 3) Recorded at least the six highest emissions. Emission frequency, amplitude, antenna position, polarization and turntable position were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit , and only Q.P. reading will record in this report.
- 4) The test data of the worst case condition(s) was reported on the Summary Data page.

Data Sample:

| Freq. (MHz) | Raw Data (dB) | Corr. Factor (dBuV) | Emiss. Level (dBuV/m) | Limits | Margin (dB) |
|----------------|-----------------------|---------------------------|-------------------------------|--------|----------------|
| xx.xx | 14.0 | 11.2 | 26.2 | 30 | -3.8 |

| | |
|---------------------|---|
| Freq. | = Emission frequency in MHz |
| Raw Data (dB) | = Uncorrected Analyzer / Receiver reading |
| Corr. Factor (dBuV) | = Correction factors of antenna factor and cable loss |
| Emiss. Level | = Raw reading converted to dBuV and CF added |
| Limit dBuV/m | = Limit stated in standard |
| Margin dB | = Reading in reference to limit |

RADIATED EMISSION LIMIT

| Frequency (MHz) | Distance (m) | Maximum Field Strength Limit (dBuV/m/ Q.P.) |
|--------------------|-----------------|--|
| 30-230 | 10 | 30 |
| 230-1000 | 10 | 37 |

Note: The lower limit shall apply at the transition frequency.

SUMMARY DATA

(LINE CONDUCTED TEST)

Model Number: 104TVA

Location: Site # 3

Tested by: Michael Chen

Test Mode: 800 x 600

Test Results: Passed

Temperature: 24°C

Humidity: 60%RH

(The chart below shows the highest readings taken from the final data)

| | | | | | | | |
|--------|------|-----|------|------|-------|-----|----|
| 0.215 | 38.3 | --- | 63.0 | 53.0 | -24.7 | --- | L1 |
| 0.325 | 29.3 | --- | 59.5 | 49.5 | -30.2 | --- | L1 |
| 0.760 | 28.9 | --- | 56.0 | 46.0 | -27.1 | --- | L1 |
| 1.630 | 31.0 | --- | 56.0 | 46.0 | -25.0 | --- | L1 |
| 2.390 | 31.1 | --- | 56.0 | 46.0 | -24.9 | --- | L1 |
| 25.520 | 30.4 | --- | 60.0 | 50.0 | -29.6 | --- | L1 |
| 0.220 | 40.6 | --- | 62.8 | 52.8 | -22.2 | --- | L2 |
| 0.325 | 31.8 | --- | 59.5 | 49.5 | -27.7 | --- | L2 |
| 0.435 | 29.1 | --- | 57.1 | 47.1 | -28.0 | --- | L2 |
| 1.090 | 28.9 | --- | 56.0 | 46.0 | -27.1 | --- | L2 |
| 2.400 | 29.1 | --- | 56.0 | 46.0 | -26.9 | --- | L2 |
| 26.210 | 28.1 | --- | 60.0 | 50.0 | -31.9 | --- | L2 |

L1 = Line One (Hot side) / L2 = Line Two (Neutral side)

****NOTE:** "—" denotes the emission level was or more than 2dB below the Average limit, so no re-check anymore.


C&C Lab. Conduction Test Site 3

FCC Class B

EUT: 104TVA
Manuf: GRANDVIEW
Op Cond: 800*600
Operator: Michael Chen
Test Spec: LISN=L1
Comment: 115VAC/60HZ
File name: CISPR22B.SPC
Date: 12. Jul 99 14:44

Scan Settings (1 Range)

| Frequencies | | | Receiver Settings | | | | |
|-------------|------|------|-------------------|----------|--------|-------|--------|
| Start | Stop | Step | IF BW | Detector | M-Time | Atten | Preamp |
| 150k | 30M | 5k | 9k | PK | 20ms | 0dBLN | OFF |



C&C Lab. Co.

File No: 00009 T


C&C Lab. Conduction Test Site 3

FCC Class B

EUT: 104TVA
Manuf: GRANDVIEW
Op Cond: 800*600
Operator: Michael Chen
Test Spec: LISN=N
Comment: 115VAC/60HZ
File name: CISPR22B.SPC
Date: 13. Jul 99 14:32

Scan Settings (1 Range)

| Frequencies | | | Receiver Settings | | | | |
|-------------|------|------|-------------------|----------|--------|-------|--------|
| Start | Stop | Step | IF BW | Detector | M-Time | Atten | Preamp |
| 150k | 30M | 5k | 9k | PK | 20ms | 0dB | OFF |



C&C Lab. Co.

File No: 990709-F

SUMMARY DATA

(RADIATED EMISSION TEST)

Model Number: 104TVA

Location: Site # 3

Tested by: Michael Chen

Polar: Vertical -- 10m

Test Mode: 800 x 600

Test Results: Passed

Temperature: 25°C

Humidity: 60%RH

(The chart below shows the highest readings taken from the final data)

| Freq. (MHz) | Raw Data (dB) | Corr. Factor (dBuV) | Emiss. Level (dBuV/m) | Limits | Margin (dB) |
|----------------|-----------------------|---------------------------|-------------------------------|--------|----------------|
| 39.26 | 10.8 | 14.6 | 25.4 | 30.0 | -4.6 |
| 131.82 | 11.8 | 14.6 | 26.4 | 30.0 | -3.6 |
| 156.09 | 12.8 | 13.8 | 26.6 | 30.0 | -3.4 |
| 206.46 | 13.4 | 12.8 | 26.2 | 30.0 | -3.8 |
| 221.47 | 11.3 | 14.1 | 25.4 | 30.0 | -4.6 |
| 479.09 | 9.9 | 22.6 | 32.5 | 37.0 | -4.5 |

SUMMARY DATA

(RADIATED EMISSION TEST)

Model Number: 104TVA

Location: Site # 3

Tested by: Michael Chen

Polar: Horizontal -- 10m

Test Mode: 800 x 600

Test Results: Passed

Temperature: 25°C

Humidity: 60%RH

(The chart below shows the highest readings taken from the final data)

| Freq. (MHz) | Raw Data (dB) | Corr. Factor (dBuV) | Emiss. Level (dBuV/m) | Limits | Margin (dB) |
|----------------|-----------------------|---------------------------|-------------------------------|--------|----------------|
| 130.93 | 10.9 | 14.7 | 25.6 | 30.0 | -4.4 |
| 181.27 | 12.1 | 12.8 | 24.9 | 30.0 | -5.1 |
| 206.50 | 13.6 | 12.4 | 26.0 | 30.0 | -4.0 |
| 208.96 | 10.4 | 12.8 | 23.2 | 30.0 | -6.8 |
| 221.61 | 11.0 | 14.6 | 25.6 | 30.0 | -4.4 |
| 508.50 | 7.8 | 23.8 | 31.6 | 37.0 | -5.4 |

APPENDIX 1

LETTER OF AGENT AUTHORIZATION


Federal Communications Commission
Authorization and Evaluation Division
7435 Oakland Mills Road
Columbia, MD 21046
U.S.A

Gentlemen,

We the undersigned, hereby authorized C&C Laboratory Co., Ltd. to act on our behalf in all matters relating to applications for equipment authorizations, including the signing of all documents relating to these matters. Any and all acts carried out by C&C Laboratory Co., Ltd. on our behalf shall have the same effect as acts of our own.

The applicant certifies that, in the case of an individual applicant is not subject to a denial of federal benefits, that includes FCC benefits, pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 853 (a) , in the case of a non-individual applicant (e.g. corporation, partnership or other unincorporated association) , no party to the application is subject to a denial of federal benefits, that includes FCC benefits, pursuant to that section.

Sincerely yours,



Lydon Lee / Assistant Section Manager

CH-3 OSD

Main items

Sub-items & Adjustment

| | | | |
|----------|----------------------|---|---|
| Page 1/3 | Brightness | : | Adjust intensity of white light. |
| | Contrast | : | Adjust the ratio of white to black ☞ Intensity : White vs. Black |
| | R contrast | : | Adjust gain of red color. |
| | G contrast | : | Adjust gain of green color. |
| | B contrast | : | Adjust gain of blue color. |
| Page 2/3 | H. Position | : | Adjust horizontal position. |
| | V. Position | : | Adjust vertical position. |
| | Frequency | : | Adjust vertical flicker. |
| | Phase | : | Adjust horizontal flicker. |
| | Track | : | Fine adjusting horizontal flicker. |
| | Text/Graphics | : | For DOS / Windows. |
| | Expansion | : | Enlarge the display size. |
| Page 3/3 | Display Mode / Freq. | : | Display the resolution, H/V frequency. |
| | ROM/RAM Version | : | ROM : Version of F/W. RAM : Version of factory setting. |
| | Load Mode | : | Recall factory setting for current Timing. |
| | Load Default | : | Recall factory setting for all Timing. |

- ☞ Auto save after adjusting OSD.
OSD Auto disappear after 20 seconds if no operation.

Appendix B Timing Table

| No. | Resolution | Horizontal Frequency (KHz) | Vertical Frequency (Hz) | Pixel Frequency (MHz) | Type |
|-----|------------|----------------------------|--------------------------|-----------------------|--------------|
| 1 | 640x350 | 31.469 | 70.087 | 25.175 | IBM |
| 2 | 640x350 | 37.581 | 84.135 | 31.500 | VESA |
| 3 | 640x400 | 31.500 | 70.150 | 25.197 | NEC PC9821 |
| 4 | 640x400 | 37.861 | 84.136 | 31.500 | VESA GRAPH |
| 5 | 640x480 | 31.469 | 59.940 | 25.175 | IBM |
| 6 | 640x480 | 35.000 | 66.667 | 30.240 | Apple MacII |
| 7 | 640x480 | 37.861 | 72.809 | 31.500 | IBM/VESA |
| 8 | 640x480 | 37.500 | 75.000 | 31.500 | VESA |
| 9 | 640x480 | 43.269 | 85.008 | 36.000 | VESA |
| 10 | 720x400 | 31.469 | 70.087 | 28.322 | VESA-TEXT |
| 11 | 720x400 | 37.736 | 84.045 | 36.000 | VESA |
| 12 | 832x624 | 49.730 | 74.550 | 57.283 | Apple Mac-16 |
| 13 | 800x600 | 35.156 | 56.250 | 36.000 | IBM/VESA |
| 14 | 800x600 | 37.879 | 60.300 | 40.000 | VESA |
| 15 | 800x600 | 48.077 | 72.188 | 50.000 | VESA |
| 16 | 800x600 | 46.875 | 75.000 | 49.500 | VESA |
| 17 | 800x600 | 53.674 | 85.061 | 56.250 | VESA |

Appendix A Specification

RGB Only

| | |
|-----------------------------|---|
| Pixel Pitch | 0.33x0.33 mm |
| Max. Resolution | (1).640x480 (2).800x600 (3).640x480 |
| Max Pixel Rate | 60 MHz |
| Display area | 211.2x158.4 mm |
| Color | 262,144 |
| Contrast Ratio | 100:1 |
| Brightness | 250,250,300 cd/m ² |
| Response Time (Tr/Tf) | (1). 50/50 (2). 50/50 (3). 20/40 ms |
| View angle (L/R/T/B) | (1). 20/-10/30/-30 (2). 20/-10/30/-30 (3). 70/-70/40/-70 |
| Backlight | 2 CCFT |
| Lamp Life | 25000 hrs |
| Input Signal | Analog RGB 0.7 Vp-p/75 Ω |
| Scan frequency | H : 31 ~ 53 KHZ V : 55 ~ 85 Hz |
| OSD Control for RGB Signal | Page 1 : Brightness, Contrast, R Contrast, G Contrast, B Contrast Page 2 : H Position, V Position, Frequency, Phase, Track Text/Graphics, Expansion Page 3 : Display Mode/Freq. , ROM/RAM Version Lode mode, Lode default |
| Plug&Play | DDC1 / DDC2B |
| Power Management | VESA DPMS |
| Compatibility of PC | VGA, SVGA, MACII, PC98 |
| Input | AC 90-264V, 50-60Hz |
| Output | DC 12V / 3A |
| Power Consumption | 18 W / Standby 4W |
| Operation Environment | Temperature 0~40 °C Humidity : Less than 85% |
| Dimension (WxHxD), w/ stand | 312x236x73 mm |
| Weight (w/ Stand) | 1.7~1.9Kg (w/ Triangle Stand) |
| Wall Mount (Built-in) | Yes |
| Terminal | VGA, DC-in RS232 (Optional for Touch panel) |
| Buttons on front panel | Power, Menu , Sel , Up, Down LED |
| Package | Adapter, Power cord, VGA cable User Manual, Warranty Card |
| Safety&EMI | UL/cUL, TUV/Rh-GS, TUV/CB, FCC-B, CE |

* Specifications are subject to change without Notice.

APPENDIX 6

TEST FACILITY

TEST FACILITY

Location: No. 15, 14 Line, Chin Twu Chi, Lu Chu Hsiang, Taoyuan, Taiwan, R.O.C.

Description: There are two 3/10m open area test sites and two line conducted labs for final test, and one 3/10m open area test site for engineering lab. The Open Area Test Sites and the Line Conducted labs are constructed and calibrated to meet the FCC requirements in documents ANSI C63.4: 1992 and CISPR 22/EN 55022 requirements.

Site Filing: A site description is on file with the Federal Communications Commission, 7435 Oakland Mills Road, Columbia, MD 21046.

Registration also was made with Voluntary Control Council for Interference (VCCI).


Site Accreditation: Accredited by NEMKO (Authorization #: ELA 124) for EMC & A2LA (Certificate #: 824.01) for Emission

Instrument Tolerance: All measuring equipment is in accord with ANSI C63.4 and CISPR22 requirement that meet industry regulatory agency and accreditation agency requirement.

Ground Plane: Two conductive reference ground planes were used during the Line Conducted Emission, one in vertical and the other in horizontal. The dimensions of these ground planes are as below. The vertical ground plane was placed distancing 40 cm to the rear of the wooden test table on where the EUT and the support equipment were placed during test. The horizontal ground plane projected 50 cm beyond the footprint of the EUT system and distanced 80 cm to the wooden test table. For Radiated Emission Test, one horizontal conductive ground plane extended at least 1m beyond the periphery of the EUT and the largest measuring antenna, and covered the entire area between the EUT and the antenna. It has no holes or gaps having longitudinal dimensions larger than one-tenth of a wavelength at the highest frequency of measurement up to 1GHz.

Site #1 and # 3 Line Conducted Test Site: Vertical ground plane (2.2m x 2.2m)
Horizontal ground plane (2.5m x 2.5m)

Site #4 Line Conducted Test Site: At Shielding Room



**THE AMERICAN
ASSOCIATION
FOR LABORATORY
ACCREDITATION**

ACCREDITED LABORATORY

A2LA has accredited

C & C LABORATORY CO., LTD
Taoyuan, Taiwan, R.O.C


for technical competence in the field of

Electrical (EMC) Testing

The accreditation covers the specific tests and types of tests listed on the agreed scope of accreditation. This laboratory meets the requirements of ISO/IEC Guide 25-1990 "General Requirements for the Competence of Calibration and Testing Laboratories" (equivalent to relevant requirements of the ISO 9000 series of standards) and any additional program requirements in the identified field of testing.

Presented this 7th day of November, 1997.





President
For the Accreditation Council
Certificate Number 824.04
Valid to January 31, 2000

For tests or types of tests to which this accreditation applies, please refer to the
laboratory's Electrical (EMC) Scope of Accreditation
(REVISED)



American Association for Laboratory Accreditation

SCOPE OF ACCREDITATION TO ISO/IEC GUIDE 25-1990 and EN 45001-1989

C & C LABORATORY CO., LTD
No. 15, 14 Lin, Chin Twu Chi
Lu Chu Hsiang, Taoyuan, TAIWAN, R.O.C.
Charles Wang Phone: 002 886 3 324 5966
Fax: 002 886 3 324 5235

ELECTRICAL (EMC)

Valid to: January 31, 2000

Certificate Number: 0824-01

In recognition of the successful completion of the A2LA evaluation process, accreditation is granted to this laboratory to perform the following tests:

Electrical Emissions – Enclosure – 3 & 10 Meters; to 6.5 GHz (Sites 1, 3 and 4)
Electrical Emissions – AC Power – 0 - 300 V; 50 - 400 Hz (Sites 1, 3 and 4)
Electrical Immunity – Enclosure – 27 - 80 MHz / 3V/m; 80 MHz - 1 GHz / 10V/m
Electrical Immunity – AC Power, DC Power, Signal & Control
Electrical Fast Transient (EFT)
Electrostatic Discharge (ESD) to 16 kV
Electrical Power Surge
Power Magnetic Field Immunity
Voltage Dips, Shots, Variations

On the following products/equipment:

Computer Components and Peripherals; Networking Components; Wireless Communications Components; Electronic Components; Televisions; Home Appliances

Using the following test methods/specifications/standards:

Code of Federal Regulations (CFR) 47, FCC Part 15 using ANSI C63.4
AS/NZS 3548
BSMI CNS: 13438, 13439, 13783, 13803
CISPR: 11, 14, 22
EN: 50081-1, 50082-1, 55011, 55022, 55014, 61000-4-2, 61000-4-3, 61000-4-4, 61000-4-5, 61000-4-6, 61000-4-8, 61000-4-11
VCCI V3
IEC: 801-2, 801-3, 801-4

Peter Abney
Revised 03/05/99



EMC Laboratory Authorization

Aut. No. : ELA 124

EMC Laboratory:

C&C Laboratory Taiwan

No. 28 Wen-Hwa Street, 330 Taoyuan

TAIWAN R.O.C.

Scope of Authorization:

The authorization covers the following standards:

EN 50081-1

EN 50082-1

EN 55022

IEC 801-2

EN 60555-2,-3

IEC 801-3

EN 61000-3-2

IEC 801-4

EN 61000-3-3

EN 61000-4-2

EN 61000-4-3

EN 61000-4-4

This is to confirm that the abovementioned EMC Laboratory has been authorized according to the conditions described in Nemko Document ELA 10.

During Nemko's visit to the laboratory on the 08. October. 1997 an assessment was made of your facilities, qualifications and testing practices, and the relevant part of your organization. It was found that the EMC Laboratory is capable of performing tests within the scope mentioned above, accordingly, Nemko will accept your test results as a basis for attesting conformity with these EMC Standards for the products in question.


In case of product certification, your test report may be used by the applicant manufacturer, enclosed to his application.

In order to maintain the authorization, the information given in the enclosed ELA-INFOs has to be carefully followed. Nemko is to be promptly notified about any changes in the situation at your laboratory which may affect the basis for this authorization. The authorization may at any time be withdrawn if the conditions are no longer considered to be fulfilled.

The authorization is issued on the conditions that you have signed the "Statement by Authorization", ELA 3A-Form. The Statement of 08 October. 1997 is binding.

Oslo, 20. October. 1997

For Nemko as



Kjell Bergh, Head of EMC Section

附件如文

呈送件

經濟部商品檢驗局(函)

中華民國八十七年 壹月 貳拾日

受文者：程智科技股份有限公司

檢台八十七字第 90136 號

行文單位：正本：程智科技股份有限公司

副本：本局第二組(二份)、第三組、秘書室(抽四種請刊載於檢驗雜誌)、資訊室(請刊載於網際網路)、檢驗處、各分局(均無附件)

主旨：有關 貴公司電磁相容檢測實驗室申請本局電磁相容檢測領域認可案，業經實地評鑑結果，同意認可登錄，請 查照。

說明：

一、認可登錄範圍如下：

實驗室名稱：程智科技股份有限公司電磁相容檢測實驗室

實驗室地址：桃園縣蘆竹鄉永安村14鄰15號

| 認可代號 | 認可產品類別 | 報告簽署人 |
|----------|----------------------|-------|
| SL-EM-14 | (II) 資訊設備 (CNS13438) | 林淑女 |

評鑑標準：ISO Guide 25 (1998年版)

二、本案評核認可期限三年，自八十七年元月十七日起至九十年元月十六日止，評核追查頻率每年乙次，得視需要增加稽查次數。

三、上開已認可領域如有變更事項，請於變更日起二週內函送相關資料至本局辦理。

四、貴公司執行本局指定之檢驗業務，依「商品檢驗法」第二十六條規定以執行公務論，且 貴公司應依規定履行相關之責任與義務。

五、檢送「商品電磁相容型式試驗報告」格式乙份，請自行印製使用

經濟部商品檢驗局(印)

局長 陳佐鎮

依照分層負責規定授權單位主管執行

經濟部標準檢驗局 函

機關地址：台北市濟南路一段四號
傳 真：(02)二二九九三三二二四

受文者：程智科技股份有限公司
(台北市富錦街211號二樓)

速別：

密等及解密條件：

發文日期：中華民國八十八年五月二十一日

發文字號：標檢(八八)三字第一二二二五號

附件：

主旨：貴公司電磁相容試驗室申請增列「家用電器產品」檢測領域及新增測試場地(Site 2)認可案，經實地評鑑結果，同意認可登錄，實驗室登錄號碼為「SI2A1-E-14」。
請查照。

說明：依據本局檢測實驗室評核缺點總結報告辦理。

正本：程智科技股份有限公司(台北市富錦街211號二樓)

副本：本局第五組、秘書室(秘四科)、第六組、各分局、第三組

局長 陳佐鎮

監印 楊淑女
校對 程九如

FEDERAL COMMUNICATIONS COMMISSION
Equipment Authorization Division
7435 Oakland Mills Road
Columbia, MD. 21046

February 01, 1999

Registration Number: 93105

C & C Laboratory Co., Ltd.
1st FL, No. 344, Fu Ching Street
Taipei
Taiwan, R.O.C.

Attention: Charles Wang


Re: Measurement facility located at Taoyuan, Site No. 4
3 & 10 meters
Date of Listing: February 01, 1999

Gentlemen:

Your submission of the description of the subject measurement facility has been reviewed and found to be in compliance with the requirements of Section 2.948 of the FCC Rules. The description has, therefore, been placed on file and the name of your organization added to the Commission's list of facilities whose measurement data will be accepted in conjunction with applications for Certification under Parts 15 or 18 of the Commission's Rules. Please note that this filing must be updated for any changes made to the facility, and at least every three years from the date of listing the data on file must be certified as current.

If requested, the above mentioned facility has been added to our list of those who perform these measurement services for the public on a fee basis. An up-to-date list of such public test facilities is available on the Internet on the FCC Website at WWW.FCC.GOV, Electronic Filing, OET Equipment Authorization Electronic Filing.

Sincerely,



Thomas W Phillips
Electronics Engineer

FEDERAL COMMUNICATIONS COMMISSION

7435 Oakland Mills Road
Columbia, MD 21046
Telephone: 301-725-1585 (ext-218)
Facsimile: 301-344-2050

April 20, 1998

IN REPLY REFER TO
31040/SIT
1300F2

C&C Laboratory Co., Ltd.
1st Fl., No. 344, Fu Ching Street
Taipei, Taiwan

Attention: Charles Wang

Re: Measurement facility located at Taoyuan, Site No. 3
(3 and 10 meter site)

Gentlemen:

Your submission of the description of the subject measurement facility has been reviewed and found to be in compliance with the requirements of Section 2.948 of the FCC Rules. The description has, therefore, been placed on file and the name of your organization added to the Commission's list of facilities whose measurement data will be accepted in conjunction with applications for certification or notification under Parts 15 or 18 of the Commission's Rules. Our list will also indicate that the facility complies with the radiated and AC line conducted test site criteria in ANSI C63.4-1992. Please note that this filing must be updated for any changes made to the facility, and at least every three years the data on file must be certified as current.

Per your request, the above mentioned facility has been also added to our list of those who perform these measurement services for the public on a fee basis. This list is updated monthly and is available on the Laboratory's Public Access Link (PAL) at 301-725-1072, and also on the Internet at the FCC Website www.fcc.gov/oet/info/database/testsite/.

Sincerely,



Thomas W. Phillips
Electronics Engineer
Customer Service Branch

FEDERAL COMMUNICATIONS COMMISSION

7435 Oakland Mills Road
Columbia, MD 21046
Telephone: 301-725-1585 (ext-218)
Facsimile: 301-344-2050

March 13, 1998

IN REPLY REFER TO
31040/SIT
1300F2

C & C Laboratory Co., Ltd.
1st Fl., No. 344, Fu Ching Street
Taipei, Taiwan

Attention: Ceres Lin

Re: Measurement facility located at Taoyuan
(3 and 10 meter site)

Gentlemen:

Your submission of the description of the subject measurement facility has been reviewed and found to be in compliance with the requirements of Section 2.948 of the FCC Rules. The description has, therefore, been placed on file and the name of your organization added to the Commission's list of facilities whose measurement data will be accepted in conjunction with applications for certification or notification under Parts 15 or 18 of the Commission's Rules. Our list will also indicate that the facility complies with the radiated and AC line conducted test site criteria in ANSI C63.4-1992. Please note that this filing must be updated for any changes made to the facility, and at least every three years the data on file must be certified as current.

Per your request, the above mentioned facility has been also added to our list of those who perform these measurement services for the public on a fee basis. This list is updated monthly and is available on the Laboratory's Public Access Link (PAL) at 301-725-1072, and also on the Internet at the FCC Website www.fcc.gov/oet/info/database/testsite/.

Sincerely,



Thomas W. Phillips
Electronics Engineer
Customer Service Branch



MINISTRY OF COMMERCE
Te Manatū Tauhokohoko

ENG 3/9
AJD

22 January 1998

C & C Laboratory Co Ltd
1st Fl
No. 344
Fu Ching Street
Taipei
TAIWAN ROC

Attention: Mr Tony Houng

Dear Sir

LABORATORY APPROVAL

Thank you for your submission of 21 January regarding the approval of your testing laboratory to the Ministry of Commerce's laboratory approval criteria. Thank you for your interest in this matter.

I am pleased to advise that your submission has been successful and your laboratory has been added to the list of Ministry-approved laboratories. Your approved status is valid until 31 December 1998. At this time, the Approved Laboratory scheme will cease operation with the implementation of the new radiocommunications regulations. Test reports from your laboratory will be accepted under the new framework. Please find enclosed a copy of the Ministry's discussion paper, DP10, outlining the proposed compliance process from 1 January 1999.

If you have any further questions on this matter please do not hesitate to contact me.

Yours faithfully

Andrew Dyke
Senior Technical Officer(Regulatory)



CERTIFICATE

Company : C&C Laboratory Co., Ltd.

Facility : C&C Open Area Test Site No.1

(Conducted Interference Measurement)

Address : No.15, 14 Lin, Chin Twu Chi,

Lu Chu Hsiang Taoyuan Shien, Taiwan

*This is to certify that the following measuring facility
has been registered in accordance with the Regulations
for Voluntary Control Measures*


Registration No. : C-402

Date of Registration : July 1, 1999

This Certificate is valid until September 30, 2002

Voluntary Control Council for Interference by

Information Technology Equipment





CERTIFICATE

Company : C&C Laboratory Co., Ltd.

Facility : C&C Open Area Test Site No.1

(Radiation 3 and 10 meter site)

Address : No.15, 14 Lin, Chin Twu Chi,

Lu Chu Hsiang Taoyuan Shien, Taiwan


*This is to certify that the following measuring facility
has been registered in accordance with the Regulations
for Voluntary Control Measures*

Registration No. : R-393

Date of Registration : July 1, 1999

This Certificate is valid until September 30, 2002

*Voluntary Control Council for Interference by
Information Technology Equipment*





CERTIFICATE

F a c i l i t y : C&C Conducted Interference Test Site No.3

(Conducted Interference Measurement)

Company : C&C Laboratory Co., Ltd.

Address : No.15, 14Lin, Chin Twu Chi, Lu Chu Hsiang Taoyuan Shien


*This is to certify that the following measuring facility
has been registered in accordance with the Regulations
for Voluntary Control Measures.*

Registration No. : C-747

Date of Registration : May 1, 1998

This Certificate is valid until June 30, 2001

***Voluntary Control Council for Interference by
Information Technology Equipment***





CERTIFICATE

Facility : C&C Open Area Test Site No.3

(Radiation 3 and 10 meter site)

Company : C&C Laboratory Co., Ltd.

Address : No.15, 14Lin, Chin Twu Chi, Lu Chu Hsiang Taoyuan Shien


*This is to certify that the following measuring facility
has been registered in accordance with the Regulations
for Voluntary Control Measures.*

Registration No. : R-725

Date of Registration : May 1, 1998

This Certificate is valid until June 30, 2001

***Voluntary Control Council for Interference
Information Technology Equipment***





CERTIFICATE

Company : C&C Laboratory Co., Ltd.

**Facility : C&C Conducted Interference Test Site No.4
(Conducted Interference Measurement)**

Address : No.15, 14 Lin, Chin Twu Chi, Lu Chu Hsiang Taoyuan Shien, Taiwan


*This is to certify that the following measuring facility
has been registered in accordance with the Regulations
for Voluntary Control Measures*

Registration No. : C-912

Date of Registration : March 26, 1999

This Certificate is valid until March 31, 2002

*Voluntary Control Council for Interference by
Information Technology Equipment*





CERTIFICATE

Company : C&C Laboratory Co., Ltd.

Facility : C&C Open Area Test Site No.4

(Radiation 3 and 10 meter site)

Address : No.15, 14 Lin, Chin Twu Chi, Lu Chu Hsiang Taoyuan Shien, Taiwan


*This is to certify that the following measuring facility
has been registered in accordance with the Regulations
for Voluntary Control Measures*

Registration No. : R-879

Date of Registration : March 26, 1999

This Certificate is valid until March 31, 2002

*Voluntary Control Council for Interference by
Information Technology Equipment*





中華民國實驗室認證體系認可證書

Chinese National Laboratory Accreditation Certificate ROC


No.CNLA-ZL98078

Page 1 of 4

茲以 程智科技股份有限公司程智科技電磁相容實驗室之電性測試領域經評鑑認可

十項發給本證書有效期限至九十年十一月十四日 此證

This is to certify that C & C Laboratory Co., Ltd. has been recognized by the Council of Chinese National Laboratory Accreditation as an accredited laboratory. The laboratory has been registered for ten specific tests within the field of Electrical Testing. The details of the scope of accreditation is described in the following pages and this Certificate is valid until Nov. 14, 2001.



中華民國實驗室認證委員會
主任

Chen, Ming-Bang

The Chairman of Chinese National Laboratory Accreditation Council

中華民國 八十七年十一月十五日

(本證書共 4 頁分發使用為宜 This document is invalid unless accompanied by all 4 pages.)


19

機構名稱 : 程智科技股份有限公司
 實驗室名稱 : 程智科技電腦相容實驗室
 認可編號 : 0363
 實驗室負責人 : 王耀義
 測試領域 : 電性測試
 證書領日期 : 1998.11.15


Organization : C & C Laboratory Co., Ltd.
 Laboratory : C & C Laboratory Co., Ltd.
 Registration : 0363
 Laboratory Head : WANG, Chiahs
 Testing Field : Electrical Testing
 Date of Registration: 1998.11.15

| 認可項目 Registration items | 測試件 Test items | 測試方法 Test methods | 範圍 Range | 認可之最佳測試能力 Best test capability recognized | 備註 Remarks |
|---|--|---|--|--|---------------|
| J0102 谐波电流干擾 harmonic current emissions | 資訊類及其週邊產品 ITE and peripheral Products | RFC 1000-3-2(1995) EN 61000-3-2(1995) | 電壓: 100~240VAC(單相) 電流: 0~16 電阻: 1~40 | | |
| J0103 電壓變動與閃爍干擾 voltage fluctuations and flicker | 資訊類及其週邊產品 ITE and peripheral Products | RFC 1000-3-3(1994) EN 61000-3-3(1995) | 電壓: 100~240VAC(單相) 電流: 1~16 A | | |
| J0122 電信及資訊技術系統及儀器 systems and apparatus of the telecommunication and | 資訊類及其週邊產品 ITE and peripheral Products | CISPR 22(1996) EN 55022(1995) CNS 13098(1997) AS/NZS 3548(1995) VCCI(1997) ROE Part 15(1996) | 電磁干擾: 150 kHz~30 MHz 電靜干擾: 30 MHz~1.0 GHz | | |
| | | | 電磁干擾: 450 kHz~30 MHz 電靜干擾: 30 MHz~2.0 GHz | | |

| 認可項目 Registration items | 測試件 Test items | 測試方法 Test methods | 範圍 Range | 認可之最佳測試能力 Best test capability recognized | 備註 Remarks |
|---|--|---|--|--|---------------|
| information technology EJ0202 靜電放電測試 Electrostatic discharge tests | 資訊類及其周邊產品 ITE and peripheral Products | IEC 6100-4-2(1995) EN 6100-4-2(1995) CNS 6100-4(1992) | IEC 6100-4-2 EN 6100-4-2 CNS 6100-4 | IEC 6100-4-2 EN 6100-4-2 CNS 6100-4 | |
| EJ0203 輻射耐受測試 Radiated susceptibility tests | 資訊類及其周邊產品 ITE and peripheral Products | IEC 60813 IEC 60813-2 EN 60813-2 EN 50204(1995) | IEC 60813 IEC 60813-2 EN 60813-2 EN 50204 | IEC 60813 IEC 60813-2 EN 60813-2 EN 50204 | |
| EJ0204 電性快速突波測試 Electrical fast transient/burst tests | 資訊類及其周邊產品 ITE and peripheral Products | IEC 6100-4-6(1995) IEC 6100-4-6(1995) EN 6100-4-6(1995) CNS 6100-4-6(1992) | IEC 6100-4-6 EN 6100-4-6 CNS 6100-4-6 | IEC 6100-4-6 EN 6100-4-6 CNS 6100-4-6 | |
| EJ0205 突波/雷擊測試 Surge/lightening tests | 資訊類及其周邊產品 ITE and peripheral Products | IEC 6100-4-5(1995) EN 6100-4-5(1995) CNS 6100-4-5(1992) | IEC 6100-4-5 EN 6100-4-5 CNS 6100-4-5 | IEC 6100-4-5 EN 6100-4-5 CNS 6100-4-5 | |
| EJ0206 傳導耐受測試 Conducted susceptibility tests | 資訊類及其周邊產品 ITE and peripheral Products | IEC 6100-4-6(1995) EN 6100-4-6(1995) | IEC 6100-4-6 EN 6100-4-6 | IEC 6100-4-6 EN 6100-4-6 | |
| EJ0208 電源線率磁場耐受 | 資訊類及其周邊產品 ITE and peripheral Products | IEC 6100-4-8(1995) EN 6100-4-8(1995) | IEC 6100-4-8 EN 6100-4-8 | IEC 6100-4-8 EN 6100-4-8 | |



NO. CNLA-21-00078

| 認可項目 Registration items | 測試件 Test items | 測試方法 Test methods | 範圍 Range | 認可之最優測試能力 Best test capability recognized | 備註 Remarks |
|---|--|--|---|--|---------------|
| 測試 Power frequency magnetic field immunity test E10211 電壓下降、瞬斷和緩變耐受測試 Voltage dips, short interruptions and voltage variations immunity tests (以下空白) | Products 資訊類及其派生產品 ITE and peripheral Products | TEC 1008-4-11(1994) EN 61000-4-11(1994) |  <p> 認證範圍: 1000% 標準: GB-0-1000% 認證項目: 電壓瞬斷、電壓緩變、電壓下陷、電壓中斷 </p> | | |

APPENDIX 7

TEST EQUIPMENT

MEASURING INSTRUMENT SETTING

| TEST TYPE | DETECTOR | FREQUENCY RANGE | RESOLUTION BANDWIDTH | VIDEO BANDWIDTH |
|-----------|-------------|-----------------|----------------------|-----------------|
| Conducted | Peak/QP/Avg | 150kHz-30MHz | 9kHz | 9kHz |
| Radiated | Peak | 30MHz-1GHz | 100kHz | 100kHz |
| Radiated | QP | 30MHz-1GHz | 120kHz | 120kHz |
| Radiated | Peak/Avg | Above 1GHz | 1MHz | 1MHz |

Note: All readings on data pages are taken with the detector in peak mode unless otherwise stated.

UNITS OF MEASUREMENT

Measurements of radiated interference are reported in terms of dBuV/m, at a specified distance. The indicated readings on the spectrum analyzer are converted to dBuV/m by use of appropriate conversion factors. Measurements of conducted interference are reported in terms of dBuV.

TEST EQUIPMENT LIST

Instrumentation: The following list contains equipment used at C & C Laboratory, Co., Ltd. for testing. The equipment conforms to the American National Standard Specifications for Electromagnetic Interference and Field Strength Instrumentation from 10kHz to 2GHz.

Equipment used during the tests:

Open Area Test Site: # 1; # 3; # 4

| EQUIPMENT TYPE | * MFR | MODEL NUMBER | SERIAL NUMBER | LAST CAL. | CAL. DUE |
|-------------------|---------|--------------|---------------|------------|------------|
| Spectrum Analyzer | HP | 8568B | 3001A05004 | 04/16/1999 | 04/15/2000 |
| S.P.A Display | HP | 85662A | 3104A18846 | 04/16/1999 | 04/15/2000 |
| RF Pre-selector | HP | 85685A | 2947A01064 | 04/16/1999 | 04/15/2000 |
| Q.P Adaptor | HP | 85650A | 2811A01399 | 04/16/1999 | 04/15/2000 |
| Precision Dipole | R&S | HZ-12 | 846932/0004 | 06/16/1999 | 06/16/2000 |
| Precision Dipole | R&S | HZ-13 | 846556/0008 | 06/16/1999 | 06/16/2000 |
| Horn Antenna | EMCO | 3115 | 9602-4659 | 04/04/1999 | 04/04/2000 |
| Bilog Antenna | CHASE | CBL6112A | 2309 | 03/14/1999 | 03/14/2000 |
| Turn Table | EMCO | 2081-1.21 | N/A | N/A | N/A |
| Antenna Tower | EMCO | 2075-2 | 9707-2604 | N/A | N/A |
| Controller | EMCO | 2090 | N/A | N/A | N/A |
| RF Switch | ANRITSU | MP59B | N/A | N/A | N/A |
| Site Information | C&C | N/A | N/A | 01/23/1999 | 01/23/2000 |

| EQUIPMENT TYPE | * MFR | MODEL NUMBER | SERIAL NUMBER | LAST CAL. | CAL. DUE |
|-------------------|-----------|--------------|---------------|------------|------------|
| Spectrum Analyzer | ADVANTEST | R3261C | 71720533 | 10/27/1998 | 10/26/1999 |
| Pre-Amplifier | HP | 8447D | 2944A09173 | 01/28/1999 | 01/27/2000 |
| EMI Test Receiver | R&S | ESVS20 | 838804/004 | 12/12/1998 | 12/11/1999 |
| Precision Dipole | R&S | HZ-12 | 846932/0004 | 06/06/1999 | 06/06/2000 |
| Precision Dipole | R&S | HZ-13 | 846556/0008 | 06/16/1999 | 06/16/2000 |
| Horn Antenna | EMCO | 3115 | 9602-4659 | 04/04/1999 | 04/04/2000 |
| Bilog Antenna | CHASE | CBL6112A | 2179 | 11/14/1998 | 11/14/1999 |
| Turn Table | EMCO | 2081-1.21 | 9709-1885 | N/A | N/A |
| Antenna Tower | EMCO | 2075-2 | 9707-2060 | N/A | N/A |
| Controller | EMCO | 2090 | 9709-1256 | N/A | N/A |
| RF Switch | ANRITSU | MP59B | N/A | N/A | N/A |
| Site Information | C&C | N/A | N/A | 01/31/1999 | 01/31/2000 |

| EQUIPMENT TYPE | * MFR | MODEL NUMBER | SERIAL NUMBER | LAST CAL. | CAL. DUE |
|-------------------|-------------|--------------|---------------|-------------|-------------|
| Spectrum Analyzer | ADVANTEST | R3261C | 81720301 | AUG/19/1998 | AUG/18/1999 |
| Pre-Amplifier | HP | 8447F | 2944A03748 | OCT/22/1998 | OCT/21/1999 |
| EMI Test Receiver | R&S | ESVS10 | 846285/016 | DEC/19/1998 | DEC/18/1999 |
| Turn Table | Chance most | N/A | N/A | N/A | N/A |
| Antenna Tower | Chance most | N/A | N/A | N/A | N/A |
| Controller | Chance most | N/A | N/A | N/A | N/A |
| Bilog Antenna | Chase | CBL 6112B | 2462 | JAN/01/1999 | JAN/01/2000 |
| Site NSA | C&C Lab. | N/A | N/A | DEC/27/1998 | DEC/27/1999 |

Conducted Emission Test Site: # 1 ; # 3 ; # 4

| EQUIPMENT TYPE | * MFR | MODEL NUMBER | SERIAL NUMBER | LAST CAL. | CAL. DUE |
|-------------------|-------|--------------|---------------|------------|------------|
| Spectrum Analyzer | HP | 8568B | 3001A05004 | 04/16/1999 | 04/15/2000 |
| S.P.A Display | HP | 85662A | 3104A18846 | 04/16/1999 | 04/15/2000 |
| RF Pre-selector | HP | 85685A | 2947A01064 | 04/16/1999 | 04/15/2000 |
| Q.P Adaptor | HP | 85650A | 2811A01399 | 04/16/1999 | 04/15/2000 |
| LISN | EMCO | 3825/2 | 9106-1809 | 08/14/1998 | 08/14/1999 |
| LISN | EMCO | 3825/2 | 9106-1810 | 08/14/1998 | 08/14/1999 |

| EQUIPMENT TYPE | * MFR | MODEL NUMBER | SERIAL NUMBER | LAST CAL. | CAL. DUE |
|-------------------|-----------|--------------|---------------|------------|------------|
| Spectrum Analyzer | ADVANTEST | R3261A | 91720031 | 03/25/1999 | 03/24/2000 |
| EMI Test Receiver | R&S | ESHS10 | 843743/015 | 12/09/1998 | 12/08/1999 |
| LISN | R&S | ESH3-Z5 | 848773/014 | 10/22/1998 | 10/21/1999 |
| LISN | EMCO | 3825/2 | 9003-1628 | 04/29/1999 | 04/28/2000 |

| EQUIPMENT TYPE | * MFR | MODEL NUMBER | SERIAL NUMBER | LAST CAL. | CAL. DUE |
|-------------------|-------|--------------|---------------|------------|------------|
| EMI Test Receiver | R&S | ESCS30 | 847793/012 | 12/19/1998 | 12/18/1999 |
| LISN | R&S | ESH2-Z5 | 848773/014 | 12/04/1998 | 12/03/1999 |
| LISN | EMCO | 3825/2 | 9003-1628 | 01/09/1999 | 01/08/2000 |

The calibrations of the measuring instruments, including any accessories that may effect such calibration, are checked frequently to assure their accuracy. Adjustments are made and correction factors applied in accordance with instructions contained in the manual for the measuring instrument.

APPENDIX 8

BLOCK DIAGRAM OF TEST SETUP


System Diagram of Connections between EUT and Simulators

EUT: LCD Monitor

Trade Name: GrandView

Model Number: 104TVA

Power Cord: Unshielded, 1.8m



APPENDIX 9

PHOTOGRAPHS