

FCC ID: OKUBRC17602

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})]^*$

$[\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

$f(\text{GHz})$ is the RF channel transmit frequency in GHz;

Power and distance are rounded to the nearest mW and mm before calculation;

The result is rounded to one decimal place for comparison;

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm

and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

We use 5mm as separation distance to calculate.

Maximum measured transmitter power:

BT DSS:

Transmit Frequency (GHz)	Mode	Max Conducted Power (dBm)	tune up maximum power	Result calculation	1-g SAR
2.402	GFSK	3.999	3dBm-5dBm	0.98	3.0
2.441	GFSK	2.863	2dBm-4dBm	0.78	3.0
2.480	GFSK	2.157	2dBm-4dBm	0.79	3.0
2.402	$\pi/4$ -DQPSK	4.564	3dBm-5dBm	0.98	3.0
2.441	$\pi/4$ -DQPSK	3.439	2dBm-4dBm	0.78	3.0
2.480	$\pi/4$ -DQPSK	2.742	2dBm-4dBm	0.79	3.0
2.402	8DPSK	4.806	3dBm-5dBm	0.98	3.0
2.441	8DPSK	3.528	2dBm-4dBm	0.78	3.0
2.480	8DPSK	2.838	2dBm-4dBm	0.79	3.0

Conclusion:

For the max result : $0.98 \leq 3.0$ for 1-g SAR extremity SAR, No SAR is required.

Signature:



Date: 2015-08-11

NAME AND TITLE (Please print or type): David Lee/Manager

COMPANY (Please print or type): Shenzhen EMTEK Co.,Ltd./Building 69, Majialong Industry Zone, Nanshan District, Shenzhen,Guangdong,China