## FCC ID: OKUCAB36671

## Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] \*  $[\sqrt{f(GHz)}] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR, where

f(GHz) is the RF channel transmit frequency in GHz;

Power and distance are rounded to the nearest mW and mm before calculation;

The result is rounded to one decimal place for comparison:

The test exclusions are applicable only when the minimum test separation distance is  $\leq$  50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion. We use 5mm as separation distance to calculate.

Maximum measured transmitter power:

## BT DSS:

Transmit Frequency (GHz)	Mode	Measured Power (dBm)	Tune-up power (dBm)	Max tune-up	Result calculation	1-g SAR
2.402	GFSK	0.526	0.5±1	1.5	0.438	3
2.441	GFSK	1.353	0.5±1	1.5	0.441	3
2.48	GFSK	0.923	0.5±1	1.5	0.445	3
2.402	π /4-DQPSK	-0.236	0.5±1	1.5	0.438	3
2.441	π /4-DQPSK	0.513	0.5±1	1.5	0.441	3
2.48	π /4-DQPSK	0.678	0.5±1	1.5	0.445	3
2.402	8DPSK	0.489	0.5±1	1.5	0.438	3
2.441	8DPSK	1.273	0.5±1	1.5	0.441	3
2.48	8DPSK	1.066	0.5±1	1.5	0.445	3

## Conclusion:

For the max result : 0.445≤ 3.0 for 1-g SAR extremity SAR, No SAR is required.

Signature: Date: 2016-01-25

NAME AND TITLE (Please print or type): David Lee/Manager

**COMPANY** (Please print or type): EMTEK (Shenzhen) Co., Ltd./Building 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China