

# Maximum Permissible Exposure Report




For

**SHENZHEN JUNLAN ELECTRONIC LTD**

**No. 277 PingKui Road, Shijing Community, Pingshan**

**Street, Pingshan New District, Shenzhen, China**

**FCC ID: OKUSBB-61250**

<b>FCC Rule(s):</b>	<u>FCC 47CFR Part 1.1310</u>
<b>Product Description:</b>	<u>CH BLUETOOTH SOUNDBAR SPEAKER</u>
<b>Tested Model:</b>	<u>SBB-61250</u>
<b>Report No.:</b>	<u>HCT18AR016E-2</u>
<b>Sample Receipt Date:</b>	<u>2018-02-07</u>
<b>Tested Date:</b>	<u>2018-02-08 to 2018-02-27</u>
<b>Issued Date:</b>	<u>2018-02-28</u>
<b>Tested By:</b>	<u>Jason Su / Engineer</u> 
<b>Reviewed By:</b>	<u>Silin Chen / EMC Manager</u> 
<b>Approved &amp; Authorized By:</b>	<u>Jandy So / PSQ Manager</u> 
<b>Prepared By:</b>	

**Shenzhen SEM Test Technology Co. Ltd**  
1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,  
Bao'an District, Shenzhen, 518101, China  
Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

**Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM Test Technology Co., Ltd.**

**TABLE OF CONTENTS**

**1. GENERAL INFORMATION.....3**  
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....3  
1.2 TEST STANDARDS.....3  
1.3 GENERAL DESCRIPTION OF TEST.....3  
1.4 HUMAN EXPOSURE ASSESSMENT RESULTS.....4

## 1. GENERAL INFORMATION

### 1.1 Product Description for Equipment Under Test (EUT)

#### Client Information

Applicant: SHENZHEN JUNLAN ELECTRONIC LTD  
Address of applicant: No. 277 PingKui Road, Shijing Community, Pingshan Street, Pingshan New District, Shenzhen, China  
Manufacturer: SHENZHEN JUNLAN ELECTRONIC LTD  
Address of manufacturer: No. 277 PingKui Road, Shijing Community, Pingshan Street, Pingshan New District, Shenzhen, China

General Description of EUT	
Product Name:	CH BLUETOOTH SOUNDBAR SPEAKER
Trade Name:	NAXA
Model No.:	SBB-61250
Adding Model(s):	NHS-2012
Rated Voltage:	DC 5.8V
Power Adapter Model:	GKYP50200058US1 Input:AC100-240V~50/60Hz, 0.5A Output:DC5.8V/2000mA
<i>Note: The test data is gathered from a production sample provided by the manufacturer.</i>	

Technical Characteristics of EUT	
Frequency Range:	2402-2480MHz
Data Rate:	1Mbps, 2Mbps, 3Mbps
Modulation:	GFSK, Pi/4 QDPSK, 8DPSK
Quantity of Channels:	79
Type of Antenna:	PCB
Antenna Gain:	0 dBi

### 1.2 Test Standards

The objective of the following report is used to demonstrate that EUT operated in a manner that ensures the public is not exposed to radio frequency energy levels in excess of the relative provisions of FCC 47CFR Part 1.1310

### 1.3 General Description of Test

Items	Description
EUT Frequency band	<input type="checkbox"/> FHSS: 2.400GHz ~ 2.483GHz <input type="checkbox"/> WLAN: 2.400GHz ~ 2.483GHz <input type="checkbox"/> WLAN: 5.150GHz ~ 5.250GHz

	<input type="checkbox"/> WLAN: 5.745GHz ~ 5825GHz <input checked="" type="checkbox"/> Others: <u>BT: 2402-2480MHz</u>
Device category	<input type="checkbox"/> Portable (<20cm separation) <input type="checkbox"/> Mobile (>20cm separation) <input checked="" type="checkbox"/> Others <u>Fixed location (&gt;20cm separation)</u>
Exposure classification	<input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm <sup>2</sup> ) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm <sup>2</sup> ) <input type="checkbox"/> Others: _____
Antenna diversity	<input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas: <ul style="list-style-type: none"> <li><input type="checkbox"/> Tx diversity</li> <li><input type="checkbox"/> Rx diversity</li> <li><input type="checkbox"/> Tx/Rx diversity</li> </ul>
Max. output power	-5.967dBm = 0.25 mW
Antenna gain (Max)	0 dBi
Evaluation applied	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation
<p><b>Note:</b></p> <p>1. For mobile or fixed location transmitters, no SAR consideration applied. The minimum separation generally be used is at least 20 cm, even if the calculations indicate that the MPE distance would be lesser.</p>	

### 1.4 Human Exposure Assessment Results

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposure</b>				
0.3–3.0 .....	614	1.63	* 100	6
3.0–30 .....	1842/f	4.89/f	* 900/f <sup>2</sup>	6
30–300 .....	61.4	0.163	1.0	6
300–1,500 .....	.....	.....	f/300	6
1,500–100,000 .....	.....	.....	5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3–1.34 .....	614	1.63	* 100	30
1.34–30 .....	824/f	2.19/f	* 180/f <sup>2</sup>	30
30–300 .....	27.5	0.073	0.2	30
300–1,500 .....	.....	.....	f/1500	30
1,500–100,000 .....	.....	.....	<b>1.0</b>	30

f = frequency in MHz \* = Plane-wave equivalent power density

**Calculation**

Given  $E = \frac{\sqrt{30 \times P \times G}}{d}$  &  $S = \frac{E^2}{3770}$

Where  $E =$  Field Strength in Volts / meter

$P =$  Power in Watts

$G =$  Numeric antenna gain

$d =$  Distance in meters

$S =$  Power Density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770d^2}$$

Changing to units of mW and cm, using:

$P (mW) = P (W) / 1000$  and

$d (cm) = 100 * d (m)$

Yields

$$S = \frac{30 \times (P/1000) \times G}{3770 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2}$$

*Equation 1*

Where  $d =$  distance in cm

$P =$  Power in mW

$G =$  Numeric antenna gain

$S =$  Power Density in mW / cm<sup>2</sup>

<b>EUT parameter (data from the separate report)</b>	
Given $E = \frac{\sqrt{30 \times P \times G}}{d} \text{ \& \ } S = \frac{E^2}{3770}$	Where G: numerical gain of transmitting antenna; TP: Transmitted power in watt; d: distance from the transmitting antenna in meter
Exposure classification	S=1mW/cm <sup>2</sup>
Minimum distance in meter (d) (from transmitting structure to the human body)	20cm (0.2m)
Yields $S = \frac{30 \times P \times G}{3770d^2}, \quad d=0.2m=20cm$ $P=0.00025W=0.25 \text{ mW}, \quad G = 1,$ $S=0.00005mW/cm^2$	

Conclusion:

$S=0.00005\text{mW}/\text{cm}^2$  is significant lower than the FCC 47CFR Part 1.1310 Limit  $1\text{mW}/\text{cm}^2$  .

(For mobile or fixed location transmitters, the maximum power density is  $1.0\text{ mW} / \text{cm}^2$  even if the calculation indicates that the power density would be larger.)