

FCC 47 CFR PART 15 SUBPART C

CERTIFICATION TEST REPORT

For

MEDIA CENTER

MODEL No.: SBB-32170, WMSMCZ3, SBB-31069, SB17P

FCC ID: OKUSBB32170

Trademark: CONNEXX

REPORT NO.: ES150717233E

ISSUE DATE: August 20, 2015

Prepared for

Shenzhen Junlan Electronic Ltd No.277 PingKui Road, Shijing Community, Pingshan Street, Pingshan New District, Shenzhen, China

Prepared by

SHENZHEN EMTEK CO., LTD.

Bldg 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China TEL: 86-755-26954280 FAX: 86-755-26954282



Table of Contents

	RESULT CERTIFICATION	J
EUT	TECHNICAL DESCRIPTION	4
SUM	MARY OF TEST RESULT	5
TEST	METHODOLOGY	6
4.1 4.2 4.3	MEASUREMENT EQUIPMENT USED	6
FACI	LITIES AND ACCREDITATIONS	8
5.1 5.2	FACILITIES LABORATORY ACCREDITATIONS AND LISTINGS	8 8
TEST	SYSTEM UNCERTAINTY	9
SETU	JP OF EQUIPMENT UNDER TEST	10
7.1 7.2 7.3	RADIO FREQUENCY TEST SETUP 2	
FREC	QUENCY HOPPING SYSTEM REQUIREMENTS	12
8.1 8.2 8.3 8.4	EUT PSEUDORANDOM FREQUENCY HOPPING SEQUENCE	
TEST	REQUIREMENTS	14
9.1 9.2 9.3 9.4 9.5 9.6 9.7 9.8	CARRIER FREQUENCY SEPARATION NUMBER OF HOPPING FREQUENCIES. AVERAGE TIME OF OCCUPANCY (DWELL TIME) MAXIMUM PEAK CONDUCTED OUTPUT POWER CONDUCTED SUPRIOUS EMISSION RADIATED SPURIOUS EMISSION	20 26 28 31 32 39
	SUMI TEST 4.1 4.2 4.3 FACII 5.1 5.2 TEST 5.2 7.1 7.2 7.3 FREC 8.1 8.2 8.3 8.4 TEST 9.1 9.2 9.3 9.4 9.5 9.6	 4.2 MEASUREMENT EQUIPMENT USED



1 TEST RESULT CERTIFICATION

Applicant:	Shenzhen Junlan Electronic Ltd No.277 PingKui Road, Shijing Community, Pingshan Street, Pingshan New District, Shenzhen, China
Manufacturer:	Shenzhen Junlan Electronic Ltd No.277 PingKui Road, Shijing Community, Pingshan Street, Pingshan New District, Shenzhen, China
Product Description:	MEDIA CENTER
Model Number:	SBB-32170, WMSMCZ3, SBB-31069, SB17P (Note: These models are identical in circuitry and electrical, mechanical and physical construction; the only differences are the appearance, trade name and model no. for trading purpose. We prepare SBB-32170 for test, and the worst result recorded in the report.)
File Number:	ES150714182E
Date of Test:	July 14, 2015 to August 20, 2015

Measurement Procedure Used:

APPLICABLE STANDARDS			
STANDARD TEST RESULT			
FCC 47 CFR Part 2, Subpart J FCC 47 CFR Part 15, Subpart C	PASS		

The above equipment was tested by SHENZHEN EMTEK CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10(2009) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 2 and Part 15.247

The test results of this report relate only to the tested sample identified in this report

Date of Test :	July 14, 2015 to August 20, 2015
Test by :	king kung
	KingKong /Tester
Prepared by :	Yaping Shen
	Yaping Shen/Editor
	2005
Approve & Authorized Signer :	Lisa Wang/Manager



2 EUT TECHNICAL DESCRIPTION

Characteristics	Description
Data Rate	1Mbps for GFSK modulation 2Mbps for pi/4-DQPSK modulation 3Mbps for 8DPSK modulation
Modulation:	GFSK modulation (1Mbps) pi/4-DQPSK modulation (2Mbps) 8DPSK modulation (3Mbps)
Operating Frequency Range(s):	2402-2480MHz
Number of Channels:	79 channels
Transmit Power Max:	6.310 dBm
Antenna Type :	PCB antenna
Antenna Gain:	0 dBi
	DC supply: DC 12V by battery and the EUT can't be recharged
Power supply:	AC supply:
Temperature Range	-10°C ~ +55°C

Note: for more details, please refer to the User's manual of the EUT.



3 SUMMARY OF TEST RESULT

FCC Part Clause	Test Parameter	Verdict	Remark
15.247(a)(1)	20 dB Bandwidth	PASS	
15.247(a)(1)	Carrier Frequency Separation	PASS	
15.247(a)(1)	Number of Hopping Frequencies	PASS	
15.247(a)(1)	Average Time of Occupancy (Dwell Time)	PASS	
15.247(b)(1)	Maximum Peak Conducted Output Power	PASS	
15.247(c)	Conducted Spurious Emissions	PASS	
15.247(d) 15.209	Radiated Spurious Emissions	PASS	
15.207	Conducted Emission	N/A	
15.247(b)	Antenna Application	PASS	
NOTE *: The proc	duct is powered by DC 12V battery and the EUT can't b	be charged.	

RELATED SUBMITTAL(S) / GRANT(S):

This submittal(s) (test report) is intended for FCC ID: OKUSBB32170 filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.



4 TEST METHODOLOGY

4.1 GENERAL DESCRIPTION OF APPLIED STANDARDS

According to its specifications, the EUT must comply with the requirements of the following standards: FCC 47 CFR Part 2, Subpart J FCC 47 CFR Part 15, Subpart C DA 00-705

4.2 MEASUREMENT EQUIPMENT USED

4.2.1 Radiated Emission Test Equipment

EQUIPMENT	MFR	MODEL	SERIAL	LAST CAL.	CAL. DUE
TYPE		NUMBER	NUMBER		
EMI Test Receiver	Rohde & Schwarz	ESU	1302.6005.26	05/16/2015	05/15/2016
Pre-Amplifier	HP	8447D	2944A07999	05/16/2015	05/15/2016
Bilog Antenna	Schwarzbeck	VULB9163	142	05/16/2015	05/15/2016
Loop Antenna	ARA	PLA-1030/B	1029	05/16/2015	05/15/2016
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170399	05/16/2015	05/15/2016
Horn Antenna	Schwarzbeck	BBHA 9120	D143	05/16/2015	05/15/2016
Cable	Schwarzbeck	AK9513	ACRX1	05/16/2015	05/15/2016
Cable	Rosenberger	N/A	FP2RX2	05/16/2015	05/15/2016
Cable	Schwarzbeck	AK9513	CRPX1	05/16/2015	05/15/2016
Cable	Schwarzbeck	AK9513	CRRX2	05/16/2015	05/15/2016

4.2.2 Radio Frequency Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL. DUE
Spectrum Analyzer	Agilent	E4407B	88156318	05/16/2015	05/15/2016
Power meter	Anritsu	ML2495A	0824006	05/16/2015	05/15/2016
Power sensor	Anritsu	MA2411B	0738172	05/16/2015	05/15/2016
Signal Analyzer	Agilent	N9010A	My53470879	05/16/2015	05/15/2016

Remark: Each piece of equipment is scheduled for calibration once a year.



4.3 DESCRIPTION OF TEST MODES

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (1Mbps for Bluetooth v2.1 BR GFSK modulation; 2Mbps for Bluetooth v2.1 EDR pi/4-DQPSK modulation; 3Mbps for Bluetooth v2.1 EDR 8DPSK modulation) were used for all test.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	
0	2402	39	2441			
1	2403	40	2442	76	2478	
2	2404	41	2443	77	2479	
				78	2480	
Note: fc=2402MHz+(k-1)×1MHz k=1 to 79						

Frequency and Channel list for Bluetooth v2.1:

Test Frequency and channel for Bluetooth v2.1:

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	39	2441	78	2480



5 FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

Bldg 69, Majialong Industry Zone District, Nanshan District, Shenzhen, China The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

5.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

EMC Lab.

- : Accredited by CNAS, 2013.10.29 The certificate is valid until 2016.10.28 The Laboratory has been assessed and proved to be in compliance with CNAS-CL01: 2006(identical to ISO/IEC17025: 2005) The Certificate Registration Number is L2291
- : Accredited by TUV Rheinland Shenzhen, 2010.5.25 The Laboratory has been assessed according to the requirements ISO/IEC 17025.
- : Accredited by FCC, July 24, 2013 The Certificate Registration Number is 406365.
- : Accredited by FCC, April 17, 2013 The Certificate Registration Number is 709623.
- : Accredited by Industry Canada, November 29, 2012 The Certificate Registration Number is 4480A-2



6 TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Parameter	Uncertainty
Radio Frequency	±1x10^-5
Maximum Peak Output Power Test	±1.0dB
Conducted Emissions Test	±2.0dB
Radiated Emission Test	±2.0dB
Occupied Bandwidth Test	±1.0dB
Band Edge Test	±3dB
All emission, radiated	±3dB
Antenna Port Emission	±3dB
Temperature	±0.5℃
Humidity	±3%


Measurement Uncertainty for a level of Confidence of 95%



7 SETUP OF EQUIPMENT UNDER TEST

7.1 RADIO FREQUENCY TEST SETUP 1

The Bluetooth v2.1 component's antenna ports(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



7.2 RADIO FREQUENCY TEST SETUP 2


The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10. The test distance is 3m.The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2009 and CAN/CSA-CEI/IEC CISPR 22.

Below 30MHz:


The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna (loop antenna). The Antenna should be positioned with its plane vertical at the specified distance from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. The center of the loop shall be 1 m above the ground. For certain applications, the loop antenna plane may also need to be positioned horizontally at the specified distance from the EUT.

Above 30MHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H). (a) Radiated Emission Test Set-Up, Frequency Below 30MHz








(b) Radiated Emission Test Set-Up, Frequency Below 1000MHz

(c) Radiated Emission Test Set-Up, Frequency above 1000MHz



7.3 SUPPORT EQUIPMENT

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID/IC:	Note
1.	iPhone	Apple	iPhone 5/A1526	FCC ID:BCG-E2694A	accessory equipment

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.

2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.



8 FREQUENCY HOPPING SYSTEM REQUIREMENTS

8.1 Standard Applicable

According to FCC Part 15.247(a)(1), The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

(g) Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.


(h) The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

8.2 EUT Pseudorandom Frequency Hopping Sequence


The channel is represented by a pseudo-random hopping sequence hopping through the 79 RF channels. The hopping sequence is unique for the piconet and is determined by the Bluetooth device address of the master; the phase in the hopping sequence is determined by the Bluetooth clock of the master. The channel is divide into time slots where each slot corresponds to an RF hop frequency. Consecutive hops correspond to different RF hop frequencies. The normal hop is 1 600 hops/s.

The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage, and the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones. Number of shift register stages: 9

Length of pseudo-random sequence: 29-1 = 524 bits Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence





Each frequency used equally on the average by each transmitter.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

8.3 Equal Hopping Frequency Use

All Bluetooth units participating in the piconet are time and hop-synchronized to the channel.

Example of a 79 hopping sequence in data mode:

35, 27, 6, 44, 14, 61, 74, 32, 1, 11, 23, 2, 55, 65, 29, 3, 9, 52, 78, 58, 40, 25, 0, 7, 18, 26, 76, 60, 47, 50, 2, 5, 16, 37, 70, 63, 66, 54, 20, 13, 4, 8, 15, 21, 26, 10, 73, 77, 67, 69, 43, 24, 57, 39, 46, 72, 48, 33, 17, 31, 75, 19, 41, 62, 68, 28, 51, 66, 30, 56, 34, 59, 71, 22, 49, 64, 38, 45, 36, 42, 53 Each Frequency used equally on the average by each transmitter

8.4 Frequency Hopping System

This transmitter device is frequency hopping device, and complies with FCC part 15.247 rule.

This device uses Bluetooth radio which operates in 2400-2483.5 MHz band. Bluetooth uses a radio technology called frequency-hopping spread spectrum, which chops up the data being sent and transmits chunks of it on up to 79 bands (1 MHz each; centred from 2402 to 2480 MHz) in the range 2,400-2,483.5 MHz. The transmitter switches hop frequencies 1,600 times per second to assure a high degree of data security. All Bluetooth devices participating in a given piconet are synchronized to the frequency-hopping channel for the piconet. The frequency hopping sequence is determined by the master's device address and the phase of the hopping sequence (the frequency to hop at a specific time) is determined by the master's internal clock. Therefore, all slaves in a piconet must know the master's device address and must synchronize their clocks with the master's clock.

Adaptive Frequency Hopping (AFH) was introduced in the Bluetooth specification to provide an effective way for a Bluetooth radio to counteract normal interference. AFH identifies "bad" channels, where either other wireless devices are interfering with the Bluetooth signal or the Bluetooth signal is interfering with another device. The AFH- enabled Bluetooth device will then communicate with other devices within its piconet to share details of any identified bad channels. The devices will then switch to alternative available "good" channels, away from the areas of interference, thus having no impact on the bandwidth used.



9 TEST REQUIREMENTS

9.1 20DB BANDWIDTH

9.1.1 Applicable Standard

According to FCC Part 15.247(a)(1) and DA 00-705

9.1.2 Conformance Limit

No limit requirement.

9.1.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

9.1.4 Test Procedure

The EUT was operating in Bluetooth v2.1 mode and controlled its channel. Printed out the test result from the spectrum by hard copy function.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously

Set RBW = 30 kHz.

Set the video bandwidth (VBW) =100 kHz.

Set Span= approximately 2 to 3 times the 20 dB bandwidth

Set Detector = Peak.

Set Trace mode = max hold.

Set Sweep = auto couple.

The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the markerdelta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission.


If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation.

Measure and record the results in the test report.


Temperature:	24 °C	Test Date:	August 07, 2015
Humidity:	53 %	Test By:	KK

Modulation	Channel	Channel Frequency	Measurement Bandwidth	Limit	Verdict	
Mode	Number	(MHz)	(kHz)	(kHz)	verdict	
	00	2402	909.8	N/A	PASS	
GFSK	39	2441	911.5	N/A	PASS	
	78	2480	876.8	N/A	PASS	
	00	2402	1238	N/A	PASS	
pi/4-DQPSK	39	2441	1241	N/A	PASS	
	78	2480	1249	N/A	PASS	
	00	2402	1210	N/A	PASS	
8DPSK	39	2441	1211	N/A	PASS	
	78	2480	1213	N/A	PASS	
Note: N/A (Not Applicable)						


























9.2 CARRIER FREQUENCY SEPARATION

9.2.1 Applicable Standard

According to FCC Part 15.247(a)(1) and DA 00-705

9.2.2 Conformance Limit

Frequency hopping systems operating in the 2400-2483.5MHz band shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater.

In case of an output power less than 125mW, the frequency hopping system may have channels separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater.

9.2.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

9.2.4 Test Procedure

According to FCC Part15.247(a)(1)

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings: Set the RBW =100kHz. Set VBW =300kHz.

Set the span = wide enough to capture the peaks of two adjacent channels

Set Sweep time = auto couple.


Set Detector = peak. Set Trace mode = max hold.

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section. Submit this plot.


Temperature:	24 ℃	Test Date:	August 07, 2015
Humidity:	53 %	Test By:	KK

Modulation	Channel	Channel Frequency	Measurement Bandwidth	Limit	Verdict
Mode	Number	(MHz)	(kHz)	(kHz)	veruici
	0	2402	1000	>606.533	PASS
GFSK	39	2441	1000	>607.667	PASS
	78	2480	1000	>584.533	PASS
	0	2402	1000	>825.333	PASS
pi/4-DQPSK	39	2441	1000	>827.333	PASS
	78	2480	1000	>832.667	PASS
	0	2402	1000	>806.667	PASS
8DPSK	39	2441	1000	>807.333	PASS
7	78	2480	1000	>808.667	PASS
Note: Limit = 20dB bandwidth*2/3, if it is greater than 25kHz and the output power is less than 125mW (21dBm).					


























9.3 NUMBER OF HOPPING FREQUENCIES

9.3.1 Applicable Standard

According to FCC Part 15.247(a)(1) (iii)and DA 00-705

9.3.2 Conformance Limit

Frequency hopping systems operating in the 2400-2483.5MHz band shall use at least 15 channels.

9.3.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1


9.3.4 Test Procedure

According to FCC Part15.247(a)(1)(iii)
 The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:
 Span = the frequency band of operation (2390-2440MHz) and(2440-2490MHz)
 RBW ≥ 1% of the span
 VBW ≥ RBW
 Sweep = auto
 Detector function = peak
 Trace = max hold
 Allow the trace to stabilize. It may prove necessary to break the span up to sections, in order to clearly show all of the hopping frequencies.

Temperature:	24℃	Test Date:	August 07, 2015
Humidity:	53 %	Test By:	KK
Hopping Chan	nel Frequency	Quantity of Hopping Channel	Quantity of Hopping Ch

Hopping Channel Frequency Range	Quantity of Hopping Channel	Quantity of Hopping Channel limit
2402-2480	79	>15







9.4 AVERAGE TIME OF OCCUPANCY (DWELL TIME)

9.4.1 Applicable Standard

According to FCC Part 15.247(a)(1)(iii) and DA 00-705

9.4.2 Conformance Limit

For frequency hopping systems operating in the 2400-2483.5MHz band, the average time of occupancy on any channel shall not be greater than 0.4s within a period of 0.4s multiplied by the number of hopping channels employed.

9.4.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

9.4.4 Test Procedure

■ According to FCC Part15.247(a)(1)(iii)

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = zero span, centered on a hopping channel

RBW = 1 MHz

 $\mathsf{VBW}\,\geqslant\,\mathsf{RBW}$

Sweep = as necessary to capture the entire dwell time per hopping channel

Detector function = peak

Trace = max hold

If possible, use the marker-delta function to determine the dwell time. If this value


varies with different modes of operation (e.g., data rate, modulation format, etc.),

repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section.


9.4.5 Test Results

Temperature: Humidity:	24℃ 53 %		Test Da Test By		07, 2015		
Modulation	Channel	Packet	Pluse width	Number per	dwell time	Limit	Verdict
Mode	Number	type	(ms)	channel in 31.6s	(ms)	(ms)	veruici
	0	DH1	0.416	320.00	133.12	<400	PASS
GFSK	0	DH3	1.648	160.00	263.68	<400	PASS
	0	DH5	2.928	106.67	312.33	<400	PASS
Note:							











9.5 MAXIMUM PEAK CONDUCTED OUTPUT POWER

9.5.1 Applicable Standard

According to FCC Part 15.247(b)(1) and DA 00-705

9.5.2 Conformance Limit

The max For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

9.5.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

9.5.4 Test Procedure

According to FCC Part15.247(b)(1)

As an alternative to a peak power measurement, compliance with the limit can be based on a measurement of the maximum conducted output power.

Use the following spectrum analyzer settings:

Set Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel (about 10MHz) Set RBW > the 20 dB bandwidth of the emission being measured (about 3MHz)

Set VBW ≥ RBW

Set Sweep = auto

Set Detector function = peak

Set Trace = max hold

Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission to determine the peak amplitude level.

Temperature:	24℃	Test Date:	August 07, 2015
Humidity:	53 %	Test By:	KK

Operation	Channel	Channel Frequency	Measurement Level	Limit	Vordiat
Mode	Number	(MHz)	(dBm)	(dBm)	Verdict
	0	2402	5.494	30	PASS
GFSK	39	2441	6.310	30	PASS
	78	2480	5.977	30	PASS
pi/4-DQPSK	0	2402	3.237	30	PASS
	39	2441	4.368	30	PASS
	78	2480	4.051	30	PASS
	0	2402	3.760	30	PASS
8DPSK	39	2441	4.709	30	PASS
	78	2480	4.364	30	PASS
Note: N/A					



9.6 CONDUCTED SUPRIOUS EMISSION

9.6.1 Applicable Standard

According to FCC Part 15.247(d) and DA 00-705

9.6.2 Conformance Limit

According to FCC Part 15.247(d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted, provided the transmitter demonstrates compliance with the peak conducted power limits.

9.6.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

9.6.4 Test Procedure

The transmitter output (antenna port) was connected to the spectrum analyzer

Reference level measurement

Establish a reference level by using the following procedure:

Set instrument center frequency to DSS channel center frequency.

Set Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel.

Set the RBW = 100 kHz. Set the VBW \ge 3 x RBW.

Set Detector = peak. Set Sweep time = auto couple.

Set Trace mode = max hold. Allow trace to fully stabilize.

Use the peak marker function to determine the maximum Maximum conduceted level.

Note that the channel found to contain the maximum conduceted level can be used to establish the reference level.

■ Band-edge Compliance of RF Conducted Emissions

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the emission operating on the channel closest to the band-edge, as well as any modulation products which fall outside of the authorized band of operation Set RBW \geq 1% of the span=100kHz Set VBW \geq RBW

Set Sweep = auto Set Detector function = peak Set Trace = max hold

Allow the trace to stabilize. Set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. The marker-delta value now displayed must comply with the limit specified in this Section.

Now, using the same instrument settings, enable the hopping function of the EUT. Allow the trace to stabilize. Follow the same procedure listed above to determine if any spurious emissions caused by the hopping function also comply with the specified limit.

Conduceted Spurious RF Conducted Emission

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic.(30MHz to

25GHz). Set RBW = 100 kHz Set VBW \ge RBW


Set Sweep = auto Set Detector function = peak Set Trace = max hold

Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded. The level displayed must comply with the limit specified in this Section.


9.6.5 Test Results

Bluetooth (GFSK, pi/4-DQPSK, 8DPSK) mode have been tested, and the worst result(GFSK) was report as below:





























9.7 RADIATED SPURIOUS EMISSION

9.7.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and DA 00-705

9.7.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)). According to FCC Part15.205, Restricted bands

According to FOOT art 13.203, Restricted bands										
MHz	MHz	GHz								
16.42-16.423	399.9-410	4.5-5.15								
16.69475-16.69525	608-614	5.35-5.46								
16.80425-16.80475	960-1240	7.25-7.75								
25.5-25.67	1300-1427	8.025-8.5								
37.5-38.25	1435-1626.5	9.0-9.2								
73-74.6	1645.5-1646.5	9.3-9.5								
74.8-75.2	1660-1710	10.6-12.7								
123-138	2200-2300	14.47-14.5								
149.9-150.05	2310-2390	15.35-16.2								
156.52475-156.52525	2483.5-2500	17.7-21.4								
156.7-156.9	2690-2900	22.01-23.12								
162.0125-167.17	3260-3267	23.6-24.0								
167.72-173.2	3332-3339	31.2-31.8								
240-285	3345.8-3358	36.43-36.5								
322-335.4	3600-4400	(2)								
	MHz 16.42-16.423 16.69475-16.69525 16.80425-16.80475 25.5-25.67 37.5-38.25 73-74.6 74.8-75.2 123-138 149.9-150.05 156.52475-156.52525 156.7-156.9 162.0125-167.17 167.72-173.2 240-285	MHzMHz16.42-16.423399.9-41016.69475-16.69525608-61416.80425-16.80475960-124025.5-25.671300-142737.5-38.251435-1626.573-74.61645.5-1646.574.8-75.21660-1710123-1382200-2300149.9-150.052310-2390156.52475-156.525252483.5-2500156.7-156.92690-2900162.0125-167.173260-3267167.72-173.23332-3339240-2853345.8-3358								

According to FCC Part15.205, the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

Restricted Frequency(MHz)	Field Strength (µV/m)	Field Strength (dBµV/m)	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log (uV/m)	300
0.490-1.705	2400/F(KHz)	20 log (uV/m)	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

9.7.3 Test Configuration

Test according to clause 7.2 radio frequency test setup 2

9.7.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \ge 1$ GHz(1GHz to 25GHz), 100 kHz for f < 1 GHz(30MHz to 1GHz)

 $VBW \ge RBW$

Sweep = auto

Detector function = peak Trace = max hold



Follow the guidelines in ANSI C63.10-2009 respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data. Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from 20log(dwell time/100 ms), in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

Repeat above procedures until all frequency measured was complete.

9.7.5 Test Results

■ Spurious Emission below 30MHz (9KHz to 30MHz)

Temperature:	24 ℃	Test Date:	August 07, 2015
Humidity:	53 %	Test By:	KK
Test mode:	TX Mode	-	

Freq.	Ant.Pol.		sion BuV/m)	Limit 3m	(dBuV/m)	Over(dB)	
(MHz)	H/V	PK È	ÁV	PK	AV	PK	AV

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor =40log(Specific distance/ test distance)(dB);

Limit line=Specific limits(dBuV) + distance extrapolation factor

Spurious Emission Above 1GHz (1GHz to 25GHz)

Bluetooth (GFSK, pi/4-DQPSK, 8DPSK) mode have been tested, and the worst result(GFSK) was report as below:

Temperature:	24 °C	Test Date:	August 07, 2015
Humidity:	53 %	Test By:	KK
Test mode:	GFSK	Frequency:	Channel 0: 2402MHz

Freq.	Ant.Pol.		ssion BuV/m)	Limit 3m((dBuV/m)	Over(dB)		
(MHz)	H/V	PK	ÁV	PK	AV	PK	AV	
1778.55	V	56.74	43.47	74.00	54.00	-17.26	-10.53	
4510.99	V	53.93	39.10	74.00	54.00	-20.07	-14.90	
5639.89	V	55.55	42.47	74.00	54.00	-18.45	-11.53	
1778.55	Н	56.27	42.51	74.00	54.00	-17.73	-11.49	
2962.17	Н	55.68	41.66	74.00	54.00	-18.32	-12.34	
5628.90	Н	56.11	41.66	74.00	54.00	-17.89	-12.34	



Temperature	e: 24°	C	Test Da	ate:	August	07, 2015			
Humidity:	53	%	Test By	/ :	кк	KK			
Test mode:		SK	Freque		Channe	39: 2441M	Ηz		
				5					
Freq.	Ant.Pol.	Emission Le	evel(dBuV/m)	Limit 3r	n(dBuV/m)	Ov	er(dB)		
(MHz)	H/V	PK	À AV Ó	PK	AV	PK	ÂV		
1856.55	V	55.39	43.07	74.00	54.00	-18.61	-10.93		
2771.09	V	53.69	38.69	74.00	54.00	-20.31	-15.31		
3819.90	V	56.12	42.05	74.00	54.00	-17.88	-11.95		
1856.55	Н	58.16	42.77	74.00	54.00	-15.84	-11.23		
2922.18	Н	53.49	53.49 38.82 74.00 54.00 -20.5		-20.51	-15.18			
3523.90	Н	55.05	40.91	74.00	54.00	-18.95	-13.09		
Temperature	e: 24°	C	Test Da	ate:	August	August 07, 2015			
Humidity:	53	%	Test By	/ :	KK				
Test mode:	GF	SK	Freque	ency:	Channe	178: 2480MH	Ηz		
			-	-					
Freq.	Ant.Pol.	Emission Lev	el(dBuV/m)	Limit 3m	(dBuV/m)	Ove	er(dB)		
(MHz)	H/V	PK	AV	PK	AV	PK	AV		
1934.55	V	55.85	42.76	74.00	54.00	-18.15	-11.24		
4560.90	V	54.26	39.91	74.00	54.00	-19.74	-14.09		

Nata	(1) All Deadings are Dea	1/2/01/02/1/D/A/-2/41	and Deals Value	(1/D) (1 - 10) (-1)
note:	(1) All Readings are Pea	k value (v bvv=sivi⊓z) and Peak value ($(V \square V V = I U \square Z).$

40.85

41.52

39.88

41.96

(2) Emission Level= Reading Level+Probe Factor +Cable Loss.

(3) Data of measurement within this frequency range shown " -- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

74.00

74.00

74.00

74.00

54.00

54.00

54.00

54.00

-18.12

-19.82

-20.36

-17.85

-13.15

-12.48

-14.12

-12.04

5669.30

1934.55

2673.22

3848.09

V

Η

Η

Η

55.88

54.18

53.64

56.15



■ Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz Bluetooth (GFSK, pi/4-DQPSK, 8DPSK, Hopping) mode have been tested, and the worst result(GFSK, Hopping) was report as below:

Temperature: Humidity: Test mode:	24℃ 53 % GFSK	Te	st Date: st By: equency:	кк	et 07, 2015 nel 0: 2402MHz		
Frequency (MHz)	Polarity H/V	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	Margin (dB)	AV(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	Margin (dB)
2383.52	Н	39.62	74	-34.20	24.34	54	-29.66
2387.60	V	39.90	74	-34.10	23.69	54	-30.31
Temperature: Humidity: Test mode:	24℃ 53 % GFSK	Te	Test Date: August 07, 2015 Test By: KK Frequency: Channel 78: 2480MHz				
Frequency (MHz)	Polarity H/V	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	Margin (dB)	AV(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	Margin (dB)
2484.06	Н	39.62	74	-34.38	25.32	54	-28.68
2484.26	V	40.11	74	-33.89	26.18	54	-27.82
Temperature: Humidity: Test mode:	24℃ 53 % GFSK	Te	Test Date: August 07, 2015 Test By: KK Frequency: Hopping				
Frequency (MHz)	Polarity H/V	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	Margin (dB)	AV(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	Margin (dB)
2400.00	Н	40.79	74	-33.21	27.38	54	-26.62
2483.50	Н	37.46	74	-36.54	24.13	54	-29.87
2400.00	V	39.68	74	-34.32	26.82	54	-27.18

Note: (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).

(2) Emission Level= Reading Level+Probe Factor +Cable Loss.

38.08

(3) Data of measurement within this frequency range shown " -- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

-35.92

25.68

54


-28.32

74


2483.50

V

















■ Spurious Emission below 1GHz (30MHz to 1GHz)


Bluetooth (GFSK, pi/4-DQPSK, 8DPSK) mode have been tested, and the worst result(GFSK) was report as below:



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	1	91.9900	49.43	-17.11	32.32	43.50	-11.18	QP			
2	2	263.7700	48.07	-12.75	35.32	46.00	-10.68	QP			
3	2	288.0200	49.62	-13.07	36.55	46.00	-9.45	QP			
4	* 3	35.5500	53.47	-12.70	40.77	46.00	-5.23	QP			
5	3	359.8000	48.25	-10.76	37.49	46.00	-8.51	QP			
6	4	08.3000	48.63	-9.10	39.53	46.00	-6.47	QP			

*:Maximum data x:Over limit !:over margin






No.	Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	47.4600	44.43	-13.97	30.46	40.00	-9.54	QP			
2		128.9400	46.25	-17.16	29.09	43.50	-14.41	QP			
3		288.0200	43.90	-13.07	30.83	46.00	-15.17	QP			
4		384.0500	37.41	-9.77	27.64	46.00	-18.36	QP			
5		431.5800	37.26	-10.45	26.81	46.00	-19.19	QP			
6		551.8600	37.17	-7.38	29.79	46.00	-16.21	QP			

*:Maximum data x:Over limit !:over margin






No.	Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		191.9900	49.95	-17.11	32.84	43.50	-10.66	QP			
2		288.0200	49.99	-13.07	36.92	46.00	-9.08	QP			
3	*	335.5500	52.74	-12.70	40.04	46.00	-5.96	QP			
4		408.3000	46.43	-9.10	37.33	46.00	-8.67	QP			
5		455.8300	49.89	-11.33	38.56	46.00	-7.44	QP			
6		504.3300	42.88	-7.77	35.11	46.00	-10.89	QP			

*:Maximum data x:Over limit !:over margin






No.	Mł	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		216.2400	46.55	-16.38	30.17	46.00	-15.83	QP			
2		263.7700	46.05	-12.75	33.30	46.00	-12.70	QP			
3		288.0200	48.79	-13.07	35.72	46.00	-10.28	QP			
4		408.3000	42.84	-9.10	33.74	46.00	-12.26	QP			
5	*	431.5800	46.43	-10.45	35.98	46.00	-10.02	QP			
6		528.5800	39.87	-7.56	32.31	46.00	-13.69	QP			

*:Maximum data x:Over limit !:over margin






Note:

No.	Mł	c. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		134.7600	42.59	-17.51	25.08	43.50	-18.42	QP			
2	*	191.9900	50.97	-17.11	33.86	43.50	-9.64	QP			
3		288.0200	48.76	-13.07	35.69	46.00	-10.31	QP			
4		335.5500	45.43	-12.70	32.73	46.00	-13.27	QP			
5		383.0800	44.69	-9.83	34.86	46.00	-11.14	QP			
6		480.0800	37.60	-9.53	28.07	46.00	-17.93	QP			

*:Maximum data x:Over limit !:over margin





Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		47.4600	39.75	-13.97	25.78	40.00	-14.22	QP			
2		124.0900	42.19	-16.72	25.47	43.50	-18.03	QP			
3	,	143.4900	48.62	-17.88	30.74	43.50	-12.76	QP			
4	* •	191.9900	48.65	-17.11	31.54	43.50	-1 1.96	QP			
5	2	288.0200	40.04	-13.07	26.97	46.00	-19.03	QP			
6	4	401.5100	38.36	-8.92	29.44	46.00	-16.56	QP			

*:Maximum data x:Over limit !:over margin



9.8 ANTENNA APPLICATION

9.8.1 Antenna Requirement

Standard	Requirement
FCC CRF Part 15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

The EUT has 1 antenna: a PCB antenna for BT, the gain is 0 dBi; Note:Antenna use a permanently attached antenna which is not replaceable. which in accordance to section 15.203, please refer to the internal photos.

9.8.2 Result

PASS.