

# TEST REPORT

**Reference No.**..... : WTD21D06061614W002  
**FCC ID** ..... : OKUSBB62647  
**Applicant**..... : Shenzhen Junlan Electronic Ltd  
**Address**..... : No.277 PingKui Road, Shijing Community, Pingshan Street,  
Pingshan New District, Shenzhen, China  
**Manufacturer** ..... : Shenzhen Junlan Electronic Ltd  
**Address**..... : No.277 PingKui Road, Shijing Community, Pingshan Street,  
Pingshan New District, Shenzhen, China  
**Product**..... : 26 inch Sound bar  
**Model(s)** ..... : SB-26, SBB-62647, SB-XX, SBB-XXXXX(X means unit color and  
Buyer different, it can A to Z or N/A)  
**Standards**..... : FCC Part 2.1091  
**Date of Receipt sample** .... : 2021-06-24  
**Date of Test** ..... : 2021-06-24 to 2021-07-14  
**Date of Issue**..... : 2021-07-14  
**Test Result**..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

**Prepared By:**


**Waltek Testing Group Co., Ltd.**

Address: No. 77, Houjie Section, Guantai Road, Houjie Town, Dongguan City, Guangdong, China

Tel: +86-769-2267 6998


Fax: +86-769-2267 6828

Compiled by:



Andy Feng / Project Engineer

Approved by:



Daniel Liu / Designated Reviewer

## 2. Contents

	<b>Page</b>
<b>1 COVER PAGE</b> .....	<b>1</b>
<b>2 CONTENTS</b> .....	<b>2</b>
<b>3 REVISION HISTORY</b> .....	<b>3</b>
<b>4 GENERAL INFORMATION</b> .....	<b>4</b>
4.1. GENERAL DESCRIPTION OF E.U.T.....	4
4.2. DETAILS OF E.U.T.....	4
4.3. TEST FACILITY .....	4
<b>5 TEST SUMMARY</b> .....	<b>5</b>
<b>6 RF EXPOSURE</b> .....	<b>6</b>
6.1. REQUIREMENTS.....	6
6.2. THE PROCEDURES / LIMIT .....	6
6.3. MPE CALCULATION METHOD .....	7
6.4. RESULT: COMPLIANCE .....	7

### 3. Revision History

Test report No.	Date of Receipt sample	Date of Test	Date of Issue	Purpose	Comment	Approved
WTD21D06061614 W002	2021-06-24	2021-06-24 to 2021-07-14	2021-07-14	Original	-	Valid

## 4. General Information

### 4.1. General Description of E.U.T.

Product:	26 inch Sound bar
Model(s):	SB-26, SBB-62647, SB-XX, SBB-XXXXX(X means unit color and Buyer different, it can A to Z or N/A)
Additional model(s):	Color and Buyer different
Operation Frequency:	2402-2480MHz, 79 Channels in total
Max. RF output power:	7.74dBm
Antenna installation:	PCB Printed Antenna
Antenna Gain:	0dBi
Type of Modulation:	GFSK, $\pi/4$ DQPSK, 8DPSK
Hardware Version:	SBB-62647-MAIN-V1.1
Software Version:	V1.0

### 4.2. Details of E.U.T.

Ratings:	DC 12V
----------	--------

### 4.3. Test Facility

FCC Designation No.: CN1201. Test Firm Registration No.: 523476.  
ISED CAB identifier: CN0013. Test Firm Registration No.: 7760A.

## 5. Test Summary

Test Items	Test Requirement	Result
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	FCC Part 2.1091	PASS

## 6. RF Exposure

Test Requirement: FCC Part 2.1091

Evaluation Method: KDB 447498 D01 General RF Exposure Guidance v06

### 6.1. Requirements

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device.

### 6.2. The procedures / limit

#### (A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

#### (B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz; \*Plane-wave equivalent power density

### 6.3. MPE Calculation Method

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)

P = output power to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

From the peak EUT RF output power, the minimum mobile separation distance, R=20cm, as well as the gain of the used antenna, the RF power density can be obtained

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. conducted Output Power (dBm)	Max. conducted Output Power (mW)	Power Density (mW/cm <sup>2</sup> )	Limit of Power Density (mW/cm <sup>2</sup> )	Result
0.00	1.000	7.74	5.94	0.001182	1	Compliance

### 6.4. Result: Compliance

No SAR measurement is required.

=====End of Report=====