



Product Service

RF - TEST REPORT

Report Number : **68.760.9.258.01** Date of Issue: 28 December 2009

Model : **287380**

Product Type : MP6 Module

Applicant : ICON Health & Fitness Inc.

Address : 1500 S. 1000 W. LOGAN, UT84321

Production Facility : Wanlida Group Co., Ltd.

Address : Wanlida Industry Zone, Nanjing, Fujian, China 363601

Test Result : **Positive** **Negative**

Total pages including
Appendices : 45

Jiangsu TÜV Product Service Ltd. – Shenzhen Branch is a subcontractor to TÜV SÜD Product Service GmbH according to the principles outlined in ISO 17025.

Jiangsu TÜV Product Service Ltd. – Shenzhen Branch reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations. Jiangsu TÜV Product Service Ltd. – Shenzhen Branch shall have no liability for any deductions, inferences or generalizations drawn by the client or others from Jiangsu TÜV Product Service Ltd. – Shenzhen Branch issued reports.

This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval



1 Table of Contents

1	Table of Contents.....	2
2	Details about the Test Laboratory.....	3
3	Description of the Equipment Under Test.....	4
4	Summary of Test Standards.....	5
5	Summary of Test Results.....	6
6	General Remarks.....	7
7	Technical Requirements.....	8
7.1	Conducted Emission AC Power Port.....	8
7.2	Conducted Peak Power.....	12
7.3	Band edge compliance of RF emission.....	14
7.4	Spurious RF Conducted emission.....	24
7.5	Spurious radiated emissions.....	29
7.6	6dB bandwidth.....	33
7.7	Power spectral density.....	39
8	System Measurement Uncertainty.....	45



2 Details about the Test Laboratory

Details about the Test Laboratory

Company name: Jiangsu TÜV Product Service Ltd. – Shenzhen Branch
6th Floor, H Hall,
Century Craftwork Culture Square,
No. 4001, Fuqiang Road,
Futian District 518048,
Shenzhen,P.R.C.

Telephone: 86 755 8828 6998
Fax: 86 755 8828 5299

Company name: China Shenzhen Academy of Metrology and Quality Inspection,
Metrology and Quality Inspection building,
Central Section of LongZhu Road,
Nan Shan,
Shenzhen,

Telephone: 86 755 2694 1599
Fax: 86 755 2694 1545

Company name: Audix Technology (shenzhen) Co.,Ltd
Block Shenzhen, Science & Industry Park,
Nantou, Shenzhen,
Guangdong,
China

Telephone: 86 755 2663 9496
Fax: 86 755 2663 2877



3 Description of the Equipment Under Test

Description of the Equipment Under Test

Product: MP6 Module

Model no.: 287380

Serial number: NIL

Options and accessories: NIL

Rating: DC 5V, 10W
AC Adaptor:
Input: 100-240V ~ 50/60Hz 0.5A
Output: 5V DC 2A

Antenna: Integral antenna inside enclosure of EUT, NOT accessible by end user
Antenna Gain=1dBi

RF Transmission
Frequency: 2412-2462MHz

Description of the EUT: NIL

Auxiliary Equipment and Cable Used during Test:

DESCRIPTION	MANUFACTURER	MODEL NO.(SHIELD)	S/N(LENGTH)
USB flash drive	Kingston	Data Traveller	----
SD card	Kingston	SD4/4GBFE	----



Product Service

4 Summary of Test Standards

Test Standards	
FCC Part 15 Subpart C	PART 15 - RADIO FREQUENCY DEVICES Subpart C - Intentional Radiators

**5 Summary of Test Results**

Technical Requirements				
FCC Part 15 Subpart C				
Test Condition	Pages	Test Result		
		Pass	Fail	N/A
15.207 Conducted Emission AC Power Port	8	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
15.247 (b) (1) Conducted peak output power	12	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
15.247(d) Band edge compliance of RF emissions	14	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
15.247(d) Spurious RF conducted emissions	24	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
15.247(d) 15.209 Spurious radiated emissions	29	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
15.247(a)(2) 6dB bandwidth	33	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
15.247(e) Power spectral density	39	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>



6 General Remarks

Remarks

This submittal(s) (test report) is intended for FCC ID: OMC287380 comply with Section 15.207, 15.209, 15.247 of the FCC Part 15, Subpart C Rules.

SUMMARY:

All tests according to the regulations cited on page 5 were

- Performed

- **Not** Performed

The Equipment Under Test

- **Fulfills** the general approval requirements.

- **Does not** fulfill the general approval requirements.

Sample Received Date: 17 December 2009

Testing Start Date: 23 December 2009

Testing End Date: 25 December 2009

- Jiangsu TÜV Product Service Ltd. – Shenzhen Branch -

Reviewed by:

Prepared by:

Paul Yu
EMC Project Manager

Ken Li
EMC Test Engineer

7 Technical Requirement

7.1 Conducted Emission

Test Method

- 1 The EUT was placed on a table, which is 0.8m above ground plane
- 2 The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.).
- 3 Maximum procedure was performed to ensure EUT compliance
- 4 A EMI test receiver (R&S Test Receiver ESCS30) is used to test the emissions from both sides of AC line

Limit


Frequency MHz	QP Limit dB μ V	AV Limit dB μ V
0.150-0.500	66-56*	56-46*
0.500-5	56	46
5-30	60	50

Decreasing linearly with logarithm of the frequency

Conducted Emission

Conducted disturbance

EUT: M/N:287380
 Op Cond: WiFi
 Test Spec: L
 Comment: AC 120V/60Hz



Frequency MHz	Cable Loss dB	Reading dBμV	QP Test result dBμV	QP Limit dBμV	Margin dB
0.174	9.8	28.6	38.4	64.8	26.4
0.210	9.8	23.7	33.5	63.2	29.7
0.550	9.9	23.1	33.0	56	23


Frequency MHz	Cable Loss dB	Reading dBμV	AV Test result dBμV	AV Limit dBμV	Margin dB
0.174	9.8	10.9	20.7	54.8	34.1
0.210	9.8	4.4	14.2	53.2	39
0.550	9.9	3.4	13.3	46	32.7

Remark: Test Result= Reading + Cable Loss

Conducted Emission

Conducted disturbance

EUT: M/N:287380
 Op Cond: WiFi
 Test Spec: N
 Comment: AC 120V/60Hz



Frequency MHz	Cable Loss dB	Reading dBμV	QP Test result dBμV	QP Limit dBμV	Margin dB
0.174	9.8	28.3	38.1	64.8	26.7
0.550	9.9	23.2	33.1	56	22.9
6.715	9.9	16.5	26.4	60	33.6

Frequency MHz	Cable Loss dB	Reading dBμV	AV Test result dBμV	AV Limit dBμV	Margin dB
0.174	9.8	9.1	18.9	54.8	35.9
0.550	9.9	3.7	13.6	46	32.4
6.715	9.9	4.9	14.8	50	35.2

Remark: Test Result= Reading + Cable Loss



Test Equipment List

DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL DUE DATE
EMI Test Receiver	Rohde & Schwarz	ESCS30	100003	Dec 23 2009
AMN	Rohde & Schwarz	ESH3-Z5	100229	Dec 23 2009
AMN	Rohde & Schwarz	ENV216	100042	Dec 23 2009

7.2 Conducted peak output power

Test Method

The transmitter output is connected to the Spectrum analyzer. The Spectrum analyzer is set to the peak power detection.

Limits for conducted peak output power measurements

Frequency Range MHz	Limit W	Limit dBm
2400-2483	≤1	≤30

Conducted peak output power

IEEE 802.11g modulation (6Mbps) Test Result

Frequency MHz	Conducted Peak Output Power dBm	Result
CH1 2412MHz	16.95	Pass
CH6 2437MHz	17.06	Pass
CH11 2462MHz	16.74	Pass

IEEE 802.11b modulation (1Mbps) Test Result

Frequency MHz	Conducted Peak Output Power dBm	Result
CH1 2412MHz	17.74	Pass
CH6 2437MHz	17.63	Pass
CH11 2462MHz	17.28	Pass



Product Service

Test Equipment

DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL DUE DATE
Spectrum Analyzer	Agilent	E4446A	US44300459	2010-05-10

7.3 Band edge compliance of RF emissions

Test Method

The band edge compliance of RF radiated emission should be measured by following the guidance in ANSI C63.4 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW and VBW to 1MHz to measure the peak field strength and set RBW to 1MHz and VBW to 10Hz to measure the average radiated field strength.

The conducted RF band edge was measured by using a spectrum analyzer. Set span wide enough to capture the highest in-band emission and the emission at the band edge. Set RBW and VBW to 100kHz, to measure the conducted peak band edge.

Limits


According to §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)).

Frequency MHz	Limit Average dBuV/m	Limit Peak dBuV/m
Below 2390 Above 2483.5	54	74

Band edge compliance of RF emissions

IEEE 802.11g modulation (6 Mbps) Test Result

Lower Edge PK plot:




Site no. : 3m Chamber Data no. : 11
 Dis. / Ant. : 3m 3115(0911) Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 25°C/60% Engineer : Paul Tian
 EUT : 287380
 Power : 120V/60Hz
 Test mode : Tx 11g CH1
 M/N :

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2360.600	29.42	8.44	35.91	45.92	47.87	74.00	26.13	Peak
2	2390.000	29.44	8.41	36.09	54.53	56.29	74.00	17.71	Peak
3	2400.000	29.44	8.60	36.09	68.88	70.83	74.00	3.17	Peak
4	2418.905	29.45	8.60	35.95	92.83	94.93	74.00	-20.93	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Lower Edge AV plot:



Site no.	: 3m Chamber	Data no.	: 12
Dis. / Ant.	: 3m 3115(0911)	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C AV	Engineer	: Paul Tian
Env. / Ins.	: 25°C/60%		
EUT	: 287380		
Power	: 120V/60Hz		
Test mode	: Tx 11g CH1		
M/N	:		


	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	29.41	8.57	35.99	32.86	34.85	54.00	19.15	Average
2	29.44	8.41	36.09	37.35	39.11	54.00	14.89	Average
3	29.44	8.60	36.09	45.54	47.49	54.00	6.51	Average
4	29.45	8.60	35.95	70.30	72.40	54.00	-18.40	Average

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Upper Edge PK plot:

Data: 13 File: E:\2009 test data\T\TUV\20091225.EM6 (16) Date: 2009-12-25



```

Site no.      : 3m Chamber           Data no.   : 13
Dis. / Ant.  : 3m 3115(0911)       Ant. pol.  : HORIZONTAL
Limit        : FCC PART 15C PEAK
Env. / Ins.  : 25*C/60%           Engineer   : Paul Tian
EUT         : 287380
Power       : 120V/60Hz
Test mode    : Tx 11g CH11
M/N         :
    
```


	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2455.100	29.48	8.48	36.02	94.66	96.60	74.00	-22.60	Peak
2	2483.500	29.49	8.94	35.97	58.29	60.75	74.00	13.25	Peak
3	2500.000	29.50	8.89	36.00	45.17	47.56	74.00	26.44	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Upper Edge AV plot:

Data: 14 File: E:\2009 test data\T\TUV\20091225.EM6 (16) Date: 2009-12-25



Site no.	: 3m Chamber	Data no.	: 14
Dis. / Ant.	: 3m 3115(0911)	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C AV		
Env. / Ins.	: 25°C/60%	Engineer	: Paul Tian
EUT	: 287380		
Power	: 120V/60Hz		
Test mode	: Tx 11g CH11		
M/N	:		

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBUV)	Emission			Remark
						Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	
1	2467.400	29.48	8.76	36.02	70.85	73.07	54.00	-19.07	Average
2	2483.500	29.49	8.94	35.97	39.12	41.58	54.00	12.42	Average
3	2500.000	29.50	8.89	36.00	33.52	35.91	54.00	18.09	Average


Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Band edge compliance of RF emissions

IEEE 802.11b modulation (6 Mbps) Test Result

Lower Edge PK Plot:




Site no.	: 3m Chamber	Data no.	: 3
Dis. / Ant.	: 3m 3115(0911)	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK	Engineer	: Paul Tian
Env. / Ins.	: 25°C/60%		
EUT	: 287380		
Power	: 120V/60Hz		
Test mode	: Tx 11b CH1		
M/N	:		

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2334.725	29.41	8.64	35.99	45.72	47.78	74.00	26.22	Peak
2	2390.000	29.44	8.41	36.09	44.62	46.38	74.00	27.62	Peak
3	2397.055	29.44	8.41	36.09	54.27	56.03	74.00	17.97	Peak
4	2400.000	29.44	8.60	36.09	50.40	52.35	74.00	21.65	Peak
5	2412.925	29.45	8.60	35.95	92.21	94.31	74.00	-20.31	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Lower Edge AV Plot:



Site no.	: 3m Chamber	Data no.	: 4
Dis. / Ant.	: 3m 3115(0911)	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C AV	Engineer	: Paul Tian
Env. / Ins.	: 25°C/60%		
EUT	: 287380		
Power	: 120V/60Hz		
Test mode	: Tx 11b CH1		
M/N	:		

	Ant. Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2326.675	29.40	8.64	36.06	32.66	34.64	54.00	19.36	Average
2	2390.000	29.44	8.41	36.09	33.15	34.91	54.00	19.09	Average
3	2397.630	29.44	8.41	36.09	41.93	43.69	54.00	10.31	Average
4	2400.000	29.44	8.60	36.09	37.75	39.70	54.00	14.30	Average
5	2411.200	29.45	8.60	35.95	68.41	70.51	54.00	-16.51	Average


Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Upper Edge PK Plot:

Data: 5 File: E:\2009 test data\TUV\20091225.EM6 (16)

Date: 2009-12-25



Site no.	: 3m Chamber	Data no.	: 5
Dis. / Ant.	: 3m 3115(0911)	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK	Engineer	: Paul Tian
Env. / Ins.	: 25°C/60%		
EUT	: 287380		
Power	: 120V/60Hz		
Test mode	: Tx 11b CH11		
M/N	:		


	Ant. Factor (MHz)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark	
1	2463.020	29.48	8.76	36.02	88.66	90.88	74.00	-16.88	Peak
2	2483.500	29.49	8.94	35.97	43.59	46.05	74.00	27.95	Peak
3	2500.000	29.50	8.89	36.00	43.94	46.33	74.00	27.67	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Lower Edge AV Plot:

Data: 6 File: E:\2009 test data\T\TUV\20091225.EM6 (16) Date: 2009-12-25



Site no.	: 3m Chamber	Data no.	: 6
Dis. / Ant.	: 3m 3115(0911)	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C AV	Engineer	: Paul Tian
Env. / Ins.	: 25°C/60%		
EUT	: 287380		
Power	: 120V/60Hz		
Test mode	: Tx 11b CH11		
M/N	:		

	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	29.48	8.76	36.02	65.94	68.16	54.00	-14.16	Average
2	29.49	8.94	35.97	33.01	35.47	54.00	18.53	Average
3	29.50	8.89	36.00	32.59	34.98	54.00	19.02	Average

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.



Test Equipment List

DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL DUE DATE
Spectrum	Agilent	E4446A	US44300459	May 10 2010
Amp	HP	8449B	3008A02495	May 10 2010
Antenna	EMCO	3115	9607-4877	May 10 2010
HF Cable	Hubersuhne	Sucoflex104	---	May 10 2010

7.4 Spurious RF conducted emissions

Test Method

The transmitter output is connected to the Spectrum analyzer. The Spectrum analyzer is set to the peak power detection.


Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The resolution bandwidth(RBW) and the video bandwidth (VBW) of the spectrum analyzer were respectively set to 100kHz and 100kHz.


Limit

Frequency Range MHz	Limit (dBc)
1000-25000	-20

Spurious RF conducted emissions
 IEEE 802.11g modulation (6 Mbps) Test Result
 2412MHz




2437MHz




Spurious RF conducted emissions

2462MHz




IEEE 802.11b modulation (1 Mbps) Test Result

2412MHz




Spurious RF conducted emissions

2437MHz



2462MHz





Product Service

Test Equipment List

DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL.DUE.DATE
Spectrum Analyzer	Agilent	E4446A	US44300459	2010-05-10

7.5 Spurious radiated emissions

Test Method

- 1 The EUT is placed on a turntable, which is 0.8m above ground plane.
- 2 The turntable shall be rotated for 360 degrees to determine the position of maximum emission level
- 3 EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
- 4 Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 5 Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.

Limit

Frequency MHz	Field Strength uV/m	Field Strength dB μ V/m	Detector
30-88	100	40	QP
88-216	150	43.5	QP
216-960	200	46	QP
960-1000	500	54	QP
Above 1000	500	54	AV
Above 1000	5000	74	PK

Radiated Emission

IEEE 802.11g modulation (6 Mbps) CH1 2412MHz Test Result

Frequency MHz	Cable Loss dB	Antenna Factor dB/m	Reading dBuV	Emission Level dBuV/m	Polarization	Limit dBuV/m	Detector	Result
138.857	2.1	12.1	20.1	43.5	Vertical	40.0	QP	Pass
243.871	2.7	12.4	26.2	46.0	Horizontal	46.0	QP	Pass
333.246	2.9	14.7	22.1	46.0	Horizontal	40.0	QP	Pass
4824.000	4.2	33.3	3.8	41.3	Horizontal	74	PK	Pass
4824.000	4.2	33.3	1.2	38.7	Horizontal	54	AV	Pass
7236.000	-	-	-	-	-	-	-	-
7236.000	-	-	-	-	-	-	-	-

IEEE 802.11g modulation (6 Mbps) CH6 2437MHz Test Result

Frequency MHz	Cable Loss dB	Antenna Factor dB/m	Reading dBuV	Emission Level dBuV/m	Polarization	Limit dBuV/m	Detector	Result
4874.000	4.3	33.3	3.7	41.3	Horizontal	74	PK	Pass
4874.000	4.3	33.3	1.7	39.3	Horizontal	54	AV	Pass
7311.000	-	-	-	-	-	-	-	-
7311.000	-	-	-	-	-	-	-	-

IEEE 802.11g modulation (6 Mbps) CH11 2462MHz Test Result

Frequency MHz	Cable Loss dB	Antenna Factor dB/m	Reading dBuV	Emission Level dBuV/m	Polarization	Limit dBuV/m	Detector	Result
4924.000	4.3	33.3	3.0	40.6	Horizontal	74	PK	Pass
4924.000	4.3	33.3	1.5	39.1	Horizontal	54	AV	Pass
7386.000	-	-	-	-	-	-	-	-
7386.000	-	-	-	-	-	-	-	-

Remark:

- (1) Emission Level= Cable Loss(include amplifier factor) + Antenna Factor + Reading
- (2) Data of measurement within this frequency range shown "-" in the table above means the reading of emissions are attenuated more than 20db below the permissible limits or the field strength is too small to be measured.

Radiated Emission

IEEE 802.11b modulation (1 Mbps) CH1 2412MHz Test Result

Frequency MHz	Cable Loss dB	Antenna Factor dB/m	Reading dBuV	Emission Level dBuV/m	Polarization	Limit dBuV/m	Detector	Result
288.537	2.9	13.5	18.6	35.0	Vertical	46.0	QP	Pass
288.537	2.9	13.5	24.3	40.7	Horizontal	46.0	QP	Pass
465.430	3.6	17.4	17.8	38.8	Horizontal	46.0	QP	Pass
4824.000	4.2	33.3	4.5	42.0	Horizontal	74	PK	Pass
4824.000	4.2	33.3	2.0	39.5	Horizontal	54	AV	Pass
7236.000	-	-	-	-	-	-	-	-
7236.000	-	-	-	-	-	-	-	-

IEEE 802.11b modulation (1 Mbps) CH6 2437MHz Test Result

Frequency MHz	Cable Loss dB	Antenna Factor dB/m	Reading dBuV	Emission Level dBuV/m	Polarization	Limit dBuV/m	Detector	Result
4874.000	4.3	33.3	4.5	42.1	Horizontal	74	PK	Pass
4874.000	4.3	33.3	1.7	39.3	Horizontal	54	AV	Pass
7311.000	-	-	-	-	-	-	-	-
7311.000	-	-	-	-	-	-	-	-

IEEE 802.11b modulation (1 Mbps) CH11 2462MHz Test Result

Frequency MHz	Cable Loss dB	Antenna Factor dB/m	Reading dBuV	Emission Level dBuV/m	Polarization	Limit dBuV/m	Detector	Result
4924.000	4.3	33.3	4.2	41.8	Horizontal	74	PK	Pass
4924.000	4.3	33.3	1.6	39.2	Horizontal	54	AV	Pass
7386.000	-	-	-	-	-	-	-	-
7386.000	-	-	-	-	-	-	-	-

Remark:

- (1) Emission Level= Cable Loss(include amplifier factor) + Antenna Factor + Reading
- (2) Data of measurement within this frequency range shown "-" in the table above means the reading of emissions are attenuated more than 20db below the permissible limits or the field strength is too small to be measured.



Test Equipment List

DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL DUE DATE
EMI Test Receiver	Rohde & Schwarz	ES126	838786/013	Dec 23 2009
Bilog Antenna	Chase	CBL6112B	2591	Dec 23 2009
Signal Generator	Rohde & Schwarz	SMR20	100047	Dec 23 2009
Antenna	Schwarzbeck	VUBA9117	115	Dec 23 2009
Horn Antenna	Rohde & Schwarz	HF906	100013	Dec 23 2009

7.6 6 dB bandwidth

Test Method

- 1 Place the EUT on the table and set it in the transmitting mode.
- 2 Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3 Mark the peak frequency and -6dB (upper and lower) frequency.

Limit


Limit [kHz]

≥ 500


6 dB bandwidth

IEEE 802.11g modulation (6Mbps) Test Result

Frequency MHz	Bandwidth kHz	Limit kHz	Result
2412	16424	≥ 500	Pass
2437	16429	≥ 500	Pass
2462	16443	≥ 500	Pass




6 dB bandwidth




6 dB bandwidth

IEEE 802.11b modulation (1Mbps) Test Result

Frequency MHz	Bandwidth kHz	Limit kHz	Result
2412	10146	≥ 500	Pass
2437	9217	≥ 500	Pass
2462	10146	≥ 500	Pass



6 dB bandwidth





Product Service

Test Equipment

DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL.DUE.DATE
Spectrum Analyzer	Agilent	E4446A	US44300459	2010-05-10

7.7 Power spectral density

Test Method

- 1 Place the EUT on the table and set it in transmitting mode. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 2 Set the spectrum analyzer as RBW = 3 kHz, VBW = 10 kHz, Span = 300kHz, Sweep = 100 s
- 3 Record the max reading.

Limit


Limit
dBm / 3 kHz

8



Power spectral density

IEEE 802.11g modulation (6Mbps) Test Result

Frequency MHz	P dBm	Result
2412	-21.54	Pass
2437	-19.97	Pass
2462	-19.71	Pass




Power spectral density





Power spectral density

IEEE 802.11b modulation (1Mbps) Test Result

Frequency MHz	P dBm	Result
2412	-7.98	Pass
2437	-4.60	Pass
2462	1.98	Pass



Power spectral density





Product Service

Test Equipment

DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL.DUE.DATE
Spectrum Analyzer	Agilent	E4446A	US44300459	2010-05-10

8 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

System Measurement Uncertainty

Items		Extended Uncertainty
RE	Field strength (dB μ V/m)	U=4.6dB; k=2(30MHz-1GHz)
CE	Disturbance Voltage (dB μ V)	U=3.3dB; k=2