



RF EXPOSURE REPORT

Product: 402548 module

Model Name: MP14-ARGON

FCC ID: OMC402548

Applicant: Icon Health & Fitness, Inc.

Address: 1500 South 1000 West 435-786-5915 Logan, UT 84321, United

States

Manufacturer: Icon Health & Fitness, Inc.

Address: 1500 South 1000 West 435-786-5915 Logan, UT 84321, United

States

Prepared by: BV 7Layers Communications Technology (Shenzhen) Co. Ltd

Lab Location: No.B102, Dazu Chuangxin Mansion, North of Beihuan Avenue,

North Area, Hi-Tech Industrial Park, Nanshan District,

Shenzhen, Guangdong, China

TEL: +86 755 8869 6566

FAX: +86 755 8869 6577

E-MAIL: customerservice.dg@cn.bureauveritas.com

Report No.: SA180830W006-1

Received Date: Aug. 30, 2018

Test Date: Aug. 31, 2018 ~ Oct. 23, 2018

Issued Date: Oct. 24, 2018

This report should not be used by the client to claim product certification, approval, or endorsement by A2LA or any government agencies.

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute you unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



TABLE OF CONTENTS

RI	FEXE	POSURE REPORT	1
RI	ELEA	ASE CONTROL RECORD	3
		CERTIFICATION	
2		GENERAL INFORMATION	5
		GENERAL DESCRIPTION OF EUT	
3		RF EXPOSURE	7
	3.1	LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)	7
	3.2	MPE CALCULATION FORMULA	7
	3.3	CLASSIFICATION	7
	3.4	CONDUCTED POWER	8
		CALCULATION RESULT OF MAXIMUM CONDUCTED POWER	

Tel: +86 755 8869 6566



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
SA180830W006-1	Original release	Oct. 24, 2018

Report Version 1

Tel: +86 755 8869 6566

Fax: +86 755 8869 6577

BV 7Layers Communications Technology

(Shenzhen) Co. Ltd



1 CERTIFICATION

PRODUCT: 402548 module

BRAND NAME: N/A

MODEL NAME: MP14-ARGON

APPLICANT: Icon Health & Fitness, Inc.

TESTED: Aug. 31, 2018 ~ Oct. 23, 2018

TEST SAMPLE: Production Unit

STANDARDS: FCC Part 2 (Section 2.1091)

FCC OET Bulletin 65, Supplement C (01-01)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1

The above equipment has been tested by **BV 7Layers Communications Technology (Shenzhen) Co. Ltd** and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

(Roger Li/ Engineer)

APPROVED BY: , **DATE**: Oct. 24, 2018

(Sam Tung / Manager)



2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT	402548 module		
MODEL NAME	MP14-ARGON		
NOMINAL VOLTAGE	12Vdc (adapter or h	nost equipment)	
OPERATING TEMPERATURE RANGE	0 ~ 40°C		
	WLAN	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM	
MODULATION TYPE	BT_LE	BT-LE(GFSK) for DTS	
	Bluetooth	GFSK, π/4-DQPSK, 8DPSK	
OPERATING FREQUENCY	WLAN	2412 ~ 2462MHz for 11b/g/n(HT20) 5180 ~ 5240MHz, 5260 ~ 5320MHz, 5500 ~ 5700MHz, 5745 ~ 5805MHz for 11a/n(HT20)/n(HT40)	
	Bluetooth/BT_LE	2402MHz ~ 2480MHz	
ANTENNA TYPE	PIFA Antenna		
ANTENNA GAIN	2.17dBi for BT/2.4G WLAN 2.93dBi for 5G WLAN		
HW VERSION	A184C V2.0		
SW VERSION	Model number J1002		
I/O PORTS	Refer to user's manual		
CABLE SUPPLIED	N/A		

NOTE:

- 1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- 2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
- 3. The EUT was powered by the following LCD Panels:

LCD PANEL 1				
BRAND:	N/A			
MODEL:	NV140FHM-N46			
SPEC:	14.0 inch			
MANUFACTUR:	CHONGQINGBOE OPTOELECTRONICS			
IVIAINUFACTUR:	TECHNOLOGY CO, LTD			

Page 5 of 12



LCD Panel 2				
BRAND:	N/A			
MODEL:	NV140-FHM-N43			
SPEC:	14.0 inch			
MANUFACTUR:	BEIJING BOE DISPLAY TECHNOLOGY			

4. LCD 1 Full test, LCD 2 verify, only the worst case data include in the report.



3 RF EXPOSURE

3.1 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm²)	AVERAGE TIME (minutes)		
LIMI	LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE					
300-1500			F/1500	30		
1500-100,000			1.0	30		

F = Frequency in MHz

3.2 MPE CALCULATION FORMULA

Pd = (Pout*G) / (4*pi*r2)

where

Pd = power density in mW/cm2

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

3.3 CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.



3.4 CONDUCTED POWER

Bluetooth

GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	Tune-up Power (dBm)	PASS/FAIL
0	2402	5.60	6.0	N/A
39	2441	5.08	6.0	N/A
78	2480	3.81	4.0	N/A

π /4 DQPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	Tune-up Power (dBm)	PASS/FAIL
0	2402	1.37	1.5	N/A
39	2441	2.58	3.0	N/A
78	2480	2.96	3.0	N/A

8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	Tune-up Power (dBm)	PASS/FAIL
0	2402	2.67	3.0	N/A
39	2441	2.11	3.0	N/A
78	2480	1.39	1.5	N/A

BT-LE (GFSK)

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	Tune-up Power (dBm)	PASS/FAIL
0	2402	-1.30	-1.0	N/A
19	2440	-1.40	-1.0	N/A
39	2480	-2.41	-2.0	N/A



WIFI 2.4G

802.11b

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	Tune-up Power (dBm)	PASS/FAIL
1	2412	14.93	15.5	N/A
6	2437	15.06	15.5	N/A
11	2462	15.03	15.5	N/A

802.11g

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	Tune-up Power (dBm)	PASS/FAIL
1	2412	13.06	13.5	N/A
6	2437	13.98	14.0	N/A
11	2462	12.90	13.5	N/A

802.11n (20MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	Tune-up Power (dBm)	PASS/FAIL	
1	2412	12.87	13.0	N/A	
6	6 2437		13.0	N/A	
11	2462	12.85	13.0	N/A	



WIFI 5G

802.11a

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	Tune-up Power (dBm)	PASS/FAIL
36	5180	14.04	14.5	PASS
40	5200	14.03	14.5	PASS
48	5240	14.07	14.5	PASS
52	5260	13.98	14.5	PASS
60	5300	14.14	14.5	PASS
64	5320	13.92	14.5	PASS
100	5500	14.26	14.5	PASS
116	5580	14.04	14.5	PASS
140	5700	13.90	14.5	PASS
149	5745	13.83	14.5	PASS
157	5785	14.10	14.5	PASS
161	5805	14.09	14.5	PASS

802.11n (20MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	Tune-up Power (dBm)	PASS/FAIL
36	5180	13.41	13.5	PASS
40	5200	13.18	13.5	PASS
48	5240	13.02	13.5	PASS
52	5260	13.08	13.5	PASS
60	5300	13.26	13.5	PASS
64	5320	12.97	13.5	PASS
100	5500	13.36	13.5	PASS
116	5580	13.08	13.5	PASS
140	5700	13.07	13.5	PASS
149	5745	13.24	13.5	PASS
157	5785	13.13	13.5	PASS
161	5805	13.31	13.5	PASS



802.11n (40MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	Tune-up Power (dBm)	PASS/FAIL	
38	5190	12.40	12.5	PASS	
46	5230	13.16	13.5	PASS	
54	5270	13.28	13.5	PASS	
62	5310	12.13	12.5	PASS	
102	5510	11.56	12.0	PASS	
110	5550	13.25	13.5	PASS	
134	5670	13.16	13.5	PASS	
151	5755	12.98	13.5	PASS	
159	5795	13.28	13.5	PASS	

Page 11 of 12



3.5 CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

TUNE-UP POWER TABLE

Band	Frequency (MHz)	Operating Mode	Tune-Up Power And Tolerance (dBm)	
Bluetooth	2402	GFSK	5.5 ± 0.5	
WIFI 2.4G	2437	11b	15.0 ± 0.5	
WIFI 5G B1	5240	11a	14.0 ± 0.5	
WIFI 5G B2	5300	11a	14.0 ± 0.5	
WIFI 5G B3	5500	11a	14.0 ± 0.5	
WIFI 5G B4	5785	11a	14.0 ± 0.5	

CALCULATION RESUL

Band	Frequency (MHz)		Gain	Tune-up Power	E.I.R.P Power	Power Density	limit (mW/cm^2)	PASS / FAIL
Plustaath	2402	GFSK	(dBi) 2.17	(dBm)	(mW) 6.561	(mW/cm^2) 0.001	,	PASS
Bluetooth WIFI 2.4G	2402	11b	2.17	6.0 15.5	58.479	0.001	1.00	PASS
WIFI 5G B1	5240	11a	2.93	14.5	55.335	0.012	1.00	PASS
WIFI 5G B2	5300	11a	2.93	14.5	55.335	0.011	1.00	PASS
WIFI 5G B3	5500	11a	2.93	14.5	55.335	0.011	1.00	PASS
WIFI 5G B4	5785	11a	2.93	14.5	55.335	0.011	1.00	PASS

Note: The WLAN and Bluetooth cannot transmit simultaneously, so there is no co-location test requirement for WLAN and Bluetooth.

--END--