



# RF EXPOSURE REPORT

**REPORT NO.:** SA950918L07

**MODEL NO.:** DL-MEMOR 001-904-416  
DL-MEMOR 001-804-416

**ACCORDING:** FCC Guidelines for Human Exposure  
IEEE C95.1

**APPLICANT:** Datalogic S.p.A.

**ADDRESS:** ViaCandini,2 40012 Lippo di Calderara di Reno  
Bologna-Italy

**ISSUED BY:** Advance Data Technology Corporation

**LAB ADDRESS:** 47 14<sup>th</sup> Lin, Chiapau Tsun, Linko, Taipei, Taiwan,  
R.O.C.

**TEST LOCATION:** No. 19, Hwa Ya 2<sup>nd</sup> Rd., Kueishan, Taoyuan,  
Taiwan, R.O.C.



## Conclusion

No Evaluation Required if power is below this threshold:

F(GHz)		mW
Low	2.402	24.580
High	2.480	

Maximum measured transmitter power:

Pout (dBm)		Pout (mW)
Conducted Power	1.300	1.349
EIRP Power	3.050	2.018

**\*NOTE:** The antenna is Printed antenna with 1.75dBi gain

Threshold for no SAR evaluation is 24.580mW

Transmitter power is 2.018mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold