

FCC EMC Test Report

Project No. : 1909C108
Equipment : ALARM CLOCK
Brand Name : LA CROSSE
Test Model : 617-148
Series Model : CA79806, CA79806-INT, CA79806vX, CA79806vX-INT, CA79806-XX, CA79806-XX-INT, 617-148-INT, 617-148vX, 617-148vX-INT, 617-148-XX, 617-148-XX-INT (X can be 0~9, the difference for different version are the product shell color , software, and packaging upgrade version number, when upgrade a version the number progressed to next number)
Applicant : La Crosse Technology Ltd.
Address : 2809 Losey Blvd. S. La Crosse Wisconsin 54601 United States
Manufacturer : La Crosse Technology
Address : 2809 Losey Blvd. S. La Crosse Wisconsin 54601 United States
Factory : La Crosse Technology
Address : 2809 Losey Blvd. S. La Crosse Wisconsin 54601 United States
Date of Receipt : Sep. 19, 2019
Date of Test : Sep. 23, 2019 ~ Sep. 30, 2019
Issued Date : Oct. 22, 2019
Report Version : R01
Test Sample : Engineering Sample No.: DG20190919114
Standard(s) : FCC Part 18

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

Simon Ling

Prepared by : Simon Ling

Kevin Li

Approved by : Kevin Li



Certificate #5123.02

Add: No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, Guangdong, China.

Tel: +86-769-8318-3000

Web: www.newbtl.com

Declaration

BTL represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

BTL's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

The report must not be used by the client to claim product certification, approval, or endorsement by NIST, A2LA, or any agency of the U.S. Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and ourselves, the test report shall not be reproduced, except in full, without our written approval.

BTL's laboratory quality assurance procedures are in compliance with the **ISO/IEC 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

BTL is not responsible for the sampling stage, so the results only apply to the sample as received.

The information, data and test plan are provided by manufacturer which may affect the validity of results, so it is manufacturer's responsibility to ensure that the apparatus meets the essential requirements of applied standards and in all the possible configurations as representative of its intended use.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Please note that the measurement uncertainty is provided for informational purpose only and are not use in determining the Pass/Fail results.

Table of Contents	Page
REPORT ISSUED HISTORY	4
1 . SUMMARY OF TEST RESULTS	5
1.1 TEST FACILITY	6
1.2 MEASUREMENT UNCERTAINTY	6
1.3 TEST ENVIRONMENT CONDITIONS	6
2 . GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF EUT	7
2.2 DESCRIPTION OF TEST MODES	7
2.3 EUT OPERATING CONDITIONS	8
2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	8
2.5 DESCRIPTION OF SUPPORT UNITS	8
3 . EMC EMISSION TEST	9
3.1 AC POWER LINE CONDUCTED EMISSIONS TEST	9
3.1.1 LIMIT	9
3.1.2 MEASUREMENT INSTRUMENTS LIST	9
3.1.3 TEST PROCEDURE	10
3.1.4 DEVIATION FROM TEST STANDARD	10
3.1.5 TEST SETUP	10
3.1.6 TEST RESULTS	10
3.2 RADIATED EMISSIONS 9KHZ TO 30MHZ	13
3.2.1 LIMITS	13
3.2.2 MEASUREMENT INSTRUMENTS LIST	13
3.2.3 TEST PROCEDURE	14
3.2.4 DEVIATION FROM TEST STANDARD	14
3.2.5 TEST SETUP	14
3.2.6 TEST RESULTS	14
4 . EUT TEST PHOTO	17

REPORT ISSUED HISTORY

Report Version	Description	Issued Date
R00	Original Issue.	Oct. 11, 2019
R01	Changed series model name.	Oct. 22, 2019

1. SUMMARY OF TEST RESULTS

Emission		
Ref Standard(s)	Test Item	Result
FCC/OST MP-5 (1986)	AC Power Line Conducted Emissions	PASS
	Radiated emission 9kHz to 30MHz	PASS
	Radiated emission between 30MHz and 1000MHz	N/A
	Radiated emission Above 1 GHz	N/A

NOTE:

(1) "N/A" denotes test is not applicable to this device.

1.1 TEST FACILITY

The test facilities used to collect the test data in this report at the location of No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, Guangdong, China.

BTL's Test Firm Registration Number for FCC: 357015

BTL's Designation Number for FCC: CN1240

1.2 MEASUREMENT UNCERTAINTY

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

The BTL measurement uncertainty as below table:

A. AC power line conducted emissions test:

Test Site	Method	Measurement Frequency Range	U,(dB)
DG-C02	CISPR	150 kHz ~ 30MHz	2.32

B. Radiated emissions test:

Test Site	Method	Measurement Frequency Range	U,(dB)
DG-CB01	CISPR	9kHz ~ 150kHz	2.58
		150kHz ~ 30MHz	2.70

Note: Unless specifically mentioned, the uncertainty of measurement has not been taken into account to declare the compliance or non-compliance to the specification.

1.3 TEST ENVIRONMENT CONDITIONS

Test Item	Temperature	Humidity	Tested By
AC Power Line Conducted Emissions	25°C	53%	Jason Liang
Radiated emissions 9kHz to 30MHz	25°C	60%	Jason Liang

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	ALARM CLOCK
Brand Name	LA CROSSE
Test Model	617-148
Series Model	CA79806, CA79806-INT, CA79806vX, CA79806vX-INT, CA79806-XX, CA79806-XX-INT, 617-148-INT, 617-148vX, 617-148vX-INT, 617-148-XX, 617-148-XX-INT
Model Difference(s)	X can be 0~9, the difference for different version are the product shell color , software, and packaging upgrade version number, when upgrade a version the number progressed to next number
Power Source	DC Voltage supplied from AC/DC adapter. Model: HX13-0502500-AU-001
Power Rating	I/P:100-240V~50/60Hz 0.5A Max O/P:5.0V---2.5A
Connecting I/O Port(s)	1* DC port 1* USB port
Highest Internal Frequency(Fx)	205 kHz

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	FULL SYSTEM

AC Power Line Conducted Emissions test	
Final Test Mode	Description
Mode 1	FULL SYSTEM


Radiated Emissions 9kHz to 30MHz test	
Final Test Mode	Description
Mode 1	FULL SYSTEM

2.3 EUT OPERATING CONDITIONS

The EUT exercise program used during radiated and/or conducted emission measurement was designed to exercise the various system components in a manner similar to a typical use. The standard test signals and output signal as following:

1. EUT connected to adapter via DC cable.
2. EUT connected to load via USB cable.
3. The mobile phone is putted on the EUT.

2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



2.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.
A	Mobile Phone	SAMSUNG	SM-3650/DS	R28KA0BBEEE
B	Load	N/A	N/A	N/A

Item	Cable Type	Shielded Type	Ferrite Core	Length
1	DC Cable	NO	NO	1.5m
2	USB Cable	NO	NO	1m

3. EMC EMISSION TEST

3.1 AC POWER LINE CONDUCTED EMISSIONS TEST

3.1.1 LIMIT

Frequency of Emission (MHz)	Class B (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56 *	56 - 46 *
0.5 - 5.0	56.00	46.00
5.0 - 30.0	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.
- (3) The test result calculated as following:
 Measurement Value = Reading Level + Correct Factor
 Correct Factor = Insertion Loss + Cable Loss + Attenuator Factor(if use)
 Margin Level = Measurement Value - Limit Value

3.1.2 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	EMI Test Receiver	R&S	ESCI	100382	Mar. 10, 2020
2	LISN	EMCO	3816/2	52765	Mar. 10, 2020
3	TWO-LINE V-NETWORK	R&S	ENV216	101447	May. 19, 2020
4	50Ω Terminator	SHX	TF5-3	15041305	Mar. 10, 2020
5	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A
6	Cable	N/A	RG223	12m	Mar. 12, 2020

Remark: "N/A" denotes no model name, serial no. or calibration specified.
 All calibration period of equipment list is one year.


3.1.3 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.
- f. Measuring frequency range from 150KHz to 30MHz.

3.1.4 DEVIATION FROM TEST STANDARD

No deviation

3.1.5 TEST SETUP




3.1.6 TEST RESULTS

Remark


- (1) Reading in which marked as QP means measurements by using are Quasi-Peak Mode with Detector BW=9 kHz; SPA setting in RBW=10 kHz, VBW =10 kHz, Swp. Time = 0.3 sec./MHz. Reading in which marked as AV means measurements by using are Average Mode with instrument setting in RBW=10 kHz, VBW=10 kHz, Swp. Time =0.3 sec./MHz.
- (2) All readings are QP Mode value unless otherwise stated AVG in column of 『Note』. If the QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only QP Mode was measured, but AVG Mode didn't perform. In this case, a “*” marked in AVG Mode column of Interference Voltage Measured.

Test Voltage	AC 120V/60Hz	Phase	Line
Test Mode	Mode 1		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.5370	33.60	9.88	43.48	56.00	-12.52	QP	
2		0.5370	24.15	9.88	34.03	46.00	-11.97	AVG	
3	*	0.5820	37.38	9.89	47.27	56.00	-8.73	QP	
4		0.5820	23.52	9.89	33.41	46.00	-12.59	AVG	
5		1.2345	32.06	9.94	42.00	56.00	-14.00	QP	
6		1.2345	20.15	9.94	30.09	46.00	-15.91	AVG	
7		2.3955	32.20	10.02	42.22	56.00	-13.78	QP	
8		2.3955	21.52	10.02	31.54	46.00	-14.46	AVG	
9		3.1200	31.64	10.06	41.70	56.00	-14.30	QP	
10		3.1200	20.00	10.06	30.06	46.00	-15.94	AVG	
11		18.1860	39.40	11.03	50.43	60.00	-9.57	QP	
12		18.1860	26.85	11.03	37.88	50.00	-12.12	AVG	

Test Voltage	AC 120V/60Hz	Phase	Neutral
Test Mode	Mode 1		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.5460	38.34	10.03	48.37	56.00	-7.63	QP	
2		0.5460	26.00	10.03	36.03	46.00	-9.97	AVG	
3	*	0.5685	40.23	10.04	50.27	56.00	-5.73	QP	
4		0.5685	26.52	10.04	36.56	46.00	-9.44	AVG	
5		0.6000	37.37	10.04	47.41	56.00	-8.59	QP	
6		0.6000	23.52	10.04	33.56	46.00	-12.44	AVG	
7		0.6405	34.26	10.05	44.31	56.00	-11.69	QP	
8		0.6405	21.90	10.05	31.95	46.00	-14.05	AVG	
9		1.1490	33.80	10.13	43.93	56.00	-12.07	QP	
10		1.1490	23.62	10.13	33.75	46.00	-12.25	AVG	
11		1.7205	32.98	10.17	43.15	56.00	-12.85	QP	
12		1.7205	22.63	10.17	32.80	46.00	-13.20	AVG	

3.2 RADIATED EMISSIONS 9KHZ TO 30MHZ

3.2.1 LIMITS

Operating frequency	Field Strength (uV/m)	Measurement Distance (meters)	F.S Limitation at 3m Distance
			(dBuV/m)
Any non-ISM	15	300	103.50

NOTE:

- (1) The Equipment is for 18.305(b) Any type unless otherwise specified (miscellaneous) Operating frequency in any non-ISM frequency
- (2) Operation of ISM equipment within the following safety, search and rescue frequency bands is prohibited: 490–510 kHz, 2170–2194 kHz, 8354–8374 kHz, 121.4–121.6 MHz, 156.7–156.9 MHz, and 242.8–243.2 MHz.
- (3) Distance extrapolation factor = $40 \log(\text{specific distance} / \text{test distance})$ (dB);
Limit line = specific limits (dBuV) + distance extrapolation factor.
- (4) The test result calculated as following:
Measurement Value = Reading Level + Correct Factor
Correct Factor = Antenna Factor + Cable Loss
Margin Level = Measurement Value - Limit Value

3.2.2 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Antenna	ETS	3142B	26419	Mar. 23, 2020
2	EMI Test Receiver	R&S	ESCI	100895	Mar. 10, 2020
3	Cable	Mlcable Inc.	B10-01-01-15M(10MHz~26.5GHz)	18047122	Mar. 22, 2020
4	Controller	ETS-Lindgren	2090	N/A	N/A
5	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A

Remark: "N/A" denotes no model name, serial no. or calibration specified.
All calibration period of equipment list is one year.


3.2.3 TEST PROCEDURE

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The height of the equipment or of the substitution antenna shall be 0.8 m; the antenna shall be supported in the vertical plane and be rotatable about a vertical axis. The lowest point of the loop shall be 1 m above ground level.
- c. The initial step in collecting radiated emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- d. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.2.4 DEVIATION FROM TEST STANDARD

No deviation

3.2.5 TEST SETUP




3.2.6 TEST RESULTS

Remark:


- (1) All readings are Peak unless otherwise stated QP in column of 『 Note 』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform ◦
- (2) Measuring frequency range from 9kHz to 30MHz.
- (3) If the peak scan value lower limit more than 20dB, then this signal data does not show in table.

Test Voltage:	AC 120V/60Hz
Test Mode:	Mode 1



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.0290	41.07	13.85	54.92	103.50	-48.58	QP	
2		0.0393	46.31	13.89	60.20	103.50	-43.30	QP	
3		0.0413	43.74	13.90	57.64	103.50	-45.86	QP	
4		0.0790	39.12	13.54	52.66	103.50	-50.84	QP	
5		0.0827	36.31	13.54	49.85	103.50	-53.65	QP	
6	*	0.1237	61.05	13.55	74.60	103.50	-28.90	QP	

Test Voltage:	AC 120V/60Hz
Test Mode:	Mode 1




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1	*	0.2404	44.92	13.65	58.57	103.50	-44.93	QP	
2		0.3615	43.85	13.39	57.24	103.50	-46.26	QP	
3		0.4837	36.54	13.10	49.64	103.50	-53.86	QP	
4		0.6043	36.48	12.86	49.34	103.50	-54.16	QP	
5		2.1783	43.53	11.71	55.24	103.50	-48.26	QP	
6		13.7680	30.40	11.58	41.98	103.50	-61.52	QP	

4. EUT TEST PHOTO

AC Power Line Conducted Emissions



Radiated Emissions 9 KHz to 30 MHz



End of Test Report