

FCC RF EXPOSURE REPORT

FCC ID: OMOTX145WSDTH

Project No. : 1907C173
Equipment : WIND SENSOR WITH SOLAR PANEL AND
TEMP&HUMIDITY SENSOR
Test Model : TX145WSDTH
Series Models : TX145WSDTH-INT
TX145WSDTHvX
TX145WSDTHvX-INT
TX145WSDTH-XX
TX145WSDTH-XX-INT
Applicant : La Crosse Technology Ltd.
Address : 2809 Losey Blvd. S. La Crosse Wisconsin
54601 United States
According: : FCC Guidelines for Human Exposure IEEE
C95.1 & KDB447498 D01

B T L I N C .

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan,
Guangdong, China.

TEL: +86-769-8318-3000 FAX: +86-769-8319-6000



Certificate #5123.02

REPORT ISSUED HISTORY

Report Version	Description	Issued Date
R00	Original Issue.	Aug. 13, 2019

GENERAL CONCLUSION:

Maximum measured transmitter power:

Output Power (dBm)	Output Power (mW)	Limit(mW)
-29.79	0.0010	10

According to FCC KDB447498 D01 V06, Appendix A, SAR Test Exclusion Thresholds for 100MHz-6GHz and ≤ 50 mm

The maximum measured output peak power of this EUT is 0.0010mW, less than 10mW at 20cm distance.

Conclusion: No SAR evaluation required since transmitter power is below FCC threshold.

End of Test Report