



FCC TEST REPORT

According to

FCC 47 CFR PART 22 SUBPART H AND PART 24 SUBPART E

Applicant	: MAXWEST TELECOM
Address	: 11037 warner ave #201 fountain valley, ca, 92708 USA
Manufacturer	: MAXWEST TELECOM
Address	: 11037 warner ave #201 fountain valley, ca, 92708 USA
Equipment	: Tablet
Model No.	: VIRTUE PHABLET 7; VIRTUE PHABLET 7S; GRAVITY PHABLET 7
Trade Name	: MAXWEST
FCC ID	: ONGVIRTUETAB7

I **HEREBY** CERTIFY THAT :

The measurements shown in this test report were made in accordance with the procedures given in **ANSI C63.4** The equipment was **passed** the test performed according to **FCC Rules and Regulations Part 15 Subpart C (2010)**.

The test was carried out on Jun 10,2014 at **Cerpass Technology (Suzhou) Co.,Ltd**

- The test result refers exclusively to the test presented test model / sample.
- Without written approval of **Cerpass Technology Corp.** the test report shall not be reproduced except in full.
- The test report must not be used by the clients to claim product certification approval by



NVLAP or any agency of the Government.

Table of Contents

1. Report of Measurements and Examinations	6
2. Test Configuration of Equipment under Test	7
2.1. Feature of Equipment under Test	7
2.2. Test Manner	8
2.3. Description of Test System	8
2.4. General Information of Test	9
2.5. Measurement Uncertainty	9
3. Test of Conducted Emission	10
3.1. Test Limit	10
3.2. Test Procedures	10
3.3. Typical Test Setup	11
3.4. Measurement Equipment	11
3.5. Test Result and Data	12
4. FIELD STRENGTH OF SPURIOUS RADIATION MEASUREMENT	14
4.1. Test Limit	14
4.2. Test Procedures	14
4.3. Typical Test Setup	15
4.4. Measurement Equipment	16
4.5. Test Result and Data	17
5. Occupied Bandwidth	53
5.1. Test Limit	53
5.2. Test Procedures	53
5.3. Test Setup Layout	53
5.4. Measurement Equipment	53
5.5. Test Result and Data	54
6. Maximum Peak Output Power	66
6.1. Test Limit	66
6.2. Test Procedure	66
6.3. Test Setup Layout	66
6.4. Measurement Equipment	66
6.5. Test Result and Data	67
7. ERP & EIRP MEASUREMENT	79
7.1. Test Limit	79
7.2. Test Procedure	79
7.3. Test Setup Layout	80
7.4. Measurement Equipment	81
7.5. Test Result and Data	82
8. OUT OF BAND EMISSION AT ANTENNA TERMINALS	85
8.1. Test Limit	85
8.2. Test Procedure	85



8.3.	Test Setup Layout	85
8.4.	Measurement Equipment	85
8.5.	Test Result and Data	86
9.	FREQUENCY STABILITY V.S. TEMPERATURE MEASUREMENT	104
9.1.	Test Limit.....	104
9.2.	Test Procedure	104
9.3.	Test Setup Layout.....	104
9.4.	Measurement Equipment	104
9.5.	Test Result and Data	105
10.	FREQUENCY STABILITY V.S. VOLTAGE MEASUREMENT	108
10.1.	Test Limit.....	108
10.2.	Test Procedure	108
10.3.	Test Setup Layout.....	108
10.4.	Measurement Equipment	108
10.5.	Test Result and Data	109

[illegible]



FCC TEST REPORT

according to

FCC 47 CFR PART 22 SUBPART H AND PART 24 SUBPART E

Applicant	: MAXWEST TELECOM
Address	: 11037 warner ave #201 fountain valley, ca, 92708 USA
Manufacturer	: MAXWEST TELECOM
Address	: 11037 warner ave #201 fountain valley, ca, 92708 USA
Equipment	: Tablet
Model No.	: VIRTUE PHABLET 7; VIRTUE PHABLET 7S; GRAVITY PHABLET 7
Trade Name	: MAXWEST
FCC ID	: ONGVIRTUETAB7

I HEREBY CERTIFY THAT :

The measurements shown in this test report were made in accordance with the procedures given in **ANSI C63.4 – 2009** and the energy emitted by this equipment was **passed** **FCC Rule FCC PART 22 Subpart H and PART 24 Subpart E** in both radiated and conducted emission limits.

Testing was carried out on Jul 21, 2014 at **CerpPASS Technology Corp.**

Signature

Miro Chueh/ Technical director



1. Report of Measurements and Examinations

FCC 47 CFR PART 22 SUBPART H AND PART 24 SUBPART E ANSI C63.4: 2003		
Test Parameter	Test Performed	Remark
Conducted Emission	YES	PASS
Field Strength of Spurious Radiation Measurement	YES	PASS
Occupied Bandwidth	YES	PASS
Maximum Peak Output Power	YES	PASS
ERP & EIRP Measurement	YES	PASS
Out of Band Emission at Antenna Terminals	YES	PASS
Frequency Stability V.S. Temperature Measurement	YES	PASS
Requency Stability V.S. Voltage Measurement	YES	PASS



2. Test Configuration of Equipment under Test

2.1. Feature of Equipment under Test

Tablet	Model No:	VIRTUE PHABLET 7; VIRTUE PHABLET 7S; VIRTUE PHABLET 72; VIRTUE PHABLET 75; GRAVITY PHABLET 7
Remark	All the same type machine, only model name is different	
Operation Frequency Range	WCDMA/HSUPA/HSDPA BAND5: 826.4 – 846.6 MHz WCDMA/HSUPA/HSDPA BAND2: 1852.4 – 1907.6 MHz	
Release version	HSDPA: Rel 5 HSUPA: Rel 6	
Adapter	Model No.:	S050-050-US
	Input:	100-240V 50/60Hz 0.2A
	Output:	5V 0.5A



2.2. Test Manner

Test Manner	
a	During testing, the interface cables and equipment positions were varied according to 47 CFR, Part 2, PART 22 Subpart H and PART 24 Subpart E.
b	Adjust the EUT at the test mode and the test channel. Then test.
The test modes:	
The EUT had been tested under operating condition. After verification, all tests were carried out with the worst case test modes as shown below except radiated spurious emission below 1GHz and power line conducted emissions below 30MHz, which worst case was in normal link mode only. EUT staying in continuous transmitting mode was programmed. WCDMA 850: Channel Low (CH4132), Channel Mid (CH4183) and Channel High (CH4233) were chosen for full testing. WCDMA1900: Channel Low (CH9262), Channel Mid (CH9400) and Channel High (CH9538) were chosen for full testing. HSUPA 850: Channel Low (CH4132), Channel Mid (CH4183) and Channel High (CH4233) were chosen for full testing. HSUPA 1900: Channel Low (CH9262), Channel Mid (CH9400) and Channel High (CH9538) were chosen for full testing. HSDPA 850: Channel Low (CH4132), Channel Mid (CH4183) and Channel High (CH4233) were chosen for full testing. HSDPA 1900: Channel Low (CH9262), Channel Mid (CH9400) and Channel High (CH9538) were chosen for full testing.	

2.3. Description of Test System

No.	Device	Manufacturer	Model No.	Description
1	N/A	N/A	N/A	N/A



2.4. General Information of Test

Test Site:	Cerpass Technology Corp.
Performand Location :	No.66,Tangzhuang Road, Suzhou Industrial Park, Jiangsu 215006, China
NVLAP LAB Code :	200814-0
FCC Registration Number :	916572, 331395
IC Registration Number :	7290A-1, 7290A-2
VCCI Registration Number :	T-1945 for Telecommunication Test C-2919 for Conducted emission test R-2670 for Radiated emission test below 1GHz G-227 for Radiated emission test above 1GHz

Laboratory accreditation



2.5. Measurement Uncertainty

Measurement Item	Measurement Frequency	Polarization	Uncertainty
Conducted Emission	9 kHz ~ 30 MHz	LINE/NEUTRAL	±2.71 dB
Radiated Emission	30 MHz ~ 25GHz	Vertical	±4.11 dB
		Horizontal	±4.10 dB
Occupied Bandwidth	---	---	±7500 Hz
Maximum Peak Output Power	---	---	±1.4 dB
Band Edges	---	---	±2.2 dB
Power Spectral Density	---	---	±2.2 dB



3. Test of Conducted Emission

3.1. Test Limit

Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 KHz on the 120 VAC power and return leads of the EUT according to the methods defined in ANSI C63.4-2003 Section 3.1. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane as shown in section 2.2. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions.

Frequency (MHz)	Quasi Peak (dB μ V)	Average (dB μ V)
0.15 – 0.5	66-56*	56-46*
0.5 – 5.0	56	46
5.0 – 30.0	60	50


*Decreases with the logarithm of the frequency.

3.2. Test Procedures

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.



3.3. Typical Test Setup




3.4. Measurement Equipment

Instrument/Ancillary	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date.
Test Receiver	R&S	ESCI	100565	2014.03.24	2015.03.23
AMN	R&S	ESH2-Z5	100182	2013.09.11	2014.09.10
Two-Line V-Network	R&S	ENV216	100325	2013.12.04	2014.12.03
ISN	FCC	FCC-TLISN-T2-02	20379	2014.03.24	2015.03.23
ISN	FCC	FCC-TLISN-T4-02	20380	2014.03.24	2015.03.23
ISN	FCC	FCC-TLISN-T8-02	20381	2014.03.24	2015.03.23
ISN	TESEQ	ISN ST08	30175	2014.03.24	2015.03.23
Current Probe	R&S	EZ-17	100303	2014.04.04	2015.04.03
Passive Voltage Probe	R&S	ESH2-Z3	100026	2014.03.24	2015.03.23
Pulse Limiter	R&S	ESH3-Z2	100529	2014.03.24	2015.03.23
Temperature/Humidity Meter	Zhicheng	ZC1-11	CEP-TH-004	2014.03.31	2015.03.30



3.5. Test Result and Data

Test Mode :	Normal Link		
AC Power :	AC 120V/60Hz	Phase :	LINE
Temperature :	24 °C	Humidity :	52%
Pressure(mbar) :	1002	Date:	2014/07/22




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1540	10.13	43.81	53.94	65.78	-11.84	QP
2	0.1540	10.13	22.53	32.66	55.78	-23.12	AVG
3	0.1980	10.12	32.68	42.80	63.69	-20.89	QP
4	0.1980	10.12	14.95	25.07	53.69	-28.62	AVG
5	0.4300	10.15	14.02	24.17	57.25	-33.08	QP
6	0.4300	10.15	8.06	18.21	47.25	-29.04	AVG
7	2.5300	10.18	16.77	26.95	56.00	-29.05	QP
8	2.5300	10.18	9.67	19.85	46.00	-26.15	AVG
9	16.7180	10.46	19.60	30.06	60.00	-29.94	QP
10	16.7180	10.46	10.24	20.70	50.00	-29.30	AVG
11	22.1260	10.38	24.10	34.48	60.00	-25.52	QP
12	22.1260	10.38	18.85	29.23	50.00	-20.77	AVG

Note: Measurement Level = Reading Level + Correct Factor



Test Mode :	Normal Link		
AC Power :	AC 120V/60Hz	Phase :	NEUTRAL
Temperature :	24 °C	Humidity :	52%
Pressure(mbar) :	1002	Date:	2014/07/22



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1500	10.13	44.91	55.04	65.99	-10.95	QP
2	0.1500	10.13	26.08	36.21	55.99	-19.78	AVG
3	0.1722	10.13	37.42	47.55	64.85	-17.30	QP
4	0.1722	10.13	23.35	33.48	54.85	-21.37	AVG
5	0.2180	10.13	35.17	45.30	62.89	-17.59	QP
6	0.2180	10.13	18.02	28.15	52.89	-24.74	AVG
7	0.8260	10.16	22.03	32.19	56.00	-23.81	QP
8	0.8260	10.16	6.87	17.03	46.00	-28.97	AVG
9	7.0740	10.27	16.50	26.77	60.00	-33.23	QP
10	7.0740	10.27	9.87	20.14	50.00	-29.86	AVG
11	21.9300	10.40	24.08	34.48	60.00	-25.52	QP
12	21.9300	10.40	19.16	29.56	50.00	-20.44	AVG

Note: Measurement Level = Reading Level + Correct Factor



4. FIELD STRENGTH OF SPURIOUS RADIATION MEASUREMENT

4.1. Test Limit

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10\log(P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

4.2. Test Procedures

Final radiation measurements were made on a three-meter, Semi Anechoic Chamber. The EUT system was placed on a nonconductive turntable which is 0.8 meters height, top surface 1.0 x 1.5 meter. The spectrum was examined from 250 MHz to 2.5 GHz in order to cover the whole spectrum below 10th harmonic which could generate from the EUT. During the test, EUT was set to transmit continuously & Measurements spectrum range from 30 MHz to 26.5 GHz is investigated. For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, and then the video bandwidth is set to 1 MHz for peak measurements and 10 Hz for average measurements. A nonconductive material surrounded the EUT to supporting the EUT for standing on three orthogonal planes. At each condition, the EUT was rotated 360 degrees, and the antenna was raised and lowered from one to four meters to find the maximum emission levels. Measurements were taken using both horizontal and vertical antenna polarization.

For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

Appropriate preamplifiers were used for improving sensitivity and precautions were taken to avoid

overloading or desensitizing the spectrum analyzer. No post – detector video filters were used in the test. The spectrum analyzer's 6 dB bandwidth was set to 1 MHz, and the analyzer was operated in the peak detection mode, for frequencies both below and up 1 GHz. The average levels were obtained by subtracting the duty cycle correction factor from the peak readings.

The following procedures were used to convert the emission levels measured in decibels



referenced to 1 microvolt (dBuV) into field intensity in micro volts pre meter (uV/m).

The actual field intensity in decibels referenced to 1 microvolt in to field intensity in micro volts per meter (dBuV/m). The actual field intensity in decibels referenced to 1 microvolt per meter (dBuV/m) is determined by algebraically adding the measured reading in dBuV, the antenna factor (dB), and cable loss (dB) and Subtracting the gain of preamplifier (dB) is auto calculate in spectrum analyzer.

$$(1) \text{ Amplitude (dBuV/m) = FI (dBuV) + AF (dBuV) + CL (dBuV) - Gain (dB)}$$

FI= Reading of the field intensity.

AF= Antenna factor.

CL= Cable loss.

P.S Amplitude is auto calculate in spectrum analyzer.


$$(2) \text{ Actual Amplitude (dBuV/m) = Amplitude (dBuV) - Dis(dB)}$$

The FCC specified emission limits were calculated according the EUT operating frequency and by following linear interpolation equations:

(a) For fundamental frequency : Transmitter Output < +30dBm

(b) For spurious frequency : Spurious emission limits = fundamental emission limit /10

4.3. Typical Test Setup



**4.4. Measurement Equipment**

Instrument	Model No.	Manufacturer	Serial No.	Calibration Date	Valid Date.
EMI Test Receiver	R&S	ESCI	100563	2014.02.10	2015.02.09
H64 Preamplifier	HP	8447F	3113A05582	2014.03.24	2015.03.23
Preamplifier	Agilent	8449B	3008A02342	2014.03.24	2015.03.23
Ultra Broadband Antenna	R&S	HL562	100362	2014.05.24	2015.05.23
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	9120D-619	2014.05.24	2015.05.23
Broad-Band Horn Antenna	Schwarzbeck	BBHA9170	9170-348	2013.11.04	2014.11.03
Spectrum Analyzer	R&S	FSP40	100324	2014.03.23	2015.03.24
Temperature/ Humidity Meter	Zhicheng	ZC1-11	CEP-TH-002	2014.03.31	2015.03.30



4.5. Test Result and Data

Radiated Spurious Emission Measurement Result / Under 1GHz:

Engineer : MATT	Time : 2014-07-22
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : WCDMA MOBILE PHONE	Note : WCDMA 850/ CH 4132

Frequency	Antenna	Antenna	Substitution	Emission level	Limit	Margin
(MHz)	Polarization	Terminals level	Antenna Gain	(dBm)	(dBm)	(dB)
		(dBm)	(dBd)			
39.27	V	-15.51	-11.29	-26.80	-13.00	-13.80
112.31	V	-14.81	-13.44	-28.25	-13.00	-15.25
113.51	V	-15.81	-13.78	-29.59	-13.00	-16.59
129.87	V	-16.71	-14.15	-30.86	-13.00	-17.86
138.61	V	-16.94	-14.47	-31.41	-13.00	-18.41
828.21	V	-30.51	1.87	-28.64	-13.00	-15.64
77.91	H	-14.72	-16.63	-31.35	-13.00	-18.35
88.61	H	-14.84	-15.27	-30.11	-13.00	-17.11
111.34	H	-15.04	-14.25	-29.29	-13.00	-16.29
128.56	H	-14.51	-14.15	-28.66	-13.00	-15.66
314.84	H	-18.61	-9.74	-28.35	-13.00	-15.35
898.61	H	-24.02	-2.44	-26.46	-13.00	-13.46



Engineer : MATT	Time : 2014-07-22
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : WCDMA MOBILE PHONE	Note : WCDMA 850/ CH 4183

Frequency	Antenna	Antenna	Substitution	Emission level	Limit	Margin
(MHz)	Polarization	Terminals level	Antenna Gain	(dBm)	(dBm)	(dB)
		(dBm)	(dBd)			
40.24	V	-16.51	-11.29	-27.80	-13.00	-14.80
111.54	V	-15.61	-13.44	-29.05	-13.00	-16.05
113.24	V	-14.84	-13.78	-28.62	-13.00	-15.62
130.25	V	-17.91	-14.15	-32.06	-13.00	-19.06
139.51	V	-15.74	-14.47	-30.21	-13.00	-17.21
832.51	V	-30.46	1.87	-28.59	-13.00	-15.59
76.61	H	-13.67	-16.63	-30.30	-13.00	-17.30
90.24	H	-15.54	-15.27	-30.81	-13.00	-17.81
111.51	H	-13.81	-14.25	-28.06	-13.00	-15.06
129.34	H	-14.49	-14.15	-28.64	-13.00	-15.64
315.81	H	-18.78	-9.74	-28.52	-13.00	-15.52
900.14	H	-23.65	-2.18	-25.83	-13.00	-12.83



Engineer : MATT	Time : 2014-07-22
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : WCDMA MOBILE PHONE	Note : WCDMA 850/ CH 4233

Frequency	Antenna	Antenna	Substitution	Emission level	Limit	Margin
(MHz)	Polarization	Terminals level	Antenna Gain	(dBm)	(dBm)	(dB)
		(dBm)	(dBd)			
41.54	V	-14.34	-11.29	-25.63	-13.00	-12.63
110.67	V	-15.97	-13.44	-29.41	-13.00	-16.41
114.61	V	-13.87	-13.78	-27.65	-13.00	-14.65
130.18	V	-14.57	-14.15	-28.72	-13.00	-15.72
139.45	V	-15.47	-14.47	-29.94	-13.00	-16.94
834.67	V	-30.12	1.87	-28.25	-13.00	-15.25
74.51	H	-13.82	-16.63	-30.45	-13.00	-17.45
86.81	H	-12.71	-15.27	-27.98	-13.00	-14.98
111.42	H	-12.49	-14.25	-26.74	-13.00	-13.74
130.51	H	-13.64	-14.15	-27.79	-13.00	-14.79
317.46	H	-16.72	-9.74	-26.46	-13.00	-13.46
897.47	H	-27.81	-2.44	-30.25	-13.00	-17.25



Engineer : MATT	Time : 2014-07-22
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : WCDMA MOBILE PHONE	Note : HSUPA 850/ CH 4132

Frequency	Antenna	Antenna	Substitution	Emission level	Limit	Margin
(MHz)	Polarization	Terminals level	Antenna Gain	(dBm)	(dBm)	(dB)
		(dBm)	(dBd)			
38.16	V	-15.07	-11.01	-26.08	-13.00	-13.08
107.34	V	-12.48	-13.44	-25.92	-13.00	-12.92
110.39	V	-12.04	-13.65	-25.69	-13.00	-12.69
128.37	V	-13.19	-14.15	-27.34	-13.00	-14.34
135.94	V	-14.07	-14.47	-28.54	-13.00	-15.54
828.11	V	-26.48	1.87	-24.61	-13.00	-11.61
75.37	H	-12.49	-16.63	-29.12	-13.00	-16.12
87.16	H	-11.37	-15.27	-26.64	-13.00	-13.64
108.49	H	-14.57	-14.25	-28.82	-13.00	-15.82
129.14	H	-12.49	-14.15	-26.64	-13.00	-13.64
313.94	H	-17.39	-9.74	-27.13	-13.00	-14.13
896.47	H	-23.48	-2.44	-25.92	-13.00	-12.92



Engineer : MATT	Time : 2014-07-22
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : WCDMA MOBILE PHONE	Note : HSUPA 850 CH 4183

Frequency (MHz)	Antenna Polarization	Antenna Terminals level (dBm)	Substitution Antenna Gain (dBd)	Emission level (dBm)	Limit (dBm)	Margin (dB)
39.82	V	-16.41	-11.29	-27.70	-13.00	-14.70
103.74	V	-15.74	-11.47	-27.21	-13.00	-14.21
113.27	V	-14.64	-13.78	-28.42	-13.00	-15.42
128.71	V	-14.81	-14.15	-28.96	-13.00	-15.96
138.51	V	-16.42	-14.47	-30.89	-13.00	-17.89
819.47	V	-27.51	1.87	-25.64	-13.00	-12.64
77.67	H	-12.27	-16.63	-28.90	-13.00	-15.90
88.54	H	-14.01	-15.27	-29.28	-13.00	-16.28
109.47	H	-13.42	-14.25	-27.67	-13.00	-14.67
128.91	H	-13.74	-14.15	-27.89	-13.00	-14.89
314.81	H	-15.84	-9.74	-25.58	-13.00	-12.58
898.75	H	-23.68	-2.44	-26.12	-13.00	-13.12



Engineer : MATT	Time : 2014-07-22
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : WCDMA MOBILE PHONE	Note: HSUPA 850/ CH 4233

Frequency (MHz)	Antenna Polarization	Antenna Terminals level (dBm)	Substitution Antenna Gain (dBd)	Emission level (dBm)	Limit (dBm)	Margin (dB)
39.21	V	-14.65	-11.29	-25.94	-13.00	-12.94
107.44	V	-11.50	-13.44	-24.94	-13.00	-11.94
112.71	V	-11.00	-13.78	-24.78	-13.00	-11.78
128.64	V	-12.96	-14.15	-27.11	-13.00	-14.11
137.76	V	-11.87	-14.47	-26.34	-13.00	-13.34
829.42	V	-28.11	1.87	-26.24	-13.00	-13.24
76.91	H	-10.65	-16.63	-27.28	-13.00	-14.28
87.49	H	-10.23	-15.27	-25.50	-13.00	-12.50
108.67	H	-9.80	-14.25	-24.05	-13.00	-11.05
129.72	H	-12.01	-14.15	-26.16	-13.00	-13.16
312.19	H	-16.08	-9.74	-25.82	-13.00	-12.82
898.43	H	-23.54	-2.44	-25.98	-13.00	-12.98



Engineer : Matt	Time : 2014-07-22
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : WCDMA MOBILE PHONE	Note : HSDPA 850 / CH 4132

Frequency (MHz)	Antenna Polarization	Antenna Terminals level (dBm)	Substitution Antenna Gain (dBd)	Emission level (dBm)	Limit (dBm)	Margin (dB)
38.43	V	-15.61	-11.29	-26.90	-13.00	-13.90
109.74	V	-15.07	-13.44	-28.51	-13.00	-15.51
114.91	V	-16.71	-13.78	-30.49	-13.00	-17.49
130.41	V	-15.91	-14.15	-30.06	-13.00	-17.06
139.72	V	-16.84	-14.47	-31.31	-13.00	-18.31
830.78	V	-28.67	1.87	-26.80	-13.00	-13.80
76.24	H	-14.21	-16.63	-30.84	-13.00	-17.84
87.71	H	-14.94	-15.27	-30.21	-13.00	-17.21
110.76	H	-15.82	-14.25	-30.07	-13.00	-17.07
129.51	H	-14.74	-14.15	-28.89	-13.00	-15.89
314.67	H	-20.84	-9.74	-30.58	-13.00	-17.58
897.64	H	-25.37	-2.44	-27.81	-13.00	-14.81



Engineer : MATT	Time : 2014-07-22
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : WCDMA MOBILE PHONE	Note : HSDPA 850 / CH 4183

Frequency (MHz)	Antenna Polarization	Antenna Terminals leve (dBm)	Substitution Antenna Gain (dBd)	Emission level (dBm)	Limit (dBm)	Margin (dB)
40.35	V	-15.37	-11.29	-26.66	-13.00	-13.66
108.65	V	-15.34	-13.44	-28.78	-13.00	-15.78
112.16	V	-14.85	-13.78	-28.63	-13.00	-15.63
129.88	V	-15.68	-14.15	-29.83	-13.00	-16.83
138.34	V	-13.49	-14.47	-27.96	-13.00	-14.96
829.11	V	-27.54	1.87	-25.67	-13.00	-12.67
76.48	H	-12.37	-16.63	-29.00	-13.00	-16.00
88.69	H	-14.41	-15.27	-29.68	-13.00	-16.68
108.37	H	-13.87	-14.25	-28.12	-13.00	-15.12
129.34	H	-15.79	-14.15	-29.94	-13.00	-16.94
312.45	H	-19.81	-9.74	-29.55	-13.00	-16.55
901.34	H	-24.24	-2.18	-26.42	-13.00	-13.42



Engineer : MATT	Time : 2014-07-22
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : WCDMA MOBILE PHONE	Note : HSDPA 850 / CH 4233

Frequency (MHz)	Antenna Polarization	Antenna Terminals level (dBm)	Substitution Antenna Gain (dBd)	Emission level (dBm)	Limit (dBm)	Margin (dB)
40.34	V	-17.47	-11.29	-28.76	-13.00	-15.76
109.74	V	-16.94	-13.44	-30.38	-13.00	-17.38
120.04	V	-14.71	-13.78	-28.49	-13.00	-15.49
130.42	V	-16.46	-14.15	-30.61	-13.00	-17.61
139.75	V	-16.38	-14.47	-30.85	-13.00	-17.85
833.64	V	-29.81	1.87	-27.94	-13.00	-14.94
77.64	H	-12.51	-16.63	-29.14	-13.00	-16.14
87.46	H	-12.49	-15.27	-27.76	-13.00	-14.76
110.81	H	-13.72	-14.25	-27.97	-13.00	-14.97
129.48	H	-14.57	-14.15	-28.72	-13.00	-15.72
315.71	H	-18.61	-9.74	-28.35	-13.00	-15.35
900.51	H	-26.22	-2.44	-28.66	-13.00	-15.66



Engineer : MATT	Time :2014-07-22
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : WCDMA MOBILE PHONE	Note : WCDMA1900 /CH 9262

Frequency	Antenna	Antenna	Substitution	Emission level	Limit	Margin
(MHz)	Polarization	Terminals level	Antenna Gain	(dBm)	(dBm)	(dB)
		(dBm)	(dBd)			
37.68	V	-16.57	-11.01	-27.58	-13.00	-14.58
107.81	V	-13.64	-13.44	-27.08	-13.00	-14.08
112.64	V	-12.67	-13.65	-26.32	-13.00	-13.32
130.51	V	-14.51	-14.15	-28.66	-13.00	-15.66
137.05	V	-15.61	-14.47	-30.08	-13.00	-17.08
828.61	V	-27.42	1.87	-25.55	-13.00	-12.55
80.46	H	-12.69	-16.63	-29.32	-13.00	-16.32
87.16	H	-12.94	-15.27	-28.21	-13.00	-15.21
105.61	H	-15.51	-14.25	-29.76	-13.00	-16.76
132.67	H	-14.38	-14.15	-28.53	-13.00	-15.53
318.04	H	-15.01	-9.74	-24.75	-13.00	-11.75
894.61	H	-25.67	-2.44	-28.11	-13.00	-15.11



Engineer : MATT	Time : 2014-07-22
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : WCDMA MOBILE PHONE	Note : WCDMA 1900/ CH 9400

Frequency	Antenna	Antenna	Substitution	Emission level	Limit	Margin
(MHz)	Polarization	Terminals level	Antenna Gain	(dBm)	(dBm)	(dB)
		(dBm)	(dBd)			
37.61	V	-16.52	-11.29	-27.81	-13.00	-14.81
102.94	V	-15.91	-11.47	-27.38	-13.00	-14.38
115.28	V	-14.52	-13.78	-28.30	-13.00	-15.30
130.42	V	-14.28	-14.15	-28.43	-13.00	-15.43
142.25	V	-15.51	-14.47	-29.98	-13.00	-16.98
819.14	V	-27.54	1.87	-25.67	-13.00	-12.67
78.64	H	-14.52	-16.63	-31.15	-13.00	-18.15
87.28	H	-13.35	-15.27	-28.62	-13.00	-15.62
110.34	H	-12.97	-14.25	-27.22	-13.00	-14.22
128.51	H	-13.64	-14.15	-27.79	-13.00	-14.79
317.95	H	-15.71	-9.74	-25.45	-13.00	-12.45
897.94	H	-24.31	-2.44	-26.75	-13.00	-13.75



Engineer : MATT	Time : 2014-07-22
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : WCDMA MOBILE PHONE	Note : WCDMA 1900 /CH 9538

Frequency	Antenna	Antenna	Substitution	Emission level	Limit	Margin
(MHz)	Polarization	Terminals leve	Antenna Gain	(dBm)	(dBm)	(dB)
		(dBm)	(dBd)			
38.51	V	-15.52	-11.29	-26.81	-13.00	-13.81
110.29	V	-14.57	-13.44	-28.01	-13.00	-15.01
114.61	V	-13.81	-13.78	-27.59	-13.00	-14.59
129.82	V	-14.75	-14.15	-28.90	-13.00	-15.90
137.51	V	-16.51	-14.47	-30.98	-13.00	-17.98
831.35	V	-27.68	1.87	-25.81	-13.00	-12.81
77.81	H	-12.21	-16.63	-28.84	-13.00	-15.84
83.72	H	-12.67	-15.27	-27.94	-13.00	-14.94
110.64	H	-12.72	-14.25	-26.97	-13.00	-13.97
136.81	H	-13.61	-14.15	-27.76	-13.00	-14.76
316.61	H	-17.51	-9.74	-27.25	-13.00	-14.25
901.25	H	-24.75	-2.44	-27.19	-13.00	-14.19



Engineer : MATT	Time : 2014-07-22
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : WCDMA MOBILE PHONE	Note : HSUPA 1900/ CH 9262

Frequency	Antenna	Antenna	Substitution	Emission level	Limit	Margin
(MHz)	Polarization	Terminals level	Antenna Gain	(dBm)	(dBm)	(dB)
		(dBm)	(dBd)			
41.34	V	-15.24	-11.29	-26.53	-13.00	-13.53
109.62	V	-14.52	-13.44	-27.96	-13.00	-14.96
112.64	V	-15.53	-13.78	-29.31	-13.00	-16.31
129.51	V	-15.95	-14.15	-30.10	-13.00	-17.10
137.82	V	-17.52	-14.47	-31.99	-13.00	-18.99
829.57	V	-29.42	1.87	-27.55	-13.00	-14.55
76.68	H	-13.28	-16.63	-29.91	-13.00	-16.91
87.81	H	-14.94	-15.27	-30.21	-13.00	-17.21
110.52	H	-14.52	-14.25	-28.77	-13.00	-15.77
129.64	H	-14.05	-14.15	-28.20	-13.00	-15.20
313.51	H	-19.84	-9.74	-29.58	-13.00	-16.58
897.85	H	-25.74	-2.44	-28.18	-13.00	-15.18



Engineer : MATT	Time : 2014-07-22
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : WCDMA MOBILE PHONE	Note : HSUPA 1900/ CH 9400

Frequency (MHz)	Antenna Polarization	Antenna Terminals level (dBm)	Substitution Antenna Gain (dBd)	Emission level (dBm)	Limit (dBm)	Margin (dB)
41.52	V	-16.34	-11.29	-27.63	-13.00	-14.63
108.61	V	-15.82	-13.44	-29.26	-13.00	-16.26
113.57	V	-14.21	-13.78	-27.99	-13.00	-14.99
130.24	V	-16.84	-14.15	-30.99	-13.00	-17.99
138.51	V	-15.51	-14.47	-29.98	-13.00	-16.98
829.75	V	-29.68	1.87	-27.81	-13.00	-14.81
77.59	H	-12.54	-16.63	-29.17	-13.00	-16.17
88.51	H	-14.62	-15.27	-29.89	-13.00	-16.89
110.25	H	-13.51	-14.25	-27.76	-13.00	-14.76
129.84	H	-14.53	-14.15	-28.68	-13.00	-15.68
313.01	H	-18.67	-9.74	-28.41	-13.00	-15.41
901.54	H	-24.33	-2.18	-26.51	-13.00	-13.51



Engineer : MATT	Time : 2014-07-22
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : WCDMA MOBILE PHONE	Note : HSUPA 1900/ CH 9538

Frequency	Antenna	Antenna	Substitution	Emission level	Limit	Margin
(MHz)	Polarization	Terminals level	Antenna Gain	(dBm)	(dBm)	(dB)
		(dBm)	(dBd)			
40.24	V	-16.30	-11.29	-27.59	-13.00	-14.59
109.51	V	-15.43	-13.44	-28.87	-13.00	-15.87
113.72	V	-13.61	-13.78	-27.39	-13.00	-14.39
129.51	V	-14.52	-14.15	-28.67	-13.00	-15.67
138.31	V	-15.81	-14.47	-30.28	-13.00	-17.28
832.54	V	-30.27	1.87	-28.40	-13.00	-15.40
77.61	H	-12.49	-16.63	-29.12	-13.00	-16.12
86.94	H	-12.61	-15.27	-27.88	-13.00	-14.88
109.28	H	-12.97	-14.25	-27.22	-13.00	-14.22
130.47	H	-14.24	-14.15	-28.39	-13.00	-15.39
314.61	H	-17.51	-9.74	-27.25	-13.00	-14.25
899.72	H	-26.74	-2.44	-29.18	-13.00	-16.18



Engineer : MATT	Time :2014-07-22
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : WCDMA MOBILE PHONE	Note : HSDPA 1900 / CH 9262

Frequency (MHz)	Antenna Polarization	Antenna Terminals leve (dBm)	Substitution Antenna Gain (dBd)	Emission level (dBm)	Limit (dBm)	Margin (dB)
39.61	V	-16.97	-11.29	-28.26	-13.00	-15.26
109.84	V	-14.52	-13.44	-27.96	-13.00	-14.96
112.72	V	-13.34	-13.78	-27.12	-13.00	-14.12
130.24	V	-15.56	-14.15	-29.71	-13.00	-16.71
136.86	V	-14.72	-14.47	-29.19	-13.00	-16.19
829.51	V	-26.37	1.87	-24.50	-13.00	-11.50
77.61	H	-13.24	-16.63	-29.87	-13.00	-16.87
88.62	H	-12.57	-15.27	-27.84	-13.00	-14.84
109.85	H	-16.51	-14.25	-30.76	-13.00	-17.76
130.51	H	-14.72	-14.15	-28.87	-13.00	-15.87
315.49	H	-19.52	-9.74	-29.26	-13.00	-16.26
898.64	H	-23.57	-2.44	-26.01	-13.00	-13.01



Engineer : MATT	Time : 2014-07-22
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : WCDMA MOBILE PHONE	Note : HSDPA 1900 / CH 9400

Frequency (MHz)	Antenna Polarization	Antenna Terminals leve (dBm)	Substitution Antenna Gain (dBd)	Emission level (dBm)	Limit (dBm)	Margin (dB)
39.46	V	-15.51	-11.29	-26.80	-13.00	-13.80
103.24	V	-16.84	-11.47	-28.31	-13.00	-15.31
113.81	V	-15.27	-13.78	-29.05	-13.00	-16.05
129.27	V	-15.20	-14.15	-29.35	-13.00	-16.35
138.24	V	-15.92	-14.47	-30.39	-13.00	-17.39
820.24	V	-26.02	1.87	-24.15	-13.00	-11.15
77.52	H	-12.87	-16.63	-29.50	-13.00	-16.50
89.67	H	-13.97	-15.27	-29.24	-13.00	-16.24
110.67	H	-12.51	-14.25	-26.76	-13.00	-13.76
129.51	H	-14.57	-14.15	-28.72	-13.00	-15.72
314.67	H	-16.72	-9.74	-26.46	-13.00	-13.46
899.68	H	-23.42	-2.44	-25.86	-13.00	-12.86



Engineer : MATT	Time : 2014-07-22
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : WCDMA MOBILE PHONE	Note : HSDPA 1900 / CH 9538

Frequency (MHz)	Antenna Polarization	Antenna Terminals leve (dBm)	Substitution Antenna Gain (dBd)	Emission level (dBm)	Limit (dBm)	Margin (dB)
40.24	V	-16.61	-11.29	-27.90	-13.00	-14.90
108.64	V	-14.82	-11.47	-26.29	-13.00	-13.29
114.67	V	-15.67	-13.78	-29.45	-13.00	-16.45
129.82	V	-14.62	-14.15	-28.77	-13.00	-15.77
138.37	V	-15.72	-14.47	-30.19	-13.00	-17.19
831.67	V	-29.35	1.87	-27.48	-13.00	-14.48
78.67	H	-13.64	-16.63	-30.27	-13.00	-17.27
89.82	H	-13.55	-15.27	-28.82	-13.00	-15.82
109.95	H	-13.72	-14.25	-27.97	-13.00	-14.97
131.64	H	-14.87	-14.15	-29.02	-13.00	-16.02
314.82	H	-18.62	-9.74	-28.36	-13.00	-15.36
899.64	H	-24.57	-2.44	-27.01	-13.00	-14.01

**Above 1G:**

Engineer : MATT	Time : 2014-07-22
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : WCDMA MOBILE PHONE	Note :WCDMA 850 / CH 4132

Frequency (MHz)	Antenna Polarization	Antenna Terminals leve (dBm)	Substitution Antenna Gain (dBd)	Emission leve (dBm)	Limit (dBm)	Margin (dB)
3192.25	V	-48.62	1.29	-47.33	-13.00	-34.33
3200.24	H	-50.54	1.31	-49.23	-13.00	-36.23

Note :The other harmonic spurious emissions are under limit 20dB more,
so the results were not shown in the table.



Engineer : MATT	Time : 2014-07-22
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : WCDMA MOBILE PHONE	Note : WCDMA 850 /CH 4183

Frequency (MHz)	Antenna Polarization	Antenna Terminals leve (dBm)	Substitution Antenna Gain (dBd)	Emission leve (dBm)	Limit (dBm)	Margin (dB)
3202.67	V	-50.21	1.29	-48.92	-13.00	-35.92
3205.34	H	-52.37	1.31	-51.06	-13.00	-38.06

Note :The other harmonic spurious emissions are under limit 20dB more,
so the results were not shown in the table.



Engineer : MATT	Time : 2014-07-22
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : WCDMA MOBILE PHONE	Note : WCDMA 850 / CH 4233

Frequency (MHz)	Antenna Polarization	Antenna Terminals leve (dBm)	Substitution Antenna Gain (dBd)	Emission level (dBm)	Limit (dBm)	Margin (dB)
3205.24	V	-46.02	1.29	-44.73	-13.00	-31.73
3202.64	H	-45.68	1.31	-44.37	-13.00	-31.37

Note :The other harmonic spurious emissions are under limit 20dB more,
so the results were not shown in the table.



Engineer : MATT	Time : 2014-07-22
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : WCDMA MOBILE PHONE	Note : HSUPA 850 / CH 4132

Frequency (MHz)	Antenna Polarization	Antenna Terminals leve (dBm)	Substitution Antenna Gain (dBi)	Emission level (dBm)	Limit (dBm)	Margin (dB)
3202.64	V	-50.02	1.29	-48.73	-13.00	-35.73
3203.34	H	-52.26	1.31	-50.95	-13.00	-37.95

Note :The other harmonic spurious emissions are under limit 20dB more,
so the results were not shown in the table.



Engineer : MATT	Time : 2014-07-22
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : WCDMA MOBILE PHONE	Note : HSUPA 850 / CH 4183

Frequency (MHz)	Antenna Polarization	Antenna Terminals leve (dBm)	Substitution Antenna Gain (dBi)	Emission level (dBm)	Limit (dBm)	Margin (dB)
3201.64	V	-49.34	1.29	-48.05	-13.00	-35.05
3203.57	H	-53.64	1.31	-52.33	-13.00	-39.33

Note :The other harmonic spurious emissions are under limit 20dB more,
so the results were not shown in the table.



Engineer : MATT	Time : 2014-07-22
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : WCDMA MOBILE PHONE	Note : HSUPA 850 / CH 4233

Frequency (MHz)	Antenna Polarization	Antenna Terminals leve (dBm)	Substitution Antenna Gain (dBi)	Emission level (dBm)	Limit (dBm)	Margin (dB)
3202.25	V	-50.34	1.29	-49.05	-13.00	-36.05
3204.51	H	-52.64	1.31	-51.33	-13.00	-38.33

Note :The other harmonic spurious emissions are under limit 20dB more,
so the results were not shown in the table.



Engineer : MATT	Time : 2014-07-22
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : WCDMA MOBILE PHONE	Note : HSDPA 850 / CH 4132

Frequency (MHz)	Antenna Polarization	Antenna Terminals leve (dBm)	Substitution Antenna Gain (dBi)	Emission level (dBm)	Limit (dBm)	Margin (dB)
3202.54	V	-49.54	1.29	-48.25	-13.00	-35.25
3203.61	H	-50.37	1.31	-49.06	-13.00	-36.06

Note :The other harmonic spurious emissions are under limit 20dB more,
so the results were not shown in the table.



Engineer : MATT	Time : 2014-07-22
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : WCDMA MOBILE PHONE	Note : HSDPA 850 / CH 4183

Frequency (MHz)	Antenna Polarization	Antenna Terminals leve (dBm)	Substitution Antenna Gain (dBi)	Emission level (dBm)	Limit (dBm)	Margin (dB)
3192.65	V	-49.81	1.29	-48.52	-13.00	-35.52
3203.67	H	-50.34	1.31	-49.03	-13.00	-36.03

Note :The other harmonic spurious emissions are under limit 20dB more,
so the results were not shown in the table.



Engineer : MATT	Time : 2014-07-22
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : WCDMA MOBILE PHONE	Note : HSDPA 850 / CH 4233

Frequency (MHz)	Antenna Polarization	Antenna Terminals leve (dBm)	Substitution Antenna Gain (dBi)	Emission level (dBm)	Limit (dBm)	Margin (dB)
3203.41	V	-49.64	1.29	-48.35	-13.00	-35.35
3204.82	H	-51.34	1.31	-50.03	-13.00	-37.03

Note :The other harmonic spurious emissions are under limit 20dB more,
so the results were not shown in the table.



Engineer : MATT	Time : 2014-07-22
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : WCDMA MOBILE PHONE	Note : WCDMA 1900 / CH 9262

Frequency (MHz)	Antenna Polarization	Antenna Terminals level (dBm)	Substitution Antenna Gain (dBd)	Emission level (dBm)	Limit (dBm)	Margin (dB)
3205.51	V	-47.67	1.29	-46.38	-13.00	-33.38
3202.34	H	-51.34	1.31	-50.03	-13.00	-37.03

Note :The other harmonic spurious emissions are under limit 20dB more,
so the results were not shown in the table.



Engineer : MATT	Time : 2014-07-22
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : WCDMA MOBILE PHONE	Note : WCDMA1900 / CH9400

Frequency (MHz)	Antenna Polarization	Antenna Terminals leve (dBm)	Substitution Antenna Gain (dBd)	Emission level (dBm)	Limit (dBm)	Margin (dB)
3198.67	V	-48.61	1.29	-47.32	-13.00	-34.32
3200.64	H	-51.35	1.31	-50.04	-13.00	-37.04

Note :The other harmonic spurious emissions are under limit 20dB more,
so the results were not shown in the table.



Engineer : MATT	Time : 2014-07-22
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : WCDMA MOBILE PHONE	Note : WCDMA 1900 / CH 9538

Frequency (MHz)	Antenna Polarization	Antenna Terminals level (dBm)	Substitution Antenna Gain (dBd)	Emission level (dBm)	Limit (dBm)	Margin (dB)
3196.92	V	-47.93	1.29	-46.64	-13.00	-33.64
3204.67	H	-50.34	1.31	-49.03	-13.00	-36.03

Note :The other harmonic spurious emissions are under limit 20dB more,
so the results were not shown in the table.



Engineer : MATT	Time : 2014-07-22
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : WCDMA MOBILE PHONE	Note : HSUPA 1900 / CH 9262

Frequency (MHz)	Antenna Polarization	Antenna Terminals leve (dBm)	Substitution Antenna Gain (dBi)	Emission level (dBm)	Limit (dBm)	Margin (dB)
3202.34	V	-50.67	1.29	-49.38	-13.00	-36.38
3204.24	H	-54.34	1.31	-53.03	-13.00	-40.03

Note :The other harmonic spurious emissions are under limit 20dB more,
so the results were not shown in the table.



Engineer : MATT	Time : 2014-07-22
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : WCDMA MOBILE PHONE	Note : HSUPA 1900 / CH 9400

Frequency (MHz)	Antenna Polarization	Antenna Terminals leve (dBm)	Substitution Antenna Gain (dBi)	Emission level (dBm)	Limit (dBm)	Margin (dB)
3198.61	V	-51.24	1.29	-49.95	-13.00	-36.95
3204.02	H	-52.64	1.31	-51.33	-13.00	-38.33

Note :The other harmonic spurious emissions are under limit 20dB more,
so the results were not shown in the table.



Engineer : MATT	Time : 2014-07-22
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : WCDMA MOBILE PHONE	Note : HSUPA 1900 / CH 9538

Frequency (MHz)	Antenna Polarization	Antenna Terminals leve (dBm)	Substitution Antenna Gain (dBi)	Emission level (dBm)	Limit (dBm)	Margin (dB)
3191.53	V	-50.34	1.29	-49.05	-13.00	-36.05
3205.37	H	-53.46	1.31	-52.15	-13.00	-39.15

Note :The other harmonic spurious emissions are under limit 20dB more,
so the results were not shown in the table.



Engineer : MATT	Time : 2014-07-22
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : WCDMA MOBILE PHONE	Note : HSDPA 1900 / CH 9262

Frequency (MHz)	Antenna Polarization	Antenna Terminals leve (dBm)	Substitution Antenna Gain (dBi)	Emission level (dBm)	Limit (dBm)	Margin (dB)
3199.61	V	-50.34	1.29	-49.05	-13.00	-36.05
3204.37	H	-50.97	1.31	-49.66	-13.00	-36.66

Note :The other harmonic spurious emissions are under limit 20dB more,
so the results were not shown in the table.



Engineer : MATT	Time : 2014-07-22
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : WCDMA MOBILE PHONE	Note : HSDPA 1900 / CH 9400

Frequency (MHz)	Antenna Polarization	Antenna Terminals leve (dBm)	Substitution Antenna Gain (dBi)	Emission level (dBm)	Limit (dBm)	Margin (dB)
3199.75	V	-50.24	1.29	-48.95	-13.00	-35.95
3204.75	H	-51.82	1.31	-50.51	-13.00	-37.51

Note :The other harmonic spurious emissions are under limit 20dB more,
so the results were not shown in the table.



Engineer : MATT	Time : 2014-07-22
Site : EMC Lab AC 102	Margin : 6
Limit : FCC_Part22&24	Probe : VERTICAL/ HORIZONTAL
EUT : WCDMA MOBILE PHONE	Note : HSDPA 1900 / CH 9538

Frequency (MHz)	Antenna Polarization	Antenna Terminals leve (dBm)	Substitution Antenna Gain (dBi)	Emission level (dBm)	Limit (dBm)	Margin (dB)
3191.24	V	-51.71	1.29	-50.42	-13.00	-37.42
3204.67	H	-52.84	1.31	-51.53	-13.00	-38.53

Note :The other harmonic spurious emissions are under limit 20dB more,
so the results were not shown in the table.



5. Occupied Bandwidth


5.1. Test Limit

According to §FCC 2.1049.

5.2. Test Procedures

The EUT's output RF connector was connected with a short cable to the spectrum analyzer, RBW was set to about 1% of emission BW, VBW is set to 3 times the RBW, -26dBc display line was placed on the screen (or 99% bandwidth), the occupied bandwidth is the delta frequency between the two points where the display line intersects the signal trace.

5.3. Test Setup Layout



5.4. Measurement Equipment


Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Calibration Date	Valid Date
Spectrum Analyzer	Agilent	E4407B	MY44211883	2013.09.25	2014.09.25
Temperature/ Humidity Meter	Zhicheng	ZC1-11	CEP-TH-002	2014.03.31	2015.03.30

5.5. Test Result and Data

Test Item	Occupied Bandwidth
Test Mode	WCDMA 850
Test Date	2014-07-21


Channel No.	Frequency (MHz)	Measurement Level (kHz)
4132	826.4	4685
4183	836.6	4685
4233	846.6	4698

Channel 4132






Channel 4183



Channel 4233






Test Item	Occupied Bandwidth
Test Mode	WCDMA 1900
Test Date	2014-07-21


Channel No.	Frequency (MHz)	Measurement Level (kHz)
9262	1852.4	4700
9400	1880.0	4716
9538	1907.6	4730

Channel 9262






Channel 9400



Channel 9538






Test Item	Occupied Bandwidth
Test Mode	HSUPA 850
Test Date	2014-07-21


Channel No.	Frequency (MHz)	Measurement Level (kHz)
4132	826.4	4694
4183	836.6	4683
4233	846.6	4687

Channel 4132






Channel 4183



Channel 4233






Test Item	Occupied Bandwidth
Test Mode	HSUPA 1900
Test Date	2014-07-21


Channel No.	Frequency (MHz)	Measurement Level (kHz)
9262	1852.4	4704
9400	1880.0	4687
9538	1907.6	4714

Channel 9262






Channel 9400



Channel 9538






Test Item	Occupied Bandwidth
Test Mode	HSDPA 850
Test Date	2014-07-21


Channel No.	Frequency (MHz)	Measurement Level (kHz)
4132	826.4	4687
4183	836.6	4665
4233	846.6	4666

Channel 4132






Channel 4183



Channel 4233






Test Item	Occupied Bandwidth
Test Mode	HSDPA 1900
Test Date	2014-07-21


Channel No.	Frequency (MHz)	Measurement Level (kHz)
9262	1852.4	4722
9400	1880.0	4693
9538	1907.6	4716

Channel 9262






Channel 9400



Channel 9538





6. Maximum Peak Output Power


6.1. Test Limit

According to FCC §2.1046.

6.2. Test Procedure

- Place the EUT on a bench and set it in transmitting mode.
- Connect a low loss RF cable from the antenna port to a spectrum analyzer and CMU200 by a Directional Coupler.
- EUT Communicate with CMU200, then selects a channel for testing.
- Add a correction factor to the display of spectrum, and then test.

6.3. Test Setup Layout



6.4. Measurement Equipment

Instrument/Ancillary	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date
Spectrum Analyzer	Agilent	E4407B	MY44211883	2013.09.25	2014.09.25
Temperature/ Humidity Meter	Zhicheng	ZC1-11	CEP-TH-002	2014.03.31	2015.03.30
Universal Radio Communication Tester	R&S	CMU200	108823	2014.01.09	2015.01.08




6.5. Test Result and Data

Test Item	Maximum Peak Output Power
Test Mode	WCDMA 850
Test Date	2014-07-21


Channel No.	Frequency (MHz)	Average Power (dBm)	Peak Power (dBm)
4132	826.4	21.51	22.403
4183	836.6	21.23	22.219
4233	846.6	21.64	22.430

Channel 4132






Channel 4183



Channel 4233






Test Item	Maximum Peak Output Power
Test Mode	WCDMA 1900
Test Date	2014-07-21


Channel No.	Frequency (MHz)	Average Power (dBm)	Peak Power (dBm)
9262	1852.4	19.32	20.669
9400	1880.0	19.85	20.858
9538	1907.6	19.51	20.798

Channel 9262






Channel 9400



Channel 9538






Test Item	Maximum Peak Output Power
Test Mode	HSUPA 850
Test Date	2014-07-21


Channel No.	Frequency (MHz)	Average Power (dBm)	Peak Power (dBm)
4132	826.4	20.04	22.293
4183	836.6	20.77	21.935
4233	846.6	20.13	21.316

Channel 4132






Channel 4183



Channel 4233






Test Item	Maximum Peak Output Power
Test Mode	HSUPA 1900
Test Date	2014-07-21


Channel No.	Frequency (MHz)	Average Power (dBm)	Peak Power (dBm)
9262	1852.4	18.94	20.502
9400	1880.0	19.06	20.723
9538	1907.6	18.75	20.703

Channel 9262






Channel 9400



Channel 9538






Test Item	Maximum Peak Output Power
Test Mode	HSDPA 850
Test Date	2014-07-21


Channel No.	Frequency (MHz)	Average Power (dBm)	Peak Power (dBm)
4132	826.4	20.93	21.978
4183	836.6	20.71	21.430
4233	846.6	21.08	22.195

Channel 4132






Channel 4183



Channel 4233






Test Item	Maximum Peak Output Power
Test Mode	HSDPA 1900
Test Date	2014-07-21


Channel No.	Frequency (MHz)	Average Power (dBm)	Peak Power (dBm)
9262	1852.4	19.32	20.421
9400	1880.0	19.63	20.811
9538	1907.6	19.05	20.075

Channel 9262






Channel 9400



Channel 9538





7. ERP & EIRP MEASUREMENT

7.1. Test Limit

According to FCC §2.1046

FCC 22.913(a): The Effective Radiated Power (ERP) of mobile transmitters must not exceed 7 Watts.

FCC 24.232(b): The equivalent Isotropic Radiated Power (EIRP) must not exceed 2 Watts.

7.2. Test Procedure

The EUT was placed on a non-conductive turntable using a non-conductive support. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and EMI spectrum analyzer.

During the measurement of the EUT, the resolution bandwidth was set to 3MHz and the average bandwidth was set to 3MHz. The highest emission was recorded with the rotation of the turntable and the lowering of the test antenna. The reading was recorded and the field strength (E in dBuV/m) was calculated.

ERP in frequency band 824-849MHz, and EIRP in frequency band 1850 –1910MHz were measured using a substitution method. The EUT was replaced by half-wave dipole (824-849MHz) or horn antenna (1850-1910MHz) connected to a signal generator. The spectrum analyzer reading was recorded and ERP/EIRP was calculated as follows:


$$\text{ERP} = \text{S.G. output (dBm)} + \text{Antenna Gain (dBd)} - \text{Cable (dB)}$$

$$\text{EIRP} = \text{S.G. output (dBm)} + \text{Antenna Gain (dBi)} - \text{Cable (dB)}$$




7.3. Test Setup Layout

Below 1 GHz




Above 1 GHz





For Substituted Method Test Set-UP



7.4. Measurement Equipment

Instrument/Ancillary	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date
Spectrum Analyzer	Agilent	E4407B	MY44211883	2013.09.25	2014.09.25
H64 Amplifier	HP	8447F	3113A05582	2014.03.24	2015.03.23
Preamplifier	Agilent	8449B	ED-HE-EMI-077	2014.03.24	2015.03.23
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	9120D-619	2014.05.24	2015.05.23
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	9120D-618	2014.05.24	2015.05.23
Temperature/Humidity Meter	Zhicheng	ZC1-11	CEP-TH-002	2014.03.31	2015.03.30



7.5. Test Result and Data

WCDMA 850 TEST DATA

Channel	Frequency (MHz)	Antenna Pol.	Reading level (Peak) (dB)	Correction Factor (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
4132	826.4	V	22.58	1.01	23.59	38.5	-14.91
	826.4	H	21.77	0.96	22.73	38.5	-15.77
4183	836.6	V	20.49	1.77	22.26	38.5	-16.24
	836.6	H	20.38	1.46	21.84	38.5	-16.66
4233	846.6	V	19.74	1.85	21.59	38.5	-16.91
	846.6	H	20.31	1.54	21.85	38.5	-16.65

WCDMA1900 TEST DATA

Channel	Frequency (MHz)	Antenna Pol.	Reading level (Peak) (dB)	Correction Factor (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
9262	1852.4	V	20.32	2.34	22.66	33	-10.34
	1852.4	H	19.79	1.88	21.67	33	-11.33
9400	1880	V	20.63	2.12	22.75	33	-10.25
	1880	H	19.58	2.41	21.99	33	-11.01
9538	1907.6	V	20.84	2.34	23.18	33	-9.82
	1907.6	H	19.71	1.98	21.69	33	-11.31

**HSUPA 850 TEST DATA**

Channel	Frequency (MHz)	Antenna Pol.	Reading level (Peak) (dB)	Correction Factor (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
4132	826.4	V	21.86	1.01	22.87	38.5	-15.63
	826.4	H	21.43	0.96	22.39	38.5	-16.11
4183	836.6	V	20.77	1.77	22.54	38.5	-15.96
	836.6	H	20.19	1.46	21.65	38.5	-16.85
4233	846.6	V	21.15	1.85	23	38.5	-15.5
	846.6	H	19.52	1.54	21.06	38.5	-17.44

HSUPA 1900 TEST DATA

Channel	Frequency (MHz)	Antenna Pol.	Reading level (Peak) (dB)	Correction Factor (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
9262	1852.4	V	20.41	2.34	22.75	33	-10.25
	1852.4	H	20.85	1.88	22.73	33	-10.27
9400	1880	V	20.63	2.12	22.75	33	-10.25
	1880	H	19.71	2.41	22.12	33	-10.88
9538	1907.6	V	20.52	2.34	22.86	33	-10.14
	1907.6	H	20.74	1.98	22.72	33	-10.28

**HSDPA 850 TEST DATA**

Channel	Frequency (MHz)	Antenna Pol.	Reading level (Peak) (dB)	Correction Factor (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
4132	826.4	V	21.52	1.01	22.53	38.5	-15.97
	826.4	H	21.23	0.96	22.19	38.5	-16.31
4183	836.6	V	20.69	1.77	22.46	38.5	-16.04
	836.6	H	20.75	1.46	22.21	38.5	-16.29
4233	846.6	V	20.81	1.85	22.66	38.5	-15.84
	846.6	H	20.52	1.54	22.06	38.5	-16.44

HADPA 1900 TEST DATA

Channel	Frequency (MHz)	Antenna Pol.	Reading level (Peak) (dB)	Correction Factor (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
9262	1852.4	V	20.47	2.34	22.81	33	-10.19
	1852.4	H	20.28	1.88	22.16	33	-10.84
9400	1880	V	20.09	2.12	22.21	33	-10.79
	1880	H	19.43	2.41	21.84	33	-11.16
9538	1907.6	V	20.77	2.34	23.11	33	-9.89
	1907.6	H	20.93	1.98	22.91	33	-10.09



8. OUT OF BAND EMISSION AT ANTENNA TERMINALS

8.1. Test Limit

According to FCC §2.1051, FCC §22.917, FCC §24.238(a).

Out of Band Emissions: The mean power of emission must be attenuated below the mean power of the non-modulated carrier (P) on any frequency twice or more than twice the fundamental frequency by at least $43 + 10 \log P$ dB.

Mobile Emissions in Base Frequency Range: The mean power of any emissions appearing in the base station frequency range from cellular mobile transmitters operated must be attenuated to a level not exceed -80 dBm at the transmit antenna connector.

Band Edge Requirements: In the 1MHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 1% of the emission bandwidth of the fundamental emission of the transmitter may be employed to measure the Out of band Emission.


8.2. Test Procedure

The RF output of the transceiver was connected to a spectrum analyzer through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 1MHz, sufficient scans were taken to show the out of band Emissions if any up to 10th harmonic.

For the out of band: Set the RBW, VBW = 1MHz, Start=30MHz, Stop= 10 th harmonic. Limit = -13dBm

Band Edge Requirements (824 MHz and 849 MHz /1850MHz and 1910MHz): In the 1 MHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 1 percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to measure the out of band Emissions. Limit, -13dBm.

8.3. Test Setup Layout



8.4. Measurement Equipment


Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Calibration Date	Valid Date
Spectrum Analyzer	Agilent	E4407B	MY44211883	2013.09.25	2014.09.25
Temperature/ Humidity Meter	Zhicheng	ZC1-11	CEP-TH-002	2014.03.31	2015.03.30



8.5. Test Result and Data

Test Item	Conducted spurious emissions, 30MHz - 20GHz
Test Mode	WCDMA 850
Test Date	2014-07-21

Channel 4132






Channel 4183



Channel 4233





Test Item	Conducted spurious emissions, 30MHz - 20GHz
Test Mode	WCDMA 1900
Test Date	2014-07-21

Channel 9262






Channel 9400



Channel 9538





Test Item	Conducted spurious emissions, 30MHz - 20GHz
Test Mode	HSUPA 850
Test Date	2014-07-21

Channel 4132





Channel 4183



Channel 4233





Test Item	Conducted spurious emissions, 30MHz - 20GHz
Test Mode	HSUPA 1900
Test Date	2014-07-21

Channel 9262






Channel 9400



Channel 9538





Test Item	Conducted spurious emissions, 30MHz - 20GHz
Test Mode	HSDPA 850
Test Date	2014-07-21

Channel 4132






Channel 4183




Channel 4233





Test Item	Conducted spurious emissions, 30MHz - 20GHz
Test Mode	HSDPA 1900
Test Date	2014-07-21

Channel 9262






Channel 9400




Channel 9538






Test Item	Band Edge emissions
Test Mode	WCDMA 850
Test Date	2014-07-21

Channel 4132




Channel 4233






Test Item	Band Edge emissions
Test Mode	WCDMA 1900
Test Date	2014-07-21

Channel 9262




Channel 9538






Test Item	Band Edge emissions
Test Mode	HSUPA 850
Test Date	2014-07-21

Channel 4132




Channel 4233






Test Item	Band Edge emissions
Test Mode	HSUPA 1900
Test Date	2014-07-21

Channel 9262




Channel 9538






Test Item	Band Edge emissions
Test Mode	HSDPA 850
Test Date	2014-07-21

Channel 4132




Channel 4233






Test Item	Band Edge emissions
Test Mode	HSDPA 1900
Test Date	2014-07-21

Channel 9262



Channel 9538





9. FREQUENCY STABILITY V.S. TEMPERATURE MEASUREMENT

9.1. Test Limit


According to FCC §2.1055, FCC §22.355, .FCC §24.235.

Frequency Tolerance: 2.5 ppm

9.2. Test Procedure

The equipment under test was connected to an external AC or DC power supply and input rated voltage. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. The EUT was placed inside the temperature chamber. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 20°C operating frequency as reference frequency. Turn EUT off and set the chamber temperature to -30°C. After the temperature stabilized for approximately 30 minutes recorded the frequency. Repeat step measure with 10°C increased per stage until the highest temperature of +50°C reached.

9.3. Test Setup Layout



9.4. Measurement Equipment

Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Calibration Date	Valid Date
Spectrum Analyzer	Agilent	E4407B	MY44211883	2013.09.25	2014.09.25
Temperature/ Humidity Meter	Zhicheng	ZC1-11	CEP-TH-002	2014.03.31	2015.03.30

**9.5. Test Result and Data**

Test Item	FREQUENCY STABILITY V.S. TEMPERATURE
Test Mode	WCDMA 850 Channel 4183
Test Date	2014-07-21

Reference Frequency: WCDMA Mid Channel 836.6 MHz @ 20°C				
Limit: +/- 2.5 ppm = 2090 Hz				
Power Supply Vac	Environment Temperature (°C)	Frequency (Hz)	Delta (Hz)	Limit (Hz)
3.7	50	836600057	57	2090
	40	836600079	79	
	30	836600042	42	
	20	836600000	0	
	10	836600052	52	
	0	836600039	39	
	-30	836600018	18	

Test Item	FREQUENCY STABILITY V.S. TEMPERATURE
Test Mode	WCDMA 1900 Channel 9440
Test Date	2014-07-21

Reference Frequency: WCDMA Mid Channel 1880 MHz @ 20°C				
Limit: ± 2.5 ppm = 4700 Hz				
Power Supply Vac	Environment Temperature (°C)	Frequency (Hz)	Delta (Hz)	Limit (Hz)
3.7	50	1880000039	39	4700
	40	1880000027	27	
	30	1880000071	71	
	20	1880000000	0	
	10	1880000052	52	
	0	1880000063	63	
	-30	1880000089	89	



Test Item	FREQUENCY STABILITY V.S. TEMPERATURE
Test Mode	HSUPA 850 Channel 4183
Test Date	2014-07-21

Reference Frequency: HSUPA Mid Channel 836.6 MHz @ 20°C				
Limit: +/- 2.5 ppm = 2090 Hz				
Power Supply Vac	Environment Temperature (°C)	Frequency (Hz)	Delta (Hz)	Limit (Hz)
3.7	50	836600042	42	2090
	40	836600075	75	
	30	836600059	59	
	20	836600000	0	
	10	836600096	96	
	0	836600082	82	
	-30	836600043	43	

Test Item	FREQUENCY STABILITY V.S. TEMPERATURE
Test Mode	HSUPA 1900 Channel 9400
Test Date	2014-07-21

Reference Frequency: HSUPA Mid Channel 1880 MHz @ 20°C				
Limit: ± 2.5 ppm = 4700 Hz				
Power Supply Vac	Environment Temperature (°C)	Frequency (Hz)	Delta (Hz)	Limit (Hz)
3.7	50	1880000052	52	4700
	40	1880000079	79	
	30	1880000023	23	
	20	1880000000	0	
	10	1880000057	57	
	0	1880000041	41	
	-30	1880000036	36	



Test Item	FREQUENCY STABILITY V.S. TEMPERATURE
Test Mode	HSDPA 850 Channel 4183
Test Date	2014-07-21

Reference Frequency: HSDPA Mid Channel 836.6 MHz @ 20°C				
Limit: +/- 2.5 ppm = 2090 Hz				
Power Supply Vac	Environment Temperature (°C)	Frequency (Hz)	Delta (Hz)	Limit (Hz)
3.7	50	836600052	52	2090
	40	836600087	87	
	30	836600071	71	
	20	836600000	0	
	10	836600038	38	
	0	836600097	97	
	-30	836600079	79	

Test Item	FREQUENCY STABILITY V.S. TEMPERATURE
Test Mode	HSDPA 1900 Channel 9400
Test Date	2014-07-21

Reference Frequency: HSDPA Mid Channel 1880 MHz @ 20°C				
Limit: ± 2.5 ppm = 4700 Hz				
Power Supply Vac	Environment Temperature (°C)	Frequency (Hz)	Delta (Hz)	Limit (Hz)
3.7	50	1880000052	52	4700
	40	1880000031	31	
	30	1880000069	69	
	20	1880000000	0	
	10	1880000097	97	
	0	1880000041	41	
	-30	1880000072	72	



10. FREQUENCY STABILITY V.S. VOLTAGE MEASUREMENT

10.1. Test Limit


According to FCC §2.1055, FCC §22.355, .FCC §24.235.

10.2. Test Procedure

Set chamber temperature to 20°C. Use a variable AC power supply / DC power source to power the EUT and set the voltage to rated voltage. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency.

Reduce the input voltage to specify extreme voltage variation ($\pm 10\%$) and endpoint, record the maximum frequency change.

10.3. Test Setup Layout



10.4. Measurement Equipment

Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Calibration Date	Valid Date
Spectrum Analyzer	Agilent	E4407B	MY44211883	2013.09.25	2014.09.25
Temperature/ Humidity Meter	Zhicheng	ZC1-11	CEP-TH-002	2014.03.31	2015.03.30

**10.5. Test Result and Data**

Test Item	REQUENCY STABILITY V.S. VOLTAGE
Test Mode	WCDMA 850 Channel 4183
Test Date	2014-07-21

Reference Frequency: WCDMA Mid Channel 836.6 MHz @ 20°C				
Limit: ± 2.5 ppm = 2090Hz				
Power Supply Vac	Environment Temperature (°C)	Frequency (Hz)	Delta (Hz)	Limit (Hz)
4.2	20	836599968	32	2090
3.7		836600000	0	
3.6		836599962	38	

Test Item	REQUENCY STABILITY V.S. VOLTAGE
Test Mode	WCDMA 1900 Channel 9400
Test Date	2014-07-21

Reference Frequency: WCDMA Mid Channel 1880 MHz @ 20°C				
Limit: ± 2.5 ppm = 4700 Hz				
Power Supply Vac	Environment Temperature (°C)	Frequency (Hz)	Delta (Hz)	Limit (Hz)
4.2	20	1879999937	63	4700
3.7		1880000000	0	
3.6		1879999988	12	



Test Item	REQUENCY STABILITY V.S. VOLTAGE
Test Mode	HSUPA 850 Channel 4183
Test Date	2014-07-21

Reference Frequency: HSUPA Mid Channel 836.6 MHz @ 20°C				
Limit: ± 2.5 ppm = 2090Hz				
Power Supply Vac	Environment Temperature (°C)	Frequency (Hz)	Delta (Hz)	Limit (Hz)
4.2	20	836599941	59	2090
3.7		836600000	0	
3.6		836599972	28	

Test Item	REQUENCY STABILITY V.S. VOLTAGE
Test Mode	HSUPA 1900 Channel 9400
Test Date	2014-07-21

Reference Frequency: HSUPA Mid Channel 1880 MHz @ 20°C				
Limit: ± 2.5 ppm = 4700 Hz				
Power Supply Vac	Environment Temperature (°C)	Frequency (Hz)	Delta (Hz)	Limit (Hz)
4.2	20	1879999948	52	4700
3.7		1880000000	0	
3.6		1879999965	35	



Test Item	REQUENCY STABILITY V.S. VOLTAGE
Test Mode	HSDPA 850 Channel 4183
Test Date	2014-07-21

Reference Frequency: HSDPA Mid Channel 836.6 MHz @ 20°C				
Limit: ± 2.5 ppm = 2090Hz				
Power Supply Vac	Environment Temperature (°C)	Frequency (Hz)	Delta (Hz)	Limit (Hz)
4.2	20	836599985	15	2090
3.7		836600000	0	
3.6		836599932	68	

Test Item	REQUENCY STABILITY V.S. VOLTAGE
Test Mode	HSDPA 1900 Channel 9400
Test Date	2014-07-21

Reference Frequency: HSDPA Mid Channel 1880 MHz @ 20°C				
Limit: ± 2.5 ppm = 4700 Hz				
Power Supply Vac	Environment Temperature (°C)	Frequency (Hz)	Delta (Hz)	Limit (Hz)
4.2	20	1879999952	48	4700
3.7		1880000000	0	
3.6		1879999987	13	