

RF Exposure Considerations for FCC ID: OO4-IDS1010

SAR Test exclusion evaluation for device used as portable

Per FCC KDB 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by (Eq.1) below:

$$SAR = \frac{MaxPower(mW)}{d(mm)} \times \sqrt{f(GHz)} \quad (Eq. 1)$$

Where:

- *SAR* is the calculation for test exclusion threshold;
- *MaxPower* is the maximum power of channel, including tune-up tolerance, in mW;
- *d* is the minimum test separation distance, in mm;
- *f* is the RF channel transmit frequency, in GHz.

Power and distance are rounded to the nearest mW and mm before calculation.

The result is rounded to one decimal place for comparison.

If result of Eq.1 is less than or equal to the exemption limits below, then corresponding SAR test is not required.

SAR Test Configuration	Exemption limit
1-g SAR	Result of Eq.1 ≤ 3.0
10-g extremity SAR	Result of Eq.1 ≤ 7.5

The test exclusions are applicable only when the minimum *test separation distance* is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

COORDONNEES

SMEE
R385, Rue René Rambaud, ZA Le Parvis 2
38500 VOIRON - France

TEL : 04 76 65 76 50
FAX : 04 76 66 18 30

SAS au capital de 50 000 € / RC Grenoble B534 796 453 / SIRET 534 796 453 00023 / code APE 7490B / n° TVA : FR 59 534 796 453



For the device, the parameters for consideration are as follows:

<i>Frequency (MHz)</i>	<i>Maximum source-based time averaged conducted output power including tune-up tolerance</i>	<i>Minimum separation distance (mm)</i>	<i>Result of Eq. 1</i>	<i>Limit for 1-g SAR</i>	<i>Limit for 10-g extremity SAR</i>	<i>Verdict</i>
902.5 to 927.5MHz	0.46mW*	5	0.089	3.0	7.5	Exempt from SAR

(*EIRP)

Conclusion: Therefore the device complies with FCC's RF radiation exposure limits for general population without SAR evaluation when it is used at a distance of 5mm.

Prepared By
Laurent CHAPUS (Agent for this device)

SMEE

385, Rue René Rambaud

ZA Le Parvis 2

38500 Voiron - France

laurent.chapus@smee.fr

FCC Registration Number: 0020356952 (FRN)

A handwritten signature in black ink, appearing to read "Laurent Chapus".

Applicant for this device:
IDENITEC SOLUTIONS AG

Millennium Park 2

A-6890 Lustenau

Austria

ContactPhone: +43 5577 87387 0