

H



SENTON

Choose certainty.
Add value.

November 25,
2009

Prüfbericht / Test Report

Nr. / No. 69860-00094-12 (Edition 3)

Applicant: IDENTEC SOLUTIONS Deutschland GmbH
Type of equipment: UHF Transponder Reader
Type designation: i-Port H310
Order No.: 1930117
Test standards: FCC Code of Federal Regulations,
CFR 47, Part 15,
Sections 15.107, 15.109, 15.205, 15.207, 15.215, 15.231 and 15.240

Industry Canada Radio Standards Specifications
RSS-Gen Issue 2, Sections 7.2.2, 7.2.3 and
RSS-210 Issue 7, Sections 2.2, A1.1 and A5 (Category I Equipment)

Note:

The test data of this report is related only to the individual item which has been tested. This report shall not be reproduced except in full extent without the written approval of the testing laboratory.



Table of Contents

1	Description of the Equipment Under Test (EUT).....	3
2	Administrative Data	4
3	Identification of the Test Laboratory.....	5
4	Summary.....	6
5	Operation Mode and Configuration of EUT	7
6	Measurement Procedures	9
6.1	Bandwidth Measurements	9
6.2	Radiated Emission Measurement 9 kHz to 30 MHz.....	10
6.3	Radiated Emission in Fully or Semi Anechoic Room.....	14
6.4	Radiated Emission at Open Field Test Site	16
7	Photographs Taken During Testing.....	18
8	Test Results for Transmitter	22
8.1	Occupied Bandwidth	24
8.2	Bandwidth of the Emission.....	28
8.3	Bandwidth of Momentary Signals	30
8.4	Designation of Emissions.....	31
8.5	Restricted Bands of Operation.....	32
8.6	Periodic Operation Requirements	33
8.7	Radiated Emission Measurement 9 kHz to 30 MHz.....	39
8.8	Radiated Emission Measurement 30 MHz to 4.5 GHz.....	41
8.9	Exposure of Humans to RF Fields	49
9	Test Results for Receiver.....	51
9.1	Radiated Emission Measurement 30 MHz to 2.5 GHz.....	52
10	Referenced Regulations.....	54
11	Referenced Regulations.....	54
12	Revision History	56

1 Description of the Equipment Under Test (EUT)

General data of EUT

Type designation ¹ :	i-Port H310
Parts ² :	
Serial number(s):	MC9X
Manufacturer:	IDENTEC SOLUTIONS Deutschland GmbH
Type of equipment:	UHF Transponder Reader
Version:	As received
FCC ID:	---
Additional parts/accessories:	

Technical data of EUT

Application frequency range:	433.5 - 434.5 MHz
Frequency range:	433.92 MHz
Operating frequency:	433.92 MHz
Type of modulation:	FSK
Pulse train:	Not applicable
Pulse width:	Not applicable
Number of RF-channels:	1
Channel spacing:	---
Designation of emissions ³ :	248kF1D
Type of antenna:	Fix connected
Size/length of antenna:	17 cm
Connection of antenna:	<input type="checkbox"/> detachable <input checked="" type="checkbox"/> not detachable
Type of power supply:	AC supply
Specifications for power supply:	nominal voltage: 12 V
	nominal frequency: DC Hz

¹ Type designation of the system if EUT consists of more than one part.

² Type designations of the parts of the system, if applicable.

³ Also known as "Class of Emission".



2 Administrative Data

Application details

Applicant (full address):	IDENTEC SOLUTIONS Deutschland GmbH Hertzstraße 10 69469 Weinheim Deutschland
Contact person:	Herr Hans-Günther Meuthen
Order number:	1930117
Receipt of EUT:	July 07, 2009
Date(s) of test:	August 2009
Note(s):	Mr. Meuthen representing the applicant attended testings on July 2009

Report details

Report number:	69860-00094-12
Edition:	3
Issue date:	November 25, 2009



3 Identification of the Test Laboratory

Details of the Test Laboratory

Company name:	TÜV SÜD SENTON GmbH
Address:	Aeussere Fruehlingstrasse 45 D-94315 Straubing Germany
Laboratory accreditation:	DAR-Registration No. DAT-P-171/94-02
FCC test site registration number	90926
Industry Canada test site registration:	3050A-1
Contact person:	Mr. Johann Roidt
	Phone: +49 9421 5522-0 Fax: +49 9421 5522-99

4 Summary

Summary of test results

The tested sample complies with the requirements set forth in the
Code of Federal Regulations CFR 47, Part 15, Sections 15.107, 15.109, 15.205, 15.207, 15.215, 15.231(a)-(d) and 15.240
of the Federal Communication Commission (FCC) and the
**Radio Standards Specifications
RSS-Gen Issue 2, Sections 7.2.2, 7.2.3 and
RSS-210 Issue 7, Sections 2.2, A1.1.1 to A1.1.4 and A5 (Category I Equipment)**
of Industry Canada (IC).

Personnel involved in this report

Laboratory Manager:



Mr. Johann Roidt

Responsible for testing:

Mr. Johann Roidt

Responsible for test report:

Mr. Johann Roidt

5 Operation Mode and Configuration of EUT

Operation Modes

Full tests were performed in transmitting and receiving mode.

Configuration of EUT

The EUT was configured as a manually triggered device. The TX power was set to -15dBm by software.

List of devices connected to EUT

<i>Item</i>	<i>Description</i>	<i>Type Designation</i>	<i>Serial no. or ID</i>	<i>Manufacturer</i>
	None			

List of support devices

<i>Item</i>	<i>Description</i>	<i>Type Designation</i>	<i>Serial no. or ID</i>	<i>Manufacturer</i>
	AC Adapter 12 V	HP-O2040D43	N/A	HIPRO
	Mobile Computer	MC 9090	40847F40P	Bartec GmbH



List of ports and cables

<i>Port</i>	<i>Description</i>	<i>Classification⁴</i>	<i>Cable type</i>	<i>Cable length</i>
	DC Supply Input	dc power	unshielded	2 m

⁴ Ports shall be classified as ac power, dc power or signal/control port




6 Measurement Procedures

6.1 Bandwidth Measurements

Measurement Procedure:	
Rules and specifications:	CFR 47 Part 2, section 2.202(a) CFR 47 Part 15, section 15.215(c) IC RSS-Gen Issue 2, sections 4.6.1 and 4.6.2 IC RSS-210 Issue 7, section A1.1.3 ANSI C63.4, annex H.6
Guide:	ANSI C63.4 / IC RSS-Gen Issue 2, sections 4.6.1 and 4.6.2
Measurement setup:	<input type="checkbox"/> Conducted: See below <input checked="" type="checkbox"/> Radiated: Radiated Emission in Fully or Semi Anechoic Room (6.4)
<p>If antenna is detachable bandwidth measurements shall be performed at the antenna connector (conducted measurement) when the transmitter is adjusted in accordance with the tune-up procedure, if applicable. The RF output terminals are connected to a spectrum analyzer. If required, a resistive matching network equal to the impedance specified or employed for the antenna is used as well as dc block and appropriate attenuators (50 Ohms). The electrical characteristics of the radio frequency load attached to the output terminals shall be stated, if applicable.</p> <p>If radiated measurements are performed the same test setups and instruments are used as with radiated emission measurements for the appropriate frequency range.</p> <p>The analyzer settings are specified by the test description of the appropriate test record(s).</p>	

6.2 Radiated Emission Measurement 9 kHz to 30 MHz

Measurement Procedure:	
Rules and specifications:	CFR 47 Part 15, sections 15.215(b) and 15.231(b)(3) IC RSS-210 Issue 7, section A1.1.2(b)
Guide:	ANSI C63.4
<p>Radiated emission in the frequency range 9 kHz to 30 MHz is measured using an active loop antenna. First the whole spectrum of emission caused by the equipment is recorded at a distance of 3 meters in a fully or semi anechoic room with the detector of the spectrum analyzer or EMI receiver set to peak. This configuration is also used for recording the spectrum of intentional radiators.</p> <p>Hand-held or body-worn devices are rotated through three orthogonal axes to determine which attitude and configuration produces the highest emission relative to the limit and therefore shall be used for final testing. EUT is rotated all around to find the maximum levels of emissions. Equipment and cables are placed and moved within the range of position likely to find their maximum emissions.</p> <p>If worst case emission of the EUT cannot be recorded with EUT in standard position and loop antenna in vertical polarization the EUT (or the radiating part of the EUT) is rotated by 90 degrees instead of changing the loop antenna to horizontal polarization. This procedure is selected to minimize the influence of the environment (e.g. effects caused by the floor especially with longer distances).</p> <p>Final measurement is performed at a test distance D of 30 meters using an open field test site. In case the regulation requires testing at other distances, the result is extrapolated by either making measurements at an additional distance D of 10 meters to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). In cases of very low emissions measurements are performed at shorter distances and results are extrapolated to the required distance. The provisions of CFR 47 Part 15 sections 15.31(d) and (f)(2) apply. According to CFR 47 Part 15 section 15.209(d) final measurement is performed with detector function set to quasi-peak except for the frequency bands 9 to 90 kHz and 110 to 490 kHz where, for non-pulsed operation, average detector is employed.</p> <p>If the radiated emission limits are expressed in terms of the average value of the emission there also is a peak limit corresponding to 20 dB above the maximum permitted average limit. Additionally, if pulsed operation is employed, the average field strength is determined by averaging over one complete pulse train, including blanking intervals, as specified in CFR 47 Part 15 section 15.35(c). If the pulse train exceeds 0.1 second that 0.1 second interval during which the value of the emission is at its maximum is selected for calculation. The pulse train correction is added to the peak value of the emission to get the average value.</p>	






Test instruments used:

Used	Type	Model	Serial No. or ID	Manufacturer
<input checked="" type="checkbox"/>	Spectrum Analyzer	FSP 30	100063	Rohde & Schwarz
<input type="checkbox"/>	EMI test receiver	ESMI	839379/013 839587/006	Rohde & Schwarz
<input checked="" type="checkbox"/>	Test receiver	ESHS 10	860043/016	Rohde & Schwarz
<input type="checkbox"/>	Preamplifier	CPA9231A	3393	Schaffner
<input checked="" type="checkbox"/>	Loop antenna	HFH2-Z2	882964/1	Rohde & Schwarz
<input checked="" type="checkbox"/>	Fully anechoic room	No. 2	1452	Albatross Projects
<input type="checkbox"/>	Semi-anechoic room	No. 3	1453	Siemens
<input checked="" type="checkbox"/>	Open field test site	EG 1	1450	Senton

6.3 Conducted AC Powerline Emission

Measurement Procedure:	
Rules and specifications:	CFR 47 Part 15, section 15.207 IC RSS-Gen Issue 2, section 7.2.2
Guide:	ANSI C63.4 (CISPR 22)
<p>Conducted emission tests in the frequency range 150 kHz to 30 MHz are performed using Line Impedance Stabilization Networks (LISNs). To simplify testing with quasi-peak and average detector the following procedure is used:</p> <p>First the whole spectrum of emission caused by the equipment under test (EUT) is recorded with detector set to peak using CISPR bandwidth of 10 kHz. After that all emission levels having less margin than 10 dB to or exceeding the average limit are retested with detector set to quasi-peak.</p> <p>If average limit is kept with quasi-peak levels no additional scan with average detector is necessary. In cases of emission levels between quasi-peak and average limit an additional scan with detector set to average is performed.</p> <p>According to ANSI C63.4, section 13.1.3.1, testing of intentional radiators with detachable antenna shall be performed using a suitable dummy load connected to the antenna output terminals. Otherwise, the tests shall be made with the antenna connected and, if adjustable, fully extended.</p> <p>Testing with dummy load may be necessary to distinguish (unintentional) conducted emissions on the supply lines from (intentional) emissions radiated by the antenna and coupling directly to supply lines and/or LISN. Usage of dummy load has to be stated in the appropriate test record(s) and notes should be added to clarify the test setup.</p>	






Test instruments used:

Used	Type	Model	Serial No. or ID	Manufacturer
<input type="checkbox"/>	EMI receiver	ESHS 10	860043/016	Rohde & Schwarz
<input type="checkbox"/>	LISN	ESH3-Z5	862770/021	Rohde & Schwarz
<input type="checkbox"/>	LISN	ESH3-Z5	830952/025	Rohde & Schwarz
<input type="checkbox"/>	Artificial mains network	ESH 2-Z5	842966/004	Rohde & Schwarz
<input type="checkbox"/>	Shielded room	No. 1	1451	Albatross Projects
<input type="checkbox"/>	Shielded room	No. 4	3FD-100 544	Euroshield

6.4 Radiated Emission in Fully or Semi Anechoic Room

Measurement Procedure:	
Rules and specifications:	CFR 47 Part 15, sections 15.109, 15.215(b) and 15.231 IC RSS-Gen Issue 2, sections 6(a) and 7.2.3.2 IC RSS-210 Issue 7, section A1.1.2
Guide:	ANSI C63.4
<p>Radiated emission in fully or semi anechoic room is measured in the frequency range from 30 MHz to the maximum frequency as specified in CFR 47 Part 15 section 15.33.</p> <p>Measurements are made in both the horizontal and vertical planes of polarization in a fully anechoic room using a spectrum analyzer with the detector function set to peak and resolution as well as video bandwidth set to 100 kHz (below 1 GHz) or 1 MHz (above 1 GHz).</p> <p>Testing up to 1 GHz is performed with a linear polarized logarithmic periodic antenna combined with a 4:1 broadband dipole ("Trilog broadband antenna"). For testing above 1 GHz horn antennas are used.</p> <p>All tests below 8.2 GHz are performed at a test distance D of 3 meters. For higher frequencies the test distance may be reduced (e.g. to 1 meter) due to the sensitivity of the measuring instrument(s) and the test results are calculated according to CFR 47 Part 15 section 15.31(f)(1) using an extrapolation factor of 20 dB/decade. If required, preamplifiers are used for the whole frequency range. Special care is taken to avoid overload, using appropriate attenuators and filters, if necessary.</p> <p>If the radiated emission limits are expressed in terms of the average value of the emission there also is a peak limit corresponding to 20 dB above the maximum permitted average limit. Additionally, if pulsed operation is employed, the average field strength is determined by averaging over one complete pulse train, including blanking intervals, as specified in CFR 47 Part 15 section 15.35(c). If the pulse train exceeds 0.1 second that 0.1 second interval during which the value of the emission is at its maximum is selected for calculation. The pulse train correction is added to the peak value of the emission to get the average value.</p> <p>Hand-held or body-worn devices are rotated through three orthogonal axes to determine which attitude and configuration produces the highest emission relative to the limit and therefore shall be used for final testing.</p> <p>During testing the EUT is rotated all around to find the maximum levels of emissions. Equipment and cables are placed and moved within the range of position likely to find their maximum emissions.</p> <p>For final testing below 1 GHz an open field test-site is used and the plots recorded in the fully or semi anechoic room are indicated as prescans.</p>	



Test instruments used:

Used	Type	Model	Serial No. or ID	Manufacturer
<input checked="" type="checkbox"/>	Spectrum Analyzer	FSP 30	100063	Rohde & Schwarz
<input type="checkbox"/>	EMI test receiver	ESPI7	101018	Rohde & Schwarz
<input type="checkbox"/>	EMI test receiver	ESMI	839379/013 839587/006	Rohde & Schwarz
<input checked="" type="checkbox"/>	Preamplifier	CPA9231A	3393	Schaffner
<input type="checkbox"/>	Preamplifier	R14601		Advantest
<input checked="" type="checkbox"/>	Preamplifier 1-8 GHz	AFS3-00100800-32-LN	847743	Miteq
<input type="checkbox"/>	Preamplifier 0.5-8 GHz	AMF-4D-005080-25-13P	860149	Miteq
<input type="checkbox"/>	Preamplifier 8-18 GHz	ACO/180-3530	32641	CTT
<input type="checkbox"/>	External Mixer	WM782A	845881/005	Tektronix
<input type="checkbox"/>	Harmonic Mixer	FS-Z30	843389/007	Rohde & Schwarz
	Accessories			
<input checked="" type="checkbox"/>	Trilog broadband antenna	VULB 9163	9163-188	Schwarzbeck
<input checked="" type="checkbox"/>	Horn antenna	3115	9508-4553	EMCO
<input type="checkbox"/>	Horn antenna	3160-03	9112-1003	EMCO
<input type="checkbox"/>	Horn antenna	3160-04	9112-1001	EMCO
<input type="checkbox"/>	Horn antenna	3160-05	9112-1001	EMCO
<input type="checkbox"/>	Horn antenna	3160-06	9112-1001	EMCO
<input type="checkbox"/>	Horn antenna	3160-07	9112-1008	EMCO
<input type="checkbox"/>	Horn antenna	3160-08	9112-1002	EMCO
<input type="checkbox"/>	Horn antenna	3160-09	9403-1025	EMCO
<input type="checkbox"/>	Horn antenna	3160-10	399185	EMCO
<input checked="" type="checkbox"/>	Fully anechoic room	No. 2	1452	Albatross Projects
<input type="checkbox"/>	Semi-anechoic room	No. 3	1453	Siemens

6.5 Radiated Emission at Open Field Test Site

Measurement Procedure:

Rules and specifications: CFR 47 Part 15, sections 15.109, 15.215(b) and 15.231
 IC RSS-Gen Issue 2, sections 6(a) and 7.2.3.2
 IC RSS-210 Issue 7, section A1.1.2


Guide: ANSI C63.4

Radiated emission at open field test site is measured in the frequency range 30 MHz to 1 GHz using a biconical antenna up to 300 MHz and a logarithmic periodic antenna above. The measurement bandwidth of the test receiver is set to 120 kHz with quasi-peak detector selected.

If the radiated emission limits are expressed in terms of the average value of the emission there also is a peak limit corresponding to 20 dB above the maximum permitted average limit. Additionally, if pulsed operation is employed, the average field strength is determined by averaging over one complete pulse train, including blanking intervals, as specified in CFR 47 Part 15 section 15.35(c). If the pulse train exceeds 0.1 second that 0.1 second interval during which the value of the emission is at its maximum is selected for calculation. The pulse train correction is added to the peak value of the emission to get the average value.

Hand-held or body-worn devices are tested in the position producing the highest emission relative to the limit as verified by prescans in the fully anechoic room. EUT is rotated all around and receiving antenna is raised and lowered within 1 meter to 4 meters to find the maximum levels of emission. Equipment and cables are placed and moved within the range of position likely to find their maximum emissions.

For measuring emissions of intentional radiators and receivers a test distance D of 3 meters is selected. Testing of unintentional radiators is performed at a distance of 10 meters. If limits specified for 3 meters shall be used for measurements performed at 10 meters distance the limits are calculated according to CFR 47 Part 15 section 15.31(d) and (f)(1) using an inverse linear-distance extrapolation factor of 20 dB/decade.






Test instruments used:

Used	Type		Model	Serial No. or ID	Manufacturer
<input checked="" type="checkbox"/>	EMI receiver	EG 1	ESVP	881120/024	Rohde & Schwarz
<input type="checkbox"/>	EMI receiver		ESVP	891846/003	Rohde & Schwarz
<input checked="" type="checkbox"/>	Biconical antenna	EG 1	HK 116	842204/001	Rohde & Schwarz
<input checked="" type="checkbox"/>	Log. per. antenna	EG 1	HL 223	841516/023	Rohde & Schwarz
<input checked="" type="checkbox"/>	Open field test site		EG 1	1450	Senton




7 Photographs Taken During Testing



Test setup for conducted AC powerline emission measurement



Test setup for radiated emission measurement 9 kHz – 30 MHz



Test setup for radiated emission measurement





8 Test Results for Transmitter

FCC CFR 47 Parts 2 and 15			
Section(s)	Test	Page	Result
2.1046(a)	Conducted output power	---	Not applicable
2.202(a)	Occupied bandwidth	24	Recorded
15.215(c) 15.231(c)	Bandwidth of the emission	28	Test passed
2.201, 2.202	Class of emission	31	Calculated
15.35(c)	Pulse train measurement for pulsed operation	---	Not applicable
15.205(a)	Restricted bands of operation	32	Test passed
15.207	Conducted AC powerline emission 150 kHz to 30 MHz		Test pass
15.231(a) 15.240(b)	Periodic operation requirements	33	Test passed
15.205(b) 15.231(b)	Radiated emission 9 kHz to 30 MHz	39	Test passed
15.205(b) 15.215(b) 15.231(b) 15.240(b)	Radiated emission 30 MHz to 4.5 GHz	41	Test passed
15.231(d)	Carrier frequency stability	---	Not applicable



IC RSS-Gen Issue 2			
<i>Section(s)</i>	<i>Test</i>	<i>Page</i>	<i>Result</i>
4.8	Transmitter output power (conducted)	---	Not applicable
4.6.1	Occupied Bandwidth	24	Recorded
3.2(h), 8	Designation of emissions	31	Calculated
4.5	Pulsed operation		Not applicable
7.2.2	Transmitter AC power lines conducted emissions 150 kHz to 30 MHz		Test pass
5.5	Exposure of Humans to RF Fields	49	Exempted from SAR and RF evaluation

IC RSS-210 Issue 7			
<i>Section(s)</i>	<i>Test</i>	<i>Page</i>	<i>Result</i>
2.2(a)	Restricted bands and unwanted emission frequencies	32	Test passed
A1.1.1 A5	Requirements for momentarily operated devices	33	Test passed
A1.1.2 2.2(b)(c), 2.6	Unwanted emissions 9 kHz to 30 MHz	39	Test passed
A1.1.2 2.2(b)(c), 2.6	Unwanted emissions 30 MHz to 4.5 GHz	41	Test passed
A1.1.3	Bandwidth of momentary signals	30	Test passed
A1.1.4	Carrier frequency stability	---	Not applicable



8.1 Occupied Bandwidth

Rules and specifications:	CFR 47 Part 2, section 2.202(a) ANSI C63.4, annex H.6	
Guide:	ANSI C63.4	
Description:	The occupied bandwidth according to CFR 47 Part 2, section 2.202(a), is measured as the 99% emission bandwidth, i.e. below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5% of the total mean power radiated by a given emission.	
	The occupied bandwidth according to ANSI C63.4, annex H.6; is measured as the frequency range defined by the points that are 26 dB down relative to the maximum level of the modulated carrier.	
	The resolution bandwidth of the spectrum analyzer shall be set to a value greater than 5.0% of the allowed bandwidth. If no bandwidth specifications are given, the following guidelines are used:	
	Fundamental frequency	Minimum resolution bandwidth
	9 kHz to 30 MHz	1 kHz
	30 MHz to 1000 MHz	10 kHz
	1000 MHz to 40 GHz	100 kHz
	The video bandwidth shall be at least three times greater than the resolution bandwidth.	
Measurement procedure:	Bandwidth Measurements (6.1)	


Comment:	
Date of test:	21 July 2009
Test site:	Fully anechoic room, cabin no. 2

Occupied Bandwidth (99 %):



SWEEP TIME
 60 s
 Ref 70 dBµV *Att 20 dB

*RBW 10 kHz Marker 1 [T1]
 *VBW 100 kHz 47.62 dBµV
 *SWT 60 s 433.970000000 MHz



Date: 20 APR 2009 14:20:48

Occupied Bandwidth (99 %): **248 kHz**



Occupied Bandwidth (continued)

Rules and specifications:	IC RSS-Gen Issue 2, section 4.6.1
Guide:	IC RSS-Gen Issue 2, section 4.6.1
Description:	<p>If not specified in the applicable RSS the occupied bandwidth is measured as the 99% emission bandwidth.</p> <p>The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts. The resolution bandwidth shall be set to as close to 1% of the selected span as is possible without being below 1%. The video bandwidth shall be set to 3 times the resolution bandwidth.</p> <p>The trace data points are recovered and are directly summed in linear terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached and that frequency recorded. The process is repeated for the highest frequency data points. This frequency is also recorded. The span between the two recorded frequencies is the occupied bandwidth.</p>
Measurement procedure:	Bandwidth Measurements (6.1)


Comment:	
Date of test:	21 July 2009
Test site:	Fully anechoic room, cabin no. 2

Occupied Bandwidth (99 %):



SWEEP TIME
 60 s
 Ref 70 dBµV *Att 20 dB

*RBW 10 kHz Marker 1 [T1]
 *VBW 100 kHz 47.62 dBµV
 *SWT 60 s 433.970000000 MHz



Date: 20.APR.2009 14:20:48


Occupied Bandwidth (99 %): **248 kHz**



8.2 Bandwidth of the Emission

Rules and specifications:	CFR 47 Part 15, section 15.215(c)	
Guide:	ANSI C63.4	
Description:	<p>The 20 dB bandwidth of the emission is measured as the frequency range defined by the points that are 20 dB down relative to the maximum level of the modulated carrier.</p> <p>For intentional radiators operating under the alternative provisions to the general emission limits the requirement to contain the 20 dB bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.</p> <p>The resolution bandwidth of the spectrum analyzer shall be set to a value greater than 5.0% of the allowed bandwidth. If no bandwidth specifications are given, the following guidelines are used:</p>	
	Fundamental frequency	Minimum resolution bandwidth
	9 kHz to 30 MHz	1 kHz
	30 MHz to 1000 MHz	10 kHz
	1000 MHz to 40 GHz	100 kHz
	The video bandwidth shall be at least three times greater than the resolution bandwidth.	
Measurement procedure:	Bandwidth Measurements (6.1)	

Comment:	
Date of test:	22 July 2009
Test site:	Fully anechoic room, cabin no. 2



Date: 20.APR.2009 14:17:31

Permitted frequency band:	433.5 - 434.5 MHz	
20 dB bandwidth:	286 kHz	
Carrier frequency stability:	<input type="checkbox"/> specified	<input checked="" type="checkbox"/> not specified
Maximum frequency tolerances:		
Bandwidth of the emission:	286kHz	within permitted frequency band⁵: <input checked="" type="checkbox"/> yes <input type="checkbox"/> no

Test Result:	Test passed
--------------	-------------

⁵ If a frequency stability is not specified, it is recommended that the fundamental emission is kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.



8.3 Bandwidth of Momentary Signals

Rules and specifications:	IC RSS-210 Issue 7, section A1.1.3
Guide:	IC RSS-Gen Issue 2, section 4.6.1
Limit:	For the purpose of Section A1.1, the 99% bandwidth shall be no wider than 0.25% of the centre frequency for devices operating between 70 and 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the centre frequency.

Operating frequency:	433.92 MHz
Bandwidth limit:	1084.8 kHz
Occupied bandwidth:	248 kHz
Emission bandwidth within bandwidth limit:	<input checked="" type="checkbox"/> yes <input type="checkbox"/> no

Test Result:	Test passed
--------------	-------------



8.4 Designation of Emissions

Rules and specifications:	CFR 47 Part 2, sections 2.201 and 2.202 IC RSS-Gen Issue 2, sections 3.2(h) and 8
Guide:	ANSI C63.4 / TRC-43

Type of modulation:	Frequency Shift Keying (FSK)
---------------------	------------------------------


B_n = Necessary Bandwidth	$B_n = 2DK + B$
D = Peak deviation	D = 54 kHz
K = Overall numerical factor	K = 1
B = Modulation rate	B = 70 kHz
Calculation:	$B_n = 2 \cdot (54 \text{ kHz}) \cdot 1 + 2 \cdot (70 \text{ kHz}) = 248 \text{ kHz}$

Designation of Emissions:	248kF1D
---------------------------	----------------

8.5 Restricted Bands of Operation

Rules and specifications:	CFR 47 Part 15, section 15.205(a) IC RSS-210 Issue 7, section 2.2(a)
Guide:	ANSI C63.4
Limit:	Only spurious emissions are permitted in any of the frequency bands listed in CFR 47 Part 15, section 15.205(a) or IC RSS-210 Issue 7, section 2.2(a).
Measurement procedure:	Radiated Emission in Fully or Semi Anechoic Room (6.4)

Comment:	
Date of test:	21 July 2009
Test site:	Fully anechoic room, cabin no. 2
Test distance:	3 meters



Date: 21.JUL.2009 15:50:09

Test Result:	Test passed
--------------	-------------




8.6 Periodic Operation Requirements

Rules and specifications:	CFR 47 Part 15, section 15.231(a) CFR 47 Part 15, section 15.240(b) IC RSS-210 Issue 7, section A1.1.1 IC RSS-210 Issue 7, section A5(a)
Guide:	---

Periodic operation requirements	Applicable	Declared by applicant	Test performed	Passed
The transmitter is used for				
<input type="checkbox"/> security or safety applications <input type="checkbox"/> other applications		<input checked="" type="checkbox"/>		
The transmitter is operated				
<input checked="" type="checkbox"/> manually <input type="checkbox"/> automatically			<input checked="" type="checkbox"/>	
Periodic operation according to				
<input checked="" type="checkbox"/> CFR 47 Part 15, section 15.231(a) / IC RSS-210 Issue 7, section A1.1.1				
Only control signals are sent and there is no continuous transmission	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
A manually operated transmitter employs a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
A transmitter activated automatically ceases transmission within 5 seconds after activation	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Periodic transmissions at regular predetermined intervals are <input checked="" type="checkbox"/> not performed <input type="checkbox"/> performed with total transmission time of two seconds per hour or less (for polling or supervision transmissions to determine system integrity of transmitters used in security or safety applications)	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/> CFR 47 Part 15, section 15.231(e) / IC RSS-210 Issue 7, section A1.1.5				
The device is provided with a means for automatically limiting operation so that the duration of each transmission is not greater than one second and the silent period between transmissions is at least 30 times the duration of the transmission but in no case less than 10 seconds.	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input checked="" type="checkbox"/> CFR 47 Part 15, section 15.240(b) / IC RSS-210 Issue 7, section A5(a)				
The device shall be provided with a means for limiting operation so that the duration of each transmission shall not be greater than 60 seconds and be only permitted to reinitiate an interrogation in the case of a transmission error. Absent such a transmission error, the silent period between transmissions shall not be less than 10 seconds	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

Note: Result may be based on the appropriate declaration of the applicant (i.e. no test is performed). However, in this case there is no verification by the test laboratory.



Note: Transmitter is activated manually and total transmission time is limited to 2.62 seconds per activation.



8.7 Conducted Powerline Emission Measurement 150 kHz to 30 MHz

Rules and specifications:	CFR 47 Part 15, section 15.207 IC RSS-Gen Issue 2, section 7.2.2		
Guide:	ANSI C63.4 / CISPR 22		
Limit:	Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
		Quasi-peak	Average
	0.15 - 0.5	66 to 56	56 to 46
	0.5 - 5	56	46
	5 - 30	60	50
Measurement procedure:	Conducted AC Powerline Emission (6.3)		

Comment:	
Date of test:	November 2009
Test site:	Shielded room, cabin no. 4

Test Result:	Test passed
--------------	-------------



Live Wire																															
Peak / Quasi-Peak Detector	Average Detector																														
	<p>Note: Peak levels below average limit, retest with average detector omitted</p>																														
<table border="1"> <thead> <tr> <th>Frequency MHz</th> <th>Reading dBµV</th> <th>Correction factor dB</th> <th>Value dBµV</th> <th>Limit dBµV</th> <th>Margin dB</th> </tr> </thead> <tbody> <tr> <td>0.210</td> <td>48.3</td> <td></td> <td>48.3</td> <td>63.2</td> <td>14.9</td> </tr> <tr> <td>0.320</td> <td>40.2</td> <td></td> <td>40.2</td> <td>59.7</td> <td>19.5</td> </tr> <tr> <td>0.640</td> <td>37.8</td> <td></td> <td>37.8</td> <td>56.0</td> <td>18.2</td> </tr> <tr> <td>3.835</td> <td>34.6</td> <td></td> <td>34.6</td> <td>56.0</td> <td>21.4</td> </tr> </tbody> </table>	Frequency MHz	Reading dBµV	Correction factor dB	Value dBµV	Limit dBµV	Margin dB	0.210	48.3		48.3	63.2	14.9	0.320	40.2		40.2	59.7	19.5	0.640	37.8		37.8	56.0	18.2	3.835	34.6		34.6	56.0	21.4	<p>Note: Peak levels below average limit, retest with average detector omitted</p>
Frequency MHz	Reading dBµV	Correction factor dB	Value dBµV	Limit dBµV	Margin dB																										
0.210	48.3		48.3	63.2	14.9																										
0.320	40.2		40.2	59.7	19.5																										
0.640	37.8		37.8	56.0	18.2																										
3.835	34.6		34.6	56.0	21.4																										


Neutral Wire																															
Peak / Quasi-Peak Detector	Average Detector																														
	<p>Note: Peak levels below average limit, retest with average detector omitted</p>																														
<table border="1"> <thead> <tr> <th>Frequency MHz</th> <th>Reading dBµV</th> <th>Correction factor dB</th> <th>Value dBµV</th> <th>Limit dBµV</th> <th>Margin dB</th> </tr> </thead> <tbody> <tr> <td>0.215</td> <td>45.1</td> <td></td> <td>45.1</td> <td>63.0</td> <td>17.9</td> </tr> <tr> <td>0.640</td> <td>37.2</td> <td></td> <td>37.2</td> <td>56.0</td> <td>18.8</td> </tr> <tr> <td>3.505</td> <td>31.1</td> <td></td> <td>31.1</td> <td>56.0</td> <td>24.9</td> </tr> <tr> <td>3.615</td> <td>32.5</td> <td></td> <td>32.5</td> <td>56.0</td> <td>23.5</td> </tr> </tbody> </table>	Frequency MHz	Reading dBµV	Correction factor dB	Value dBµV	Limit dBµV	Margin dB	0.215	45.1		45.1	63.0	17.9	0.640	37.2		37.2	56.0	18.8	3.505	31.1		31.1	56.0	24.9	3.615	32.5		32.5	56.0	23.5	<p>Note: Peak levels below average limit, retest with average detector omitted</p>
Frequency MHz	Reading dBµV	Correction factor dB	Value dBµV	Limit dBµV	Margin dB																										
0.215	45.1		45.1	63.0	17.9																										
0.640	37.2		37.2	56.0	18.8																										
3.505	31.1		31.1	56.0	24.9																										
3.615	32.5		32.5	56.0	23.5																										

8.8 Radiated Emission Measurement 9 kHz to 30 MHz

Rules and specifications:	CFR 47 Part 15, sections 15.215(b) and 15.231(b)(3) IC RSS-210 Issue 7, section A1.1.2(b)			
Guide:	ANSI C63.4			
Limit:	Frequency of Emission (MHz)	Field Strength ($\mu\text{V}/\text{m}$)	Field Strength (dB $\mu\text{V}/\text{m}$)	Measurement Distance d (meters)
	0.009 - 0.490	2400/F(kHz)	67.6 - 20 · log(F(kHz))	300
	0.490 - 1.705	24000/F(kHz)	87.6 - 20 · log(F(kHz))	30
	1.705 - 30.000	30	29.5	30
	Additionally, the level of any unwanted emissions shall not exceed the level of the fundamental emission.			
Measurement procedure:	Radiated Emission Measurement 9 kHz to 30 MHz (6.2)			

Comment:	
Date of test:	July 22, 2009
Test site:	Open field test site

Test Result:	Test passed
--------------	-------------



No emissions above noise level detected

Sample calculation of final values:

$$\text{Extrapolation Factor (dB)} = (\text{Log}(d) - \text{Log}(d_1)) \cdot \text{Extrapolation Factor (dB/decade)}$$

$$\begin{aligned} \text{Final Value (dB}\mu\text{V/m)} &= \text{Reading Value } d_1 \text{ (dB}\mu\text{V)} + \text{Correction Factor (dB/m)} \\ &+ \text{Extrapolation Factor (dB)} + \text{Pulse Train Correction (dB)} \end{aligned}$$

Note: Extrapolation factor (dB) and final value (dB μ V/m) are relating to distance d.

8.9 Radiated Emission Measurement 30 MHz to 4.5 GHz

Rules and specifications:	CFR 47 Part 15, sections 15.205, 15.215(b), 15.231(b), 15.240(b) IC RSS-210 Issue 7, sections A1.1.2 and A5(b)					
Guide:	ANSI C63.4					
Limit:	15.231, A1.1.2:	In addition to the provisions of section 15.205, the field strength shall not exceed the levels as listed in the table below or the general limits shown in section 15.209, whichever limit permits a higher field strength. In no case shall the level of the unwanted emissions exceed the field strength of the fundamental emission.				
		Frequency of Emission (MHz)	Field Strength of Fundamental ($\mu\text{V/m}$) (dB $\mu\text{V/m}$)		Field Strength of Spurious Emissions ($\mu\text{V/m}$) (dB $\mu\text{V/m}$)	
		40.66 - 40.70	2,250	67.0	225 **	47.0
		70 - 130	1,250	61.9	125	41.9
		130 - 174	1,250 to 3,750 *	61.9 to 71.5	125 to 375 *	41.9 to 51.5
		174 - 260	3,750	71.5	375	51.5
		260 - 470	3,750 to 12,500 *	71.5 to 81.9	375 to 1,250 *	51.5 to 61.9
		Above 470	12,500	81.9	1,250	61.9
		* linear interpolations		** for harmonics only		
	15.240, A5(b):	The fieldstrength of any emissions radiated within the specified band shall not exceed 11000 $\mu\text{V/m}$ (80.8 dB $\mu\text{V/m}$) at a distance of 3 m. The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The peak level of any emissions within the specified band shall not exceed 55000 $\mu\text{V/m}$ (94.8 dB $\mu\text{V/m}$) measured at a distance of 3 m. The field strength of emissions radiated on any frequency outside the specified band shall not exceed the general radiated emission limits.				
Measurement procedures:	Radiated Emission in Fully or Semi Anechoic Room (6.4) Radiated Emission at Open Field Test Site (6.5)					

Comment:	Handheld device, tested in three orthogonal positions
Date of test:	22 July 2009
Test site:	Frequencies \leq 1 GHz: Open field test site Frequencies $>$ 1 GHz: Fully anechoic room, cabin no. 2
Test distance:	3 meters


Test Result:	Test passed
--------------	-------------





Frequency (MHz)	Antenna Polarisation	Detector	Receiver Reading (dBµV)	Correction Factor (dB/m)	Duty Cycle Correction	Final Value (dBµV/m)	Limit (dBµV/m)	Margin (dB)
	Position 1							
433.92	Horizontal	Quasi Peak	61.0	17,80	0	78.8	80.8	2.0
	Vertical	Quasi Peak	53.0	17.80	0	70.8	80.8	10.0
	Position 2							
433.92	Horizontal	Quasi Peak	60.0	17,80	0	79.8	80.8	3.0
	Vertical	Quasi Peak	52.0	17.80	0	69.8	80.8	11.0
	Position 3							
433.92	Horizontal	Quasi Peak	53.0	17,80	0	70.8	80.8	10.0
	Vertical	Quasi Peak	61.0	17.80	0	78.8	80.8	2.0


Sample calculation of final values:


$$\text{Final Value (dBµV/m)} = \text{Reading Value (dBµV)} + \text{Correction Factor (dB/m)} + \text{Pulse Train Correction (dB)}$$
















8.10 Exposure of Humans to RF Fields

Rules and specifications:	IC RSS-Gen Issue 2, section 5.5
Guide:	IC RSS-102 Issue 2, section 2.5

Exposure of Humans to RF Fields	Applicable	Declared by applicant	Measured	Exemption
The antenna is				
<input type="checkbox"/> detachable				
<p>The conducted output power (CP in watts) is measured at the antenna connector:</p> $CP = \dots\dots\dots \mathbf{W}$ <p>The effective isotropic radiated power (EIRP in watts) is calculated using</p> <p><input type="checkbox"/> the numerical antenna gain: $G = \dots\dots\dots$</p> $EIRP = G \cdot CP \Rightarrow EIRP = \dots\dots\dots \mathbf{W}$ <p><input type="checkbox"/> the field strength⁶ in V/m: $FS = \dots\dots\dots \mathbf{V/m}$</p> $EIRP = \frac{(FS \cdot D)^2}{30} \Rightarrow EIRP = \dots\dots\dots \mathbf{W}$ <p>with:</p> <p>Distance between the antennas in m: $D = \dots\dots\dots \mathbf{m}$</p>				
<input checked="" type="checkbox"/> not detachable				
<p>A field strength measurement is used to determine the effective isotropic radiated power (EIRP in watts) given by⁶:</p> $EIRP = \frac{(FS \cdot D)^2}{30} \Rightarrow EIRP = \mathbf{13.4 \cdot 10^{-6} W}$ <p>with:</p> <p>Field strength in V/m: $FS = \mathbf{6.68 V/m}$</p> <p>Distance between the two antennas in m: $D = \mathbf{3 m}$</p>				
Selection of output power				
<p>The output power TP is the higher of the conducted or effective isotropic radiated power (e.i.r.p.):</p> $TP = \mathbf{13.4 \cdot 10^{-6} W}$				

⁶ The conversion formula is valid only for properly matched antennas. In other cases the transmitter output power may have to be measured by a terminated measurement when applying the exemption clauses. If an open area test site is used for field strength measurement, the effect due to the metal ground reflecting plane should be subtracted from the maximum field strength value in order to reference it to free space, before calculating TP.



9 Test Results for Receiver

FCC CFR 47 Part 15			
<i>Section(s)</i>	<i>Test</i>	<i>Page</i>	<i>Result</i>
15.107	Conducted AC powerline emission 150 kHz to 30 MHz	---	Test passed, see TX test results
15.109	Radiated emission 30 MHz to 2.5 GHz	52	Test passed
15.111(a)	Antenna power conduction emission of receivers 9 kHz to 2.5 GHz	---	Not applicable

IC RSS-Gen Issue 2			
<i>Section(s)</i>	<i>Test</i>	<i>Page</i>	<i>Result</i>
7.2.2	Transmitter AC power lines conducted emissions 150 kHz to 30 MHz	---	Test passed, see TX test results
6(a), 7.2.3.2	Receiver spurious emissions (radiated) 30 MHz to 2.5 GHz	52	Test passed
6(b), 7.2.3.1	Receiver spurious emissions (antenna conducted) 9 kHz to 2.5 GHz	---	Not applicable

9.1 Radiated Emission Measurement 30 MHz to 2.5 GHz


Rules and specifications:	CFR 47 Part 15, section 15.109 (Class B) IC RSS-Gen Issue 2, sections 6(a) and 7.2.3.2		
Guide:	ANSI C63.4		
Limit:	Frequency of Emission (MHz)	Field Strength ($\mu\text{V}/\text{m}$)	Field Strength ($\text{dB}\mu\text{V}/\text{m}$)
	30 - 88	100	40.0
	88 - 216	150	43.5
	216 - 960	200	46.0
	Above 960	500	54.0
Measurement procedures:	Radiated Emission in Fully or Semi Anechoic Room (6.4) Radiated Emission at Open Field Test Site (6.5)		

Comment:	
Date of test:	June 19, 2009
Test site:	Frequencies ≤ 1 GHz: Open field test site Frequencies > 1 GHz: Fully anechoic room, cabin no. 2
Test distance:	3 meters

Test Result:	Test passed. No emissions above noise level of test system detected.
--------------	--

Sample calculation of field final values:

$$\text{Final Value (dB}\mu\text{V}/\text{m)} = \text{Reading Value (dB}\mu\text{V)} + \text{Correction Factor (dB/m)}$$



10 Referenced Regulations

11 Referenced Regulations

All tests were performed with reference to the following regulations and standards:

<input checked="" type="checkbox"/>	CFR 47 Part 2	Code of Federal Regulations Part 2 (Frequency allocation and radio treaty matters; General rules and regulations) of the Federal Communication Commission (FCC)	October 1, 2008
<input checked="" type="checkbox"/>	CFR 47 Part 15	Code of Federal Regulations Part 15 (Radio Frequency Devices) of the Federal Communication Commission (FCC)	October 1, 2008
<input checked="" type="checkbox"/>	ANSI C63.4	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	December 11, 2003 (published on January 30, 2004)
<input checked="" type="checkbox"/>	RSS-Gen	Radio Standards Specification RSS-Gen Issue 2 containing General Requirements and Information for the Certification of Radiocommunication Equipment, published by Industry Canada	June 2007
<input checked="" type="checkbox"/>	RSS-210	Radio Standards Specification RSS-210 Issue 7 for Low Power Licence-Exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment, published by Industry Canada	June 2007
<input type="checkbox"/>	RSS-310	Radio Standards Specification RSS-310 Issue 1 for Low Power Licence-Exempt Radiocommunication Devices (All Frequency Bands): Category II Equipment, published by Industry Canada	September 2005
<input checked="" type="checkbox"/>	RSS-102	Radio Standards Specification RSS-102 Issue 2: Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)	November 2005
<input type="checkbox"/>	ICES-003	Interference-Causing Equipment Standard ICES-003 Issue 4 for Digital Apparatus, published by Industry Canada	February 7, 2004
<input checked="" type="checkbox"/>	CISPR 22	Third Edition of the International Special Committee on Radio Interference (CISPR), Pub. 22, "Information Technology Equipment – Radio Disturbance Characteristics – Limits and Methods of Measurement"	1997
<input type="checkbox"/>	CAN/CSA-CEI/IEC CISPR 22	Limits and Methods of Measurement of Radio Disturbance Characteristics of Information Technology Equipment	2002



TRC-43

Notes Regarding Designation of Emission (Including Necessary Bandwidth and Classification), Class of Station and Nature of Service, published by Industry Canada

October 9, 1982



12 Revision History

Revision History			
<i>Edition</i>	<i>Date</i>	<i>Issued by</i>	<i>Modifications</i>
1	Sept 23, 2009	J. Roidt	First Edition
2	Oct. 12, 2009	C. Jäger	Edition 2 Description of EUT (page 3) Connection of antenna changed to: not detachable
3	Nov.25, 2009	J. Roidt	Conducted Emission test results added