

P7301 Optical Mouse Technical Specification

- 1、 Model No. : P7301
- 2、 Key: Three Buttons, One 360° wheel
- 3、 Key Stroke life time:
 - Left /right 1,000,000 Cycles
 - Middle keys 100,000 Cycles
 - Wheel switch 100,000 Cycles
- 4、 Mechanical Dimension
 - 86.7mm x 45.4mm x 30mm
- 6 Mouse Report rate: 80 reports/s
- 7 Resolution: 800 DPI
- 8 System Requirement
 - Windows 95/ Windows 98/ WinNT /Windows me/ Windows 2000/
 - Windows XP(Driver required in Win95/Win98/WinNT)
- 9 Plastic Material (ABS)
- 10 Net weight 41.5g
- 11 Security Code
 - Mouse: 2048 different security code
- 12 RF Transmission mode: FSK
- 13 RF Receiver Center frequency:
 - Mouse: 27.145MHz
- 14 Tx Emission Level: $60\text{dBuV/m} \leq E_{3\text{m}} \leq 80\text{dBuV/m}$ at 3m
- 15 Batteries: 2 x AAA Size
- 16 Battery life ≥ 20 hours at Active mode with Alkaline Batter
- 17 Operating Distance
 - 1.5m in normal environment
- 18 Power consumption
 - $\leq 45\text{mA}$ (Active)