FCC PART 15C TEST REPORT FOR CERTIFICATION
On Behalf of

G. tech Technology Ltd.

2.4GHz Wireless Mouse

Model Number: WI610

FCC ID: OO9WI610

Prepared for : G. tech Technology Ltd.
No.21, Jingding Industrial Park, West Jinfeng Road,
Tangjiawan Town, Xiangzhou District Zhuhai
Guangdong China

Prepared By : Audix Technology (Shenzhen) Co., Ltd.
No. 6, Ke Feng Rd., 52 Block,
Shenzhen Science & Industrial Park,
Nantou, Shenzhen, Guangdong, China

Tel: (0755) 26639496

Report Number	:	ACS-F12094
Date of Test	:	Apr.27~28, 2012
Date of Report	:	May.07, 2012

TABLE OF CONTENTS

Description Page

1. SUMMARY OF STANDARDS AND RESULTS 1-1
1.1. Description of Standards and Results 1-1
2. GENERAL INFORMATION 2-1
2.1. Description of Device (EUT) 2-1
2.2. EUT Configuration and operation conditions for test. 2-1
2.3. Test Facility 2-2
2.4. Measurement Uncertainty (95% confidence levels, k=2) 2-2
3. POWER LINE CONDUCTED EMISSION TEST 3-1
4. RADIATED EMISSION TEST 4-1
4.1. Test Equipment 4-1
4.2. Block Diagram of Test Setup 4-1
4.3. Radiated Emission Limit Standard: FCC 15.209 and 15.249 4-2
4.4. EUT Configuration on Test 4-3
4.5. Operating Condition of EUT 4-3
4.6. Test Procedure 4-3
4.7. Radiated Emission Test Results 4-3
5. 20 DB BANDWIDTH TEST 5-1
5.1. Test Equipment 5-1
5.2. Limit 5-1
5.3. Test Results 5-1
6. BAND EDGE COMPLIANCE TEST 6-1
6.1. Test Equipment 6-1
6.2. Limit 6-1
6.3. Test Produce 6-1
6.4. Test Results 6-1
7. ANTENNA REQUIREMENT 7-6
8. RADIO FRREQUENCY EXPOSURE COMPLIANCE 8-7
9. DEVIATION TO TEST SPECIFICATIONS 9-8
10. PHOTOGRAPH OF TEST 10-1
10.1. Photos of Radiated Emission Test (30-1000MHz) 10-1
11. PHOTOGRAPH OF EUT 11-1

TEST REPORT CERTIFICATION

Applicant	:	G. tech Technology Ltd.
Manufacturer	:	G. tech Technology Ltd.
EUT Description	:	2.4GHz Wireless Mouse
FCC ID	:	OO9WI610
(A) MODEL NO.	:	WI610
(B) SERIAL NO.	:	N/A
(C) POWER SUPPLY	:	DC 1.5V
(D) TEST VOLTAGE	:	DC 1.5V

Tested for comply with:
FCC Rules and Regulations Part 15 Subpart C:2008

Test procedure used:
ANSI C63.10:2009

The device described above is tested by AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. to confirm comply with all the FCC Part 15 Subpart C requirements.

The test results are contained in this test report and AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. is assumed full responsibility for the accuracy and completeness of these tests. This report contains data that are not covered by the NVLAP accreditation. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This Report is made under FCC Part 2.1075. No modifications were required during testing to bring this product into compliance.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of AUDIX TECHNOLOGY (SHENZHEN) CO., LTD.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

Date of Test : Apr.27~28, 2012 Report of date: May.07, 2012

Prepared by : Selina Liu / Assistant

Reviewed by: Sunny Lu / Supervisor

AUDIX 科技（深圳）有限公司
Audix Technology (Shenzhen) Co., Ltd.
EMC 部門報告專用章
Stamp only for EMC Dept. Report
Signature:

Approved & Authorized Signer : Ken Lu / Manager

1. SUMMARY OF STANDARDS AND RESULTS

1.1.Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below.

EMISSION		
Description of Test Item	**Standard**	**Results**
Power Line Conducted Emission Test	FCC Part 15C: 15.207 ANSI C63.10-2009	N/A
Radiated Emission Test	FCC Part 15C: 15.209 FCC Part 15C: 15.249 ANSI C63.10-2009	PASS
Band Edge Compliance Test	FCC Part 15: 15.249 ANSI C63.10-2009	PASS
20dB Bandwidth Test	FCC Part 15: 15.215 ANSI C63.10-2009	PASS
N/A is an abbreviation for Not Applicable.		

2. GENERAL INFORMATION

2.1.Description of Device (EUT)

Product Name	:	2.4GHz Wireless Mouse
Model Number	:	WI610
FCC ID	:	OO9WI610
Operation frequency	:	2402MHz-2479MHz
Antenna	:	Integrated PCB antenna, 0dBi gain
Modulation	:	GFSK
Power Supply	:	DC 1.5V (Note: Batteries were full charged for all the test.)
Applicant	:	G. tech Technology Ltd. No.21, Jingding Industrial Park, West Jinfeng Road, Tangjiawan Town, Xiangzhou District Zhuhai Guangdong China
Manufacturer	:	G. tech Technology Ltd. No.21, Jingding Industrial Park, West Jinfeng Road, Tangjiawan Town, Xiangzhou District Zhuhai Guangdong China
Date of Test	:	Apr.27~28, 2012
Date of Receipt	:	Apr.23, 2012
Sample Type	:	Prototype production

2.2. EUT Configuration and operation conditions for test.

EUT

(EUT: 2.4GHz Wireless Mouse)

2.3.Test Facility

Site Description

Name of Firm	:	Audix Technology (Shenzhen) Co., Ltd. No. 6, Ke Feng Rd., 52 Block, Shenzhen Science & Industrial Park,Nantou, Shenzhen, Guangdong, China
3m Anechoic Chamber	:	Certificated by FCC, USA Registration Number: 90454 Valid Date: Feb.22, 2015
3m & 10m Anechoic Chamber	:	Certificated by FCC, USA Registration Number: 794232 Valid Date: Dec.30, 2012
EMC Lab.	:	Certificated by Industry Canada Registration Number: IC 5183A-1 Valid Date: Jun.13, 2014 Certificated by DAkkS, Germany Registration No: D-PL-12151-01-01 Valid Date: Feb.01, 2014 Accredited by NVLAP, USA NVLAP Code: 200372-0 Valid Date: Mar.31, 2013

2.4.Measurement Uncertainty (95% confidence levels, k=2)

Test Item	Uncertainty
Uncertainty for Radiation Emission test in 3m chamber	3.6 dB(30~200MHz, Polarize: H)
	3.8 dB(30~200MHz, Polarize: V)
	4.2 dB(200M~1GHz, Polarize: H)
	3.8 dB(200M~1GHz, Polarize: V)
Uncertainty for Radiated Spurious Emission test in RF chamber	3.57dB
Uncertainty for Conduction Spurious emission test	2.00 dB
Uncertainty for Output power test	0.73 dB
Uncertainty for Power density test	2.00 dB
Uncertainty for Frequency range test	$7x10^{-8}$
Uncertainty for Bandwidth test	83 kHz
Uncertainty for DC power test	0.038 %
Uncertainty for test site temperature and humidity	0.6℃
	3%

3. POWER LINE CONDUCTED EMISSION TEST

According to Paragraph (c) of FCC Part 15 section 15.207, Tests to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines.

4. RADIATED EMISSION TEST

4.1.Test Equipment

Frequency rang: 30~1000MHz

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	3#Chamber	AUDIX	N/A	N/A	Nov.28,11	1 Year
2	EMI Spectrum	Agilent	E4407B	MY41440292	May.08, 11	1 Year
3	Test Receiver	Rohde & Schwarz	ESVS10	834468/011	May.08, 11	1 Year
4	Amplifier	HP	8447D	2648A04738	May.08, 11	1 Year
5	Bilog Antenna	Schaffner	CBL6111C	2598	Oct.26, 10	1.5 Year
6	RF Cable	MIYAZAKI	CFD400-NL	3# Chamber No.1	Dec.06, 11	0.5Year
7	Coaxial Switch	Anritsu	MP59B	M74389	May.08, 11	1 Year

Frequency rang: above 1000MHz

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Spectrum Analyzer	Agilent	E4407B	MY41440292	May.08, 11	1 Year
2	Horn Antenna	EMCO	3115	9607-4877	July.01, 11	1 Year
3	Amplifier	Agilent	8449B	3008A00863	May.08, 11	1 Year
4	RF Cable	Hubersuhner	SUCOFLEX106	77980/6	Dec.06, 11	0.5Year
5	RF Cable	Hubersuhner	SUCOFLEX106	77977/6	Dec.06, 11	0.5Year

4.2.Block Diagram of Test Setup

For frequency range 30MHz-1000MHz



For frequency range above 1GHz



4.3. Radiated Emission Limit Standard: FCC 15.209 and 15.249

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000MHz	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	
Field Strength of fundamental emissions for 2.4GHz-2.4835GHz	3	114.0 dB(μV)/m (Peak) 94.0 dB(μV)/m (Average)	

Remark： (1) Emission level dBμV = 20 log Emission level μV/m

(2) The smaller limit shall apply at the cross point between two frequency bands.

(3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

(4) The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

4.4.EUT Configuration on Test

The following equipment are installed on Radiated Emission Test to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

4.5.Operating Condition of EUT

4.5.1. Setup the EUT and simulator as shown as Section 4.2.

4.5.2. Turned on the power of all equipment.

4.5.3. Let EUT work in Tx mode.

4.6.Test Procedure

The EUT and its simulators are placed on a turn table, which is 0.8 meter high above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarization of the antenna is set on Test. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.10-2009 on radiated emission Test.

During the pretest the EUT was rotated through three orthogonal axes to determine the attitude that maximizes the emissions.

After that the EUT was manually handled to find the orientation that has the maximum emission, which is the orientation show in the test setup photos.

The bandwidth of the EMI test receiver (R&S ESVS10) is set at 120kHz for frequency range from 30MHz to 1000 MHz.

The bandwidth of the Spectrum's RBW is set at 1MHz and VBW is set at 3MHz for peak emissions measurement above 1GHz

This device is pulse modulated, a duty cycle factor was used to calculate average level based measured peak level.

The frequency range from 30MHz to 10th harmonic (25GHz) are checked. and no any emissions were found from 18GHz to 25 GHz, So the radiated emissions from 18GHz to 25GHz were not record.

4.7.Radiated Emission Test Results

PASS.

All the emissions from 30MHz to 25GHz were comply with the 15.209 Limit.

Note: The duty cycle factor for calculate average level is 28.64dB, and average limit is 20dB below peak limit, so if peak measured level comply with peak limit, the average level was deemed to comply with average limit.

Duty cycle: 0.2533ms /8.117ms *100% = 3.12%

Duty cycle factor = 20log（1/duty cycle）= 30.12






Agilent
L
Marker
Δ Mkr1 −253.3 µs
0.95 dB
Ref 0 dBm
Atten 10 dB
#Peak
Log
10
dB/
Marker Δ
−253.3333333 µs
0.95 dB
LgAv
W1 S2
S3 FS
£(f):
f>50k
1
1R
Center 2.402 000 GHz
Span 0 Hz
Res BW 100 kHz
VBW 100 kHz
Sweep 1 ms (601 pts)
Select Marker
1 2 3 4
Normal
Delta
Delta Pair
(Tracking Ref)
Ref Δ
Span Pair
Span Center
Off
More
1 of 2
File Operation Status, A:\SCREN382.GIF file saved

Frequency: 30MHz~1GHz




```
Site no.      : 3m Chamber                    Data no.   : 2
Dis. / Ant.   : 3m   2010 CBL6111C 2598       Ant. pol.  : HORIZONTAL
Limit         : FCC PART 15 C (3M)
Env. / Ins.   : 24*C/56%                      Engineer   : Leo_Li
EUT           : 2.4GHz Wireless Mouse
Power rating  : DC 1.5V
Test Mode     : Tx Mode
                M/N:WI610
```

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	31.940	18.88	0.30	1.11	20.29	40.00	19.71	QP
2	219.150	10.16	1.09	11.38	22.63	46.00	23.37	QP
3	322.940	14.26	1.23	6.11	21.60	46.00	24.40	QP
4	371.440	15.52	1.44	6.60	23.56	46.00	22.44	QP
5	419.940	17.00	1.60	7.05	25.65	46.00	20.35	QP
6	445.160	17.10	1.50	8.64	27.24	46.00	18.76	QP

```
Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
         2. The emission levels that are 20dB below the official
            limit are not reported.
```



Site no. : 3m Chamber
Dis. / Ant. : 3m 2010 CBL6111C 2598
Limit : FCC PART 15 C (3M)
Env. / Ins. : 24*C/56%
EUT : 2.4GHz Wireless Mouse
Power rating : DC 1.5V
Test Mode : Tx Mode
M/N:WI610

Data no. : 1
Ant. pol. : VERTICAL
Engineer : Leo_Li

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	30.000	20.00	0.30	0.10	20.40	40.00	19.60	QP
2	80.440	7.80	0.60	5.53	13.93	40.00	26.07	QP
3	222.060	10.36	1.10	12.27	23.73	46.00	22.27	QP
4	253.100	13.10	1.17	4.97	19.24	46.00	26.76	QP
5	445.160	17.10	1.50	3.99	22.59	46.00	23.41	QP
6	730.340	21.30	1.85	3.63	26.78	46.00	19.22	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Frequency: 1GHz~18GHz



Site no.	: 3m Chamber	Data no.	: 1
Dis. / Ant.	: 3m 2011 3115 4580	Ant. pol.	: VERTICAL
Limit	: FCC PART 15 PEAK 2.4		
Env. / Ins.	: 23*C/54%	Engineer	: Leo-Li
EUT	: 2.4GHz Wireless Mouse		
Power supply	: DC 1.5V		
Test mode	: Tx 2402MHz		
	: WI610		



Site no. : 3m Chamber
Dis. / Ant. : 3m 2011 3115 4580
Limit : FCC PART 15 PEAK 2.4
Env. / Ins. : 23*C/54%
EUT : 2.4GHz Wireless Mouse
Power supply : DC 1.5V
Test mode : Tx 2402MHz
: WI610

Data no. : 2
Ant. pol. : VERTICAL
Engineer : Leo-Li

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.000	27.96	6.01	34.44	78.47	78.00	114.00	36.00	Peak
2	4804.000	32.86	8.52	34.60	49.75	56.53	74.00	17.47	Peak

Remarks:
1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Frequency（MHz）	Peak level（dBuv/m）	Duty cycle factor (dB)	AV level (dBuv/m)	Limit(dBuv/m)	Conclusion
4804	56.53	30.12	26.24	54	Pass



Site no.	: 3m Chamber	Data no.	: 3
Dis. / Ant.	: 3m 2011 3115 4580	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15 PEAK 2.4		
Env. / Ins.	: 23*C/54%	Engineer	: Leo-Li
EUT	: 2.4GHz Wireless Mouse		
Power supply	: DC 1.5V		
Test mode	: Tx 2402MHz		
	: WI610		



Site no. : 3m Chamber
Dis. / Ant. : 3m 2011 3115 4580
Limit : FCC PART 15 PEAK 2.4
Env. / Ins. : 23*C/54%
EUT : 2.4GHz Wireless Mouse
Power supply : DC 1.5V
Test mode : Tx 2402MHz
: WI610

Data no. : 4
Ant. pol. : HORIZONTAL
Engineer : Leo-Li

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.000	27.96	6.01	34.44	91.35	90.88	114.00	23.12	Peak
2	4804.000	32.86	8.52	34.60	48.20	54.98	74.00	19.02	Peak

Remarks:
1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Frequency（MHz）	Peak level（dBuv/m）	Duty cycle factor (dB)	AV level (dBuv/m)	Limit(dBuv/m)	Conclusion
4804	54.98	30.12	24.86	54	Pass



Site no.	: 3m Chamber	Data no.	: 7
Dis. / Ant.	: 3m 2011 3115 4580	Ant. pol.	: VERTICAL
Limit	: FCC PART 15 PEAK 2.4		
Env. / Ins.	: 23*C/54%	Engineer	: Leo-Li
EUT	: 2.4GHz Wireless Mouse		
Power supply	: DC 1.5V		
Test mode	: Tx 2439MHz		
	: WI610		




```
Site no.      : 3m Chamber              Data no.   : 8
Dis. / Ant.   : 3m   2011 3115 4580     Ant. pol.  : VERTICAL
Limit         : FCC PART 15 PEAK 2.4
Env. / Ins.   : 23*C/54%                Engineer   : Leo-Li
EUT           : 2.4GHz Wireless Mouse
Power supply  : DC 1.5V
Test mode     : Tx  2439MHz
              : WI610
```

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2439.000	28.03	6.09	34.44	80.87	80.55	114.00	33.45	Peak
2	4878.000	32.98	8.58	34.60	50.78	57.74	74.00	16.26	Peak

Remarks:
1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Frequency（MHz）	Peak level（dBuv/m）	Duty cycle factor (dB)	AV level (dBuv/m)	Limit(dBuv/m)	Conclusion
4878	57.74	30.12	27.62	54	Pass




```
Site no.      : 3m Chamber                Data no.   : 9
Dis. / Ant.   : 3m   2011 3115 4580       Ant. pol.  : HORIZONTAL
Limit         : FCC PART 15 PEAK 2.4
Env. / Ins.   : 23*C/54%                  Engineer   : Leo-Li
EUT           : 2.4GHz Wireless Mouse
Power supply  : DC 1.5V
Test mode     : Tx  2439MHz
              : WI610
```



Site no. : 3m Chamber
Dis. / Ant. : 3m 2011 3115 4580
Limit : FCC PART 15 PEAK 2.4
Env. / Ins. : 23*C/54%
EUT : 2.4GHz Wireless Mouse
Power supply : DC 1.5V
Test mode : Tx 2439MHz
: WI610

Data no. : 10
Ant. pol. : HORIZONTAL
Engineer : Leo-Li

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2439.000	28.03	6.09	34.44	90.99	90.67	114.00	23.33	Peak
2	4878.000	32.98	8.58	34.60	48.70	55.66	74.00	18.34	Peak

Remarks:
1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Frequency（MHz）	Peak level（dBuv/m）	Duty cycle factor (dB)	AV level (dBuv/m)	Limit(dBuv/m)	Conclusion
4878	55.66	30.12	25.54	54	Pass



Site no.	: 3m Chamber	Data no.	: 11
Dis. / Ant.	: 3m 2011 3115 4580	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15 PEAK 2.4		
Env. / Ins.	: 23*C/54%	Engineer	: Leo-Li
EUT	: 2.4GHz Wireless Mouse		
Power supply	: DC 1.5V		
Test mode	: Tx 2479MHz		
	: WI610		



Site no. : 3m Chamber
Dis. / Ant. : 3m 2011 3115 4580
Limit : FCC PART 15 PEAK 2.4
Env. / Ins. : 23*C/54%
EUT : 2.4GHz Wireless Mouse
Power supply : DC 1.5V
Test mode : Tx 2479MHz
: WI610

Data no. : 12
Ant. pol. : HORIZONTAL
Engineer : Leo-Li

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.000	28.08	6.15	34.45	90.33	90.11	114.00	23.89	Peak
2	4958.000	33.14	8.65	34.60	46.31	53.50	74.00	20.50	Peak

Remarks:
1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Frequency（MHz）	Peak level（dBuv/m）	Duty cycle factor (dB)	AV level (dBuv/m)	Limit(dBuv/m)	Conclusion
4958	53.50	30.12	23.38	54	Pass




```
Site no.      : 3m Chamber              Data no.   : 13
Dis. / Ant.   : 3m   2011 3115 4580     Ant. pol.  : VERTICAL
Limit         : FCC PART 15 PEAK 2.4
Env. / Ins.   : 23*C/54%                Engineer   : Leo-Li
EUT           : 2.4GHz Wireless Mouse
Power supply  : DC 1.5V
Test mode     : Tx  2479MHz
              : WI610
```



Site no. : 3m Chamber
Dis. / Ant. : 3m 2011 3115 4580
Limit : FCC PART 15 PEAK 2.4
Env. / Ins. : 23*C/54%
EUT : 2.4GHz Wireless Mouse
Power supply : DC 1.5V
Test mode : Tx 2479MHz
: WI610

Data no. : 14
Ant. pol. : VERTICAL
Engineer : Leo-Li

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.000	28.08	6.15	34.45	75.68	75.46	114.00	38.54	Peak
2	4958.000	33.14	8.65	34.60	50.17	57.36	74.00	16.64	Peak

Remarks:
1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Frequency（MHz）	Peak level（dBuv/m）	Duty cycle factor (dB)	AV level (dBuv/m)	Limit(dBuv/m)	Conclusion
4958	57.36	30.12	27.24	54	Pass

5. 20 DB BANDWIDTH TEST

5.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analyzer	Agilent	E4446A	US44300459	May.08,11	1 Year

5.2. Limit

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

5.3. Test Results

EUT: 2.4GHz Wireless Mouse		
M/N: WI610		
Test date:2012-04-27	Pressure: 101.1 kpa	Humidity: 52.6 %
Tested by: Leo-Li	Test site: RF site	Temperature：25.3 ℃

Frequency	20dB bandwidth （MHz）	Limit (MHz)
2402MHz	1.258	N/A
2439MHz	1.240	N/A
2479MHz	1.282	N/A
Conclusion：PASS		

Test Frequency: 2402MHz



Test Frequency: 2439MHz



Test Frequency: 2479MHz



6. BAND EDGE COMPLIANCE TEST

6.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analyzer	Agilent	E4446A	US44300459	May.08,11	1 Year
2.	Horn Antenna	EMCO	3115	9607-4877	May.25, 11	1.5 Year
3.	Amplifier	Agilent	8449B	3008A02495	May.08, 11	1 Year
4.	RF Cable	Hubersuhner	SUCOFLEX102	28620/2	May.08,11	1 Year
5.	RF Cable	Hubersuhner	SUCOFLEX102	28618/2	May.08,11	1 Year
6.	RF Cable	Hubersuhner	SUCOFLEX102	28610/2	May.08,11	1 Year

6.2. Limit

All the lower and upper band-edges emissions appearing within 2310MHz to 2390MHz and 2483.5MHz to 2500MHz restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

6.3. Test Produce

1. The EUT is placed on a turntable, which is 0.8m above the ground plane and worked at highest radiated power.
2. The turntable was rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upperband-edges of the emission:
   (a) PEAK: RBW=1MHz ;VBW=3MHz, PK detector, Sweep=AUTO
   (b)This device is pulse modulated, a duty cycle factor was used to calculate average level based measured peak level

6.4. Test Results

Pass (The testing data was attached in the next pages.)

Note: If the PK measured levels comply with average limit, then the average level were deemed to comply with average limit.

Note: The duty cycle factor for calculate average level is 30.12dB, and average limit is 20dB below peak limit, so if peak measured level comply with peak limit, the average level was deemed to comply with average limit.




```
Site no.      : 3m Chamber                Data no.   : 5
Dis. / Ant.   : 3m   2011 3115 4580       Ant. pol.  : HORIZONTAL
Limit         : FCC PART 15 PEAK 2.4
Env. / Ins.   : 23*C/54%                  Engineer   : Leo-Li
EUT           : 2.4GHz Wireless Mouse
Power supply  : DC 1.5V
Test mode     : Tx  2402MHz
              : WI610
```

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2373.840	27.93	5.98	34.44	47.71	47.18	74.00	26.82	Peak
2	2390.000	27.96	6.01	34.44	46.62	46.15	74.00	27.85	Peak
3	2400.000	27.96	6.01	34.44	64.19	63.72	74.00	10.28	Peak
4	2402.150	27.96	6.01	34.44	91.43	90.96	114.00	23.04	Peak

Remarks:
1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Frequency（MHz）	Peak level（dBuv/m）	Duty cycle factor (dB)	AV level (dBuv/m)	Limit(dBuv/m)	Conclusion
2400.000	63.72	30.12	33.60	54	Pass



Site no. : 3m Chamber
Dis. / Ant. : 3m 2011 3115 4580
Limit : FCC PART 15 PEAK 2.4
Env. / Ins. : 23*C/54%
EUT : 2.4GHz Wireless Mouse
Power supply : DC 1.5V
Test mode : Tx 2402MHz
: WI610

Data no. : 6
Ant. pol. : VERTICAL
Engineer : Leo-Li

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2389.040	27.96	6.01	34.44	47.29	46.82	74.00	27.18	Peak
2	2390.000	27.96	6.01	34.44	46.13	45.66	74.00	28.34	Peak
3	2400.000	27.96	6.01	34.44	54.70	54.23	74.00	19.77	Peak
4	2402.340	27.96	6.01	34.44	78.35	77.88	114.00	36.12	Peak

Remarks:
1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Frequency（MHz）	Peak level（dBuv/m）	Duty cycle factor (dB)	AV level (dBuv/m)	Limit(dBuv/m)	Conclusion
2400.000	54.23	30.12	24.11	54	Pass
2402.340	77.88	30.12	47.76	94	Pass



Site no. : 3m Chamber
Dis. / Ant. : 3m 2011 3115 4580
Limit : FCC PART 15 PEAK 2.4
Env. / Ins. : 23*C/54%
EUT : 2.4GHz Wireless Mouse
Power supply : DC 1.5V
Test mode : Tx 2479MHz
: WI610

Data no. : 15
Ant. pol. : VERTICAL
Engineer : Leo-Li

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.230	28.08	6.15	34.45	75.82	75.60	114.00	38.40	Peak
2	2483.500	28.08	6.15	34.45	45.92	45.70	74.00	28.30	Peak
3	2500.000	28.10	6.18	34.45	45.77	45.60	74.00	28.40	Peak

Remarks:
1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Frequency （MHz）	Peak level （dBuv/m）	Duty cycle factor (dB)	AV level (dBuv/m)	Limit(dBuv/m)	Conclusion
2483.500	45.70	30.12	25.58	54	Pass



Site no. : 3m Chamber
Dis. / Ant. : 3m 2011 3115 4580
Limit : FCC PART 15 PEAK 2.4
Env. / Ins. : 23*C/54%
EUT : 2.4GHz Wireless Mouse
Power supply : DC 1.5V
Test mode : Tx 2479MHz
: WI610

Data no. : 16
Ant. pol. : HORIZONTAL
Engineer : Leo-Li

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2478.822	28.08	6.15	34.45	90.39	90.17	114.00	23.83	Peak
2	2483.500	28.08	6.15	34.45	50.22	50.00	74.00	24.00	Peak
3	2483.752	28.08	6.15	34.45	50.94	50.72	74.00	23.28	Peak
4	2500.000	28.10	6.18	34.45	46.16	45.99	74.00	28.01	Peak

Remarks:
1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Frequency （MHz）	Peak level （dBuv/m）	Duty cycle factor (dB)	AV level (dBuv/m)	Limit(dBuv/m)	Conclusion
2478.822	90.17	30.12	60.05	94	Pass
2483.500	50.00	30.12	19.88	54	Pass

7. ANTENNA REQUIREMENT

RESULT : PASS

Test Date : Apr.28, 2012

Test standard : FCC Part 15.203

Limit : the use of antennas with directional gains that do not exceed 6 dBi

According to the manufacturer declared, the EUT has an internal antenna, the directional gain of antenna is 0dBi, and the antenna connector is designed with permanent attachment and no consideration of replacement. Therefore the EUT is considered sufficient to comply the provision.

8. RADIO FRREQUENCY EXPOSURE COMPLIANCE

RESULT : PASS

Test standard : FCC KDB Publication 447498

Since maximum peak output power of the transmitter is<60/f(GHz)mW, i.e.0.009438mW<25(=60/2.4)mW, hence the EUT is exclueded from SAR evaluation according to FCC KDB Publication 447498 D01:Mobile Portable RF Exposure.

9. DEVIATION TO TEST SPECIFICATIONS

[NONE]