

ESP III HAND HELD / PORTABLE / BODY WORN BATTERY OPERATED TRANSMITTER OPERATES IN 450 TO 470 MHZ RANGE TEST FREQUENCY 467.875

90.213 MINIMUM FREQUENCY STABILITY ALLOWED 2.5ppm

Variations in voltage and ambient temperature

frequency readings have been rounded off per

reading > 5 round up, reading < 5 round down

variation battery temp C frequency stability results

voltage full charge 467.875 1170 acceptable
 voltage operating end point 467.8751 1170 acceptable
 end point

temp nominal 50 467.8753 1170 acceptable
 temp nominal 40 467.8752 1170 acceptable
 temp nominal 30 467.8751 1170 acceptable
 temp nominal 20 467.875 1170 acceptable
 temp nominal 10 467.875 1170 acceptable
 temp nominal 0 467.8751 1170 acceptable
 temp nominal -10 467.8751 1170 acceptable
 temp nominal -20 467.8753 1170 acceptable
 temp nominal -30 467.8752 1170 acceptable

Geac Computers, Inc Electronic Server Pad System model 3000 ESP III

R-3463N2

RETLIF TESTING LABORATORIES
 101 NEW BOSTON ROAD
 GOLFSTOWN, N.H.