

RETLIF TESTING LABORATORIES

TABULAR DATA SHEET

TEST METHOD:	Field Strength of Spurious Emissions		
CUSTOMER:	Geac Computers, Inc.	JOB No.:	R-3463N
TEST SAMPLE:	Radio Base Station (RBSIII)		
MODEL No.:	3001	SERIAL No.:	N/A
TEST SPECIFICATION:	47CFR Part 90, Subpart C	PARAGRAPH:	
OPERATING MODE:	Transmitting at 467.875MHz		
TECHNICIAN:	T. Cricco, J. Monahan	DATE:	6/7/99
NOTES:	Peak Readings at 3 meters on OATS		

OPERATE FREQUENCY	TEST FREQUENCY	EMISSION LEVEL	CORRECTION FACTORS	RELATIVE POWER	TX RATED POWER		
MHz	MHz	dBuV	dB	dBm	dBm		
467.875	30.0						
	935.0						
	1403.0						
	1871.0						
	2339.0						
	2806.0						
	3274.0						
	3742.0						
	4210.0						
	4678.0						
	5000.0						
No spurious emissions from the EUT were observed with an amplitude that was attenuated less than 20dB below the permissible value.							
Note: The fundamental frequency of the transmitter field strength was 128.3dBuV/M at 467.875MHz							