

# **EMISSIONS TEST REPORT FOR A LOW POWER TRANSMITTER**

## **I. GENERAL INFORMATION**

Requirement: Federal Communications Commissions

Test Requirements: 15.205, 15.207, 15.209, 15.247

Applicant: Carlson Wireless Inc.  
1180-B Evergreen Rd  
Redway, CA 95560 USA

Product ID: **FCC ID: OPA-FT-512**

This product is not sold directly to end users. Systems will be sold only to CWT's Authorized Resellers. Those authorized resellers are technically trained by CWT's Engineers periodically and must follow the rules set by CWT.

## **II. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)**

### **RF Specifications**

|                          |  |
|--------------------------|--|
| RF Frequency Band        | 2.400 to 2.4835 GHz  |
| RF Channels              | Programmable in 1 MHz steps                                |
| RF Signal Bandwidth      | 12 MHz (6 non overlapping channels)                        |
| PN Code Rate             | 11 M chip/sec  |
| PN Code Length           | 16   |
| Spreading codes          | 4 programmable non orthogonal codes                        |
| Modulation Type          | BPSK (256) or QPSK (512kbs) DSSS                           |
| Transmitter Output Power | +17dBm, set to allow CDMA operation                        |
| Antennas                 | Built-in (13.8 dBi gain) or<br>External parabolic (24 dBi) |

## **III. TEST LOCATION**

All emissions tests were performed at:

Compliance Certification Services  
571F Monterey Road  
Morgan Hill, CA 95037

T.N. Cokenias  
EMC Consultant/Agent for Carlson Wireless

20 November 2002

## TEST PROCEDURES

### Measurement Equipment Used:

| TEST EQUIPMENTS LIST    |                         |                      |            |
|-------------------------|-------------------------|----------------------|------------|
| Name of Equipment       | Manufacturer            | Model No.            | Serial No. |
| Line Filter             | Lindgren 10k - 10GHz    | LMF-3489             | 497        |
| LISN                    | Fischer 9k - 100MHz     | FCC-LISN-50/250-25-2 | 114        |
| EMI Test Receiver       | Rohde & Schwarz         | ESHS 20              | 827129/006 |
| Quasi Peak Adapter      | HP9K - 1GHz             | 85650A               | 2811A01155 |
| Spectrum Display        | HP                      | 85662A               | 2816A16696 |
| Spectrum Analyzer       | HP 0.1K - 1.5GHz        | 8568B                | 2732A03661 |
| RF Preselector          | HP20Hz-2GHz             | 85685A               | 2817A00756 |
| Pre-Amplifier,25 dB     | HP0.1 - 1300MHz         | 8447D (P8)           | 2944A06589 |
| Antenna, Bilog          | Schaffner-Chase30M-2GHz | CBL6112B             | 2586       |
| Pre-Amplifier           | MITEQ1-26GHz            | NSP2600-44           | 646456     |
| Horn Antenna(1 - 18GHz) | EMCO                    | 3115                 | 6717       |
| Spectrum Analyzer       | HP                      | 8593EM               | 3710A00205 |
| Filter 4.5GHz           | FSY Microwave           | FM-4570-9SS          | 3          |
| Power Meter             | Agilent                 | e441                 | gb41291160 |


### Radiated Emissions

**Test Requirement: 15.109, 15.205, 15.209, 15.247**

### Test Procedures, 1- 26 GHz:

1. The EUT was placed on a wooden table resting on a turntable on the open air test site. The search antenna was placed 3m from the EUT. The EUT antenna was mounted vertically as per normal installation.
2. The turntable was slowly rotated to locate the direction of maximum emission at each emission falling in the restricted bands of 15.205.
3. Radiated emissions were investigated for a LOW channel, a MID channel, and HIGH channel. Emissions were investigated to the 10<sup>th</sup> harmonic.
4. Once maximum direction was determined, the search antenna was raised and lowered in both vertical and horizontal polarizations. The maximum readings so obtained are recorded in the data listed below.

## Radiated Test Set-up, 1-40 GHz



Testing was performed at 3 different frequencies

### Channel      Frequency, MHz

|      |      |
|------|------|
| Low  | 2412 |
| Mid  | 2448 |
| High | 2460 |

Radiated emissions were performed at each frequency for 2 different transmitter antennas.

Antennas tested:

| Antenna Type         | Gain     | Antenna Manufacturer | Model Number |
|----------------------|----------|----------------------|--------------|
| Integral             | 13.8 dBi | Carlton Wireless     | n/a          |
| external w/reflector | 24 dBi   | various              | n/a          |

**Test Results:** Worst case results are presented. Refer to separate Excel spread sheet files.

NOTE: For radiated emissions that fall on restricted bands per 15.205, emissions limit is 54 dBuV/m at 3 m for emissions above 960 MHz. Data plots presented for internal antenna show corrected field strengths at band edges (REF OFFSET values are correction factors). The band edge field strengths for the external antenna were obtained with Marker Delta method.

Per 15.247(c) all other undesired emissions must be 20 dB below the highest in-band emission when measured in a 100 kHz bandwidth. Conducted measurements are presented for emissions up to 26.5 GHz.

11/07/02 **FCC Measurement**  
**Compliance Certification Services, Morgan Hill Open Field Site**

Test Engr: NEELESH RAJ  
Project #: 02U1641  
Company: CARLSON WIRELESS  
EUT Descrip.: 2.4GHZ SPREAD SPECTRUM W/LAN  
EUT M/N: FT512  
Test Target: FCC

**Equipment for 1-22 GHz:**

HP8593EM Analyzer  
Miteq NSP2600-44 Preamp  
EMCO 3115 Antenna  
Cable: 15.0 feet

**Equipment for 22 - 58 GHz:**

HP8566B Analyzer  
HP 11975A Amplifier (LO)  
HP 11970K External mixer/antenna  
Cable: IF Only (321 MHz)

**Peak Measurements:**

1 MHz Resolution Bandwidth  
1MHz Video Bandwidth

**Average Measurements:**

1MHz Resolution Bandwidth  
10Hz Video Bandwidth

| f<br>GHz         | Dist<br>feet          | Read Pk<br>dBuV | Read Avg.<br>dBuV | AF<br>dB/m | CL<br>dB                       | Amp<br>dB | D Corr<br>dB | HPF | Peak<br>dBuV/m | Avg<br>dBuV/m | Pk Lim<br>dBuV/m | Avg Lim<br>dBuV/m            | Pk Mar<br>dB | Avg Mar<br>dB | Notes |
|------------------|-----------------------|-----------------|-------------------|------------|--------------------------------|-----------|--------------|-----|----------------|---------------|------------------|------------------------------|--------------|---------------|-------|
| <b>HARMONICS</b> |                       |                 |                   |            |                                |           |              |     |                |               |                  |                              |              |               |       |
| 4.824            | 3.3                   | 59.8            | 45.5              | 33.9       | 5.7                            | -36.1     | -9.5         | 1.0 | 54.9           | 40.5          | 74.0             | 54.0                         | -19.1        | -13.5         | V     |
| 7.236            | 3.3                   | 69.5            | 46.3              | 37.0       | 7.2                            | -36.3     | -9.5         | 1.0 | 68.9           | 45.7          | 74.0             | 54.0                         | -5.1         | -8.3          | V     |
| 9.647            | 3.3                   | 55.2            | 42.0              | 38.5       | 8.5                            | -35.4     | -9.5         | 1.0 | 58.3           | 45.1          | 74.0             | 54.0                         | -15.7        | -8.9          | V     |
| 12.050           | 3.3                   | 53.1            | 43.4              | 39.3       | 9.5                            | -36.3     | -9.5         | 1.0 | 57.1           | 47.4          | 74.0             | 54.0                         | -16.9        | -6.6          | V     |
|                  |                       |                 |                   |            |                                |           |              |     |                |               |                  |                              |              |               |       |
| 4.824            | 3.3                   | 63.5            | 41.7              | 33.9       | 5.7                            | -36.1     | -9.5         | 1.0 | 58.5           | 36.7          | 74.0             | 54.0                         | -15.5        | -17.3         | H     |
| 7.236            | 3.3                   | 61.9            | 45.1              | 37.0       | 7.2                            | -36.3     | -9.5         | 1.0 | 61.3           | 44.6          | 74.0             | 54.0                         | -12.7        | -9.4          | H     |
| 9.647            | 3.3                   | 54.7            | 41.2              | 38.5       | 8.5                            | -35.4     | -9.5         | 1.0 | 57.8           | 44.3          | 74.0             | 54.0                         | -16.2        | -9.7          | H     |
| 12.050           | 3.3                   | 52.4            | 42.3              | 39.3       | 9.5                            | -36.3     | -9.5         | 1.0 | 56.4           | 46.3          | 74.0             | 54.0                         | -17.6        | -7.7          | H     |
|                  |                       |                 |                   |            |                                |           |              |     |                |               |                  |                              |              |               |       |
| <b>SPURIOUS</b>  |                       |                 |                   |            |                                |           |              |     |                |               |                  |                              |              |               |       |
| 4.260            | 3.3                   | 64.2            | 52.3              | 33.1       | 5.3                            | -36.1     | -9.5         | 1.0 | 58.0           | 46.0          | 74.0             | 54.0                         | -16.0        | -8.0          | V     |
| 6.390            | 3.3                   | 49.9            | 41.3              | 35.5       | 6.8                            | -36.3     | -9.5         | 1.0 | 47.4           | 38.7          | 74.0             | 54.0                         | -26.6        | -15.3         | V     |
| 4.260            | 3.3                   | 63.2            | 52.5              | 33.1       | 5.3                            | -36.1     | -9.5         | 1.0 | 57.0           | 46.3          | 74.0             | 54.0                         | -17.0        | -7.7          | H     |
| 6.390            | 3.3                   | 52.1            | 41.5              | 35.5       | 6.8                            | -36.3     | -9.5         | 1.0 | 49.6           | 39.0          | 74.0             | 54.0                         | -24.4        | -15.0         | H     |
|                  |                       |                 |                   |            |                                |           |              |     |                |               |                  |                              |              |               |       |
| f                | Measurement Frequency |                 |                   | Amp        | Preamp Gain                    |           |              |     |                |               | Avg Lim          | Average Field Strength Limit |              |               |       |
| Dist             | Distance to Antenna   |                 |                   | D Corr     | Distance Correct to 3 meters   |           |              |     |                |               | Pk Lim           | Peak Field Strength Limit    |              |               |       |
| Read             | Analyzer Reading      |                 |                   | Avg        | Average Field Strength @ 3 m   |           |              |     |                |               | Avg Mar          | Margin vs. Average Limit     |              |               |       |
| AF               | Antenna Factor        |                 |                   | Peak       | Calculated Peak Field Strength |           |              |     |                |               | Pk Mar           | Margin vs. Peak Limit        |              |               |       |
| CL               | Cable Loss            |                 |                   | HPF        | High Pass Filter               |           |              |     |                |               |                  |                              |              |               |       |

| FCC Measurement<br>Compliance Certification Services, Morgan Hill Open Field Site |                              |                                   |                   |            |          |                                |              |     |                |               |                              |                   |              |               |       |  |
|---|------------------------------|-----------------------------------|-------------------|------------|----------|--------------------------------|--------------|-----|----------------|---------------|------------------------------|-------------------|--------------|---------------|-------|--|
| Test Engr:  | NEELESH RAJ                  |                                   |                   |            |          |                                |              |     |                |               |                              |                   |              |               |       |  |
| Project #:  | 02U1641                      |                                   |                   |            |          |                                |              |     |                |               |                              |                   |              |               |       |  |
| Company:  | CARLSON WIRELESS             |                                   |                   |            |          |                                |              |     |                |               |                              |                   |              |               |       |  |
| EUT Descrip.:   | 2.4GHZ SPREAD SPECTRUM W/LAN |                                   |                   |            |          |                                |              |     |                |               |                              |                   |              |               |       |  |
| EUT M/N:  | FT512                        |                                   |                   |            |          |                                |              |     |                |               |                              |                   |              |               |       |  |
| Test Target:  | FCC                          |                                   |                   |            |          |                                |              |     |                |               |                              |                   |              |               |       |  |
| <b>Equipment for 1.22 GHz:</b>  |                              | <b>Equipment for 22 - 58 GHz:</b> |                   |            |          |                                |              |     |                |               |                              |                   |              |               |       |  |
| HP8593EM Analyzer   |                              | HP8566B Analyzer                  |                   |            |          |                                |              |     |                |               |                              |                   |              |               |       |  |
| Miteq NSP2600-44 Preamp   |                              | HP 11975A Amplifier (LO)          |                   |            |          |                                |              |     |                |               |                              |                   |              |               |       |  |
| EMCO 3115 Antenna   |                              | HP 11970K External mixer/antenna  |                   |            |          |                                |              |     |                |               |                              |                   |              |               |       |  |
| Cable: 15.0   | feet                         | Cable: IF Only (321 MHz)          |                   |            |          |                                |              |     |                |               |                              |                   |              |               |       |  |
| <b>Peak Measurements:</b>   |                              | <b>Average Measurements:</b>      |                   |            |          |                                |              |     |                |               |                              |                   |              |               |       |  |
| 1 MHz Resolution Bandwidth  |                              | 1MHz Resolution Bandwidth         |                   |            |          |                                |              |     |                |               |                              |                   |              |               |       |  |
| 1MHz Video Bandwidth  |                              | 10Hz Video Bandwidth              |                   |            |          |                                |              |     |                |               |                              |                   |              |               |       |  |
| f<br>GHz  | Dist<br>feet                 | Read Pk<br>dBuV                   | Read Avg.<br>dBuV | AF<br>dB/m | CL<br>dB | Amp<br>dB                      | D Corr<br>dB | HPF | Peak<br>dBuV/m | Avg<br>dBuV/m | Pk Lim<br>dBuV/m             | Avg Lim<br>dBuV/m | Pk Mar<br>dB | Avg Mar<br>dB | Notes |  |
| <b>HARMONICS</b>  |                              |                                   |                   |            |          |                                |              |     |                |               |                              |                   |              |               |       |  |
| 4.896   | 3.3                          | 59.5                              | 46.2              | 34.1       | 5.8      | -36.1                          | -9.5         | 1.0 | 54.7           | 41.5          | 74.0                         | 54.0              | -19.3        | -12.5         | V     |  |
| 7.340   | 3.3                          | 61.9                              | 48.1              | 37.2       | 7.3      | -36.3                          | -9.5         | 1.0 | 61.7           | 47.8          | 74.0                         | 54.0              | -12.3        | -6.2          | V     |  |
| 9.790   | 3.3                          | 51.3                              | 42.8              | 38.6       | 8.6      | -35.5                          | -9.5         | 1.0 | 54.5           | 46.1          | 74.0                         | 54.0              | -19.5        | -7.9          | V     |  |
| 12.240  | 3.3                          | 53.0                              | 43.5              | 39.2       | 9.6      | -36.4                          | -9.5         | 1.0 | 56.9           | 47.4          | 74.0                         | 54.0              | -17.1        | -6.6          | V     |  |
| 4.896   | 3.3                          | 60.7                              | 43.8              | 34.1       | 5.8      | -36.1                          | -9.5         | 1.0 | 56.0           | 39.1          | 74.0                         | 54.0              | -18.0        | -14.9         | H     |  |
| 7.340   | 3.3                          | 56.3                              | 45.5              | 37.2       | 7.3      | -36.3                          | -9.5         | 1.0 | 56.0           | 45.2          | 74.0                         | 54.0              | -18.0        | -8.8          | H     |  |
| 9.790   | 3.3                          | 50.3                              | 42.9              | 38.6       | 8.6      | -35.5                          | -9.5         | 1.0 | 53.6           | 46.2          | 74.0                         | 54.0              | -20.4        | -7.8          | H     |  |
| 12.240  | 3.3                          | 52.1                              | 42.5              | 39.2       | 9.6      | -36.4                          | -9.5         | 1.0 | 56.0           | 46.4          | 74.0                         | 54.0              | -18.0        | -7.6          | H     |  |
| <b>SPURIOUS</b>   |                              |                                   |                   |            |          |                                |              |     |                |               |                              |                   |              |               |       |  |
| 4.330   | 3.3                          | 61.3                              | 52.9              | 33.0       | 5.3      | -36.1                          | -9.5         | 1.0 | 55.1           | 46.7          | 74.0                         | 54.0              | -18.9        | -7.3          | V     |  |
| 6.500   | 3.3                          | 62.4                              | 51.6              | 35.5       | 6.9      | -36.4                          | -9.5         | 1.0 | 59.9           | 49.1          | 74.0                         | 54.0              | -14.1        | -4.9          | V     |  |
| 4.330   | 3.3                          | 60.2                              | 51.8              | 33.0       | 5.3      | -36.1                          | -9.5         | 1.0 | 54.0           | 45.6          | 74.0                         | 54.0              | -20.0        | -8.4          | H     |  |
| 6.500   | 3.3                          | 63.2                              | 52.1              | 35.5       | 6.9      | -36.4                          | -9.5         | 1.0 | 60.7           | 49.6          | 74.0                         | 54.0              | -13.3        | -4.4          | H     |  |
|   |                              |                                   |                   |            |          |                                |              |     |                |               |                              |                   |              |               |       |  |
| f   | Measurement Frequency        |                                   |                   |            | Amp      | Preamp Gain                    |              |     |                | Avg Lim       | Average Field Strength Limit |                   |              |               |       |  |
| Dist  | Distance to Antenna          |                                   |                   |            | D Corr   | Distance Correct to 3 meters   |              |     |                | Pk Lim        | Peak Field Strength Limit    |                   |              |               |       |  |
| Read  | Analyzer Reading             |                                   |                   |            | Avg      | Average Field Strength @ 3 m   |              |     |                | Avg Mar       | Margin vs. Average Limit     |                   |              |               |       |  |
| AF  | Antenna Factor               |                                   |                   |            | Peak     | Calculated Peak Field Strength |              |     |                | Pk Mar        | Margin vs. Peak Limit        |                   |              |               |       |  |
| CL  | Cable Loss                   |                                   |                   |            | HPF      | High Pass Filter               |              |     |                |               |                              |                   |              |               |       |  |

11/07/02 **FCC Measurement**  
**Compliance Certification Services, Morgan Hill Open Field Site**

Test Engr: NEELESH RAJ  
 Project #: 02U1641  
 Company: CARLSON WIRELESS  
 EUT Descrip.: 2.4GHZ SPREAD SPECTRUM W/LAN  
 EUT M/N: FT512 using internal 13 dBi antenna  
 Test Target: FCC

**Equipment for 1-22 GHz:**

HP8593EM Analyzer  
 Miteq NSP2600-44 Preamp  
 EMC 3115 Antenna  
 Cable: 15.0 feet

**Equipment for 22 - 58 GHz:**

HP8566B Analyzer  
 HP 11975A Amplifier (LO)  
 HP 11970K External mixer/antenna  
 Cable: IF Only (321 MHz)

**Peak Measurements:**

1 MHz Resolution Bandwidth  
 1MHz Video Bandwidth

**Average Measurements:**

1MHz Resolution Bandwidth  
 10Hz Video Bandwidth

| f<br>GHz         | Dist<br>feet          | Read Pk<br>dBuV | Read Avg.<br>dBuV | AF<br>dB/m | CL<br>dB | Amp<br>dB                      | D Corr<br>dB | HPF | Peak<br>dBuV/m | Avg<br>dBuV/m | Pk Lim<br>dBuV/m             | Avg Lim<br>dBuV/m | Pk Mar<br>dB | Avg Mar<br>dB | Notes |
|------------------|-----------------------|-----------------|-------------------|------------|----------|--------------------------------|--------------|-----|----------------|---------------|------------------------------|-------------------|--------------|---------------|-------|
| <b>HARMONICS</b> |                       |                 |                   |            |          |                                |              |     |                |               |                              |                   |              |               |       |
| 4.920            | 3.3                   | 57.7            | 45.2              | 34.2       | 5.8      | -36.1                          | -9.5         | 1.0 | 53.1           | 40.6          | 74.0                         | 54.0              | -20.9        | -13.4         | V     |
| 7.380            | 3.3                   | 55.3            | 46.1              | 37.3       | 7.3      | -36.2                          | -9.5         | 1.0 | 55.2           | 46.0          | 74.0                         | 54.0              | -18.8        | -8.0          | V     |
| 9.840            | 3.3                   | 43.3            | 34.3              | 38.7       | 8.6      | -35.5                          | -9.5         | 1.0 | 46.6           | 37.7          | 74.0                         | 54.0              | -27.4        | -16.3         | V     |
| 12.300           | 3.3                   | 45.3            | 34.2              | 39.2       | 9.6      | -36.4                          | -9.5         | 1.0 | 49.2           | 38.1          | 74.0                         | 54.0              | -24.8        | -15.9         | V     |
|                  |                       |                 |                   |            |          |                                |              |     |                |               |                              |                   |              |               |       |
| 4.920            | 3.3                   | 50.4            | 41.6              | 34.2       | 5.8      | -36.1                          | -9.5         | 1.0 | 45.8           | 37.0          | 74.0                         | 54.0              | -28.2        | -17.0         | H     |
| 7.380            | 3.3                   | 52.6            | 42.7              | 37.3       | 7.3      | -36.2                          | -9.5         | 1.0 | 52.5           | 42.6          | 74.0                         | 54.0              | -21.5        | -11.4         | H     |
| 9.840            | 3.3                   | 43.3            | 34.4              | 38.7       | 8.6      | -35.5                          | -9.5         | 1.0 | 46.6           | 37.7          | 74.0                         | 54.0              | -27.4        | -16.3         | H     |
| 12.300           | 3.3                   | 44.2            | 35.0              | 39.2       | 9.6      | -36.4                          | -9.5         | 1.0 | 48.1           | 38.9          | 74.0                         | 54.0              | -25.9        | -15.1         | H     |
|                  |                       |                 |                   |            |          |                                |              |     |                |               |                              |                   |              |               |       |
| <b>SPURIOUS</b>  |                       |                 |                   |            |          |                                |              |     |                |               |                              |                   |              |               |       |
| 4.359            | 3.3                   | 62.5            | 53.1              | 33.0       | 5.4      | -36.1                          | -9.5         | 1.0 | 56.3           | 46.9          | 74.0                         | 54.0              | -17.7        | -7.1          | V     |
| 6.539            | 3.3                   | 63.7            | 52.9              | 35.6       | 6.9      | -36.4                          | -9.5         | 1.0 | 61.3           | 50.5          | 74.0                         | 54.0              | -12.7        | -3.5          | V     |
| 4.359            | 3.3                   | 61.3            | 52.9              | 33.0       | 5.4      | -36.1                          | -9.5         | 1.0 | 55.1           | 46.7          | 74.0                         | 54.0              | -18.9        | -7.3          | H     |
| 6.539            | 3.3                   | 62.8            | 51.0              | 35.6       | 6.9      | -36.4                          | -9.5         | 1.0 | 60.4           | 48.6          | 74.0                         | 54.0              | -13.6        | -5.4          | H     |
|                  |                       |                 |                   |            |          |                                |              |     |                |               |                              |                   |              |               |       |
| <b>BANDEdge</b>  |                       |                 |                   |            |          |                                |              |     |                |               |                              |                   |              |               |       |
| 2.480            | 3.3                   | 62.8            | 30.0              | 29.1       | 3.9      | -36.3                          | -9.5         | 1.0 | 51.0           | 18.2          | 74.0                         | 54.0              | -23.0        | -35.8         | H     |
| 6.539            | 3.3                   | 62.8            | 51.0              | 35.6       | 6.9      | -36.4                          | -9.5         | 1.0 | 60.4           | 48.6          | 74.0                         | 54.0              | -13.6        | -5.4          | H     |
| 6.539            | 3.3                   | 62.8            | 51.0              | 35.6       | 6.9      | -36.4                          | -9.5         | 1.0 | 60.4           | 48.6          | 74.0                         | 54.0              | -13.6        | -5.4          | H     |
| 6.539            | 3.3                   | 62.8            | 51.0              | 35.6       | 6.9      | -36.4                          | -9.5         | 1.0 | 60.4           | 48.6          | 74.0                         | 54.0              | -13.6        | -5.4          | H     |
|                  |                       |                 |                   |            |          |                                |              |     |                |               |                              |                   |              |               |       |
| f                | Measurement Frequency |                 |                   |            | Amp      | Preamp Gain                    |              |     |                | Avg Lim       | Average Field Strength Limit |                   |              |               |       |
| Dist             | Distance to Antenna   |                 |                   |            | D Corr   | Distance Correct to 3 meters   |              |     |                | Pk Lim        | Peak Field Strength Limit    |                   |              |               |       |
| Read             | Analyzer Reading      |                 |                   |            | Avg      | Average Field Strength @ 3 m   |              |     |                | Avg Mar       | Margin vs. Average Limit     |                   |              |               |       |
| AF               | Antenna Factor        |                 |                   |            | Peak     | Calculated Peak Field Strength |              |     |                | Pk Mar        | Margin vs. Peak Limit        |                   |              |               |       |
| CL               | Cable Loss            |                 |                   |            | HPF      | High Pass Filter               |              |     |                |               |                              |                   |              |               |       |

11/07/02 **FCC Measurement**  
**Compliance Certification Services, Morgan Hill Open Field Site**

Test Engr: NEELESH RAJ  
Project #: 02U1641  
Company: CARLSON WIRELESS  
EUT Descrip.: 2.4GHZ SPREAD SPECTRUM W/LAN  
EUT M/N: FT512 with 24 dBi dish antenna  
Test Target: FCC

**Equipment for 1-22 GHz:**

HP8593EM Analyzer  
Miteq NSP2600-44 Preamp  
EMCO 3115 Antenna  
Cable: 15.0 feet

**Equipment for 22 - 58 GHz:**

HP8566B Analyzer  
HP 11975A Amplifier (LO)  
HP 11970K External mixer/antenna  
Cable: IF Only (321 MHz)

**Peak Measurements:**

1 MHz Resolution Bandwidth  
1MHz Video Bandwidth

**Average Measurements:**

1MHz Resolution Bandwidth  
10Hz Video Bandwidth

| f<br>GHz         | Dist<br>feet          | Read Pk<br>dBuV | Read Avg.<br>dBuV | AF<br>dB/m | CL<br>dB                       | Amp<br>dB | D Corr<br>dB | HPF | Peak<br>dBuV/m | Avg<br>dBuV/m | Pk Lim<br>dBuV/m | Avg Lim<br>dBuV/m            | Pk Mar<br>dB | Avg Mar<br>dB | Notes |
|------------------|-----------------------|-----------------|-------------------|------------|--------------------------------|-----------|--------------|-----|----------------|---------------|------------------|------------------------------|--------------|---------------|-------|
| <b>HARMONICS</b> |                       |                 |                   |            |                                |           |              |     |                |               |                  |                              |              |               |       |
| 4.870            | 9.8                   | 57.6            | 41.3              | 34.0       | 5.8                            | -36.1     | 0.0          | 1.0 | 62.3           | 45.9          | 74.0             | 54.0                         | -11.7        | -8.1          | V     |
| 7.300            | 9.8                   | 57.5            | 42.6              | 37.1       | 7.3                            | -36.3     | 0.0          | 1.0 | 66.5           | 51.7          | 74.0             | 54.0                         | -7.5         | -2.3          | V     |
| 9.740            | 9.8                   | 46.6            | 34.2              | 38.6       | 8.6                            | -35.5     | 0.0          | 1.0 | 59.3           | 46.9          | 74.0             | 54.0                         | -14.7        | -7.1          | V     |
| 12.140           | 9.8                   | 44.5            | 35.0              | 39.2       | 9.5                            | -36.3     | 0.0          | 1.0 | 57.9           | 48.4          | 74.0             | 54.0                         | -16.1        | -5.6          | V     |
|                  |                       |                 |                   |            |                                |           |              |     |                |               |                  |                              |              |               |       |
| 4.870            | 9.8                   | 49.2            | 37.1              | 34.0       | 5.8                            | -36.1     | 0.0          | 1.0 | 53.9           | 41.7          | 74.0             | 54.0                         | -20.1        | -12.3         | H     |
| 7.300            | 9.8                   | 53.0            | 40.5              | 37.1       | 7.3                            | -36.3     | 0.0          | 1.0 | 62.1           | 49.5          | 74.0             | 54.0                         | -11.9        | -4.5          | H     |
| 9.740            | 9.8                   | 46.2            | 34.0              | 38.6       | 8.6                            | -35.5     | 0.0          | 1.0 | 58.9           | 46.7          | 74.0             | 54.0                         | -15.1        | -7.3          | H     |
| 12.140           | 9.8                   | 45.1            | 35.7              | 39.2       | 9.5                            | -36.3     | 0.0          | 1.0 | 58.5           | 49.1          | 74.0             | 54.0                         | -15.5        | -4.9          | H     |
|                  |                       |                 |                   |            |                                |           |              |     |                |               |                  |                              |              |               |       |
| <b>SPURIOUS</b>  |                       |                 |                   |            |                                |           |              |     |                |               |                  |                              |              |               |       |
| 4.300            | 9.8                   | 53.1            | 42.8              | 33.1       | 5.3                            | -36.1     | 0.0          | 1.0 | 56.3           | 46.1          | 74.0             | 54.0                         | -17.7        | -7.9          | V     |
| 6.460            | 9.8                   | 49.8            | 40.2              | 35.5       | 6.8                            | -36.3     | 0.0          | 1.0 | 56.7           | 47.2          | 74.0             | 54.0                         | -17.3        | -6.8          | V     |
| 4.300            | 9.8                   | 52.6            | 42.9              | 33.1       | 5.3                            | -36.1     | 0.0          | 1.0 | 55.8           | 46.1          | 74.0             | 54.0                         | -18.2        | -7.9          | H     |
| 6.460            | 9.8                   | 48.3            | 40.9              | 35.5       | 6.8                            | -36.3     | 0.0          | 1.0 | 55.3           | 47.9          | 74.0             | 54.0                         | -18.7        | -6.1          | H     |
|                  |                       |                 |                   |            |                                |           |              |     |                |               |                  |                              |              |               |       |
| f                | Measurement Frequency |                 |                   | Amp        | Preamp Gain                    |           |              |     |                |               | Avg Lim          | Average Field Strength Limit |              |               |       |
| Dist             | Distance to Antenna   |                 |                   | D Corr     | Distance Correct to 3 meters   |           |              |     |                |               | Pk Lim           | Peak Field Strength Limit    |              |               |       |
| Read             | Analyzer Reading      |                 |                   | Avg        | Average Field Strength @ 3 m   |           |              |     |                |               | Avg Mar          | Margin vs. Average Limit     |              |               |       |
| AF               | Antenna Factor        |                 |                   | Peak       | Calculated Peak Field Strength |           |              |     |                |               | Pk Mar           | Margin vs. Peak Limit        |              |               |       |
| CL               | Cable Loss            |                 |                   | HPF        | High Pass Filter               |           |              |     |                |               |                  |                              |              |               |       |

11/07/02 **FCC Measurement**  
**Compliance Certification Services, Morgan Hill Open Field Site**

Test Engr: NEELESH RAJ  
 Project #: 02U1641  
 Company: CARLSON WIRELESS  
 EUT Descrip.: 2.4GHZ SPREAD SPECTRUM W/LAN  
 EUT M/N: FT512  
 Test Target: FCC

**Equipment for 1-22 GHz:**

HP8593EM Analyzer  
 Miteq NSP2600-44 Preamp  
 EMCO 3115 Antenna  
 Cable: 15.0 feet

**Equipment for 22 - 58 GHz:**

HP8566B Analyzer  
 HP 11975A Amplifier (LO)  
 HP 11970K External mixer/antenna  
 Cable: IF Only (321 MHz)

**Peak Measurements:**

1 MHz Resolution Bandwidth  
 1MHz Video Bandwidth

**Average Measurements:**

1MHz Resolution Bandwidth  
 10Hz Video Bandwidth

| f<br>GHz         | Dist<br>feet          | Read Pk<br>dBuV | Read Avg.<br>dBuV | AF<br>dB/m    | CL<br>dB                       | Amp<br>dB | D Corr<br>dB | HPF | Peak<br>dBuV/m | Avg<br>dBuV/m | Pk Lim<br>dBuV/m | Avg Lim<br>dBuV/m            | Pk Mar<br>dB | Avg Mar<br>dB | Notes |
|------------------|-----------------------|-----------------|-------------------|---------------|--------------------------------|-----------|--------------|-----|----------------|---------------|------------------|------------------------------|--------------|---------------|-------|
| <b>HARMONICS</b> |                       |                 |                   |               |                                |           |              |     |                |               |                  |                              |              |               |       |
| 4.890            | 9.8                   | 54.0            | 38.8              | 34.1          | 5.8                            | -36.1     | 0.0          | 1.0 | 58.7           | 43.5          | 74.0             | 54.0                         | -15.3        | -10.5         | V     |
| 7.340            | 9.8                   | 55.9            | 42.7              | 37.2          | 7.3                            | -36.3     | 0.0          | 1.0 | 65.1           | 51.9          | 74.0             | 54.0                         | -8.9         | -2.1          | V     |
| 9.780            | 9.8                   | 45.8            | 34.1              | 38.6          | 8.6                            | -35.5     | 0.0          | 1.0 | 58.5           | 46.8          | 74.0             | 54.0                         | -15.5        | -7.2          | V     |
| 12.235           | 9.8                   | 44.7            | 34.8              | 39.2          | 9.6                            | -36.4     | 0.0          | 1.0 | 58.0           | 48.1          | 74.0             | 54.0                         | -16.0        | -5.9          | V     |
|                  |                       |                 |                   |               |                                |           |              |     |                |               |                  |                              |              |               |       |
| 4.890            | 9.8                   | 49.5            | 37.7              | 34.1          | 5.8                            | -36.1     | 0.0          | 1.0 | 54.3           | 42.4          | 74.0             | 54.0                         | -19.7        | -11.6         | H     |
| 7.340            | 9.8                   | 54.6            | 40.4              | 37.2          | 7.3                            | -36.3     | 0.0          | 1.0 | 63.8           | 49.6          | 74.0             | 54.0                         | -10.2        | -4.4          | H     |
| 9.780            | 9.8                   | 45.8            | 34.2              | 38.6          | 8.6                            | -35.5     | 0.0          | 1.0 | 58.5           | 46.9          | 74.0             | 54.0                         | -15.5        | -7.1          | H     |
| 12.235           | 9.8                   | 44.6            | 34.3              | 39.2          | 9.6                            | -36.4     | 0.0          | 1.0 | 57.9           | 47.6          | 74.0             | 54.0                         | -16.1        | -6.4          | H     |
|                  |                       |                 |                   |               |                                |           |              |     |                |               |                  |                              |              |               |       |
| <b>SPURIOUS</b>  |                       |                 |                   |               |                                |           |              |     |                |               |                  |                              |              |               |       |
| 4.330            | 9.8                   | 55.0            | 46.5              | 33.0          | 5.3                            | -36.1     | 0.0          | 1.0 | 58.3           | 49.7          | 74.0             | 54.0                         | -15.7        | -4.3          | V     |
| 6.500            | 9.8                   | 52.7            | 42.5              | 35.5          | 6.9                            | -36.4     | 0.0          | 1.0 | 59.6           | 49.5          | 74.0             | 54.0                         | -14.4        | -4.5          | V     |
| 4.330            | 9.8                   | 55.3            | 47.0              | 33.0          | 5.3                            | -36.1     | 0.0          | 1.0 | 58.5           | 50.2          | 74.0             | 54.0                         | -15.5        | -3.8          | H     |
| 6.500            | 9.8                   | 51.3            | 42.6              | 35.5          | 6.9                            | -36.4     | 0.0          | 1.0 | 58.3           | 49.6          | 74.0             | 54.0                         | -15.7        | -4.4          | H     |
|                  |                       |                 |                   |               |                                |           |              |     |                |               |                  |                              |              |               |       |
|                  |                       |                 |                   |               |                                |           |              |     |                |               |                  |                              |              |               |       |
|                  |                       |                 |                   |               |                                |           |              |     |                |               |                  |                              |              |               |       |
| <b>f</b>         | Measurement Frequency |                 |                   | <b>Amp</b>    | Preamp Gain                    |           |              |     |                |               | <b>Avg Lim</b>   | Average Field Strength Limit |              |               |       |
| Dist             | Distance to Antenna   |                 |                   | <b>D Corr</b> | Distance Correct to 3 meters   |           |              |     |                |               | <b>Pk Lim</b>    | Peak Field Strength Limit    |              |               |       |
| Read             | Analyzer Reading      |                 |                   | <b>Avg</b>    | Average Field Strength @ 3 m   |           |              |     |                |               | <b>Avg Mar</b>   | Margin vs. Average Limit     |              |               |       |
| AF               | Antenna Factor        |                 |                   | <b>Peak</b>   | Calculated Peak Field Strength |           |              |     |                |               | <b>Pk Mar</b>    | Margin vs. Peak Limit        |              |               |       |
| CL               | Cable Loss            |                 |                   | <b>HPF</b>    | High Pass Filter               |           |              |     |                |               |                  |                              |              |               |       |

11:07:11 NOV 18, 2002

CARLSON WIRELESS RES.BAND CH. 1 RAD VERT

DISPLAY LINE

ACTV DET: PEAK

74.0 dB $\mu$ V

MEAS DET: PEAK QP AVG

MKR 2.38980 GHz


71.88 dB $\mu$ V

REF OFFST 22.5 dB

LOG REF 118.5 dB $\mu$ V

10  
dB/  
#ATN  
0 dB

DL  
74.0  
dB $\mu$ V  
VA SB  
SC FC  
CORR



START 2.31000 GHz

#IF BW 1.0 MHz

STOP 2.39000 GHz

#AVG BW 1 MHz

SWP 20.0 msec

11:08:21 NOV 18, 2002

CARLSON WIRELESS RES.BAND CH. 1 RAD VERT

DISPLAY LINE

54.0 dB $\mu$ V

ACTV DET: PEAK

MEAS DET: PEAK QP AVG

MKR 2.38540 GHz


52.00 dB $\mu$ V

REF OFFST 22.5 dB

LOG REF 118.5 dB $\mu$ V

10  
dB/  
#ATN  
0 dB

DL  
54.0  
dB $\mu$ V  
VA SB  
SC FC  
CORR



START 2.31000 GHz

#IF BW 1.0 MHz

#AVG BW 10 Hz

STOP 2.39000 GHz

SWP 24.0 sec

10:40:58 NOV 18, 2002

CARLSON WIRELESS BANDEDGE CH.5 RAD VERT

MARKER

2.4865 GHz

72.53 dB $\mu$ V

ACTV DET: PEAK

MEAS DET: PEAK QP AVG

MKR 2.4865 GHz


72.53 dB $\mu$ V

REF OFFST 22.5 dB

LOG REF 119.5 dB $\mu$ V

10  
dB/  
#ATN  
Ø dB

DL  
74.Ø  
dB $\mu$ V  
VA SB  
SC FC  
CORR



START 2.4335 GHz

#IF BW 1.Ø MHz

#AVG BW 1 MHz

STOP 2.5335 GHz

SWP 2Ø.Ø msec

10:40:11 NOV 18, 2002

CARLSON WIRELESS BANDEDGE CH.5 RAD VERT

MARKER

2.4875 GHz

51.39 dB $\mu$ V

ACTV DET: PEAK

MEAS DET: PEAK QP AVG

MKR 2.4875 GHz


51.39 dB $\mu$ V

REF OFFST 22.5 dB

LOG REF 119.5 dB $\mu$ V

10  
dB/  
#ATN  
Ø dB

DL  
54.Ø  
dB $\mu$ V  
VA SB  
SC FC  
CORR



START 2.4335 GHz

#IF BW 1.Ø MHz

#AVG BW 1Ø Hz

STOP 2.5335 GHz

SWP 3Ø.Ø sec

11/07/02 **FCC Measurement**  
**Compliance Certification Services, Morgan Hill Open Field Site**

Test Engr: Neelesh Raj

Project #:

Company: Carlson Wireless

EUT Descrip.: 2.4 GHZ DTS

EUT M/N: FT512 with 24 dBi external Antenna

Test Target: 15.205, 15.209 bandedge

**Equipment for 1-22 GHz:**

HP8566B Analyzer  
 Miteq NSP2600-44 Preamp  
 EMCO 3115 Antenna  
 Cable: 13.5 feet

**Equipment for 22 - 58 GHz:**

HP8566B Analyzer  
 HP 11975A Amplifier (LO)  
 HP 11970K External mixer/antenna  
 Cable: IF Only (321 MHz)

**Peak Measurements:**

1 MHz Resolution Bandwidth  
 1MHz Video Bandwidth

**Average Measurements:**

1MHz Resolution Bandwidth  
 10Hz Video Bandwidth

NOTE: Peak and Average readings were derived from data using the Marker Delta method. Refer to spectrum analyzer plots

| f<br>GHz | Dist<br>feet | Read Pk<br>dBuV | Read Avg.<br>dBuV | AF<br>dB/m | CL<br>dB | Amp<br>dB | D Corr<br>dB | HPF | Peak<br>dBuV/m | Avg<br>dBuV/m | Pk Lim<br>dBuV/m | Avg Lim<br>dBuV/m | Pk Mar<br>dB | Avg Mar<br>dB | Notes |
|----------|--------------|-----------------|-------------------|------------|----------|-----------|--------------|-----|----------------|---------------|------------------|-------------------|--------------|---------------|-------|
| 2.385    | 3.3          | 44.7            | 21.1              | 28.8       | 3.4      | 0.0       | -9.5         | 0.0 | 67.5           | 43.9          | 74.0             | 54.0              | -6.5         | -10.1         | CH2   |
| 2.485    | 3.3          | 41.0            | 15.3              | 29.1       | 3.5      | 0.0       | -9.5         | 0.0 | 64.1           | 38.3          | 74.0             | 54.0              | -9.9         | -15.7         | CH4   |

|      |                       |        |                                |         |                              |
|------|-----------------------|--------|--------------------------------|---------|------------------------------|
| f    | Measurement Frequency | Amp    | Preamplifier Gain              | Avg Lim | Average Field Strength Limit |
| Dist | Distance to Antenna   | D Corr | Distance Correct to 3 meters   | Pk Lim  | Peak Field Strength Limit    |
| Read | Analyzer Reading      | Avg    | Average Field Strength @ 3 m   | Avg Mar | Margin vs. Average Limit     |
| AF   | Antenna Factor        | Peak   | Calculated Peak Field Strength | Pk Mar  | Margin vs. Peak Limit        |
| CL   | Cable Loss            | HPF    | High Pass Filter               |         |                              |

13:44:10 NOV 07, 2002

CARLSON-OPAFT512 DISH ANTENNA BANDEdge CH.2 MARKER DE

MARKER

2.3845 GHz

37.74 dB $\mu$ V


ACTV DET: PEAK

MEAS DET: PEAK QP AVG

MKR 2.3845 GHz

37.74 dB $\mu$ V

LOG REF 92.0 dB $\mu$ V



START 2.3100 GHz

#IF BW 30 kHz

#AVG BW 30 kHz

STOP 2.4408 GHz

SWP 436 msec

13: 43: 40 NOV 07, 2002

CARLSON-OPAFT512 DISH ANTENNA BANDEDGE CH.2 MARKER DE

MARKER  $\Delta$

39.2 MHz

52.39 dB


ACTV DET: PEAK

MEAS DET: PEAK QP AVG

MKR 39.2 MHz

52.39 dB

LOG REF 92.0 dB $\mu$ V



START 2.3100 GHz

#IF BW 30 kHz

STOP 2.4408 GHz

#AVG BW 30 kHz

SWP 436 msec


13:37:38 NOV 07, 2002

CARLSON-OPAFT512 DISH ANTENNA BANDEDGE CH.2 MARKER DE

AVERAGE BANDWIDTH  
1 MHz

ACTV DET: PEAK  
MEAS DET: PEAK QP AVG  
MKR 2.4246 GHz  
97.13 dB $\mu$ V

LOG REF 102.0 dB $\mu$ V



START 2.3466 GHz

#IF BW 1.0 MHz #AVG BW 1 MHz

STOP 2.5025 GHz

SWP 20.0 msec

13:41:45 NOV 07, 2002

CARLSON-OPAFT512 DISH ANTENNA BANDEDGE CH.2 MARKER DE

SWEEPTIME

100 sec

ACTV DET: PEAK

MEAS DET: PEAK QP AVG


MKR 2.4180 GHz

68.50 dB $\mu$ V

LOG REF 102.0 dB $\mu$ V

10  
dB/  
ATN  
10 dB

WA SB  
SC FC  
CORR



START 2.3466 GHz

#IF BW 1.0 MHz

#AVG BW 10 Hz

STOP 2.5025 GHz

#SWP 100 sec

13:21:44 NOV 07, 2002

CARLSON-OPAFT512 DISH ANTENNA BANDEDGE CH.4 MARKER DE

REF LEVEL

102.0 dB $\mu$ V

ACTV DET: PEAK

MEAS DET: PEAK QP AVG


MKR 2.4472 GHz

95.17 dB $\mu$ V

LOG REF 102.0 dB $\mu$ V

10  
dB/  
ATN  
10 dB

MA SB  
SC FC  
CORR



START 2.3704 GHz

#IF BW 1.0 MHz

STOP 2.5263 GHz

SWP 20.0 msec

#AVG BW 1 MHz

13: 25: 48 NOV 07, 2002

CARLSON-OPAFT512 DISH ANTENNA BANDEDGE CH. 4 MARKER DE

SWEETIME

100 sec


ACTV DET: PEAK

MEAS DET: PEAK QP AVG

MKR 2.4410 GHz

69.45 dB $\mu$ V

LOG REF 102.0 dB $\mu$ V



START 2.3704 GHz

#IF BW 1.0 MHz

#AVG BW 10 Hz

STOP 2.5263 GHz

#SWP 100 sec

14:16:07 NOV 07, 2002

CARLSON-OPAFT512 DISH ANTENNA BANDEDGE CH.4 MARKER DE

MARKER  $\Delta$

-38.83 MHz

54.20 dB


ACTV DET: PEAK

MEAS DET: PEAK QP AVG

MKR -38.83 MHz

54.20 dB

LOG REF 92.0 dB  $\mu$ V



START 2.43885 GHz

#IF BW 30 kHz

STOP 2.50000 GHz

#AVG BW 30 kHz

SWP 204 msec

14: 15: 50 NOV 07, 2002

CARLSON-OPAFT512 DISH ANTENNA BANDEDGE CH.4 MARKER DE

MARKER

2.48502 GHz

35.82 dB $\mu$ V


ACTV DET: PEAK

MEAS DET: PEAK QP AVG

MKR 2.48502 GHz

35.82 dB $\mu$ V

LOG REF 92.0 dB $\mu$ V



START 2.43885 GHz


#IF BW 30 kHz

STOP 2.50000 GHz

#AVG BW 30 kHz

SWP 204 msec

## **Radiated Test Set-up, 30 - 1000 MHz**



## **Test Procedures, 30 -1000 MHz**

The EUT was set to RECEIVE/TRANSMIT mode. Radiation emissions from the digital portion of the EUT were measured according to the dictates of ANSI C63.4.

## **Test Results**

Refer to tabulated data sheet.



# COMPLIANCE

Certification Services

FCC, VCCI, CISPR, CE, AUSTEL, NZ  
UL, CSA, TUV, BSMI, DHHS, NVLAP

561F MONTEREY ROAD, SAN JOSE, CA 95037-9001  
PHONE: (408) 463-0885 FAX: (408) 463-0888

*Project #:* 02U1641  
*Report #:* 110802B1  
*Date & Time:* 11/08/02 1:46 PM  
*Test Engr:* NEELESH RAJ

|                             |                                      |
|-----------------------------|--------------------------------------|
| <i>Company:</i>             | CARLSON WIRELESS                     |
| <i>EUT Description:</i>     | FT512 (2.4GHz SPREAD SPECTRUM W/LAN) |
| <i>Test Configuration :</i> | EUT/AC ADAPTER                       |
| <i>Type of Test:</i>        | EN55022-B                            |
| <i>Mode of Operation:</i>   | TRANSMITTING                         |

<< Main Sheet

| Mark<br>(P/Q/A) |
|-----------------|
| QP              |
| P               |
| QP              |
| P               |
| QP              |
| P               |

**AC Line Conducted Emissions**  
**Test Requirement: 15.107, 15.207**

**Measurement Equipment Used:**

Rohde & Schwarz EMI Receiver ESHS-20  
Fischer Custom Communication LISN, FCC-LISN-50/250-25-2

**Test Procedure**

1. The EUT was placed on a wooden table 40 cm from a vertical ground plane and approximately 80 cm above the horizontal ground plane on the floor. The EUT was set to transmit in normally.
2. Line conducted data was recorded for both NEUTRAL and HOT lines.

**Test Results**


PASS. Refer to data sheets below. Data is presented for 120 VAC and 240 VAC models.



561F Monterey Road,  
San Jose, CA 95037 USA  
Tel: (408) 463-0885  
Fax: (408) 463-0888

Data#: 7 File#: 02U1641D.EMI

Date: 11-08-2002 Time: 16:24:03  
Compliance Certification Service



Trace: 5

Ref Trace:


Project #: 02u1641  
Test Engineer : NEELESH RAJ  
Company : CARLSON WIRELESS  
EUT : 2.4GHz SPREAD SPECTRUM W/LAN  
Model Name : FT512  
Test Config. : EUT/AC ADAPTER  
Test of Target: EN55022 Class B  
Mode of Op. : TRANSMITTING  
: 115VAC@60Hz  
: L1 (peak; black quasipeak; green)



561F Monterey Road,  
San Jose, CA 95037 USA  
Tel: (408) 463-0885  
Fax: (408) 463-0888

Data#: 7 File#: 02U1641C.EMI

Date: 11-08-2002 Time: 15:59:20  
Compliance Certification Service




Trace: 5

Ref Trace:

Project #: 02u1641  
Test Engineer: NEELESH RAJ  
Company: CARLSON WIRELESS  
EUT: 2.4GHz SPREAD SPECTRUM W/LAN  
Model Name: FT512  
Test Config.: EUT/AC ADAPTER  
Test of Target: EN55022 Class B  
Mode of Op.: TRANSMITTING  
: 115VAC@60Hz  
: L2 (peak; black quasipeak; green)

Data#: 7 File#: 02U1641A.EMI

Date: 11-08-2002 Time: 15:31:40  
 Compliance Certification Service




Trace: 5

Ref Trace:

Project # : 02u1641  
 Test Engineer : NEELESH RAJ  
 Company : CARLSON WIRELESS  
 EUT : 2.4GHz SPREAD SPECTRUM W/LAN  
 Model Name : FT512  
 Test Config. : EUT/AC ADAPTER  
 Test of Target: EN55022 Class B  
 Mode of Op. : TRANSMITTING  
 : 115VAC@60Hz  
 : L1 (peak; black avg; green)

Data#: 7 File#: 02U1641B.EMI

Date: 11-08-2002 Time: 15:48:50  
Compliance Certification Service


Trace: 5

Ref Trace:

Project # : 02u1641  
Test Engineer : NEELESH RAJ  
Company : CARLSON WIRELESS  
EUT : 2.4GHz SPREAD SPECTRUM W/LAN  
Model Name : FT512  
Test Config. : EUT/AC ADAPTER  
Test of Target: EN55022 Class B  
Mode of Op. : TRANSMITTING  
: 115VAC@60Hz  
: L2 (peak; black avg; green)



| Remark  |
|---------|
| L1 / L2 |
| L1      |
| L1      |
| L1      |
| L2      |
| L2      |
| L2      |

| Remark  |
|---------|
| L1 / L2 |
| L1      |
| L1      |
| L1      |
| L2      |
| L2      |
| L2      |

**Minimum 6 dB Bandwidth**  
**Test Requirement: 15.247(a)2**

**Measurement Equipment Used:**

HP 8593EM Spectrum Analyzer  
20 dB attenuator  
3ft length low loss coaxial cable

**Test Procedures**

The EUT was configured on a test bench. The EUT was set for continuous operation . Frequency was set to LOW channel. While the transmitter broadcast a steady stream of digital data, the analyzer MAX HOLD function was used to capture the envelope of the transmission occupied bandwidth.

The test was repeated at MID channel and at HIGH channel.

**Test Results:** Refer to attached spectrum analyzer charts. Data taken with RES BW of 100 kHz shows minimum 6 dB BW of 9.2 MHz. Minimum requirement: 500 kHz

**Channel      Frequency, MHz**

|      |      |
|------|------|
| Low  | 2412 |
| Mid  | 2448 |
| High | 2460 |


**NOTE:** 6 dB bandwidth was measured at each modulation, with essentially the same bandwidth resulting. Data is presented for the 512 kbps modulation setting.

**15.247(a)2: Minimum 6 dB Bandwidth**

12:42:59 NOV 06, 2002  
CARLSON-OPAFT512 6dB BW LOW

ACTV DET: PEAK  
MEAS DET: PEAK QP AVG  
MKR 9.20 MHz  
- .01 dB

REF OFFSET 21.0 dB  
LOG REF 21.0 dBm



CENTER 2.41200 GHz

#IF BW 100 kHz

#AVG BW 100 kHz

SPAN 20.00 MHz


SWP 20.0 msec

CH1

12:13:26 NOV 06, 2002  
CARLSON-OPAFT512 6dB BW MID

ACTV DET: PEAK  
MEAS DET: PEAK QP AVG  
MKR 9.15 MHz  
.34 dB

REF OFFST 21.0 dB  
LOG REF 21.0 dBm



CENTER 2.44800 GHz

SPAN 20.00 MHz

#IF BW 100 kHz

#AVG BW 100 kHz

SWP 20.0 msec


ch 4

09:38:38 NOV 08, 2002  
CARLSON-OPAFT512 6dB BW CH.5

MARKER  $\Delta$   
-9.05 MHz  
1.17 dB

ACTV DET: PEAK  
MEAS DET: PEAK QP AVG  
MKR -9.05 MHz  
1.17 dB

REF OFFST 11.0 dB  
LOG REF 10.0 dBm



CENTER 2.45928 GHz

#IF BW 100 kHz

#AVG BW 100 kHz

SPAN 20.00 MHz

SWP 20.0 msec

## **RF Power Output**

**Test Requirement: 15.247(b)**

### **Measurement Equipment Used:**

Agilent E4416A power meter

Agilent E9327A RF sensor

20 dB attenuator

### **Test Procedures**

1. The EUT was configured on a test bench. The power meter was zeroed and calibrated. The control software was activated and power was set to produce highest output level.
2. The 20 dB attenuator was connected to the antenna port of the EUT. The power meter head was connected to the other end of the attenuator. Peak power was read directly off the meter, accounting for the 20 dB attenuator.
3. The process in (1) and (2) was repeated for MID channel and HIGH channel.

### **Test Results**

Power level readings converted to dBm are shown below. Refer also to spectrum analyzer graphs. Reference level offset corrects for external attenuation and cable loss.

| <b>Channel</b> | <b>Frequency, MHz</b> | <b>Output Power, dBm</b> |
|----------------|-----------------------|--------------------------|
| 1 LOW          | 2412                  | 17.6                     |
| 3 MID          | 2436                  | 17.5                     |
| 5 HIGH         | 2460                  | 17.4                     |

Maximum output power output variation within 0.6 dBm of design maximum 18 dBm output.

**NOTE:** Data is presented for the 512 kbps modulation setting. Maximum power output is independent of modulation type

**Spurious Emissions, Conducted  
Test Requirement: 15.247(c)**

**Measurement Equipment Used:**

HP 8593EM Spectrum Analyzer  
20 dB attenuator  
3 ft length low loss A coaxial RF cable

**Test Procedure**

1. The EUT was configured on a test bench. The cable was connected between the EUT antenna port and the spectrum analyzer input port.

Spectrum analyzer RES BW was set to 100 kHz. While the transmitter broadcast a steady stream of digital data, the analyzer MAX HOLD function was used to capture the envelope of the transmission.

Readings were taken out to 10fo.

2. The process in (1) was repeated for MID channel and HIGH channel.

**Test Results**

Refer to attached data sheets. Data shows out of band emissions are suppressed well below the -20 dBc minimum required by the Rules.

| <b>Channel</b> | <b>Frequency, MHz</b> |
|----------------|-----------------------|
| 1 LOW          | 2412                  |
| 4 MID          | 2448                  |
| 5 HIGH         | 2460                  |


**NOTE:** Data is presented for the 512 kbps modulation setting.

**15.247(c): Spurious Emissions, Conducted**

12:36:27 NOV 06, 2002  
CARLSON-OPAFT512 SPURIOUS LOW

ACTV DET: PEAK  
MEAS DET: PEAK QP AVG  
MKR 2.405 GHz  
6.83 dBm

REF OFFSET 21.0 dB  
LOG REF 21.0 dBm



START 30 MHz

#IF BW 100 kHz

#AVG BW 100 kHz

STOP 2.900 GHz


SWP 861 msec

CH 1

12:39:05 NOV 06, 2002  
CARLSON-OPAFT512 SPURIOUS LOW

ACTV DET: PEAK  
MEAS DET: PEAK QP AVG  
MKR 22.78 GHz  
-32.66 dBm

REF OFFSET 21.0 dB  
LOG REF 21.0 dBm



START 2.90 GHz

#IF BW 100 kHz

#AVG BW 100 kHz

STOP 26.50 GHz

SWP 7.08 sec

CH1

12:24:37 NOV 06, 2002

CARLSON-OPAFT512 SPURIOUS MID

DISPLAY LINE

-14.9 dBm

ACTV DET: PEAK

MEAS DET: PEAK QP AVG

MKR 2.448 GHz

5.07 dBm

REF OFFST 21.0 dB

LOG REF 21.0 dBm

10

dB/

ATN

10 dB

DL


-14.9

dBm

VA SB

SC FC

CORR



START 30 MHz

#IF BW 100 kHz

#AVG BW 100 kHz

STOP 2.900 GHz

SWP 861 msec

ch4

12:26:43 NOV 06, 2002

CARLSON-OPAFT512 SPURIOUS MID

STOP

26.50 GHz

ACTV DET: PEAK

MEAS DET: PEAK QP AVG

MKR 22.78 GHz

-33.45 dBm


REF OFFSET 21.0 dB

LOG REF 21.0 dBm

10  
dB/  
ATN  
10 dB

DL  
-14.9  
dBm

VA SB  
SC FC  
CORR



START 2.90 GHz

#IF BW 100 kHz

#AVG BW 100 kHz

STOP 26.50 GHz

SWP 7.08 sec

ch4

17:51:13 NOV 08, 2002

CARLSON-OPAFT512 CH.5 SPURIOUS

MARKER

2.175 GHz

-46.29 dBm

ACTV DET: PEAK

MEAS DET: PEAK QP AVG

MKR 2.175 GHz

-46.29 dBm

REF OFFST 11.0 dB

LOG REF 11.0 dBm

10

dB/

ATN

10 dB

DL


-13.8

dBm

VA SB

SC FC

CORR



START 30 MHz

#IF BW 100 kHz

#AVG BW 100 kHz

STOP 2.900 GHz

SWP 861 msec

17: 52: 00 NOV 08, 2002

CARLSON-OPAFT512 CH.5 SPURIOUS

STOP

26.50 GHz

ACTV DET: PEAK

MEAS DET: PEAK QP AVG

MKR 23.08 GHz

-43.45 dBm

REF OFFST 11.0 dB

LOG REF 11.0 dBm

10

dB/

ATN

10 dB

DL


-13.8

dBm

MA SB

SC FC

CORR



START 2.90 GHz

#IF BW 100 kHz

#AVG BW 100 kHz

STOP 26.50 GHz

SWP 7.08 sec

**Power Spectral Density**  
**Test Requirement: 15.247(d)**

**Measurement Equipment Used:**

HP 8593EM Spectrum Analyzer  
2 ft length low loss A coaxial RF cable

**Test Procedure**

For the LOW channel, the emission peak was set to the center of the display. The SPAN was set to 300 kHz, the RES BW and VID BW were set to 3 kHz, and SWEEP TIME was set to 100 seconds. The maximum trace was recorded and compared to the 8 dBm limit.

The test was repeated for MID and HIGH channel.

**Test Results**

Maximum measured PSD was approximately -4.5 dBm. Refer to attached spectrum analyzer charts.

**Channel      Frequency, MHz**

|          |      |
|----------|------|
| 1 (Low)  | 2412 |
| 4 (Mid)  | 2448 |
| 5 (High) | 2460 |

**NOTE:** Data is presented for the 512 kbps modulation setting. Readings essentially identical for all modulation types, 512 kbps appearing to be worst case.


**15.247(d): Power Spectral Density**

13:41:41 NOV 06, 2002  
CARLSON-OPAFT512 PPSD LOW

SWEEPTIME  
100 sec

ACTV DET: PEAK  
MEAS DET: PEAK QP AVG  
MKR 2.4112140 GHz  
-4.87 dBm

REF OFFST 21.0 dB  
LOG REF 21.0 dBm



CENTER 2.4112500 GHz SPAN 300.0 kHz  
#IF BW 3.0 kHz #AVG BW 3 kHz #SWP 100 sec


Ch 1

12:19:17 NOV 06, 2002  
CARLSON-OPAFT512 PPSD MID

DISPLAY LINE  
8.0 dBm

ACTV DET: PEAK  
MEAS DET: PEAK QP AVG  
MKR 2.4486035 GHz  
-6.34 dBm

REF OFFSET 21.0 dB  
LOG REF 21.0 dBm



CENTER 2.4486035 GHz

SPAN 200.0 kHz

#IF BW 3.0 kHz

#AVG BW 3 kHz

#SWP 100 sec

CH 4

09:43:32 NOV 08, 2002

CARLSON-OPAFT512 6dB BW CH.5

SWEEPTIME

100 sec

ACTV DET: PEAK

MEAS DET: PEAK QP AVG

MKR 2.4592218 GHz

-4.45 dBm

REF OFFST 11.0 dB

LOG REF 10.0 dBm

10  
dB/

ATN

10 dB

DL


8.0

dBm

VA SB

SC FC

CORR



CENTER 2.4592750 GHz

#IF BW 3.0 kHz

#AVG BW 3 MHz

SPAN 300.0 kHz

#SWP 100 sec