

## RF Exposure Requirements

**RF Exposure Requirements:** **§1.1307(b)(1) and §1.1307(b)(2):** Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines.

**RF Radiation Exposure Limit:** **§1.1310:** As specified in this section, the Maximum Permissible Exposure (MPE) Limit shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in Sec. 1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of Sec. 2.1093 of this chapter.

MPE Limit Calculation: EUT's operating frequencies @ 5875–5905 MHz (20MHz BW)  
highest conducted power = 6.91 dBm therefore, **Limit for Uncontrolled exposure: 1 mW/cm<sup>2</sup> or 10 W/m<sup>2</sup>**

EUT maximum antenna gain = 16 dBi.

Equation from page 18 of OET 65, Edition 97-01

### EUT with 16 dBi Antenna

$$S = PG / 4\pi R^2 \quad \text{or} \quad R = \sqrt{PG / 4\pi S}$$

where, S = Power Density (1 mW/cm<sup>2</sup>)

P = Power Input to antenna (4.91 mW)

G = Antenna Gain (39.81 numeric)

$$R = \sqrt{(4.91 * 39.81) / (4 * 3.14 * 1)} = 3.94 \text{ cm}$$

$$S = (4.91 * 39.81 / 4 * 3.14 * 20.0^2) = (195.43 / 5024) = 0.039 \text{ mW/cm}^2 \text{ @ 20cm separation}$$