



FCC PART 15C TEST REPORT FOR CERTIFICATION  
On Behalf of

Sounding Audio Industrial Ltd

AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/ Sirius XM Ready Heavy Duty Radio

Model Number: JCV1640BT

FCC ID: OPDJCV1640BT

Prepared for : Sounding Audio Industrial Ltd  
Unit N, 7/F, Stage 2, Wah Fung Industrial, Centre 33-39  
Kwai Fung Road, Kwai Chung, Hong Kong

Prepared By : Audix Technology (Shenzhen) Co., Ltd.  
No. 6, Ke Feng Rd., 52 Block,  
Shenzhen Science & Industrial Park,  
Nantou, Shenzhen, Guangdong, China

Tel: (0755) 26639496

Report Number : ACS-F14016  
Date of Test : Dec.14~23, 2013  
Date of Report : Jan.22, 2014

**TABLE OF CONTENTS**

<u>Description</u>	<u>Page</u>
<b>1. SUMMARY OF STANDARDS AND RESULTS .....</b>	<b>1-1</b>
1.1. Description of Standards and Results.....	1-1
<b>2. GENERAL INFORMATION.....</b>	<b>2-1</b>
2.1. Description of Device (EUT) .....	2-1
2.2. Test information .....	2-2
2.3. Tested Supporting System Details .....	2-1
2.4. Block Diagram of Test Setup.....	2-1
2.5. Test Facility.....	2-2
2.6. Measurement Uncertainty (95% confidence levels, k=2) .....	2-2
<b>3. RADIATED EMISSION MEASUREMENT .....</b>	<b>3-1</b>
3.1. Test Equipment .....	3-1
3.2. Block Diagram of Test Setup.....	3-1
3.3. Radiated Emission Limit Standard: FCC 15.209 .....	3-2
3.4. EUT Configuration on Test.....	3-2
3.5. Operating Condition of EUT.....	3-3
3.6. Test Procedure.....	3-3
3.7. Radiated Emission Test Results .....	3-3
<b>4. CONDUCTED SPURIOUS EMISSIONS .....</b>	<b>4-1</b>
4.1. Test Equipment .....	4-1
4.2. Limit.....	4-1
4.3. Test Procedure.....	4-1
4.4. Test result.....	4-1
<b>5. CARRIER FREQUENCY SEPARATION TEST .....</b>	<b>5-1</b>
5.1. Test Equipment .....	5-1
5.2. Limit.....	5-1
5.3. Test Results .....	5-1
<b>6. 20 DB BANDWIDTH TEST .....</b>	<b>6-1</b>
6.1. Test Equipment .....	6-1
6.2. Limit.....	6-1
6.3. Test Results .....	6-1
<b>7. NUMBER OF HOPPING FREQUENCY TEST .....</b>	<b>7-1</b>
7.1. Test Equipment .....	7-1
7.2. Limit.....	7-1
7.3. Test Results .....	7-1
<b>8. DWELL TIME.....</b>	<b>8-1</b>
8.1. Test Equipment .....	8-1
8.2. Limit.....	8-1
8.3. Test Results .....	8-1
<b>9. MAXIMUM PEAK OUTPUT POWER TEST.....</b>	<b>9-1</b>
9.1. Test Equipment .....	9-1
9.2. Limit.....	9-1
9.3. Test Procedure.....	9-1
9.4. Test Results .....	9-2
<b>10. BAND EDGE COMPLIANCE TEST .....</b>	<b>10-1</b>

10.1. Test Equipment .....	10-1
10.2. Limit.....	10-1
10.3. Test Produce.....	10-1
10.4. Test Results .....	10-1
<b>11. DEVIATION TO TEST SPECIFICATIONS .....</b>	<b>11-1</b>
<b>12. PHOTOGRAPH OF TEST.....</b>	<b>12-1</b>
12.1. Photos of Radiated Emission Test (30-1000MHz).....	12-1
<b>13. PHOTOS OF THE EUT .....</b>	<b>13-1</b>

### TEST REPORT CERTIFICATION

Applicant : Sounding Audio Industrial Ltd  
 Manufacturer : AR Electronics Co., Ltd.  
 EUT Description : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/ Sirius XM Ready Heavy Duty Radio  
 FCC ID : OPDJCV1640BT  
 (A) MODEL NO. : JCV1640BT  
 (B) Serial No. : N/A  
 (C) POWER SUPPLY : DC 12V  
 (D) TEST VOLTAGE : DC 12V

Tested for comply with:  
 FCC Rules and Regulations Part 15 Subpart C: 2012  
 Test procedure used:  
 ANSI C63.10: 2009

The device described above is tested by AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. to confirm comply with all the FCC Part 15 Subpart C requirements. The test results are contained in this test report and AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. is assumed full responsibility for the accuracy and completeness of these tests. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC and IC requirements. This report contains data that are not covered by the NVLAP accreditation.

This Report is made under FCC Part 2.1075. No modifications were required during testing to bring this product into compliance.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of AUDIX TECHNOLOGY (SHENZHEN) CO., LTD.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

Date of Test : Dec.14~23, 2013 Report of date: Jan.22, 2014

Prepared by : Julia Zhu Reviewed by : [Signature]  
 Julia Zhu / Assistant Sunny Lu / Assistant Manager



Approved & Authorized Signer : David Jin / Manager

## 1. SUMMARY OF STANDARDS AND RESULTS

### 1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below.

EMISSION		
Description of Test Item	Standard	Results
Power Line Conducted Emission Test	FCC Part 15: 15.207 ANSI C63.10 :2009	N/A
Radiated Emission Test	FCC Part 15: 15.209 FCC Part 15: 15.247(d) ANSI C63.10 :2009	PASS
Conducted Spurious Emissions	FCC Part 15: 15.247(a)(1) ANSI C63.10 :2009	PASS
Carrier Frequency Separation Test	FCC Part 15: 15.247(a)(1) ANSI C63.10 :2009	PASS
20dB Bandwidth Test	FCC Part 15: 15.215 ANSI C63.10 :2009	PASS
Number Of Hopping Frequency Test	FCC Part 15: 15.247(a)(1)(iii) ANSI C63.10 :2009	PASS
Dwell Time Test	FCC Part 15: 15.247(a)(1)(iii) ANSI C63.10 :2009	PASS
Maximum Peak Output Power Test	FCC Part 15: 15.247(b)(1)\ ANSI C63.10 :2009	PASS
Band Edge Compliance Test	FCC Part 15: 15.247(d) ANSI C63.10 :2009	PASS

N/A is an abbreviation for Not Applicable.

## 2. GENERAL INFORMATION

### 2.1. Description of Device (EUT)

EUT name	: AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/ Sirius XM Ready Heavy Duty Radio
Model Number	: JCV1640BT
Radio	: Bluetooth V2.1+EDR
Operation frequency	: Bluetooth 2402-2480MHz
Channel Number	: Bluetooth: 79 channels
Modulation Technology	: GFSK, $\pi/4$ DQPSK, 8-DPSK Note: $\pi/4$ DQPSK modulation is same type modulation with 8-DPSK, and according exploratory test, 8-DPSK will have worse emissions, so the final test were only performed with GFSK and 8-DPSK modulation.
Antenna Type	: Wire Antenna, 0dBi PK gain
Applicant	: Sounding Audio Industrial Ltd Unit N, 7/F, Stage 2, Wah Fung Industrial, Centre 33-39 Kwai Fung Road, Kwai Chung, Hong Kong
Manufacturer	: AR Electronics Co., Ltd. Sima District, Changping, Dongguan, Guangdong
Date of Test	: Dec.14~23, 2013
Date of Receipt	: Dec.12, 2013
Sample Type	: Prototype production

## 2.2. Test information

The test software “bluesuite.exe” was used to control EUT work in Continuous TX mode, and select test channel.


Tested mode, channel, and data rate information			
Mode	data rate (Mbps)	Channel	Frequency (MHz)
Tx Mode GFSK modulation	1	Low :CH 0	2402
	1	Middle: CH39	2441
	1	High: CH78	2480
Tx Mode 8-DPSK modulation	3	Low :CH 0	2402
	3	Middle: CH39	2441
	3	High: CH78	2480

Note:  $\pi/4$ DQPSK modulation is same type modulation with 8-DPSK, and according exploratory test, 8-DPSK will have worse emissions, so the final test were only performed with GFSK and 8-DPSK modulation.

### 2.3. Tested Supporting System Details

No.	Description	ACS No.	Manufacturer	Model	Serial Number	Approved type
1.	Speaker	ACS-EMC-SP01TB	QINLE	QL618	N/A	<input checked="" type="checkbox"/> FCC DoC <input type="checkbox"/> BSMI ID
		Cable: Shielded, Undetachabled, 0.9m				
2.	Speaker	ACS-EMC-SP02TB	QINLE	QL618	N/A	<input checked="" type="checkbox"/> FCC DoC <input type="checkbox"/> BSMI ID
		Cable: Shielded, Undetachabled, 0.9m				
3.	Speaker	ACS-EMC-SP03TB	QINLE	QL618	N/A	<input checked="" type="checkbox"/> FCC DoC <input type="checkbox"/> BSMI ID
		Cable: Shielded, Undetachabled, 0.9m				
4.	Speaker	ACS-EMC-SP04TB	QINLE	QL618	N/A	<input checked="" type="checkbox"/> FCC DoC <input type="checkbox"/> BSMI ID
		Cable: Shielded, Undetachabled, 0.9m				
5.	iPod #1	ACS-EMC-IP01	APPLE	A1199	YM706MLDVQ5	<input checked="" type="checkbox"/> FCC DoC <input checked="" type="checkbox"/> BSMI ID: R33057
		Shielded, Detachabled, 1.0m				
6.	iPod #2	ACS-EMC-IP12	APPLE	A1204	YM706MCQVQ5	<input checked="" type="checkbox"/> FCC DoC <input checked="" type="checkbox"/> BSMI ID: R33057
		Shielded, Detachabled, 1.0m				

### 2.4. Block Diagram of Test Setup



**(EUT: AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/ Sirius XM Ready Heavy Duty Radio)**



**2.5. Test Facility**

Site Description

Name of Firm : Audix Technology (Shenzhen) Co., Ltd.  
 No. 6, Ke Feng Rd., 52 Block, Shenzhen  
 Science & Industrial Park, Nantou, Shenzhen,  
 Guangdong, China

3m Anechoic Chamber : Certificated by FCC, USA  
 Registration Number: 90454  
 Valid Date: Feb.22, 2015

3m & 10m Anechoic Chamber : Certificated by FCC, USA  
 Registration Number: 794232  
 Valid Date: Oct.31, 2015

EMC Lab. : Certificated by Industry Canada  
 Registration Number: IC 5183A-1  
 Valid Date: Jun.13, 2014

: Certificated by DAkkS, Germany  
 Registration No: D-PL-12151-01-01  
 Valid Date: Feb.01, 2014

: Accredited by NVLAP, USA  
 NVLAP Code: 200372-0  
 Valid Date: Mar.31, 2014

**2.6. Measurement Uncertainty (95% confidence levels, k=2)**

Test Item	Uncertainty
Uncertainty for Radiation Emission test in 3m chamber	3.22 dB(30~200MHz, Polarize: H)
	3.23 dB(30~200MHz, Polarize: V)
	3.49 dB(200M~1GHz, Polarize: H)
	3.39 dB(200M~1GHz, Polarize: V)
Uncertainty for Radiation Emission test in 3m chamber (1GHz-18GHz)	4.97 dB(1~6GHz, Distance: 3m)
	4.99 dB(6~18GHz, Distance: 3m)
Uncertainty for Radiated Spurious Emission test in RF chamber	3.57 dB
Uncertainty for Conduction Spurious emission test	2.00 dB
Uncertainty for Output power test	0.73 dB
Uncertainty for Bandwidth test	83 kHz
Uncertainty for DC power test	0.038 %
Uncertainty for test site temperature and humidity	0.6°C
	3%

### 3. RADIATED EMISSION MEASUREMENT

#### 3.1. Test Equipment

Frequency rang: 30~1000MHz (In 3m Anechoic Chamber)


Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	3#Chamber	AUDIX	N/A	N/A	Nov.24, 13	1 Year
2	EMI Spectrum	Agilent	E4407B	MY41440292	May.08, 13	1 Year
3	Test Receiver	Rohde & Schwarz	ESVS10	834468/011	May.08, 13	1 Year
4	Amplifier	HP	8447D	2648A04738	May.08, 13	1 Year
5	Bilog Antenna	TESEQ	CBL6112D	35375	May.30, 13	1 Year
6	RF Cable	MIYAZAKI	CFD400-NL	3# Chamber No.1	May.08, 13	1 Year
7	Coaxial Switch	Anritsu	MP59B	M74389	May.08, 13	1 Year


3.1.1. For frequency range 1GHz~25GHz (In 3m Anechoic Chamber)

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Spectrum Analyzer	Agilent	E4407B	MY41440292	May.08, 13	1 Year
2	Horn Antenna	EMCO	3115	9510-4580	May.28, 13	1 Year
3	Amplifier	Agilent	8449B	3008A00863	May.08, 13	1 Year
4	RF Cable	Hubersuhner	SUCOFLEX106	77980/6	May.08, 13	1 Year
5	RF Cable	Hubersuhner	SUCOFLEX106	77977/6	May.08, 13	1 Year
6	Horn Antenna	EMCO	3116	00060089	Aug.28, 13	1 Year

#### 3.2. Block Diagram of Test Setup

For frequency range 30MHz-1000MHz





### 3.3. Radiated Emission Limit Standard: FCC 15.209

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		$\mu\text{V}/\text{m}$	$\text{dB}(\mu\text{V})/\text{m}$
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000MHz	3	74.0 $\text{dB}(\mu\text{V})/\text{m}$ (Peak) 54.0 $\text{dB}(\mu\text{V})/\text{m}$ (Average)	

Remark : (1) Emission level  $\text{dB}\mu\text{V} = 20 \log$  Emission level  $\mu\text{V}/\text{m}$

- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.
- (4) The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

### 3.4.EUT Configuration on Test

The following equipment are installed on Radiated Emission Test to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

### 3.4.1. AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/ Sirius XM Ready Heavy Duty Radio (EUT)

Model Number : JCV1640BT  
Serial Number : N/A

## 3.5. Operating Condition of EUT

3.5.1. Setup the EUT and simulator as shown as Section 3.2.

3.5.2. Turned on the power of all equipment.

3.5.3. Let EUT work in Tx mode.

## 3.6. Test Procedure

The EUT and its simulators are placed on a turn table, which is 0.8 meter high above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarization of the antenna is set on Test. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.10-2009 on radiated emission Test.

This test was performed with EUT in X, Y, Z position, and the worse case was found when EUT in X position as the test photo indicated.

The bandwidth of the EMI test receiver (R&S ESVS10) is set at 120kHz for frequency range from 30MHz to 1000 MHz.

The bandwidth of the Spectrum's RBW is set at 1MHz and VBW is set at 3MHz for peak emissions measurement above 1GHz

This device is pulse Modulated, a duty cycle factor was used to calculated average level based measured peak level.

The frequency range from 30MHz to 10th harmonic (25GHz) are checked. and no any emissions were found from 18GHz to 25 GHz, So the radiated emissions from 18GHz to 25GHz were not record.

## 3.7. Radiated Emission Test Results



**PASS.**


All the emissions from 30MHz to 25GHz were comply with the 15.209 Limit.

Note: The duty cycle factor for calculate average level is 9.09dB, and average limit is 20dB below peak limit, so if peak measured level comply with peak limit, the average level was deemed to comply with average limit.

Duty cycle:  $0.437 \text{ ms} / 1.245 \text{ ms} * 100\% = 35.10\%$

Duty cycle factor =  $20 \log (1/\text{duty cycle}) = 9.09$






**Frequency: 30MHz~1GHz**

Data: 17

File: E:\2013 Report Data\Sounding\ACS13Q2322.EM6 (18)


Date: 2013-12-23



Site no. : 3m Chamber Data no. : 17  
 Dis. / Ant. : 3m 2013 CBL6112D 35375 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15 C (3M)  
 Env. / Ins. : 24°C/65% Engineer : Leo-Li  
 EUT : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM  
 Ready Heavy Duty Radio  
 Power supply : DC 12V  
 Test mode : Tx Mode  
 M/N : JCV1640BT

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	150.280	11.27	1.60	12.59	25.46	43.50	18.04	QP
2	180.350	9.70	1.72	16.19	27.61	43.50	15.89	QP
3	248.250	12.92	1.97	9.01	23.90	46.00	22.10	QP
4	437.400	17.00	2.57	12.10	31.67	46.00	14.33	QP
5	495.600	17.91	2.74	11.69	32.34	46.00	13.66	QP
6	670.200	19.70	3.24	7.32	30.26	46.00	15.74	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 18  
 Dis. / Ant. : 3m 2013 CBL6112D 35375 Ant. pol. : VERTICAL  
 Limit : FCC PART 15 C (3M)  
 Env. / Ins. : 24°C/65% Engineer : Leo-Li  
 EUT : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM  
 Ready Heavy Duty Radio  
 Power supply : DC 12V  
 Test mode : Tx Mode  
 M/N : JCV1640BT

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	124.090	12.90	1.50	7.54	21.94	43.50	21.56	QP
2	184.230	9.60	1.73	16.84	28.17	43.50	15.33	QP
3	352.040	15.48	2.32	9.23	27.03	46.00	18.97	QP
4	435.460	17.00	2.56	7.78	27.34	46.00	18.66	QP
5	515.000	18.20	2.79	4.81	25.80	46.00	20.20	QP
6	742.950	20.30	3.45	2.95	26.70	46.00	19.30	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.




**Frequency: 1GHz~18GHz**

Data: 1

File: G:\2013 report\5\Sounding\ACS13Q2322.EM6 (44)

Date: 2013-12-14




Site no. : 3m Chamber Data no. : 1  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23\*C/54% Engineer : Leo-Li  
 EUT : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM  
 Ready Heavy Duty Radio  
 Power supply : DC 12V  
 Test mode : GFSK 2402MHz Tx  
 M/N : JCV1640BT

	Ant.	Cable	Amp.	Emission					
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark	
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)		
1	1600.000	25.62	4.63	36.14	46.64	40.75	74.00	33.25	Peak
2	2402.000	28.18	5.80	35.70	94.72	93.00	74.00	-19.00	Peak

Remarks:


1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 2  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23\*C/54% Engineer : Leo-Li  
 EUT : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM  
 Ready Heavy Duty Radio  
 Power supply : DC 12V  
 Test mode : GFSK 2402MHz Tx  
 M/N : JCV1640BT

	Freq.	Ant.	Cable	Amp.	Emission				Remark
	(MHz)	Factor	loss	Factor	Reading	Level	Limits	Margin	
		(dB/m)	(dB)	(dB)	(dBUV)	(dBUV/m)	(dBUV/m)	(dB)	
1	1600.000	25.62	4.63	36.14	44.60	38.71	74.00	35.29	Peak
2	2401.000	28.18	5.80	35.70	97.02	95.30	74.00	-21.30	Peak

Remarks:  
 1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 5  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23\*C/54% Engineer : Leo-Li  
EUT : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM  
Ready Heavy Duty Radio  
Power supply : DC 12V  
Test mode : GFSK 2402MHz Tx  
M/N : JCV1640BT




Site no. : 3m Chamber Data no. : 6  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Leo-Li  
 EUT : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM  
 Ready Heavy Duty Radio  
 Power supply : DC 12V  
 Test mode : GFSK 2402MHz Tx  
 M/N : JCV1640BT

	Ant. Factor	Cable loss	Amp. Factor	Reading	Emission Level	Limits	Margin	Remark
1	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	32.85	8.56	35.70	50.22	55.93	74.00	18.07	Peak


Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Frequency (MHz)	Peak level (dBuV/m)	Duty cycle factor (dB)	AV level (dBuV/m)	Limit(dBuv/m)	Conclusion
4804.000	55.93	9.09	46.84	54	Pass



Site no. : 3m Chamber Data no. : 7  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23\*C/54% Engineer : Leo-Li  
EUT : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM  
Ready Heavy Duty Radio  
Power supply : DC 12V  
Test mode : GFSK 2402MHz Tx  
M/N : JCV1640BT




Site no. : 3m Chamber Data no. : 8  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Leo-Li  
 EUT : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM  
 Ready Heavy Duty Radio  
 Power supply : DC 12V  
 Test mode : GFSK 2402MHz Tx  
 M/N : JCV1640BT

	Ant. Factor	Cable loss	Amp. Factor	Reading	Emission Level	Limits	Margin	Remark
1	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	32.85	8.56	35.70	49.23	54.94	74.00	19.06	Peak


Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Frequency (MHz)	Peak level (dBuV/m)	Duty cycle factor (dB)	AV level (dBuV/m)	Limit(dBuv/m)	Conclusion
4804.000	54.94	9.09	45.85	54	Pass



Site no. : 3m Chamber Data no. : 9  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM  
Ready Heavy Duty Radio  
Power supply : DC 12V  
Test mode : GFSK 2441MHz Tx  
M/N : JCV1640BT



Site no. : 3m Chamber Data no. : 10  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23\*C/54% Engineer : Leo-Li  
 EUT : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM  
 Ready Heavy Duty Radio  
 Power supply : DC 12V  
 Test mode : GFSK 2441MHz Tx  
 M/N : JCV1640BT


	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	32.99	8.64	35.70	49.84	55.77	74.00	18.23	Peak

Remarks:


- Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
- The emission levels that are 20dB below the official limit are not reported.

Frequency (MHz)	Peak level (dBuV/m)	Duty cycle factor (dB)	AV level (dBuV/m)	Limit(dBuV/m)	Conclusion
4882.000	55.77	9.09	46.68	54	Pass





Site no. : 3m Chamber Data no. : 11  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23\*C/54% Engineer : Leo-Li  
EUT : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM  
Ready Heavy Duty Radio  
Power supply : DC 12V  
Test mode : GFSK 2441MHz Tx  
M/N : JCV1640BT




Site no. : 3m Chamber Data no. : 12  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Leo-Li  
 EUT : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM  
 Ready Heavy Duty Radio  
 Power supply : DC 12V  
 Test mode : GFSK 2441MHz Tx  
 M/N : JCV1640BT

	Ant.	Cable	Amp.	Emission					
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark	
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)		
1 4882.000	32.99	8.64	35.70	48.36	54.29	74.00	19.71	Peak	

Remarks:

- Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
- The emission levels that are 20dB below the official limit are not reported.


Frequency (MHz)	Peak level (dBuV/m)	Duty cycle factor (dB)	AV level (dBuV/m)	Limit(dBuv/m)	Conclusion
4882.000	54.29	9.09	45.2	54	Pass



Site no. : 3m Chamber Data no. : 13  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23\*C/54% Engineer : Leo-Li  
 EUT : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM  
 Ready Heavy Duty Radio  
 Power supply : DC 12V  
 Test mode : GFSK 2441MHz Tx  
 M/N : JCV1640BT

	Freq.	Ant.	Cable	Amp.	Emission				Remark
	(MHz)	(dB/m)	(dB)	(dB)	Reading	Level	Limits	Margin	
					(dBUV)	(dBUV/m)	(dBUV/m)	(dB)	
1	1594.000	25.59	4.62	36.15	42.51	36.57	74.00	37.43	Peak
2	2440.000	28.27	5.86	35.70	91.88	90.31	74.00	-16.31	Peak

Remarks:  
 1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 14  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Leo-Li  
 EUT : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM  
 Ready Heavy Duty Radio  
 Power supply : DC 12V  
 Test mode : GFSK 2441MHz Tx  
 M/N : JCV1640BT

	Freq.	Ant.	Cable	Amp.	Reading	Emission	Limits	Margin	Remark
	(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2441.000	28.27	5.86	35.70	95.62	94.05	74.00	-20.05	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 15  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Leo-Li  
 EUT : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM  
 Ready Heavy Duty Radio  
 Power supply : DC 12V  
 Test mode : GFSK 2480MHz Tx  
 M/N : JCV1640BT

	Freq.	Ant.	Cable	Amp.	Reading	Emission	Limits	Margin	Remark
	(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2479.000	28.35	5.91	35.70	94.32	92.88	74.00	-18.88	Peak

Remarks:


1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 16  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23\*C/54% Engineer : Leo-Li  
 EUT : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM  
 Ready Heavy Duty Radio  
 Power supply : DC 12V  
 Test mode : GFSK 2480MHz Tx  
 M/N : JCV1640BT

	Freq.	Ant.	Cable	Amp.	Emission				Remark
	(MHz)	(dB/m)	(dB)	(dB)	Reading	Level	Limits	Margin	
					(dBUV)	(dBUV/m)	(dBUV/m)	(dB)	
1	1600.000	25.62	4.63	36.14	45.79	39.90	74.00	34.10	Peak
2	2479.000	28.35	5.91	35.70	93.28	91.84	74.00	-17.84	Peak

- Remarks:
- Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
  - The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 19  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM  
Ready Heavy Duty Radio  
Power supply : DC 12V  
Test mode : GFSK 2480MHz Tx  
M/N : JCV1640BT



Site no. : 3m Chamber Data no. : 20  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Leo-Li  
 EUT : AM/FM/WX/USB/BT/SXM Car stereo  
 Power supply : DC 12V  
 Test mode : GFSK 2480MHz Tx  
 M/N : JCV1640BT


	Ant. Factor	Cable loss	Amp. Factor	Reading	Emission Level	Limits	Margin	Remark
Freq. (MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1 4960.000	33.13	8.72	35.70	48.75	54.90	74.00	19.10	Peak

Remarks:


- Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
- The emission levels that are 20dB below the official limit are not reported.

Frequency (MHz)	Peak level (dBuV/m)	Duty cycle factor (dB)	AV level (dBuV/m)	Limit(dBuV/m)	Conclusion
4960.000	54.90	9.09	45.81	54	Pass





Site no. : 3m Chamber Data no. : 21  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23\*C/54% Engineer : Leo-Li  
EUT : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM  
Ready Heavy Duty Radio  
Power supply : DC 12V  
Test mode : GFSK 2480MHz Tx  
M/N : JCV1640BT




Site no. : 3m Chamber Data no. : 22  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Leo-Li  
 EUT : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM  
 Ready Heavy Duty Radio  
 Power supply : DC 12V  
 Test mode : GFSK 2480MHz Tx  
 M/N : JCV1640BT

	Ant.	Cable	Amp.	Emission					
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark	
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)		
1 4960.000	33.13	8.72	35.70	49.41	55.56	74.00	18.44	Peak	


Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Frequency (MHz)	Peak level (dBuV/m)	Duty cycle factor (dB)	AV level (dBuV/m)	Limit(dBuv/m)	Conclusion
4960.000	55.56	9.09	46.47	54	Pass



Site no. : 3m Chamber Data no. : 23  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23\*C/54% Engineer : Leo-Li  
EUT : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM  
Ready Heavy Duty Radio  
Power supply : DC 12V  
Test mode : 8-DPSK 2402MHz Tx  
M/N : JCV1640BT




Site no. : 3m Chamber Data no. : 24  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23\*C/54% Engineer : Leo-Li  
 EUT : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM  
 Ready Heavy Duty Radio  
 Power supply : DC 12V  
 Test mode : 8-DPSK 2402MHz Tx  
 M/N : JCV1640BT

	Ant.	Cable	Amp.	Emission					
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark	
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)		
1 4804.000	32.85	8.56	35.70	48.36	54.07	74.00	19.93	Peak	


Remarks:

- Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
- The emission levels that are 20dB below the official limit are not reported.

Frequency (MHz)	Peak level (dBuV/m)	Duty cycle factor (dB)	AV level (dBuV/m)	Limit(dBuv/m)	Conclusion
4804.000	54.07	9.09	44.98	54	Pass



Site no. : 3m Chamber Data no. : 25  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23\*C/54% Engineer : Leo-Li  
EUT : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM  
Ready Heavy Duty Radio  
Power supply : DC 12V  
Test mode : 8-DPSK 2402MHz Tx  
M/N : JCV1640BT




Site no. : 3m Chamber Data no. : 26  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Leo-Li  
 EUT : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM  
 Ready Heavy Duty Radio  
 Power supply : DC 12V  
 Test mode : 8-DPSK 2402MHz Tx  
 M/N : JCV1640BT

	Ant.	Cable	Amp.	Emission					
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark	
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)		
1 4804.000	32.85	8.56	35.70	45.74	51.45	74.00	22.55	Peak	

Remarks:


1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 27  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23\*C/54% Engineer : Leo-Li  
 EUT : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM  
 Ready Heavy Duty Radio  
 Power supply : DC 12V  
 Test mode : 8-DPSK 2402MHz Tx  
 M/N : JCV1640BT

	Freq.	Ant.	Cable	Amp.	Emission				Remark
	(MHz)	Factor	loss	Factor	Reading	Level	Limits	Margin	
		(dB/m)	(dB)	(dB)	(dBUV)	(dBUV/m)	(dBUV/m)	(dB)	
1	1600.000	25.62	4.63	36.14	41.78	35.89	74.00	38.11	Peak
2	2402.000	28.18	5.80	35.70	95.27	93.55	74.00	-19.55	Peak

Remarks:  
 1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 28  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23\*C/54% Engineer : Leo-Li  
 EUT : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM  
 Ready Heavy Duty Radio  
 Power supply : DC 12V  
 Test mode : 8-DPSK 2402MHz Tx  
 M/N : JCV1640BT

	Freq.	Ant.	Cable	Amp.	Emission				Remark
	(MHz)	Factor	loss	Factor	Reading	Level	Limits	Margin	
		(dB/m)	(dB)	(dB)	(dBUV)	(dBUV/m)	(dBUV/m)	(dB)	
1	1600.000	25.62	4.63	36.14	43.05	37.16	74.00	36.84	Peak
2	2402.000	28.18	5.80	35.70	96.38	94.66	74.00	-20.66	Peak


Remarks:

- Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
- The emission levels that are 20dB below the official limit are not reported.





Site no. : 3m Chamber Data no. : 31  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM  
Ready Heavy Duty Radio  
Power supply : DC 12V  
Test mode : 8-DPSK 2441MHz Tx  
M/N : JCV1640BT




Site no. : 3m Chamber Data no. : 32  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23\*C/54% Engineer : Leo-Li  
 EUT : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM  
 Ready Heavy Duty Radio  
 Power supply : DC 12V  
 Test mode : 8-DPSK 2441MHz Tx  
 M/N : JCV1640BT


	Freq.	Ant.	Cable	Amp.	Emission				Remark
	(MHz)	Factor	loss	Factor	Reading	Level	Limits	Margin	
		(dB/m)	(dB)	(dB)	(dBUV)	(dBUV/m)	(dBUV/m)	(dB)	
1	4882.000	32.99	8.64	35.70	46.21	52.14	74.00	21.86	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 33  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23\*C/54% Engineer : Leo-Li  
EUT : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM  
Ready Heavy Duty Radio  
Power supply : DC 12V  
Test mode : 8-DPSK 2441MHz Tx  
M/N : JCV1640BT




Site no. : 3m Chamber Data no. : 34  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23\*C/54% Engineer : Leo-Li  
 EUT : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM  
 Ready Heavy Duty Radio  
 Power supply : DC 12V  
 Test mode : 8-DPSK 2441MHz Tx  
 M/N : JCV1640BT

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4882.000	32.99	8.64	35.70	48.19	54.12	74.00	19.88	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Frequency (MHz)	Peak level (dBuV/m)	Duty cycle factor (dB)	AV level (dBuV/m)	Limit(dBuV/m)	Conclusion
4882.000	54.12	9.09	45.03	54	Pass




Site no. : 3m Chamber Data no. : 35  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Leo-Li  
 EUT : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM  
 Ready Heavy Duty Radio  
 Power supply : DC 12V  
 Test mode : 8-DPSK 2441MHz Tx  
 M/N : JCV1640BT

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	1594.000	25.59	4.62	36.15	41.18	35.24	74.00	38.76	Peak
2	1624.000	25.72	4.67	36.11	42.14	36.42	74.00	37.58	Peak
3	2441.000	28.27	5.86	35.70	94.98	93.41	74.00	-19.41	Peak

Remarks:

- Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
- The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 36  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Leo-Li  
 EUT : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM  
 Ready Heavy Duty Radio  
 Power supply : DC 12V  
 Test mode : 8-DPSK 2441MHz Tx  
 M/N : JCV1640BT

	Freq.	Ant.	Cable	Amp.	Emission				Remark
	(MHz)	Factor	loss	Factor	Reading	Level	Limits	Margin	
		(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2441.000	28.27	5.86	35.70	95.69	94.12	74.00	-20.12	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 37  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Leo-Li  
 EUT : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM  
 Ready Heavy Duty Radio  
 Power supply : DC 12V  
 Test mode : 8-DPSK 2480MHz Tx  
 M/N : JCV1640BT

	Freq.	Ant.	Cable	Amp.	Emission				Remark
	(MHz)	Factor	loss	Factor	Reading	Level	Limits	Margin	
		(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	1594.000	25.59	4.62	36.15	42.29	36.35	74.00	37.65	Peak
2	1654.000	25.85	4.71	36.08	41.57	36.05	74.00	37.95	Peak
3	2480.000	28.36	5.91	35.70	93.15	91.72	74.00	-17.72	Peak

Remarks:

- Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
- The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 38  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Leo-Li  
 EUT : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM  
 Ready Heavy Duty Radio  
 Power supply : DC 12V  
 Test mode : 8-DPSK 2480MHz Tx  
 M/N : JCV1640BT


	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	1066.000	23.64	3.86	36.73	43.90	34.67	74.00	39.33	Peak
2	1594.000	25.59	4.62	36.15	42.37	36.43	74.00	37.57	Peak
3	1654.000	25.85	4.71	36.08	41.90	36.38	74.00	37.62	Peak
4	2480.000	28.36	5.91	35.70	90.66	89.23	74.00	-15.23	Peak

Remarks:  
 1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.





Site no. : 3m Chamber Data no. : 41  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM  
Ready Heavy Duty Radio  
Power supply : DC 12V  
Test mode : 8-DPSK 2480MHz Tx  
M/N : JCV1640BT




Site no. : 3m Chamber Data no. : 42  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23\*C/54% Engineer : Leo-Li  
 EUT : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM  
 Ready Heavy Duty Radio  
 Power supply : DC 12V  
 Test mode : 8-DPSK 2480MHz Tx  
 M/N : JCV1640BT


	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	4960.000	33.13	8.72	35.70	45.79	51.94	74.00	22.06	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 43  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM  
Ready Heavy Duty Radio  
Power supply : DC 12V  
Test mode : 8-DPSK 2480MHz Tx  
M/N : JCV1640BT



Site no. : 3m Chamber Data no. : 44  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23\*C/54% Engineer : Leo-Li  
 EUT : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM  
 Ready Heavy Duty Radio  
 Power supply : DC 12V  
 Test mode : 8-DPSK 2480MHz Tx  
 M/N : JCV1640BT

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	4960.000	33.13	8.72	35.70	44.72	50.87	74.00	23.13	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

## 4. CONDUCTED SPURIOUS EMISSIONS

### 4.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analyzer	Agilent	N9030A	MY51380221	Oct.31, 13	1Year
2.	Attenuator	Agilent	8491B	MY39262165	May.08,13	1 Year
3.	RF Cable	Hubersuhner	SUCOFLEX102	28618/2	May.08,13	1Year

### 4.2. Limit

In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.



### 4.3. Test Procedure


The transmitter output was connected to a spectrum analyzer, The resolution bandwidth is set to 100 kHz, The video bandwidth is set to 300 kHz and measure all the emissions detected.

### 4.4. Test result



**PASS** (The testing data was attached in the next pages.)

**Hopping Off  
GFSK  
2402MHz**







2441MHz










2480MHz











**8-DPSK**  
2402MHz












2441MHz







2480MHz









### Hopping On GFSK



### 8-DPSK



## 5. CARRIER FREQUENCY SEPARATION TEST

### 5.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Spectrum Analyzer	Agilent	N9030A	MY51380221	Oct.31, 13	1Year

### 5.2. Limit

Frequency hopping systems shall have hopping channel carrier frequency separated by a minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

### 5.3. Test Results.

EUT:AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM Ready Heavy Duty Radio		
M/N: JCV1640BT		
Test date: 2013-12-21	Pressure: 101.2±1.0 kpa	Humidity: 51.7±3.0%
Tested by: Leo-Li	Test site: RF Site	Temperature: 20.4±0.6°C
Test Mode	Channel separation	Conclusion
8-DPSK	1.0MHz	PASS
GFSK	1.0MHz	PASS



## 6. 20 DB BANDWIDTH TEST

### 6.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analyzer	Agilent	N9030A	MY51380221	Oct.31, 13	1Year

### 6.2. Limit

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

### 6.3. Test Results

EUT: AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM Ready Heavy Duty Radio		
M/N: JCV1640BT		
Test date: 2013-12-21	Pressure: 101.2±1.0 kpa	Humidity: 51.7±3.0%
Tested by: Leo-Li	Test site: RF Site	Temperature: 20.4±0.6°C

Cable loss: 1 dB		Attenuator loss: 20 dB	
Test Mode	CH (MHz)	20dB bandwidth (KHz)	Limit (KHz)
GFSK	2402	841.9	N/A
	2441	829.2	N/A
	2480	837.2	N/A
8-DPSK	2402	1207	N/A
	2441	1204	N/A
	2480	1203	N/A
Conclusion : PASS			

**GFSK**

Test Frequency: 2402MHz



Test Frequency: 2441MHz



Test Frequency: 2480MHz



8-DPSK

Test Frequency: 2402MHz



Test Frequency: 2441MHz



Test Frequency: 2480MHz





## 7. NUMBER OF HOPPING FREQUENCY TEST

### 7.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Spectrum Analyzer	Agilent	N9030A	MY51380221	Oct.31, 13	1Year



### 7.2. Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels

### 7.3. Test Results

EUT: AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM Ready Heavy Duty Radio		
M/N: JCV1640BT		
Test date: 2013-12-21	Pressure: 101.2±1.0 kpa	Humidity: 51.7±3.0%
Tested by: Leo-Li	Test site: RF Site	Temperature: 20.4±0.6°C

Test Mode	Number of channel	Limit	Conclusion
8-DPSK	79	≥15	PASS
GFSK	79	≥15	PASS



## 8. DWELL TIME

### 8.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Spectrum Analyzer	Agilent	N9030A	MY51380221	Oct.31, 13	1Year

### 8.2. Limit

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.



### 8.3. Test Results

EUT:AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM Ready Heavy Duty Radio		
M/N: JCV1640BT		
Test date: 2013-12-21	Pressure: 101.2±1.0 kpa	Humidity: 51.7±3.0%
Tested by: Leo-Li	Test site: RF Site	Temperature: 20.4±0.6°C



Mode		dwll time	Limit	Conclusion
GFSK	DH1	$50\text{hops}/5\text{s} \times 0.4 \times 79\text{chanel} \times 0.443\text{ms} = 139.99\text{ms}$	<400ms	PASS
	DH3	$26\text{hops}/5\text{s} \times 0.4 \times 79\text{chanel} \times 1.695\text{ms} = 267.81\text{ms}$	<400ms	PASS
	DH5	$17\text{hops}/5\text{s} \times 0.4 \times 79\text{chanel} \times 2.950\text{ms} = 316.95\text{ms}$	<400ms	PASS
8-DPSK	DH1	$51\text{hops}/5\text{s} \times 0.4 \times 79\text{chanel} \times 0.451\text{ms} = 145.37\text{ms}$	<400ms	PASS
	DH3	$25\text{hops}/5\text{s} \times 0.4 \times 79\text{chanel} \times 1.704\text{ms} = 269.23\text{ms}$	<400ms	PASS
	DH5	$17\text{hops}/5\text{s} \times 0.4 \times 79\text{chanel} \times 2.955\text{ms} = 317.49\text{ms}$	<400ms	PASS

Note: All the lower levels were signal from receiver's, and should not considered in here.

**GFSK**  
**DH 1**





DH 3






### 8-DPSK

DH 1





DH 3





DH 5



## 9. MAXIMUM PEAK OUTPUT POWER TEST

### 9.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analyzer	Agilent	N9030A	MY51380221	Oct.31, 13	1 Year
2.	Amp	HP	8449B	3008A02495	May.08, 13	1 Year
3.	Horn Antenna	EMCO	3115	9510-4580	May.28, 13	1 Year
4.	HF Cable	Hubersuhne	Sucoflex104	-	May.08, 13	1 Year
5	Power Meter	Anritsu	ML2487A	6K00002472	May.08, 13	1 Year
6	Power Sensor	Anritsu	MA2491A	033005	May.08, 13	1 Year

### 9.2. Limit

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

### 9.3. Test Procedure

1. Connected the EUT's antenna port to spectrum analyzer.
2. Set the RBW> Bandwidth of test Frequency and put the test Frequency, Set the Span large enough to capture the entire signal
3. Use a peak detector on max hold
4. Reading the value from the Spectrum analyzer

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

### 9.4. Test Results

EUT: AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM Ready Heavy Duty Radio			
M/N: JCV1640BT			
Test date: 2013-12-21		Pressure: 101.2±1.0 kpa	Humidity: 52.7±1.0%
Tested by: Leo-Li		Test site: RF site	Temperature: 20.4±1.0 °C
Cable loss: 1 dB		Attenuator loss: 10 dB	
Test Mode	CH (MHz)	Peak output Power (dBm)	Limit (dBm)
GFSK	2402	4.698	30
	2441	4.193	30
	2480	3.753	30
8-DPSK	2402	3.982	30
	2441	3.386	30
	2480	2.822	30
Conclusion: PASS			

**GFSK**  
2402MHz



2441MHz




### 2480MHz



### 8-DPSK

### 2402MHz



2441MHz



2480MHz



## 10. BAND EDGE COMPLIANCE TEST

### 10.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analyzer	Agilent	N9030A	MY51380221	Oct.31, 13	1 Year
2.	Amp	HP	8449B	3008A02495	May.08, 13	1 Year
3.	Horn Antenna	EMCO	3115	9510-4580	May.28, 13	1 Year
4.	HF Cable	Hubersuhne	Sucoflex104	-	May.08, 13	1 Year

### 10.2. Limit

All the lower and upper band-edges emissions appearing within 2310MHz to 2390MHz and 2483.5MHz to 2500MHz restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

### 10.3. Test Produce

For upper band emissions that are up to two bandwidths(2MHz) away (2483.5MHz to 2485.5MHz) from the band-edge use below produce:

1. Choose a spectrum analyzer span that encompasses both the peak of the fundamental emission and the band-edge emission under investigation. Set the analyzer RBW to 100KHz and with a video bandwidth 300KHz. Record the peak levels of the fundamental emission and the relevant band-edge emission, Observe the stored trace and measure the amplitude delta between the peak of the fundamental and the peak of the band-edge emission. This is not a field strength measurement, it is only a relative measurement to determine the amount by which the emission drops at the band edge relative to the highest fundamental emission level.
2. Subtract the delta measured in step (1) from the maximum field strengths measured in clause 4 .The resultant field strengths are then used to determine band-edge compliance as required by Section 15.205


For emissions above two bandwidths away from the band-edge use below produce:

1. The EUT is placed on a turntable, which is 0.8m above the ground plane and worked at highest radiated power.
2. The turntable was rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upperband-edges of the emission:
  - (a) PEAK: RBW=1MHz ;VBW=3MHz, PK detector, Sweep=AUTO
  - (b) This is pulse Modulation device a duty cycle factor was used to calculate average level based measured peak level.

### 10.4. Test Results

Pass (The testing data was attached in the next pages.)

Note: If the PK measured levels comply with average limit, then the average level were deemed to comply with average limit.




Site no. : 3m Chamber Data no. : 3  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Leo-Li  
 EUT : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM  
 Ready Heavy Duty Radio  
 Power supply : DC 12V  
 Test mode : GFSK 2402MHz Tx  
 M/N : JCV1640BT

	Ant.	Cable	Amp.	Emission					
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark	
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)		
1	28.09	5.74	35.70	45.80	43.93	74.00	30.07	Peak	
2	28.16	5.78	35.70	43.84	42.08	74.00	31.92	Peak	
3	28.18	5.80	35.70	60.15	58.43	74.00	15.57	Peak	
4	28.18	5.80	35.70	98.07	96.35	74.00	-22.35	Peak	

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.






Site no. : 3m Chamber Data no. : 4  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Leo-Li  
 EUT : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM  
 Ready Heavy Duty Radio  
 Power supply : DC 12V  
 Test mode : GFSK 2402MHz Tx  
 M/N : JCV1640BT

	Freq.	Ant. Factor	Cable loss	Amp. Factor	Reading	Emission Level	Limits	Margin	Remark
	(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2327.385	28.02	5.69	35.70	45.68	43.69	74.00	30.31	Peak
2	2390.000	28.16	5.78	35.70	42.99	41.23	74.00	32.77	Peak
3	2400.000	28.18	5.80	35.70	56.29	54.57	74.00	19.43	Peak
4	2402.150	28.18	5.80	35.70	94.32	92.60	74.00	-18.60	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 17  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Leo-Li  
 EUT : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM  
 Ready Heavy Duty Radio  
 Power supply : DC 12V  
 Test mode : GFSK 2480MHz Tx  
 M/N : JCV1640BT

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.805	28.36	5.91	35.70	93.63	92.20	74.00	-18.20	Peak
2	2483.500	28.36	5.92	35.70	43.99	42.57	74.00	31.43	Peak
3	2495.810	28.39	5.94	35.70	45.02	43.65	74.00	30.35	Peak
4	2500.000	28.40	5.94	35.70	44.51	43.15	74.00	30.85	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 18  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Leo-Li  
 EUT : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM  
 Ready Heavy Duty Radio  
 Power supply : DC 12V  
 Test mode : GFSK 2480MHz Tx  
 M/N : JCV1640BT

	Freq.	Ant.	Cable	Amp.	Emission				
	(MHz)	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
		(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2479.805	28.36	5.91	35.70	94.99	93.56	74.00	-19.56	Peak
2	2483.500	28.36	5.92	35.70	44.09	42.67	74.00	31.33	Peak
3	2498.879	28.40	5.94	35.70	45.68	44.32	74.00	29.68	Peak
4	2500.000	28.40	5.94	35.70	42.92	41.56	74.00	32.44	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 29  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Leo-Li  
 EUT : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM  
 Ready Heavy Duty Radio  
 Power supply : DC 12V  
 Test mode : 8-DPSK 2402MHz Tx  
 M/N : JCV1640BT

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2323.110	28.01	5.69	35.70	47.05	45.05	74.00	28.95	Peak
2	2390.000	28.16	5.78	35.70	45.10	43.34	74.00	30.66	Peak
3	2400.000	28.18	5.80	35.70	62.75	61.03	74.00	12.97	Peak
4	2401.960	28.18	5.80	35.70	95.96	94.24	74.00	-20.24	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 30  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Leo-Li  
 EUT : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM  
 Ready Heavy Duty Radio  
 Power supply : DC 12V  
 Test mode : 8-DPSK 2402MHz Tx  
 M/N : JCV1640BT

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2323.015	28.01	5.68	35.70	46.86	44.85	74.00	29.15	Peak
2	2390.000	28.16	5.78	35.70	45.23	43.47	74.00	30.53	Peak
3	2400.000	28.18	5.80	35.70	64.75	63.03	74.00	10.97	Peak
4	2401.960	28.18	5.80	35.70	96.33	94.61	74.00	-20.61	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 39  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Leo-Li  
 EUT : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM  
 Ready Heavy Duty Radio  
 Power supply : DC 12V  
 Test mode : 8-DPSK 2480MHz Tx  
 M/N : JCV1640BT

	Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.871	28.36	5.91	35.70	90.25	88.82	74.00	-14.82	Peak
2	2483.500	28.36	5.92	35.70	43.78	42.36	74.00	31.64	Peak
3	2496.404	28.39	5.94	35.70	47.06	45.69	74.00	28.31	Peak
4	2500.000	28.40	5.94	35.70	43.74	42.38	74.00	31.62	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 40  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Leo-Li  
 EUT : AM/FM/RBDS/WB/USB/AUX-IN/BT/iPod Ready/Sirius XM  
 Ready Heavy Duty Radio  
 Power supply : DC 12V  
 Test mode : 8-DPSK 2480MHz Tx  
 M/N : JCV1640BT

	Freq.	Ant.	Cable	Amp.	Emission				
	(MHz)	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
		(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2480.036	28.36	5.91	35.70	93.81	92.38	74.00	-18.38	Peak
2	2483.500	28.36	5.92	35.70	46.05	44.63	74.00	29.37	Peak
3	2492.180	28.38	5.93	35.70	46.46	45.07	74.00	28.93	Peak
4	2500.000	28.40	5.94	35.70	44.20	42.84	74.00	31.16	Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

## 11.DEVIATION TO TEST SPECIFICATIONS

[NONE]