



## TEST REPORT

### Nr. R21115501

### Federal Communication Commission (FCC)

<b>Report Reference No.</b> .....	R21115501
Date of issue: .....	15.11.2021
Total number pages: .....	60
<b>Applicant's name</b> .....	Autec S.r.l.
Address .....	Via Pomaroli, 65 – 36030 Caldogno (VI) – Italy
<b>Test specification:</b>	
Standards .....	FCC Rules & Regulations, Title 47:2020 Part 15 paragraph(s): 203, 204, 205, 207, 209, 215 and 247
Non-standard test method .....	N/A
<b>Test Report Form No.</b> .....	15-247_HoppingCMC
Test Report Form(s) Originator ..	CMC Centro Misure Compatibilità S.r.l.
Master TRF .....	2021-07
<b>General disclaimer:</b>	
The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of CMC Centro Misure Compatibilità S.r.l.	
<b>Test item description</b> .....	Transceiver unit
Trademark .....	Autec
Manufacturer .....	Autec S.r.l.
Model / Type reference .....	Model SK8 Type NA5QH
FCC ID .....	OQA-SK8NA5QH
Rating(s) .....	7,4 Vdc from battery
<b>Report</b>	
Tested by (name + signature) .....	G. Gandini 
Approved by (name + signature) .....	R. Beghetto 

## 1 Summary

1	Summary.....	2
2	Reference standard .....	3
3	List of attachments.....	3
4	Deviation(s) from test specification.....	3
5	Testing location.....	3
6	General description of tested item and testing condition(s) .....	5
6.1	Photos of the test item.....	6
7	Verdict summary section .....	9
8	Test conditions.....	11
8.1	General.....	11
9	Test results .....	12
9.1	Antenna requirements .....	12
9.2	Emissions in restricted frequency bands and in unrestricted frequency bands .....	13
9.3	20 dB bandwidth.....	33
9.4	Channel separation.....	36
9.5	Number of hopping channels.....	39
9.6	Time of occupancy.....	44
9.7	Band edge .....	47
9.8	Peak Output Power.....	53

<b>2 Reference standard</b>	
FCC Rules and Regulation Title 47 part 15:2020	--
<b>3 List of attachments</b>	
Attachment 1: Instruments list, measurement uncertainty, judgement of compliance and quality manual references	
<b>4 Deviation(s) from test specification</b>	
None	
<b>5 Testing location</b>	
CMC Centro Misure Compatibilità S.r.l. Via della Fisica, 20 – 36016 Thiene (VI) – Italy Test site facility's FCC registration number: 182474	

<i>Revision index</i>	<i>Date</i>	<i>Change history</i>
1.0	15.11.2021	--

<b>Testing and sampling:</b>	
Date of receipt of test item .....	11.05.2021
Testing start date .....	18.06.2021
Testing end date .....	28.10.2021
Sampling procedure.....	Equipment used for testing was picked up by the manufacturer, at the end of the production process with random criterion.  The results relate to the sample as it has been received.
Internal identification.....	Adhesive label with the product number P210564
<b>General remarks:</b>	
<p>This report shall not be reproduced, except in full, without the written approval of CMC.            The test results presented in this report relate only to the object tested.            "(see appended table)": refers to a table appended to the report.            Throughout this report a comma is used as the decimal separator.</p>	
<b>Possible test case verdicts:</b>	
Test case does not apply to the test object:	N/A (Not Applicable)
Test object does meet the requirement:	P (Pass)
Test object does not meet the requirement:	F (Fail)
Test object does not performed:	N/E (Not Executed)
<b>Definition of symbols used in this test report:</b>	
<input checked="" type="checkbox"/> Indicates that the listed condition, standard or equipment is applicable for this report. <input type="checkbox"/> Indicates that the listed condition, standard or equipment is not applicable for this report.	




**6 General description of tested item and testing condition(s)**

Description .....	Transceiver unit						
Model Number .....	Model SK8 Type NA5QH						
FCC ID .....	OQA-SK8NA5QH						
Serial Number .....	--						
Brand name .....	Autec						
Frequency band .....	902 – 928 MHz						
Nominal frequencies .....	FL: 915,05 MHz	FM: 921,40 MHz			FH: 927,80 MHz		
Test power supply .....	Voltage and Frequency		Reference poles				
			N	L1	L2	L3	PE
	<input type="checkbox"/>	AC:	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
	<input type="checkbox"/>	AC:	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input checked="" type="checkbox"/>	DC: 7,4 V from battery					<input type="checkbox"/>	
Pseudo randomly ordered list of hopping frequencies .....	See document sk8_na5qh_operational_description-rev1						
Test configuration .....	<input type="checkbox"/>	Table top equipment					
	<input type="checkbox"/>	Floor standing equipment					
	<input checked="" type="checkbox"/>	Hand-held equipment					
Type of equipment .....	<input checked="" type="checkbox"/>	Transmitter unit					
	<input checked="" type="checkbox"/>	Receiver unit					
Type of station .....	<input checked="" type="checkbox"/>	Portable station					
	<input type="checkbox"/>	Mobile station					
Operating modes .....	No.	Operating mode of test item					
	1	EUT in continuous transmission at maximum power					
Accessories (not part of the test item) .....	Accessory		Type		Manufacturer		
	Transceiver unit		RTR		Autec		




6.1 Photos of the test item













**7 Verdict summary section**

<b>FCC Rules &amp; Regulations, Title 47:2020</b>			
<b>Part 15 paragraph(s): 203, 204, 205, 207, 209, 215 and 247</b>			
<b>Clause</b>	<b>Requirement – Test case</b>	<b>Basic standard</b>	<b>Verdict</b>
Part 15.247 (a) (1)	Pseudo randomly ordered list of hopping frequencies	--	<b>P</b>
Part 15.203	Antenna requirements	ANSI C63.10	<b>P</b>
Part 15.207	Conducted emissions	ANSI C63.10	<b>N/A (+)</b>
Part 15.209	Radiated emissions and spurious emission	ANSI C63.10	<b>P</b>
Part 15.247	20 dB Bandwidth	ANSI C63.10	<b>P</b>
Part 15.247	Channel Separation	ANSI C63.10	<b>P</b>
Part 15.247	Number of Hopping Channel	ANSI C63.10	<b>P</b>
Part 15.247	Time of occupancy	ANSI C63.10	<b>P</b>
Part 15.247	Band edge	ANSI C63.10	<b>P</b>
Part 15.209 and 15.247	Peak Output Power	ANSI C63.10	<b>P</b>

(+) Devices which only employ battery power. See FCC Part 15.207 (c)

<b>Normative references</b>	
<b>Reference no.</b>	<b>Description</b>
FCC Rules and Regulation Title 47 part 15:2020	--
KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices operating under section 15.247 of the FCC rules
ANSI C63.4:2014	American National Standard for Methods of Measuring of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz – 40 GHz
ANSI C63.10:2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

## 8 Test conditions

### 8.1 General

Environmental reference conditions.....:	The climatic conditions during the tests are within the limits specified by the manufacturer for the operation of the EUT and the test equipment. The climatic conditions during the tests were within the following limits:		
	<b>Temperature</b>	<b>Humidity</b>	<b>Atmospheric pressure</b>
	15 °C – 35 °C	30 % - 60 %	800 hPa – 1060 hPa
	If explicitly required in the basic standard or applied product standard the climatic values are recorded and documented separately in this test report.		
Measurement uncertainties .....	Attachment 1		

## 9 Test results

### 9.1 Antenna requirements

Tested by .....	G. Gandini	
Test date .....	18.06.2021	
Reference standards .....	FCC Rules and Regulation; Titles 47 Part. 15.203 and 15.204	
Test specification .....	<p>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§ 15.211, 15.213, 15.217, 15.219, 15.221, or § 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded</p>	
Antenna type.....	<input checked="" type="checkbox"/>	Integral antenna
	<input type="checkbox"/>	External antenna
Antenna gain.....	≤ 2 dBi	
External R.F. power amplifier .....	Not Present	



## 9.2 Emissions in restricted frequency bands and in unrestricted frequency bands

Tested by .....	G. Gandini	
Test date .....	18.06.2021	
Test location (stand) .....	Semi-anechoic chamber (CMC A070)	
Reference standards .....	FCC Rules and Regulation; Titles 47 Part. 15.209 ANSI C63.10 cl. 6.3, 6.4, 6.5 and 6.6	
Test set-up description .....	<input checked="" type="checkbox"/>	Table top equipment set-up (80 cm above the reference ground plane)
	<input type="checkbox"/>	Floor standing equipment set-up (insulating material up to 12 mm thick)
	<input type="checkbox"/>	False floor installation equipment set-up (insulating material up to 34 cm above the reference ground plane)
Supplementary test set-up description .....	--	
Test method applied .....	SAC with measurement distance [m]: 10 m at frequencies $\leq$ 1 GHz 3 m at frequencies $>$ 1 GHz	
Supplementary information .....	--	

### Acceptance limits

<b>Acceptance limits for emissions in restricted frequency bands (<math>f &lt; 1000</math> MHz)</b>		
Frequency range (MHz)	Test distance (m)	Limits [dB( $\mu$ V/m)]
0,009 to 0,490	300	48,5 to 13,8
0,490 to 1,705	30	33,8 to 22,9
1,705 to 30	30	29,5
30 to 88	3	40
88 to 216	3	43,5
216 to 960	3	46,0
960 to 1000	3	54

**Remarks:** The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz and 110–490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector. The results have been extrapolated to the specified distance using an extrapolation factor

<b>Acceptance limits for emissions in restricted frequency bands (<math>f \geq 1000</math> MHz)</b>			
Frequency (MHz)	Test distance (m)	AV limits [dB( $\mu$ V/m)]	Peak limits [dB( $\mu$ V/m)]
$> 1000$	3	54	74


The restricted frequency bands are listed in the following table

<i>MHz</i>	<i>MHz</i>	<i>MHz</i>	<i>GHz</i>
0,090 – 0,110	16,42 – 16,423	399,9 – 410	4,5 – 5,15
0,495 – 0,505	16,69475 – 16,69525	608 – 614	5,35 – 5,46
2,1735 – 2,1905	16,80425 – 16,80475	960 – 1240	7,25 – 7,75
4,125 – 4,128	25,5 – 25,67	1300 – 1427	8,025 – 8,5
4,17725 – 4,17775	37,5 – 38,25	1435 – 1626,5	9,0 – 9,2
4,20725 – 4,20775	73 – 74,6	1645,5 – 1646,5	9,3 – 9,5
6,215 – 6,218	74,8 – 75,2	1660 – 1710	10,6 – 12,7
6,26775 – 6,26825	108 – 121,94	1718,8 – 1722,2	13,25 – 13,4
6,31175 – 6,31225	123 – 138	2200 – 2300	14,47 – 14,5
8,291 – 8,294	149,9 – 150,05	2310 – 2390	15,35 – 16,2
8,362 – 8,366	156,52475 – 156,52525	2483,5 – 2500	17,7 – 21,4
8,37625 – 8,38675	156,7 – 156,9	2690 – 2900	22,01 – 23,12
8,41425 – 8,41475	162,0125 – 167,17	3260 – 3267	23,6 – 24,0
12,29 – 12,293	167,72 – 173,2	3332 – 3339	31,2 – 31,8
12,51975 – 12,52025	240 – 285	3345,8 – 3358	36,43 – 36,5
12,57675 – 12,57725	322 – 335,4	3600 – 4400	Above 38,6
13,36 – 13,41			

**Acceptance limits for emissions in non-restricted frequency bands**


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

**Test setup**



*Test setup PE004\_01*

Nr.	Id. Number	Manufacturer	Model	Description
2	CMC S353	Rohde & Schwarz	ESW26	EMI Test Receiver 1 Hz - 26.5 GHz
1	CMC S127	Schaffner	HLA6120	Loop Antenna 9kHz - 30MHz




*Test setup PE004\_02*

Nr.	Id. Number	Manufacturer	Model	Description
2	CMC S353	Rohde & Schwarz	ESW26	EMI Test Receiver 1 Hz - 26.5 GHz
1	CMC S271	Schwarzbeck	BBA 9106 + VHBB 9124	Broadband Antenna

*Test setup PE004\_03*

Nr.	Id. Number	Manufacturer	Model	Description
2	CMC S353	Rohde & Schwarz	ESW26	EMI Test Receiver 1 Hz - 26.5 GHz
1	CMC S287	Schwarzbeck	VUSLP 9111B	Broadband Antenna

Frequency > 1 GHz



Test setup PE004\_04

Nr.	Id. Number	Manufacturer	Model	Description
4	CMC S353	Rohde & Schwarz	ESW26	EMI Test Receiver 1 Hz - 26.5 GHz
3	CMC S108	Emco	3115	Waveguide antenna

Test setup PE004\_05

Nr.	Id. Number	Manufacturer	Model	Description
4	CMC S353	Rohde & Schwarz	ESW26	EMI Test Receiver 1 Hz - 26.5 GHz
3	CMC S290	Schwarzbeck	BBHA 9170	Horn Antenna (15-40 GHz)



**Result**

<i>Transmission channel (MHz)</i>	<i>Polarization</i>	<i>Frequency Range (MHz)</i>	<i>Graphs</i>	<i>Result</i>
Worst case	V	30 – 300	G21115501	P
Worst case	H	30 – 300	G21115502	P
915,05	V	1000 – 10000	G21115503	P
915,05	H	1000 – 10000	G21115504	P
921,40	H	1000 – 10000	G21115505	P
921,40	V	1000 – 10000	G21115506	P
927,80	V	1000 – 10000	G21115507	P
927,80	H	1000 – 10000	G21115508	P
927,80	H	300 – 1000	G21115509	P
927,80	V	300 – 1000	G21115510	P
921,40	V	300 – 1000	G21115511	P
921,40	H	300 – 1000	G21115512	P
915,05	H	300 – 1000	G21115513	P
915,05	V	300 – 1000	G21115514	P
Worst case	Loop	0,009 – 30	G21115515	P

**Remarks:** EUT was tested in 3 orthogonal planes, graphs are related to the highest detected levels. Measurements at frequencies lower than 30 MHz have been performed with an EUT – antenna distance of 10 m. Measured values have been corrected with conversion factor  $40\log(\text{test distance}/10)$  based on the measuring distance provided by the standard.

Measurements at frequencies higher than 30 MHz and lower than 1000 MHz have been performed with an EUT – antenna distance of 10 m. Measured values have been corrected with conversion factor  $20\log(\text{test distance}/10)$  based on the measuring distance provided by the standard.


Peaks above the limits are caused by the nominal transmitting frequencies

**Graphs Legend**

PK: Peak; QP [1s] (quasi-peak at 1 second) values are marked with a +  
 AV: Average; AV [1s] (average at 1 second) values are marked with a X

## Graphs

Gandini 21115501




### FINAL RESULT TABLE

QUASI PEAK		
Freq Hz	Lev dBuV/m	Margin dB
31480000	+18,25	-21,75
49240000	+14,36	-25,64
90920000	+15,47	-28,05
137680000	+15,12	-28,40
193440000	+17,95	-25,57
299360000	+23,78	-22,24

21115501\_2

Gandini 21115502




FINAL RESULT TABLE

QUASI PEAK		
Freq Hz	Lev dBuV/m	Margin dB
32200000	+18,23	-21,77
44240000	+15,52	-24,48
89800000	+13,16	-30,36
134720000	+15,04	-28,48
195560000	+17,96	-25,56
296400000	+23,87	-22,15

21115502\_2

Gandini 21115503




**FINAL RESULT TABLE**

MAX PEAK			AVERAGE		
Freq Hz	Lev dBuV/m	Margin dB	Freq Hz	Lev dBuV/m	Margin dB
1015000000	+38,19	-35,79	1236750000	+24,45	-29,53
1830000000	+45,42	-28,56	1830000000	+37,17	-16,81
2745250000	+42,92	-31,06	2745250000	+32,46	-21,52
3376500000	+44,38	-29,60	3259750000	+29,97	-24,01
3884000000	+45,75	-28,23	3660250000	+31,83	-22,15
4683500000	+45,61	-28,37	4575250000	+31,58	-22,40
5268500000	+47,51	-26,47	5490250000	+33,51	-20,47
6484250000	+47,27	-26,71	6405250000	+34,65	-19,33
7209500000	+50,99	-22,99	7320500000	+36,34	-17,64
9853000000	+53,67	-20,31	9993500000	+39,41	-14,57

21115503\_2



Gandini 21115504




**FINAL RESULT TABLE**

MAX PEAK			AVERAGE		
Freq Hz	Lev dBuV/m	Margin dB	Freq Hz	Lev dBuV/m	Margin dB
1238000000	+38,85	-35,13	1237000000	+24,47	-29,51
1830000000	+43,08	-30,90	1830000000	+36,22	-17,76
2745250000	+43,48	-30,50	2745250000	+32,67	-21,31
2999750000	+43,85	-30,13	2999750000	+30,02	-23,96
3922250000	+46,24	-27,74	3976750000	+31,72	-22,26
5197250000	+47,52	-26,46	4999750000	+33,20	-20,78
5585000000	+47,38	-26,60	5490250000	+33,14	-20,84
6403250000	+47,75	-26,23	6405250000	+34,02	-19,96
7380250000	+51,45	-22,53	7320500000	+36,19	-17,79
9875500000	+53,98	-20,00	9993000000	+39,42	-14,56

21115504\_2

Gandini 21115505




**FINAL RESULT TABLE**

MAX PEAK			AVERAGE		
Freq Hz	Lev dBuV/m	Margin dB	Freq Hz	Lev dBuV/m	Margin dB
1193000000	+38,86	-35,12	1237000000	+24,51	-29,47
1842750000	+42,14	-31,84	1842750000	+34,18	-19,80
2764250000	+43,46	-30,52	2764250000	+33,05	-20,93
2998500000	+44,40	-29,58	2998250000	+30,10	-23,88
3881500000	+46,07	-27,91	3977000000	+31,72	-22,26
4639750000	+45,57	-28,41	4607000000	+32,05	-21,93
5501250000	+47,20	-26,78	5528500000	+33,73	-20,25
7380750000	+50,52	-23,46	7371250000	+36,18	-17,80
9993750000	+54,38	-19,60	9996250000	+39,37	-14,61

21115505\_2

Gandini 21115506




**FINAL RESULT TABLE**

MAX PEAK			AVERAGE		
Freq Hz	Lev dBuV/m	Margin dB	Freq Hz	Lev dBuV/m	Margin dB
1238000000	+38,59	-35,39	1237000000	+24,49	-29,49
1842750000	+43,55	-30,43	1842750000	+34,50	-19,48
2764250000	+42,29	-31,69	2764250000	+31,41	-22,57
2999500000	+43,78	-30,20	2998500000	+30,05	-23,93
3976750000	+46,10	-27,88	3977000000	+31,72	-22,26
4607750000	+45,22	-28,76	4607000000	+31,87	-22,11
4999750000	+46,89	-27,09	4999750000	+33,19	-20,79
5646000000	+47,48	-26,50	5528500000	+34,60	-19,38
7490000000	+50,34	-23,64	7371250000	+36,36	-17,62
9887500000	+53,91	-20,07	9214000000	+39,89	-14,09

21115506\_2

Gandini 21115507




**FINAL RESULT TABLE**

MAX PEAK			AVERAGE		
Freq Hz	Lev dBuV/m	Margin dB	Freq Hz	Lev dBuV/m	Margin dB
1247000000	+38,89	-35,09	1237250000	+24,50	-29,48
1855500000	+42,35	-31,63	1855500000	+34,15	-19,83
2783500000	+42,67	-31,31	2783500000	+30,96	-23,02
2998750000	+44,11	-29,87	2999000000	+30,07	-23,91
3942000000	+46,60	-27,38	3976750000	+31,75	-22,23
4998750000	+46,95	-27,03	4999750000	+33,22	-20,76
6479000000	+47,95	-26,03	6494500000	+33,51	-20,47
7261750000	+51,14	-22,84	7422500000	+37,48	-16,50
9827750000	+54,36	-19,62	9278000000	+40,78	-13,20

21115507\_2

Gandini 21115508




**FINAL RESULT TABLE**

MAX PEAK			AVERAGE		
Freq Hz	Lev dBuV/m	Margin dB	Freq Hz	Lev dBuV/m	Margin dB
1098750000	+38,27	-35,71	1236750000	+24,46	-29,52
1855750000	+41,86	-32,12	1855500000	+33,89	-20,09
2783250000	+43,57	-30,41	2783500000	+32,59	-21,39
2998500000	+43,33	-30,65	2998500000	+30,07	-23,91
3670250000	+45,27	-28,71	3711250000	+31,54	-22,44
4094750000	+45,11	-28,87	3977000000	+31,72	-22,26
5271500000	+47,23	-26,75	5566750000	+34,65	-19,33
7408000000	+50,16	-23,82	7422500000	+36,34	-17,64
9748000000	+53,48	-20,50	9993750000	+39,39	-14,59

21115508\_2



Gandini 21115509




FINAL RESULT TABLE

QUASI PEAK		
Freq Hz	Lev dBuV/m	Margin dB
336870000	+19,30	-26,70
377430000	+20,39	-25,61
444420000	+22,19	-23,81
527040000	+23,31	-22,69
624330000	+25,66	-20,34
783420000	+25,82	-20,18
867780000	+28,16	-17,84
900000000	+29,14	-16,86
922200000	+40,01	-5,99
933390000	+40,10	-5,90
957570000	+28,94	-17,06

21115509\_2



Gandini 21115510




FINAL RESULT TABLE

QUASI PEAK		
Freq Hz	Lev dBuV/m	Margin dB
337050000	+19,19	-26,81
363120000	+19,95	-26,05
429420000	+21,75	-24,25
476850000	+22,45	-23,55
523200000	+23,63	-22,37
626250000	+25,82	-20,18
750570000	+25,67	-20,33
878130000	+28,15	-17,85
900030000	+29,82	-16,18
922200000	+38,27	-7,73
933420000	+37,19	-8,81
942480000	+28,70	-17,30
955380000	+28,70	-17,30

21115510\_2

Gandini 21115511




FINAL RESULT TABLE

QUASI PEAK		
Freq Hz	Lev dBuV/m	Margin dB
337800000	+19,41	-26,59
381060000	+20,56	-25,44
415980000	+21,70	-24,30
481320000	+22,67	-23,33
541020000	+23,24	-22,76
616620000	+25,68	-20,32
623460000	+25,55	-20,45
774060000	+26,22	-19,78
853740000	+28,01	-17,99
885090000	+28,31	-17,69
910800000	+29,81	-16,19
939840000	+30,69	-15,31
955740000	+28,67	-17,33

21115511\_2

Gandini 21115512




FINAL RESULT TABLE

QUASI PEAK		
Freq Hz	Lev dBuV/m	Margin dB
332640000	+19,18	-26,82
374430000	+20,43	-25,57
430440000	+21,74	-24,26
484980000	+22,81	-23,19
530280000	+23,35	-22,65
599040000	+25,72	-20,28
620610000	+25,67	-20,33
766620000	+26,39	-19,61
881820000	+28,46	-17,54
948690000	+28,69	-17,31
988650000	+29,24	-24,66

21115512\_2

Gandini 21115513



FINAL RESULT TABLE

QUASI PEAK		
Freq Hz	Lev dBuV/m	Margin dB
336450000	+19,28	-26,72
348840000	+19,66	-26,34
429330000	+21,76	-24,24
479400000	+22,49	-23,51
526080000	+23,40	-22,60
614010000	+25,44	-20,56
633600000	+25,70	-20,30
778290000	+26,08	-19,92
883770000	+28,51	-17,49
906570000	+37,06	-8,94
923550000	+38,48	-7,52
926340000	+37,26	-8,74
943320000	+34,31	-11,69

21115513\_2