


AC571 Labelling Information

The label below is fitted to the rear of the unit:

Label 1: 50.5mm x 40mm



The label below is fitted to the rear potted surface of the unit:

Label 2: 27mm x 13mm

5V (50mA)	
D0/CLK	20 CD
D1/SIG	External Reader
0V	
Tx + [A]	n Lin
Tx - [B]	RS-48 on-isok e Drive
Rx + [C]	485 olate ver O
Rx - [D]	nly

Material information for both of the above:

- 1. CLEAR POLYCARBONATE, 125 MICRONS THICK
- 2. SUB SURFACE PRINTED
- 3. COLOURS: BLACK GRAPHICS/TEXT. WHITE BACKGROUND
- 4. SELF ADHESIVE ON REVERSE
- 5. MATERIALS & PROCESS TO BE UL APPROVED



The label below is fitted to the front of the unit:

Label 3: 25 x 25mm



Material information for the above:

1. CLEAR POLYCARBONATE, 250 MICRONS THICK

2. SUB SURFACE PRINTED

3. COLOURS: TEXT - BLACK

LOGO - BLACK

LOGO - YELLOW PANTONE 109C LOGO - GREEN PANTONE GREEN C

BACKGROUND - GREY 420 CIRCLE UNDER LOGO - CLEAR

4. SELF ADHESIVE ON REVERSE

5. MATERIALS & PROCESS TO BE UL APPROVED

