

Equipment Identification	
Trade Name	GLOBLINK
Model Number	GL2001
System Configuration	
	<input type="checkbox"/> Narrow Band System <input checked="" type="checkbox"/> Wide Band System
Temperature range	Category III (indoor use), 0°C to +55°C
Function	Wireless Keyboard
Designed to Convey	Data
Power Supply	<input checked="" type="checkbox"/> Battery <input type="checkbox"/> Adaptor
Antenna Type	<input checked="" type="checkbox"/> Internal <input type="checkbox"/> Antenna Connector <input type="checkbox"/> Integral Antenna
Frequency Band	Lower Limit: 26.96 MHz, Upper Limit: 27.28 MHz
Channel Number	6 *
Channel Spacing	25KHz(1-2-3, 4-5-6)
Product Standard	RF: ETSI 300-220-3 EMC: ETSI 300-489-3
Transmitter Specification	
Type of Modulation	FSK
Designation of Emission	1.12×10^{-4} mW
Transmit Power Class	<input checked="" type="checkbox"/> 5a <input type="checkbox"/> 7a <input type="checkbox"/> 8 <input type="checkbox"/> 9 <input type="checkbox"/> 11 <input type="checkbox"/> 12
Duty Cycle Class	<input type="checkbox"/> 1.<0.1% <input type="checkbox"/> 2.<1% <input type="checkbox"/> 3.<10% <input checked="" type="checkbox"/> Up to 100%
Mode of Operation	<input type="checkbox"/> Duplex <input type="checkbox"/> Simplex <input type="checkbox"/> Periodic <input checked="" type="checkbox"/> Continuous
Receiver Specification	
Receiver Class	<input type="checkbox"/> Class 1 <input type="checkbox"/> Class 2 <input checked="" type="checkbox"/> Class 3

*This EUT has six channels (each with 16 ID):

- | | |
|---------------|---------------|
| 1. 26.985 MHz | 2. 27.010 MHz |
| 3. 27.035 MHz | 4. 27.210 MHz |
| 5. 27.235 MHz | 6. 27.260 MHz |