




EXHIBIT B

Test Report

Report No.	G2815477
FCC ID	OR7GL3688
Specifications	FCC Part 15, Class B
Test Method	ANSI C63.4 1992
Applicant address	2Fl., No. 101, Feenlian Street, Nei-Hu 114, Taipei, Taiwan
Applicant	GLOBLINK TECHNOLOGY INC.
Items tested	Wireless Mouse
Product name	Free Mouse 2FX
Model No.	GL3688 (Sample # G28476)
Frequency Range	26.96 – 27.28 MHz
Results	Compliance (As detailed within this report)
Date	08/03/2001 (month / day / year)(Sample received) 08/27/2001 (month / day / year)(Tested)
Prepared by	 Project Engineer
Authorized by	 V. General Manager (Jacob Lin)
Issue date	 (month / day / year)
Modifications	None
Tested by	Training Research Co., Ltd.
Office at	2, Lane 194, Huan-Ho Street, Hsichih, Taipei Hsien 221, Taiwan
Open site at	No. 15, Lane 530, Pa-Lian RD., Sec. 1, Hsichih City, Taipei Hsien, Taiwan, R.O.C.

Conditions of issue :

- (1) This test report shall not be reproduced except in full, without written approval of TRC. And the test result contained within this report only relate to the sample submitted for testing.
- (2) This report must not be used by the client to claim product endorsement by NVLAP or any agency of U.S. Government.

NVLAP LAB CODE: 200174-0

Contents

Chapter 1 Introduction

Description of EUT	3
Configuration of Test Setup	4

Chapter 2 Peak Power Measurement (Frequency Band: 26.96 ~ 27.28)

Test Setup	5
Test Procedure	5

Chapter 3 Radiated Emission Test

Test Condition and Setup	6
Radiated Test Placement	7

Appendix A :

Peak Power and Radiated test result	8
---	---

Appendix B :

Band Edge of Measurement	10
--------------------------------	----

Chapter 1 Introduction

Description of EUT:

This wireless keyboard with track ball use advanced transmission technology to allow comfortable use. However, occasionally outside sources may cause interference. The EUT power by two 1.5VDC batteries.

*This EUT has six channels (each with 16 ID):

- | | |
|---------------|---------------|
| 1. 27.060 MHz | 2. 27.085 MHz |
| 3. 27.110 MHz | 4. 27.135 MHz |
| 5. 27.160 MHz | 6. 27.185 MHz |

Test method:

All measurements contained in this report were performed according to the techniques described in Measurement procedure ANSI C63.4 – 1992.


Pretest was found that the emission of operating mode is worse than standby mode. So, The final test is made at the operating mode.

While testing, the EUT was made to transmit continuously and adjusted at a position, which transmitted the maximum emission.

The test placement as the photographs showed is the worst case emission placed. (If the emission is close to the ambient, the resolution BW and view resolution will be reduced and the data will be recorded by detection of maximum hold peak mode.)

The testing configuration of test setup is showing in the next page.

Configuration of Test Setup




EUT:

Put two AAA size, 1.5V battery into the battery cell of EUT, powers the subject device. The EUT does not be connected with any product.

Chapter 2 Peak Power Measurement (Frequency Band: 26.96 ~ 27.28)

Test Setup:

1. Test Setup:



2. Test Procedure:

- The EUT was setup in the anechoic chamber as shown above.
- The loop antenna was located upon its plane vertical, 3-meter distance from the EUT. The center of the loop is 1-meter above the ground plane.
- In order to find the maximum radiation, the EUT was rotated 360°. The measuring antenna was rotated about its axis at each azimuth about the EUT.

List of test Instrument :

Instrument Name	Model No.	Brand	Serial No.	<u>Calibration Date</u>	
				Last time	Next time
RECEIVER	SCR3502	SCHAFFNER	210	12/01/00	12/01/01
Control Box	TWR95-4	TRC	C9001-2	12/01/00	12/01/01
Active Loop Antenna	6502	EMCO	2777	07/20/01	07/20/02
Open test side (Antenna, Amplify, cable calibrated together)				05/15/01	05/15/02

The level of confidence of 95% , the uncertainty of measurement of radiated emission is ± 4.96 dB .

Test Result : Appendix A

Chapter 3 Radiated Emission Test

Test Condition and Setup:

Pretest : Prior to the final test ,the EUT is placed in an anechoic chamber, and scan from 30MHz to 1GHz. The devices rotated through three orthogonal axes to determine which attitude and configuration produces the highest emission relative to the limit. This is done to ensure the radiation exactly emits form the EUT.

Final test: Final radiation measurements is made on a **3 – meter** open-field test site. The EUT's maximum emission of radiation is placed on a nonconductive table, which is 0.8m height, the top surface is 1.0 x 1.5 meter. All placement is according to ANSI C63.4 - 1992.

The emissions was examined from 30 MHz to 1000 MHz measured by receiver.

The whole range Antenna is used to measure frequency from 30 MHz to 1 GHz. The final test is used the receiver.

Measure more than six top marked frequencies generated form pretest by computer step by step at each frequency. The EUT is rotated 360 degrees, and antenna is raised and lowered from 1 to 4 meters to find the maximum emission levels. The antenna is used with both horizontal and vertical polarization.

Appropriated preamplifier, which is made by TRC is used for improving sensitivity and precautions is taken to avoid overloading. The spectrum analyzer' s 6dB bandwidth is set to 120 KHz, and the EUT is measured at quasi-peak mode.

If the emission is close to the frequency band of ambient, the tester will recheck the data and the corrected data will be written in the test data sheet. If the emission is just within the ambient, the data from shield room will be taken as the final data.

List of test Instrument :

Instrument Name	Model No.	Brand	Serial No.	<u>Calibration Date</u>	
				Last time	Next time
RECEIVER	SCR3502	SCHAFFNER	210	12/01/00	12/01/01
Control Box	TWR95-4	TRC	C9001-2	12/01/00	12/01/01
Antenna	VULB 9160	M.E.	3063	06/26/01	06/23/02
Open test side (Antenna, Amplify, cable calibrated together)				05/15/01	05/15/02

The level of confidence of 95% , the uncertainty of measurement of radiated emission is ± 4.96 dB .

Test Result : Pass (Appendix A)

Radiated Test Placement: (Photographs)



Appendix A

Peak Power Test Result: (Horizontal)

Frequency	Reading Amplitude	Correction Factors	Corrected Amplitude	Limit	Margin
MHz	dBμV	dB/m	dBμV/m	dBμV/m	dB
27.110	62.82	-8.30	54.52	80.00	-25.48

Radiated Emission Test Result: (Horizontal)

Test Conditions:

Testing site : Temperature : 30 ° C Humidity : 70 % RH

Frequency	Reading Amplitude	Ant. Height	Table	Correction Factors	Corrected Amplitude	Class B Limit	Margin
MHz	dBμV	m	degree	dB/m	dBμV/m	dBμV/m	dB
54.1165	39.98	3.99	0	-6.62	33.36	40.00	-6.64
81.1895	42.48	3.99	32	-8.02	34.46	40.00	-5.54
162.3805	31.06	2.50	76	-4.64	26.42	43.52	-17.10
189.3970	36.66	1.00	91	-4.27	32.39	43.52	-11.133

Note:

1. Margin = Amplitude – limit, *if margin is minus means under limit.*
 2. Corrected Amplitude = Reading Amplitude – Correction Factors
 3. Correction factor = Antenna factor + (Cable Loss – Amplitude gain)
- (For example : 30MHz correction factor = 15.5 + (-15.26) = 0.24 dB/m)

Peak Power Test Result: (Vertical)

Frequency	Reading Amplitude	Correction Factors	Corrected Amplitude	Limit	Margin
MHz	dBμV	dB/m	dBμV/m	dBμV/m	dB
27.110	58.60	-8.30	50.30	80.00	-29.70

Radiated Emission Test Result: (Vertical)

Test Conditions:

Testing site : Temperature : 30 ° C Humidity : 70 % RH

Frequency	Reading Amplitude	Ant. Height	Table	Correction Factors	Corrected Amplitude	Class B Limit	Margin
MHz	dBμV	m	degree	dB/m	dBμV/m	dBμV/m	dB
54.1165	41.39	1.00	25	-6.62	34.77	40.00	-5.23
81.1895	37.99	1.00	99	-8.02	29.97	40.00	-10.03


Note:

1. Margin = Amplitude – limit, *if margin is minus means under limit.*
2. Corrected Amplitude = Reading Amplitude – Correction Factors
3. Correction factor = Antenna factor + (Cable Loss – Amplitude gain)
(For example : 30MHz correction factor = 15.5 + (–15.26) = 0.24 dB/m)

Appendix B


Band Edge of Measurement: (Frequency Band: 26.96 ~ 27.28)

Lower channel



26.96MHz << Class B Limit.

Upper channel:



27.28 MHz < < Class B Limit.