

INTERTEK TESTING SERVICES

RF Exposure

The equipment under test (EUT) is a MULTIMEDIA SPEAKER with Bluetooth function. The EUT was powered by AC 120V, 60Hz. For more detail information pls. refer to the user manual.

Modulation Type: GFSK for BT 4.0 and GFSK, $\pi/4$ DQPSK, 8DPSK for BT 2.1+EDR.
Bluetooth Version: 4.0 and 2.1 with EDR.

Antenna Type: Integral antenna.

Antenna Gain: 0dBi.

The nominal conducted output power specified: 1dBm +/-3dB.

The nominal radiated output power (e.i.r.p) specified: 1dBm (+/- 3dB)

According to the KDB 447498:

The maximum peak radiated emission for the EUT is 98.7dB μ V/m at 3m in the frequency 2402MHz of BT 2.1+EDR

The EIRP = $[(FS * D)^2 / 30]$ mW = 3.47dBm
which is within the production variation.

The minimum peak radiated emission for the EUT is 97.9dB μ V/m at 3m in the frequency 2480MHz of BT 4.0

The EIRP = $[(FS * D)^2 / 30]$ mW = 2.67dBm
which is within the production variation.

The maximum conducted output power specified is 4.0dBm = 2.51mW

The source- based time-averaging conducted output power
= 2.51 * Duty Cycle mW (where Duty Cycle \leq 1)
 \leq 2.51 mW

The SAR Exclusion Threshold Level:

= 3.0 * (min. test separation distance, mm) / sqrt(freq. in GHz)
= 3.0 * 5 / sqrt(2.480) mW
= 9.53 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.