

CTK Co., Ltd.
(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

RF EXPOSURE EVALUATION

Applicant	KMW INC.
Applicant Address	183-6, Yeongcheon-ro, Dongtan-myeon, Hwaseong-si, Gyeonggi-do, Korea
FCC ID	ORI-SPES2-080-E
Kind of Product	IT Converged Lighting
Equipment model name	SPES2-80-E
RF power	4.652 dBm Peak Conducted
Antenna type	Planar Inverted F antenna
Antenna Gain	2.59 dBi
Frequency Range	2405 MHz - 2480 MHz
Number of channels	16 CH



CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

** MPE Calculations **

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user. The MPE calculation for this exposure is shown below.

The peak radiated output power (EIRP) is calculated as follows:

EIRP = P + G	Where,
EIRP = 4.652 + 2.59 = 7.242 dBm => 5.3 mW	P = Power input to the antenna G = Power gain of the antenna (dBi)

The numeric gain(G) of the antenna with a gain specified in dB is determined by:

 $G = Log^{-1}$ (dB antenna gain / 10)

 $G = Log^{-1} (2.59 / 10)$

G = 1.82

Power density at the specific separation:

$S = PG/(4R^2\pi)$	Where,
$S = (5.3)/(4 * 20^2 * \pi)$	S = Maximum power density (mW/cm²) P = Power input to the antenna (mW) G = Numeric power gain of the antenna R = Distance to the center of the radiation of the
S =0.001 mW/cm ²	antenna (20cm = limit for MPE)

The Maximum permissible exposure (MPE) for the general population is 1 $\rm mW/cm^2$. The power density at 20cm does not exceed the 1 $\rm mW/cm^2$ limit.

Estimated safe separation:

$R = \sqrt{(PG / 4\pi)}$	Where,
$R = \sqrt{(5.3 / 4\pi)}$	P = Power input to the antenna (mW) G = Numeric power gain of the antenna R = Distance to the center of the radiation of the
R = 0.65 cm	antenna (20cm = limit for MPE)