

Oplink Communications, Inc. OPU Plus

.

Model No:HUB1111



Version 1.0 Nov, 2012



Applicant: Zhuhai FTZ Oplink Communications, Inc. Model Name: HUB1111 Brand Name: OPLINK

Product Name: OPU Plus

System	
Туре	USB HUB
Capacity	4 USB ports
Communication Port Type	USB type A
Communication Standard	USB 2.0
Performance	Support 480Mbit/s high speed
Operating Voltage	4.5~5.5VDC
Operating Environment	WorkingTemp:0℃~45℃
	Humidity:10%~90%RH non-condensing
	Storage Temp: -40°C~70°C
	Humidity:5%~90%RH
Approval	FCC/RoHS
Housing	
Dimension	56mm*43mm*20mm(USB Plug Length12mm)

V@# Áå^ça&^Á@æe Áå^^} Á¢• c*å Áse) å Á{[`} å Á{[Á&[{] | ^ Å ã @åv@ Áā[ão Á{[¦ÁselÔ]æ•ÁÔ/åå ã ãæe Áå^ça&^ÉÅ
] ` !• ` æ) ch [ÁUæb ch [Á], -Áv@ ÁzôÔ ÂU` |^• ÈÁ/@• ^ Áā[ão Áse^ Åå,• ã] } ^ å Å{[Á], [çãa ^ Á^ æ] } æà |^ Å] ![c*&cā] } Á
2 * æðj • ch @æe { ~ | Áðj c* !-^ !^ } & ^ Áðj ÁseÁ ^• ãa ^ ; cæe | ææi] } ÈÁ/@ð Á*` ³] { ^} c* ^ ?] { ^} c*] { ^} c*] { ^} c*]]

P[_^ç^\Êb@\!^/as Á, [Á* ææa) c^^Ác@eenÁsj c^\~\^} &^Á, āļÁ, [c4, &&` |Ásj Áseaf, ææa&` |æs/Asj • cæe|ææaj; } Èb@As@erÁs ^``āj { ^} c4&æe • • Á@eet{ ~` |Ásj c^\~\^} &^Át Áaæatj Á, !Ác^|^çãr āj } Á^&^] cāj } Êf, @a&@Asea As^å
a^c^\{ āj ^å ^ à^ Ác` } āj * Ás@ Á``āj { ^} c4, ~Ásej å Á; } Êb@A` • ^!/Ásr Á'; &&[` |æ* ^åÁt Ás[Ás[\\^ &ofs@ Ásj c^\~\^} & A [} ^Á; !Át [!^Át Ás@ Át ||[_,ā] * Át ^æ` !^ • HÁ

ĔĂÜ^[¦āʰ}ớĄ¦¦Á^|[&æɛ¢^Ás@·Á^&^ãçāj*Áæjơ^}}æÈ

ËKQ,&¦^æ;^Áx@;Á^]æ;aæã(}Á\$x^c;^^}Áx@;Á*``ā]{^}oÁse)åÁ^&^ãç^¦ÉA

ËŽÔ[}}^&oÁs@Á``ā]{^}oÁsjo[Áse)Á[`q^oÁ[}Áse4&ä&äóÅsä&`ãoÁsä~^\^}oÁ+[{Ás@eenÁt[Á]@B&@Ás@Á^&^ãç^¦Áse Á ÁK&[}}^&o*àĚÁ

ËŐ[}•`|Óx@A&^æ^\A,\Á,\Áœ}A*¢]^\ð\&^àAæåã,EVXÁx&@;38ãæ;A{,\Á@\]È

Á

 $\begin{aligned} CE_{f} & = \frac{1}{2} \left[\frac{1}{2}$