RETLIF TESTING LABORATORIES

TABULAR DATA SHEET

TEST METHOD:	**FREQUENCY STABILITY (INPUT POWER 85% TO 115%)**		
CUSTOMER:	Beyerdynamic	JOB No.:	R-8170-1A
TEST SAMPLE:	MCW Wireless Microphone FCC ID: OSDMCWSTATION-1		
MODEL No.:	MCW 1013	SERIAL No.:	01511
TEST SPECIFICATION:	FCC Part 90 Private Land Mobile Radio Services	PARAGRAPH:	90.213
OPERATING MODE:	Unit locked in transmit mode.		
TECHNICIAN:	N. Dragotta	DATE:	August 04, 1999
NOTES:	Tolerance: +/- .005% (+/- .0403 MHz)		

CHANNEL	TRANSMIT FREQUENCY	INPUT VOLTAGE	INPUT VOLTAGE	LOWER LIMIT	METER READING	UPPER LIMIT	CUTOFF READING	CUTOFF VOLTAGE
	MHz	%	VDC	MHz	MHz	MHz	MHz	VDC
1	806.000	85	6.1	805.9597	805.9980	806.0403		
1	806.000	100	7.2	805.9597	805.9925	806.0403	0	4
1	806.000	115	8.3	805.9597	805.9982	806.0403		

The test sample did not exhibit any malfunction or degradation of performance beyond the tolerances specified by the manufacturer.