

## SAR Test exclusion documentation according to FCC KDB 447498, RSS-102

Report identification number: 1-1581/20-01-11 Exclusion (FCC\_ISED)

contains the module with the following certification numbers	
FCC ID	OSDSpace
ISED number	3628C-SPACE
HVIN (Hardware Version Identification Number)	beyerdynamic SPACE
PMN (Product Marketing Name)	beyerdynamic SPACE
FVIN (Firmware Version Identification Number)	-/-
HMN (Host Marketing Name)	-/-

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

### Document authorised:



Alexander Hnatovskiy  
Lab Manager  
Radio Communications & EMC



Marco Scigliano  
Testing Manager  
Radio Communications & EMC

**EUT technologies:**

Technologies:	Max. measured avg*. EIRP [dBm]	#
BT Classic	1.79	A
BT LE	0.38	B

\*) NOTE: duty cycle corrected with 0.85 for BT Classic and 0.6 for BT LE

**Details and origins of the measurements shown in the table above:**

#	Results from:	Additional information
A	1-1581/20-01-09      CTC advanced GmbH	Antenna gain page 21, Conducted output power page 28, *) <b>Note:</b> Testmode during measurement has a duty cycle of 85%, the correction factor 0.85 was added to gain the Max. measured avg. EIRP
B	1-1581/20-01-10      CTC advanced GmbH	Antenna gain page 21, Conducted output power page 25, *) <b>Note:</b> Testmode during measurement has a duty cycle of 60%, the correction factor 0.6 was added to gain the Max. measured avg. EIRP

## **SAR test exclusion according to KDB447498 (General RF Exposure Guidance v06)**

Equation from Chapter 4.3.1: Standalone SAR test exclusion considerations page 11 and ff.

(1) Standalone SAR test exclusion for 100 MHz to 6 GHz at test separation distances  $\leq 50\text{mm}$

$$(\text{Threshold}_{1\text{-g};10\text{-g}}) \times d_{\text{separation}} / f^{0.5}$$

where

$\text{Threshold}_{1\text{-g};10\text{-g}}$  is 3 for 1-g; 7.5 for 10-g

$d_{\text{separation}}$  is the min. test separation distance; 5mm is used if the distance is less

$f$  is the RF channel transmit frequency

The table below gives the calculated maximal power that could be used for source based time averaged conducted or radiated power, adjusted for tune up tolerance. If this is at or below the calculated value the DUT is exempted from SAR evaluation.

frequency [MHz]	$d_{\text{separation}}$ [mm]	Threshold <sub>1-g</sub>	Powerlimit [mW]	P <sub>max-declared</sub>		Exclusion
				[dBm]	[mW]	
2450.00	<b>5</b>	3	9.58	1.79	1.51	yes

## **SAR test exclusion according to RSS-102 Issue 5 Section 2.5.1/Table 1**

The table below gives the calculated maximal power that could be used for source based time averaged conducted or radiated power, adjusted for tune up tolerance. If this is at or below the calculated value the DUT is exempted from SAR evaluation.

frequency [MHz]	$d_{\text{separation}}$ [mm]	tissue volume	Powerlimit [mW]	P <sub>max-declared</sub>		Exclusion
				[dBm]	[mW]	
2450.00	<b>5</b>	1 g	4.00	1.79	1.51	yes

The limits above are defined for body worn application and therefore cover all use cases.