



Accredited testing-laboratory

DAR registration number: DGA-PL-176/94-D1

**Federal Motor Transport Authority (KBA)
DAR registration number: KBA-P 00070-97**

Recognized by the Federal Communications Commission

Anechoic chamber registration no.: 90462 (FCC)

Anechoic chamber registration no.: 3462C-1 (IC)

Certification ID: DE 0001

Accreditation ID: DE 0002

Accredited Bluetooth® Test Facility (BQTF)

The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Cetecom ICT is under license

Test report no. : 1-2036-01-05/10 B
Type identification : Synexis TP2
Applicant : beyerdynamic GmbH & Co. KG
FCC ID : OSDSYNEXISTP2
IC Certification No : 3628A-SYNEXISTP2
Test standards : 47 CFR Part 2
47 CFR Part 95

Table of contents

- 1 General information..... 3**
 - 1.1 Notes3
 - 1.2 Testing laboratory4
 - 1.3 Details of applicant4
 - 1.4 Application details4
- 2 Test standard/s..... 5**
- 3 Technical tests..... 6**
 - 3.1 Details of manufacturer.....6
 - 3.1.1 Test item.....6
 - 3.1.2 Additional EUT information For IC Canada (appendix 2).....7
 - 3.1.3 Extreme conditions testing values8
- 4 Summary of Measurement Results and list of all performed test cases 9**
- 5 RF measurement testing 10**
 - 5.1 Description of test set-up10
 - 5.1.1 Radiated measurements.....10
 - 5.2 Referenced Documents10
 - 5.3 Additional comments10
 - 5.4 Radiated output power11
 - 5.5 Frequency tolerance12
 - 5.6 Modulation characteristics14
 - 5.7 Occupied bandwidth.....16
 - 5.8 Spectrums mask17
 - 5.9 Radiated spurious emissions22
- 6 Test equipment and ancillaries used for tests 29**
- 7 Photographs of the Test Set-up 32**
- 8 Photographs of the EUT 33**

1 General information

1.1 Notes

The test results of this test report relate exclusively to the test item specified in 3.1.1. The CETECOM ICT Services GmbH does not assume responsibility for any conclusions and generalisations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of the CETECOM ICT Services GmbH.

Test laboratory manager:

2010-08-05	Marco Bertolino	
Date	Name	Signature

Technical responsibility for area of testing:

2010-08-05	Stefan Bös	i. A.
Date	Name	Signature

1.2 Testing laboratory

CETECOM ICT Services GmbH

Untertürkheimer Straße 6 - 10

66117 Saarbrücken

Germany

Phone: + 49 681 5 98 - 0

Fax: + 49 681 5 98 - 9075

e-mail: info@ICT.cetecom.de

Internet: http://www.cetecom-ict.de

State of accreditation:

The test laboratory (area of testing) is accredited according to

DIN EN ISO/IEC 17025

DAR registration number: DGA-PL-176/94-D1

Accredited by:

Federal Motor Transport Authority (KBA)

DAR registration number: KBA-P 00070-97

Testing location, if different from CETECOM ICT Services GmbH:

Name :
Street :
Town :
Country :
Phone :
Fax :

1.3 Details of applicant

Name:	beyerdynamic GmbH & Co. KG
Street:	Theresienstraße 8
Town:	74072 Heilbronn
Country:	Germany
Telephone:	+49 (0) 7131 61 71-0
Fax:	+49 (0) 7131 617 215
Contact:	Ulrich Roth
E-mail:	roth@beyerdynamic.de
Telephone:	+49 (0) 7131 617 155

1.4 Application details

Date of receipt of order:	2010-05-05
Date of receipt of test item:	2010-06-07
Date of start test:	2010-06-07
Date of end test:	2010-06-10
Persons(s) who have been present during the test:	-/-

2 Test standard/s

47 CFR Part 2	2009-10	Title 47 of the Code of Federal Regulations; Chapter I- Federal Communications Commission Frequency allocations and radio treaty matters; general rules and regulations
47 CFR Part 95	2009-10	Title 47 of the Code of Federal Regulations; Chapter I- Federal Communications Commission subchapter D - safety and special radio services; Part 95- Personal radio services

3 Technical tests

3.1 Details of manufacturer

Name:	beyerdynamic GmbH & Co. KG
Street:	Theresienstraße 8
Town:	74072 Heilbronn
Country:	Germany

3.1.1 Test item

Kind of test item	:	Auditory communication system Synexis
Type identification	:	Synexis TP2
S/N serial number	:	No information available!
HW hardware status	:	No information available!
SW software status	:	No information available!
Frequency Band	:	216 -217 MHz
Type of Modulation	:	F3E
Number of channels	:	19
Antenna	:	Body pack transmitter Synexis TP2– integrated antenna For more information, please take a look at the sub-clause 8 → Photos of the EUT!
Power Supply	:	3 V DC batteries 2 x 1.5V
Temperature Range	:	-30 °C to +50 °C

Body pack transmitter Synexis TP2:

Max. power radiated: 2.62 dBm

FCC ID: OSDSYNEXISTP2

IC: 3628A-SYNEXISTP2

3.1.2 Additional EUT information For IC Canada (appendix 2)

IC Registration Number:	3628A-SYNEXISTP2
Model Name:	Synexis TP2
Manufacturer (complete Address):	beyerdynamic GmbH & Co. KG Theresienstraße 8 74072 Heilbronn Germany
Tested to Radio Standards Specification (RSS) No.:	RSS-210 Issue 7
Open Area Test Site Industry Canada Number:	IC 3462C-1
Frequency Range (or fixed frequency) [MHz]:	216 -217 MHz
RF: Power [W] (max):	Body pack transmitter Synexis TP2 Rad. EIRP: 1.83mW
Antenna Type:	Body pack transmitter Synexis TP2 – integrated antenna For more information, please take a look at the sub-clause 8 → Photos of the EUT!
Occupied Bandwidth (99% BW) [kHz]:	32.06
Type of Modulation:	F3E
Emission Designator (TRC-43):	32K1F3E
Transmitter Spurious (worst case):	-42.7 dBm @ 12.55 GHz
Receiver Spurious (worst case):	No receiver mode integrated!

ATTESTATION:

I attest that the testing was performed or supervised by me; that the test measurements were made in accordance with the above-mentioned departmental standard(s), and that the radio equipment identified in this application has been subject to all applicable test conditions specified in the departmental standards and all of the requirements of the standards have been met.

Signature:

Test engineer: Marco Bertolino Date: 2010-08-05

3.1.3 Extreme conditions testing values

Description	Shortcut	Unit	Value
Nominal Temperature	T _{nom}	°C	20
Nominal Humidity	H _{nom}	%	41
Nominal Power Source	V _{nom}	V	3 DC

Type of power source: 3 V DC batteries 2 x 1.5V

Deviations from these values are reported in chapter 2

4 Summary of Measurement Results and list of all performed test cases

- No deviations from the technical specifications were ascertained
- There were deviations from the technical specifications ascertained

TC identifier	Description	verdict	date	Remark
RF-Testing	47 CFR Part 2 47 CFR Part 95 G	PASSED	2010-08-05	-/-

Test Specification Clause	Test Case	Pass	Fail	Not applicable	Not performed
§ 2.1046 § 95.639 (e)	Radiated output power	Yes			
§ 2.1055 § 95.629 (d) (2)	Frequency tolerance	Yes			
§ 2.1047	Modulation characteristics	Yes			
§ 2.1047 (e) (3)	Occupied bandwidth	Yes			
§ 95.635 (c) (2) (i)	Spectrum mask	Yes			
§ 2.1053 § 2.1047 § 95.635 (c) (2) (ii)	Radiated spurious emissions	Yes			

5 RF measurement testing

5.1 Description of test set-up

5.1.1 Radiated measurements

For Part 95 we use the substitution method (TIA/EIA 603).

5.2 Referenced Documents

None

5.3 Additional comments

The channel 216.475 MHz is disabled by the software.

5.4 Radiated output power

Standards:
FCC Part 2 – subpart J: Certification § 2.1046
FCC Part 95 – subpart E: Technical regulations § 95.639 (e)

Body pack transmitter Synexis TP2:

Results:

Channel / frequency	Detected output power
01 / 216.025 MHz	2.62 dBm
10 / 216.525 MHz	2.60 dBm
19 / 216.975 MHz	2.53 dBm

Limits:

FCC Part 95 – subpart E: Technical regulations § 95.639 (e) LPRS 100 mW = 20 dBm

5.5 Frequency tolerance

Standards:
FCC Part 2 – subpart J: Certification § 2.1055
FCC Part 95 – subpart E: Technical regulations § 95.629 (d) (2)

Body pack transmitter Synexis TP2:

Results: low channel

Temperature	Frequency (MHz)	kHz / PPM
-30 °C	216.031059	1.75 / 8.08
-20 °C	216.031059	1.75 / 8.08
-10 °C	216.030980	1.67 / 7.71
0 °C	216.031012	1.70 / 7.86
10 °C	216.030241	0.93 / 4.29
20 °C (V nom)	216.029314	0 / 0 (Reference)
30 °C	216.028833	-0.48 / -2.23
40 °C	216.028480	-0.83 / -3.86
50 °C	216.026942	-2.37 / -10.98
Voltage		
85 %	216.029319	0.01 / 0.03
115 %	216.029307	-0.01 / -0.03

Results: middle channel

Temperature	Frequency (MHz)	kHz / PPM
-30 °C	216.531059	1.78 / 8.21
-20 °C	216.531205	1.92 / 8.88
-10 °C	216.531077	1.80 / 8.29
0 °C	216.530980	1.70 / 7.84
10 °C	216.530420	1.14 / 5.26
20 °C (V nom)	216.529282	0 / 0 (Reference)
30 °C	216.528961	-0.32 / -1.48
40 °C	216.528272	-1.01 / -4.66
50 °C	216.526990	-2.29 / -10.59
Voltage		
85 %	216.529280	-0.00 / -0.01
115 %	216.529314	0.03 / 0.15

Results: high channel

Temperature	Frequency (MHz)	kHz / PPM
-30 °C	216.981123	1.91 / 8.78
-20 °C	216.981125	1.91 / 8.79
-10 °C	216.981045	1.83 / 8.42
0 °C	216.980900	1.68 / 7.75
10 °C	216.980500	1.28 / 5.91
20 °C (V nom)	216.979218	0 / 0 (Reference)
30 °C	216.979025	-0.19 / -0.89
40 °C	216.978192	-1.03 / -4.73
50 °C	216.977070	-2.15 / -9.90
Voltage		
85 %	216.979197	-0.02 / -0.10
115 %	216.979234	-0.02 / 0.07

Limits:

FCC Part 95 – subpart E: Technical regulations § 95.629 (d) (2) ± 50 ppm

5.6 Modulation characteristics

Standards:
FCC Part 2 – subpart J: Certification § 2.1047

Body pack transmitter Synexis TP2:

Frequency response of audio circuit:

An audio signal at 1 kHz was adjusted for a 100 % rated FM deviation by 270 mV input. While maintaining the same amplitude, the input frequency was varied and the detected FM deviation recorded.

Frequency [kHz]	Deviation [kHz]
0.1	7.36
0.2	10.80
0.3	11.50
0.4	11.60
0.5	11.60
0.6	11.60
0.7	11.60
0.8	11.50
0.9	11.50
1.0	11.50
1.2	11.50
1.4	11.50
1.6	11.50
1.8	11.50
2.0	11.50
2.5	11.50
3.0	11.50
3.5	11.50
4.0	11.50
4.5	11.50
5.0	11.60
5.5	11.70
6.0	11.70
6.5	11.70
7.0	11.70
7.5	11.70
8.0	11.60
8.5	11.60
9.0	11.50
9.5	11.30
10.0	11.20

Modulation limiting:

While maintaining the same frequency, the input amplitude was varied and the detected FM deviation recorded.

Audio signal level	Deviation [kHz]
1 mV	1.34
2 mV	1.69
3 mV	1.93
4 mV	2.13
5 mV	2.33
10 mV	2.97
20 mV	3.89
50 mV	5.74
100 mV	7.79
200 mV	10.60
300 mV	11.50
400 mV	11.80
500 mV	11.90

5.7 Occupied bandwidth

Standards:
FCC Part 2 – subpart J: Certification § 2.1047 (e) (3)

Body pack transmitter Synexis TP2:


Channel / Frequency	99 % bandwidth
1 / 216.025 MHz	32.06 kHz
10 / 216.525 MHz	32.06 kHz
19 / 216.975 MHz	32.06 kHz

5.8 Spectrums mask


Standards:
FCC Part 95 – subpart E: Technical regulations § 95.635 (c) (2) (i)

Body pack transmitter Synexis TP2:


Plot 1: lowest channel – unmodulated carrier




Plot 2: lowest channel – 1kHz modulated carrier




Plot 3: lowest channel – Range 0.1 kHz → 10 kHz modulated carrier




Plot 4: middle channel – unmodulated carrier




Plot 5: middle channel – 1kHz modulated carrier




Plot 6: middle channel – Range 0.1 kHz → 10 kHz modulated carrier




Plot 7: highest channel – unmodulated carrier



Plot 8: highest channel – 1kHz modulated carrier



Plot 9: highest channel – Range 0.1 kHz → 10 kHz modulated carrier




5.9 Radiated spurious emissions


Standards:
FCC Part 2 – subpart J: Certification § 2.1053
FCC Part 2 § 2.1047
FCC Part 95 – subpart E: Technical regulations § 95.635 (c) (2) (ii)

Body pack transmitter Synexis TP2:


Plot 1: 0.03 – 1 GHz, vertical polarization, low channel




Plot 2: 1 – 12.75 GHz, vertical polarization, low channel




Plot 3: 0.03 – 1 GHz, horizontal polarization, low channel




Plot 4: 1 – 12.75 GHz, horizontal polarization, low channel




Plot 5: 0.03 – 1 GHz, vertical polarization, middle channel




Plot 6: 1 – 12.75 GHz, vertical polarization, middle channel




Plot 7: 0.03 – 1 GHz, horizontal polarization, middle channel




Plot 8: 1 – 12.75 GHz, horizontal polarization, middle channel




Plot 9: 0.03 – 1 GHz, vertical polarization, high channel




Plot 10: 1 – 12.75 GHz, vertical polarization, high channel



Plot 11: 0.03 – 1 GHz, horizontal polarization, high channel



Plot 12: 1 – 12.75 GHz, horizontal polarization, high channel



Results: Synexis TP2

Results:

SPURIOUS EMISSIONS LEVEL								
FCC Part 95 – subpart E: Technical regulations § 95.635 (c) (2) (ii)								
Low channel			Middle channel			High channel		
Frequency	Detector	Level	Frequency	Detector	Level	Frequency	Detector	Level
108.05 MHz	120 kHz PP	--55.56 dBm vertical --61.73 dBm horizontal	649.57 MHz	120 kHz PP	-51.16 dBm vertical -53.23 dBm horizontal	650.93 MHz	120 kHz PP	-53.88 dBm vertical -53.57 dBm horizontal
156.04 MHz	120 kHz PP	-54.95 dBm vertical -60.61 dBm horizontal	1948.50 MHz	1 MHz PP	-42.63 dBm vertical -40.67 dBm horizontal	1944.00 MHz	1 MHz PP	-42.13 dBm vertical -41.71 dBm horizontal
648.07 MHz	120 kHz PP	-52.04 dBm vertical -52.86 dBm horizontal						
1944.00 MHz	1 MHz PP	-42.87 dBm vertical -42.37 dBm horizontal						
All detected emissions are more than 20 dB below the limit.			All detected emissions are more than 20 dB below the limit.			All detected emissions are more than 20 dB below the limit.		
Measurement uncertainty ± 3 dB								

f < 1 GHz : RBW/VBW: 120 kHz

f ≥ 1GHz : RBW/VBW: 1 MHz

Limits:

FCC Part 95 – subpart E: Technical regulations § 95.635 (c) (2) (ii) -13 dBm

6 Test equipment and ancillaries used for tests

In order to simplify the identification of the equipment used at each specific test, each item of test equipment and ancillaries are provided with an identifier or number in the equipment list below.

Typically, the calibrations of the test apparatus are commissioned to and performed by an accredited calibration laboratory. The calibration intervals are determined in accordance with the DIN EN ISO/IEC 17025. In addition to the external calibrations, the laboratory executes comparison measurements with other calibrated test systems or effective verifications. Weekly chamber inspections and range calibrations are performed. Where possible, rf-generating and signalling equipment as well as measuring receivers and analyzers are connected to an external high-precision 10 MHz reference (GPS-based or rubidium frequency standard).

No.	Labor / Item	Equipment	Type	Manufact.	Serial No.	INV. No Cetecom	Kal. Art	Last Calibration	Next Calibration
1	n. a.	Double-Ridged Waveguide Horn Antenna 1-18.0GHz	3115	EMCO	8812-3088	300001032	vIKI!	05.03.2009	05.03.2011
2	n. a.	Active Loop Antenna	6502	EMCO	2210	300001015	ne		
3	n. a.	Anechoic chamber		MWB	87400/02	300000996			
4	Spec.A. 2_2e	System rack for EMI measurement solution	85900	HP I.V.	*	300000222	ne		
5	9	Artificial Mains 9 kHz to 30 MHz, 4 x 25 Ampere	ESH3-Z5	R&S	828576/020	300001210	Ve	06.01.2010	06.01.2012
6	n. a.	Relais Matrix	3488A	HP Meßtechnik	2719A15013	300001156	ne		
7	n. a.	Relais Matrix	PSU	R&S	890167/024	300001168	ne		
8	n. a.	Isolating Transformer	RT5A	Grundig	9242	300001263	ne		
9	n. a.	Three-Way Power Splitter, 50 Ohm	11850C	HP Meßtechnik		300000997	ne		
10	n. a.	Switch / Control Unit	3488A	HP	2605e08770	300001443	ne		
11	n. a.	Band Reject filter	WRCG1855/1910-1835/1925-40/8SS	Wainwright	7	300003350	ev		
12	n. a.	Band Reject filter	WRCG2400/2483-2375/2505-50/10SS	Wainwright	11	300003351	ev		
13	n. a.	TILE-Software Emission	Quantum Change, Modell TILE-	EMCO	none	300003451	ne		

			ICS/FULL						
14	n. a.	Highpass Filter	WHKX2.9/18 G-12SS	Wainwright	1	300003 492	ev		
15	n. a.	Highpass Filter	WHK1.1/15G-10SS	Wainwright	3	300003 255	ev		
16	n. a.	Highpass Filter	WHKX7.0/18 G-8SS	Wainwright	18	300003 789	ne		
17	n. a.	PSA Spectrum Analyzer 3 Hz - 26.5 GHz	E4440A	Agilent Technologies	MY482 50080	300003 812	k	05.08. 2008	05.08. 2010
18	n. a.	MXG Microwave Analog Signal Generator	N5183A	Agilent Technologies	MY474 20220	300003 813	k	06.08. 2008	06.08. 2010
19	n. a.	RF Filter Section 9kHz - 1GHz	N9039A	Agilent Technologies	MY482 60003	300003 825	vIKI!	19.08. 2008	19.08. 2010
20	n. a.	TRILOG Broadband Test-Antenna 30 MHz - 3 GHz	VULB9163	Schwarzbeck	371	300003 854	vIKI!	17.12. 2008	17.12. 2010
21	n. a.	Spectrum Analyzer 20 Hz - 50 GHz	FSU50	R&S	200012	300003 443	ve		
22	n. a.	Temperature Test Chamber	VT 4002	Heraeus Voetsch	521/841 93	300003 889	vIKI!	28.05. 2009	28.05. 2011
23	4	Radiocom. Analyzer	CMTA 54	R&S	894043/ 010	300001 175	NK!		
24	n. a.	Temperature Test Chamber	VT 4002	Heraeus Voetsch	521/837 61	300002 326	Ve	28.05. 2009	28.05. 2011
25	n. a.	Audio Analyzer 2Hz - 300 kHz	UPD	R&S	841074/ 009	300001 236	k	08.01. 2010	08.01. 2012
26	n. a.	Signal Analyzer 20Hz- 26,5GHz- 150 to + 30 DBM	FSiQ26	R&S	835111/ 0004	300002 678	Ve	06.01. 2009	06.01. 2011
27	45	Switch-Unit	3488A	HP Meßtechnik	2719A1 4505	300000 368	g		
28	50	DC power supply, 60Vdc, 50A, 1200 W	6032A	HP Meßtechnik	2920A0 4466	300000 580	k	06.01. 2009	06.01. 2011
29	n. a.	software	SPS_PHE 1.4f	Spitzberger & Spieß	B5981; 5D1081; B5979	300000 210	ne		
30	n. a.	EMI Test Receiver	ESCI 1166.5950.03	R&S	100083	300003 312	k	08.01. 2010	08.01. 2012

31	n. a.	Analyzerr-Reference-System (Harmonics and Flicker)	ARS 16/1	SPS	A3509 07/0 0205	300003 314	k		
32	n. a.	Amplifier	JS42-00502650-28-5A	MITEQ	1084532	300003 379	ev		
33	n. a.	Antenna Tower	Model 2175	ETS-LINDGRE N	64762	300003 745	izw		
34	n. a.	Positioning Controller	Model 2090	ETS-LINDGRE N	64672	300003 746	izw		
35	n. a.	Turntable Interface-Box	Model 105637	ETS-LINDGRE N	44583	300003 747	izw		
36	n. a.	TRILOG Broadband Test-Antenna 30 MHz - 3 GHz	VULB9163	Schwarzbeck	295	300003 787	k		
37	n. a.	Spectrum-Analyzer	FSU26	R&S	200809	300003 874	k	08.01. 2010	08.01. 2012

7 Photographs of the Test Set-up

Photo documentation:

Photo 1:





Photo 2:



8 Photographs of the EUT

Photo documentation: external photos

Photo 1:



Photo 2:




Photo 3:




Photo 4:



Photo 5:




Photo 6:



Photo 7:



Photo 8:



Photo documentation: internal photos

Photo 1:




Photo 2:



Photo 3:




Photo 4:




Photo 5:




Photo 6:



Photo 7:



Photo 8:




Photo 9:




Photo 10:




Photo 11:




Photo 12:




Photo 13:




Photo 14:




Photo 15:

